

High Temperature (245 °C) Thick Film Chip Resistor




For applications such as down hole applications or aircraft breaking systems, the need for parts able to withstand very severe conditions (temperature as high as 230 °C powered or up to 245 °C un-powered) has led Vishay Sfernice to push out the limit of the thick film technology. Designers might read the application note "Power Dissipation Considerations in High Precision Vishay Sfernice Thin Film Chips Resistors and Arrays (P, PRA etc.) (High Temperature Applications)" (www.vishay.com/doc?53047) in conjunction with this data sheet to help them to properly design their PCBs and get the best performances of the CHPHT. Vishay Sfernice R&D engineers will be willing to support any customer design considerations.

FEATURES

- High temperature (245 °C)
- Large ohmic value range 0.1 Ω to 100 MΩ
- Operating temperature range (- 55 °C to + 230 °C)
- SMD wraparound chip resistor
- Storage temperature range (- 55 °C to + 245 °C)
- Gold terminations for HMP process (< 1 μm thick) for temperature up to 245 °C
- Tin/silver terminations for operating temperature up to 200 °C
- Material categorization: For definitions of compliance please see www.vishay.com/doc?99912




DIMENSIONS in millimeters



CASE SIZE	A	B	C	D	E
	± 0.152	± 0.127	± 0.127	± 0.127	± 0.127
0603	1.60	0.90	0.38	0.31	0.40
0805	1.85	1.25	0.38	0.31	0.50
1206	3.00	1.73	0.38	0.40	0.50
2010	5.03	2.64	0.50	0.50	0.50

SUGGESTED LAND PATTERN (to IPC-7351A)



CASE SIZE	Z _{max.}	G _{min.}	X _{max.}
0603	2.15	0.39	1.03
0805	2.70	0.44	1.38
1206	3.85	1.59	1.85
2010	5.88	3.62	2.77



STANDARD ELECTRICAL SPECIFICATIONS							
MODEL	SIZE	RESISTANCE RANGE Ω	RATED POWER P_n W (at 230 °C)	LIMITING ELEMENT VOLTAGE V	MAX. OVERLOAD VOLTAGE V	TOLERANCE \pm %	TEMPERATURE COEFFICIENT \pm ppm/°C
CHPHT	0603	0.1 to 25M	0.0125	50	100	1, 2, 5	100, 200
CHPHT	0805	0.1 to 25M	0.02	150	300	1, 2, 5	100, 200
CHPHT	1206	0.1 to 50M	0.025	200	400	1, 2, 5	100, 200
CHPHT	2010	0.1 to 100M	0.1	200	400	1, 2, 5	100, 200

CLIMATIC SPECIFICATIONS	
Operating temperature range	- 55 °C to + 230 °C
Storage temperature range	- 55 °C to + 245 °C


MECHANICAL SPECIFICATIONS	
Substrate	Alumina
Technology	Thick film (Ruthenium oxyde)
Protection	Parts have double and organic coating (OR5 to 100M)
Terminations	N (W/A): SnAg over nickel barrier for temperature up to 200 °C G (W/A) type: Gold (< 1 μ m) over nickel barrier for temperature up to 245 °C

Note

- Refer to Application Note "Guidelines for Vishay Sfernice Resistive and Inductive Components" (document number: 52029) for recommended reflow profile. Profile #3 applies.

BEST TOL. AND TCR VERSUS OHMIC VALUE		
TIGHTEST TOLERANCE	OHMIC VALUES	BEST TCR ppm/°C
1 % (F)	$5 \Omega < R < 10M$	100 (K)
2 % (G)	$1 \Omega < R < R \text{ max.}$	200 (L)
5 % (J)	$0.1 \Omega < R < R \text{ max.}$	200 (L)

POWER DERATING CURVE



PACKAGING

ESD packaging available: Waffle pack and plastic tape and reel (low conductivity). Paper tapes available on request (ESD only). (For 0603, 0805, and 1206 only.)

SIZE	NUMBER OF PIECES PER PACKAGE		TAPE WIDTH	
	WAFFLE PACK	TAPE AND REEL		
		MIN.		MAX.
0603	100	100	5000	
0805 0705			4000	
1206	140	60	2000	
2010	60			

PACKAGING RULES

Waffle Pack

Can be filled up to maximum quantity indicated in the table here above, taking into account the minimum order quantity. When quantity ordered exceeds maximum quantity of a single waffle pack, the waffle packs are stacked up on the top of each other and closed by one single cover.

To get "not stacked up" waffle pack in case of ordered quantity > maximum number of pieces per package: Please consult Vishay Sfernice for specific ordering code

Tape and Reel

Can be filled up to maximum quantity indicated in the table here above, taking into account the minimum order quantity. When quantity ordered is between the MOQ and the maximum reel capacity, only one reel is provided.

When several reels are needed for ordered quantity within MOQ and maximum reel capacity: Please consult Vishay Sfernice for specific ordering code


POPULAR OPTIONS

For any option it is recommended to consult Vishay Sfernice for availability first.


Option: Enlarged terminations:

For stringent and special power dissipation requirements, the thermal resistance between the resistive layer and the solder joint can be reduced using enlarged terminations chip resistors which are soldered on large and thick copper pads acting as heat sinks (see application note: "Power Dissipation in High Precision Vishay Sfernice Chip Resistors and Arrays (P Thin Film, PRA Arrays, CHP Thick Film)" (www.vishay.com/doc?53048)).

Option to order: 0063 (applies to size 1206/2010).

DIMENSIONS (Option 0063) in millimeters


CASE SIZE	A	B	E	D	F		
	MAX. TOL. + 0.152 MIN. TOL. - 0.152	MAX. TOL. + 0.127 MIN. TOL. - 0.127	MAX. TOL. + 0.13 MIN. TOL. - 0.13	MAX. TOL. + 0.13 MIN. TOL. - 0.13	NOMINAL	MIN.	MAX.
	NOMINAL	NOMINAL	NOMINAL	NOMINAL	NOMINAL	MIN.	MAX.
1206	3.06 (0.120)	1.60 (0.063)	0.40 (0.016)	1.22 (0.048)	0.63 (0.024)	0.50 (0.020)	0.76 (0.030)
2010	5.08 (0.200)	2.54 (0.100)	0.48 (0.019)	2.23 (0.088)	0.63 (0.024)	0.50 (0.020)	0.76 (0.030)

SUGGESTED LAND PATTERN (Option 0063)


CHIP SIZE	DIMENSIONS (in millimeters)		
	Z _{max.}	G _{min.}	X _{max.}
1206	3.91 (0.154)	0.50 (0.020)	1.73 (0.068)
2010	5.93 (0.233)	0.50 (0.020)	2.67 (0.105)



PERFORMANCE			
TESTS	CONDITIONS	REQUIREMENTS	TYPICAL VALUES AND DRIFTS
Termination adhesion	5N for 10 s	$\pm (0.25 \% + 0.05 \Omega)$	$< \pm 0.1 \%$
Resistance to solder heat	Immersion 10 s in Sn/Pb 60/40 at + 260 °C	$\pm (0.25 \% + 0.05 \Omega)$	$< \pm 0.1 \%$
Rapid temperature change	5 cycles - 55 °C to + 155 °C	$\pm (0.25 \% + 0.05 \Omega)$	$< \pm 0.1 \%$
Climatic sequence	Phase A dry heat Phase B damp heat Phase C cold - 55 °C Phase D damp heat 5 cycles	$\pm (1 \% + 0.05 \Omega)$	$< \pm 0.2 \%$
Humidity (steady state)	56 days	$\pm (1 \% + 0.05 \Omega)$	$< \pm 0.2 \%$
Moisture resistance	AEC-Q200 85 °C/85 % RH/Pn 1000 h	3 % + 0.05 Ω	Max. $< 3 \% + 0.05 \Omega$
Short time overload	6.25 Pn for 2 s	$\pm (0.25 \% + 0.05 \Omega)$	$< \pm 0.1 \%$
Load life	1000 h at rated power at 230 °C	-	1 % max.
Shelf life	1000 h at 245 °C	-	1 % max.

GLOBAL PART NUMBER INFORMATION																	
Global Part Numbering: CHPHT0805K1001FGT																	
C	H	P	H	T	0	8	0	5	K	1	0	0	1	F	G	T	
GLOBAL MODEL	SIZE	TCR	VALUE	TOLERANCE	TERMINATION (1)	PACKAGING (2)	OPTION										
CHPHT	0603 0805 1206 2010	K = 100 ppm L = 200 ppm	The first 3 digits are significant figures and the last digit specifies the number of zeros to follow. R designates decimal point 10R0 = 10 Ω 3901 = 3900 Ω 1004 = 1 M Ω	F = $\pm 1 \%$ G = $\pm 2 \%$ J = $\pm 5 \%$	N: SnAg over nickel barrier G: Gold over nickel barrier	Blank = Waffle pack T = Tape and reel PT = Paper tape (3)	Leave blank if no option										

Notes

- (1) N terminations for temperature up to 200 °C
G terminations for temperature up to 230 °C
- (2) For specific quantity of parts per packaging please consult Vishay Sfernice
- (3) For paper tape please consult Vishay Sfernice



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.