





Copyright FCI.



PLATING CONTACT AREA:	
DASH NR:	PERFORMANCE LEVEL
-1YY	TELCORDIA CO
-2YY	CUSTOMER SPECIAL
-3YY	CUSTOMER SPECIAL
-9YY	TELCORDIA CO
-2YYLF	CUSTOMER SPECIAL
-9YYLF	TELCORDIA CO
-1YYLF	TELCORDIA CO
-3YYLF	CUSTOMER SPECIAL

OBSELETE
OBSELETE
OBSELETE
OBSELETE
OBSELETE
OBSELETE
OBSELETE

PC BOARD VERSIONS		
PRODUCTNR:	PCB THICKNESS	DIM'A"
70231-X01LF	1.6	2.90
70231-X11LF	2.4	3.53



PRODUCT AFTER HOT RIVETTING.



SEE NOTE 4.

RECOMMENDED HOLE PATTERN,
COMPONENT SIDE.

NOTES:

- 1 BODY MAT'L: LIQUID CRYSTAL POLYMER 30% GLASS
FLAME RETARDANT ACC. UL 94-V0
- 2 TERMINAL MATERIAL: PHOSPHOR BRONZE.
- 3 INDICATED HOLES ARE UNPLATED.
- 4 PRODUCT MARKING: PARTNUMBER & BATCH ID.
- 5 THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER
COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008
- 6 THE HOUSING WILL WITHSTAND EXPOSURE TO 260DEGREE PEAK
TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER
APPLICATION.
- 7 THE PRODUCT SPECIFICATION GS-12-453.

mat'l. code				tolerances unless otherwise specified			CUSTOMER COPY		FCI www.fciconnect.com								
ltr	ecn no	dr	date	linear	0.X ±0.30		projection 	title RA FEMALE POWER STB 12MM VERSION									
G	V70769	DDB	1997-06-02		0.XX ±0.15												
H	V00578	LLA	2000-03-16		0.XXX ±0.05												
J	V00847	LLA	2000-05-30	angles	0° ±2'			product family METRAL				code					
K	DG05-0107	CLU	2005-05-10	dr	R.TRLPPE	1990-09-18						size		dwg no		sheet	
L	DG07-0458	CEN	2007-11-15	enrg	BDUWKNEGT	1990-09-18						scale		A2		1 of 2	
M	N11-0131	AZH	2011-05-09	chr	VAN ZANTEN	1990-09-18	5:1	70231									
N	ELX-N-004584	AZH	2011-07-20	appd	VAN ZANTEN	1990-09-18											
sheet index		revision sheet		N	1-2												









Copyright FCI.

PLATING CONTACT AREA:	
DASH NR:	PERFORMANCE LEVEL
-1YY	TELCORDIA CO
-2YY	CUSTOMER SPECIAL
-3YY	CUSTOMER SPECIAL
-4YY	TELCORDIA CO
-5YYLF	CUSTOMER SPECIAL
-6YYLF	TELCORDIA CO
-7YYLF	TELCORDIA CO
-8YYLF	TELCORDIA CO
-9YYLF	CUSTOMER SPECIAL

OBSELETE
OBSELETE
OBSELETE
OBSELETE
OBSELETE
OBSELETE
OBSELETE

PC BOARD VERSIONS		
PRODUCTNR:	PCB THICKNESS	DIM"A"
70231-X02LF	1.6	2.90
70231-X12LF	2.4	3.53



- NOTES:
- 1 BODY MAT'L: LIQUID CRYSTAL POLYMER 30% GLASS
FLAME RETARDANT ACC. UL 94-V0
 - 2 TERMINAL MATERIAL: PHOSPHOR BRONZE.
 - 3 INDICATED HOLES ARE UNPLATED.
 - 4 PRODUCT MARKING: PARTNUMBER & BATCH ID.
 - 5 SET BACK FOR PRESS BLOCK.
 - 6 TOP SURFACE OF PRESS BLOCK MAY EXTEND UP TO
0.4MM HIGHER THAN HOUSING. THIS MAY AFFECT THE
TAIL LENGTH BEFORE APPLICATION TO A BOARD
 - 7 THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER
COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008
 - 8 THE HOUSING WILL WITHSTAND EXPOSURE TO 260DEGREE PEAK
TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER
APPLICATION.
 - 9 THE PRODUCT SPECIFICATION GS-12-453.

mat'l. code				tolerances unless otherwise specified			CUSTOMER COPY		 www.fciconnect.com								
ltr	ecn no	dr	date	linear	0.X ±0.30			projection 	title RA FEMALE POWER STB 12MM VERSION								
N	ELX-N-004584	AZH	2011-07-20		0.XX ±0.15												
					0.XXX ±0.05												
				angles	0° ±2°				product family METRAL size dwg no A2 70231								
				dr	R.TRLPPE	1990-09-18											
				enrg	BOUWKNEGT	1990-09-18											
				chr	VAN ZANTEN	1990-09-18	scale 5:1										
				appd	VAN ZANTEN	1990-09-18											
sheet index	revision sheet	N 1-2															



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.