



- Controller with power supply in a secure, tamper alarmed enclosure.
- Battery management / back-up facility (battery not supplied) provides up to 8 hours of operation during power failure.
- Vandal resistant, IP65 rated, secure keypad.
- Additional keypads also available.
- Audible and visual confirmation of code acceptance and code denied (at the keypad).
- Up to 100 programmable user codes can be stored for each keypad.



- 4, 5 and 6 digit PINs can be programmed.
- Door latched or door locked mode.
- Door forced alarm feature.
- Entry under duress alarm feature.
- Door sensor feature.
- Door bell feature with unique tone for each door.
- Software based tamper detection / alarm feature.
- Anti tamper switch on keypad to detect removal from back box.
- Back box suitable for surface fixing.
- Back box also suitable for fixing to UK, USA and European format flush mount electrical wall boxes (not supplied).



### Part Numbers

Storm-AXS StrikeMaster ES controller 240V with anti vandal keypad	DXPS1K10
Storm-AXS StrikeMaster ES controller 240V with illuminated keypad	DXPS1W10

### Specified for use with Storm AXS Access Control Solutions

	Part Numbers
Storm-AXS StrikeMaster ES Anti vandal keypad	DX1KT20
Storm-AXS StrikeMaster ES Illuminated keypad	DX2KW20
Storm-AXS Electro-magnetic door locks	DEL600, DEL1200, DEGL1200

## Stand-alone access control system for one or two doors

The new StrikeMaster ES is a robust and reliable Keypad Access Control System for installations requiring elevated security levels.



Constructed to survive in exposed, outdoor or unsupervised environments these systems combine the field proven durability of the StrikeMaster keypad with a separate, remotely secured electronic control module. The control module along with a dedicated high spec power supply is contained within a tamper alarmed steel enclosure. This enclosure is located within the secured building, protected from criminal attempts to breach or disable building security systems.

The control module supports both IN and OUT functionality of either one or two keypads (one or two doors).


Available in vandal resistant or robust illuminated versions.

### Electrical Input Specification

Voltage: 100 – 240V AC  
Max Current: 3A

### Electrical Output Specification

Voltage (on mains power): 13.4 – 14.2V DC (13.8V DC nominal)  
Voltage (on battery standby): 10 – 12.3V DC  
Max Current: 3A



Whilst every effort is made to ensure details are correct at time of print, specifications are subject to change without notice.



For more information & to order:  
[www.storm-interface.com](http://www.storm-interface.com)

Storm Interface products include technology protected by international patents and design registration. All rights reserved. Storm is a trademark of Keymat Technology Ltd. Storm Interface is a trading name of Keymat Technology Ltd.

SMESUS June 2015  
Designed & produced by NIK Design Ltd  
[www.nikdesign.co.uk](http://www.nikdesign.co.uk)



FM 39602





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.