

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0740571001](#)
Status: **Active**
Overview: [vhdm](#)
Description: 2.00mm (.079") Pitch VHDM® Board-to-Board Backplane Header, Vertical, 6-Row, Open Signal Module, 60 Circuits, 10 Columns, Pin Length 4.75mm (.187"), 0.76µm (30µ") Gold (Au) Plating

Documents:

[3D Model](#) [RoHS Certificate of Compliance \(PDF\)](#)
[Drawing \(PDF\)](#)

Agency Certification


UL E29179

General

Product Family Backplane Connectors
Series [74057](#)
Application Backplane
Application Tooling Documents Tooling Manual
Comments Open Header
Component Type PCB Header
Overview [vhdm](#)
Product Name VHDM®
Style N/A

Physical

Circuits (Loaded) 60
Circuits (maximum) 60
Color - Resin Black
Durability (mating cycles max) 200
First Mate / Last Break No
Flammability 94V-0
Guide to Mating Part No
Keying to Mating Part None
Material - Metal Beryllium Copper, High Performance Alloy (HPA)
Material - Plating Mating Gold
Material - Plating Termination Tin-Lead
Material - Resin High Temperature Thermoplastic
Number of Columns N/A
Number of Pairs Open Pin Field
Number of Rows 6
Orientation Vertical
PC Tail Length (in) 0.098 In
PC Tail Length (mm) 2.50 mm
PCB Locator No
PCB Retention None
PCB Thickness Recommended (in) 0.071 In
PCB Thickness Recommended (mm) 1.80 mm
Packaging Type Tube
Pitch - Mating Interface (in) 0.079 In
Pitch - Mating Interface (mm) 2.00 mm
Pitch - Term. Interface (in) 0.079 In
Pitch - Term. Interface (mm) 2.00 mm
Plating min: Mating (µin) 30
Plating min: Mating (µm) 0.75



Series

image - Reference only

EU RoHS

RoHS Compliant by Exemption

REACH SVHC

Contains SVHC: No Halogen-Free

Status

Halogen-Free

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[74057Series](#)

Mates With

[74030](#) VHDM® Board-to-Board Daughtercard Receptacle

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description	Product #
Flat Rock Tooling for Pneumatic Press	0622013700
VHDM® Insertion Module for Advanced Mate Signal Header, 6 Row by 11 Wide, 20.00mm (.787")	0622011101
VHDM® Signal Pin Inserter Repair Tool	0622015700

Plating min: Termination (µin)	30
Plating min: Termination (µm)	0.75
Polarized to PCB	Yes
Stackable	Yes
Surface Mount Compatible (SMC)	Yes
Temperature Range - Operating	105°C
Termination Interface: Style	Through Hole - Compliant Pin

Electrical

Current - Maximum per Contact	1A
Data Rate	3.125 Gbps
Real Signals (per 25mm)	75
Shield Type	Ground Plane Shield
Shielded	Yes
Voltage - Maximum	120V AC (RMS)/DC

Material Info

Reference - Drawing Numbers




Packaging Specification	PK-74057-003
Sales Drawing	SD-74057-002

VHDM and Very High Density Metric are trademarks of Amphenol Corporation

VHDM® 6 Row Pin and Shield Repair Tool	0622015800
VHDM® 6 Row Shield Extraction Tool	0622016000
VHDM® Insertion Module for Advanced Mate Signal Header, 6 Row by 10 Wide, 20.00mm (.787")	0622020203
VHDM® Insertion Module for Advanced Mate Signal Header, 6 Row by 10 Wide, 20.00mm (.787")	0622020207

This document was generated on 05/19/2010



PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION



BACKPLANE HOLE PATTERN RECOMMENDED DIMENSIONS


NOTES:

1. MATERIALS:
HOUSING - LIQUID CRYSTAL POLYMER (LCP),
GLASS-FILLED, UL 94V-0, COLOR: BLACK
SIGNAL PIN & SHIELD - COPPER ALLOY
2. FINISHES:
CONTACT AREA: SELECTIVE GOLD (Au)
PCB TAILS: SELECTIVE TIN/LEAD (Sn/Pb)
OR SELECTIVE MATTE TIN (Sn)
NICKEL (Ni) OVERALL.
3. THIS PART CONFORMS TO MOLEX PRODUCT
SPECIFICATION PS-74031-999
4. FOR MIXED CONTACT LENGTHS CONSULT
MOLEX FOR AVAILABILITY
5. FOR SPECIFIC MATERIAL NUMBERS & MATING
INFORMATION REFER TO SHEET 2
6. PACKAGE PER PK-74057-003
7. EITHER MARK PART WITH PART NUMBER & DATE
CODE APPROXIMATELY WHERE SHOWN OR PLACE
LABEL ON THE TUBE.





ADDED 15 COLUMN EC NO: UCP2006-1491 DRWN: JONIAK 2006/01/19 CHKD: JONIAK 2006/01/19 APPR: CBIXLER 2006/01/23				QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 2.5:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		
		mm	INCH		DRAWN BY	DATE	TITLE VHDM 6 ROW OPEN END BACKPLANE SALES ASSEMBLY						
4 PLACES		± ---	± ---		MWANG	1998/11/09							
3 PLACES		± ---	± ---		CHECKED BY	DATE							
2 PLACES		± ---	± ---		JLAURX	1998/11/09	MOLEX INCORPORATED						
1 PLACE		± ---	± ---		APPROVED BY	DATE							
		ANGULAR ±1/2°			CBIXLER	1998/11/09							
					MATERIAL NO.		DOCUMENT NO.		SHEET NO.				
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			SEE SHEET 3		SD-74057-002		1 OF 3				
K		REV			SIZE B		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION						

SIGNAL COLUMN
DAUGHTERCARD
CONNECTOR SIDE



0.41 OFFSET
SIGNAL TO SIGNAL

SHIELD
SIGNAL




ROW A

12.36

0.66
TOP DAUGHTERCARD
PCB TO $\varnothing$ ROW A

ROW A



MATERIAL NUMBER ASSIGNMENT

74057-*** ** SEE TABLES (SHEET 3)

NUMBER OF COLUMNS/PLATING
10 = 10 COLUMN TIN/LEAD
15 = 15 COLUMN TIN/LEAD
25 = 25 COLUMN TIN/LEAD
90 = 10 COLUMN MATTE TIN
95 = 15 COLUMN MATTE TIN
85 = 25 COLUMN MATTE TIN

ADDED 15 COLUMN EC NO: UCP2006-1491 DRWN: JONI AK 2006/01/19 CHKD: JONI AK 2006/01/19 APPR: CBIXLER 2006/01/23 K	QUALITY SYMBOLS ▽=0 ▽=0	DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
				mm	INCH	DRAWN BY MWANG	DATE 1998/11/09	VHDM 6 ROW OPEN END BACKPLANE SALES ASSEMBLY MOLEX INCORPORATED		
			4 PLACES	± ---	± ---	CHECKED BY	DATE			
			3 PLACES	± ---	± ---	JLAURX	1998/11/09			
			2 PLACES	± ---	± ---	APPROVED BY	DATE			
			1 PLACE	± ---	± ---	CBIXLER	1998/11/09	MOLEX		
			ANGULAR ±1/2°		MATERIAL NO.		DOCUMENT NO.		SHEET NO.	
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE SHEET 3		SD-74057-002		2 OF 3	
REV			THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION							

	10	9	8	7	6	5	4	3	2	1																																																																																																																																																																																																																																																															
F	<table><tr><th>PART NUMBER</th><th>COLUMN</th><th>NUMBER OF SIGNAL</th><th>NUMBER OF PIN</th><th>NUMBER OF SHIELD</th><th>A</th><th>B</th><th>M</th><th>Au (um) THICKNESS</th></tr><tr><td>74057-1001</td><td rowspan="2">10</td><td rowspan="2">60</td><td rowspan="2">10</td><td rowspan="2">20.00</td><td rowspan="2">18.00</td><td rowspan="6">4.75</td><td rowspan="6"></td><td>0.76</td></tr><tr><td>74057-1006</td><td>1.27</td></tr><tr><td>74057-1501</td><td rowspan="2">15</td><td rowspan="2">90</td><td rowspan="2">15</td><td rowspan="2">30.00</td><td rowspan="2">28.00</td><td>0.76</td></tr><tr><td>74057-1506</td><td>1.27</td></tr><tr><td>74057-2501</td><td rowspan="2">25</td><td rowspan="2">150</td><td rowspan="2">25</td><td rowspan="2">50.00</td><td rowspan="2">48.00</td><td>0.76</td></tr><tr><td>74057-2501</td><td>1.27</td></tr><tr><td>74057-1002</td><td rowspan="2">10</td><td rowspan="2">60</td><td rowspan="2">10</td><td rowspan="2">20.00</td><td rowspan="2">18.00</td><td>0.76</td></tr><tr><td>74057-1007</td><td>1.27</td></tr><tr><td>74057-1502</td><td rowspan="2">15</td><td rowspan="2">90</td><td rowspan="2">15</td><td rowspan="2">30.00</td><td rowspan="2">28.00</td><td>0.76</td></tr><tr><td>74057-1507</td><td>1.27</td></tr><tr><td>74057-2502</td><td rowspan="2">25</td><td rowspan="2">150</td><td rowspan="2">25</td><td rowspan="2">50.00</td><td rowspan="2">48.00</td><td>0.76</td></tr><tr><td>74057-2507</td><td>1.27</td></tr><tr><td>74057-1003</td><td rowspan="2">10</td><td rowspan="2">60</td><td rowspan="2">10</td><td rowspan="2">20.00</td><td rowspan="2">18.00</td><td rowspan="6">4.25</td><td rowspan="6"></td><td>0.76</td></tr><tr><td>74057-1008</td><td>1.27</td></tr><tr><td>74057-1503</td><td rowspan="2">15</td><td rowspan="2">90</td><td rowspan="2">15</td><td rowspan="2">30.00</td><td rowspan="2">28.00</td><td>0.76</td></tr><tr><td>74057-1508</td><td>1.27</td></tr><tr><td>74057-2503</td><td rowspan="2">25</td><td rowspan="2">150</td><td rowspan="2">25</td><td rowspan="2">50.00</td><td rowspan="2">48.00</td><td>0.76</td></tr><tr><td>74057-2508</td><td>1.27</td></tr><tr><td>74057-1004</td><td rowspan="2">10</td><td rowspan="2">60</td><td rowspan="2">10</td><td rowspan="2">20.00</td><td rowspan="2">18.00</td><td rowspan="6">5.15</td><td rowspan="6"></td><td>0.76</td></tr><tr><td>74057-1009</td><td>1.27</td></tr><tr><td>74057-1504</td><td rowspan="2">15</td><td rowspan="2">90</td><td rowspan="2">15</td><td rowspan="2">30.00</td><td rowspan="2">28.00</td><td>0.76</td></tr><tr><td>74057-1509</td><td>1.27</td></tr><tr><td>74057-2504</td><td rowspan="2">25</td><td rowspan="2">150</td><td rowspan="2">25</td><td rowspan="2">50.00</td><td rowspan="2">48.00</td><td>0.76</td></tr><tr><td>74057-2509</td><td>1.27</td></tr></table>								PART NUMBER	COLUMN	NUMBER OF SIGNAL	NUMBER OF PIN	NUMBER OF SHIELD	A	B	M	Au (um) THICKNESS	74057-1001	10	60	10	20.00	18.00	4.75		0.76	74057-1006	1.27	74057-1501	15	90	15	30.00	28.00	0.76	74057-1506	1.27	74057-2501	25	150	25	50.00	48.00	0.76	74057-2501	1.27	74057-1002	10	60	10	20.00	18.00	0.76	74057-1007	1.27	74057-1502	15	90	15	30.00	28.00	0.76	74057-1507	1.27	74057-2502	25	150	25	50.00	48.00	0.76	74057-2507	1.27	74057-1003	10	60	10	20.00	18.00	4.25		0.76	74057-1008	1.27	74057-1503	15	90	15	30.00	28.00	0.76	74057-1508	1.27	74057-2503	25	150	25	50.00	48.00	0.76	74057-2508	1.27	74057-1004	10	60	10	20.00	18.00	5.15		0.76	74057-1009	1.27	74057-1504	15	90	15	30.00	28.00	0.76	74057-1509	1.27	74057-2504	25	150	25	50.00	48.00	0.76	74057-2509	1.27	<table><tr><th>PART NUMBER</th><th>COLUMN</th><th>NUMBER OF SIGNAL</th><th>NUMBER OF PIN</th><th>NUMBER OF SHIELD</th><th>A</th><th>B</th><th>M</th><th>Au (um) THICKNESS</th></tr><tr><td>74057-9001</td><td rowspan="2">10</td><td rowspan="2">60</td><td rowspan="2">10</td><td rowspan="2">20.00</td><td rowspan="2">18.00</td><td rowspan="6">4.75</td><td rowspan="6"></td><td>0.76</td></tr><tr><td>74057-9006</td><td>1.27</td></tr><tr><td>74057-9501</td><td rowspan="2">15</td><td rowspan="2">90</td><td rowspan="2">15</td><td rowspan="2">30.00</td><td rowspan="2">28.00</td><td>0.76</td></tr><tr><td>74057-9506</td><td>1.27</td></tr><tr><td>74057-8501</td><td rowspan="2">25</td><td rowspan="2">150</td><td rowspan="2">25</td><td rowspan="2">50.00</td><td rowspan="2">48.00</td><td>0.76</td></tr><tr><td>74057-8501</td><td>1.27</td></tr><tr><td>74057-9002</td><td rowspan="2">10</td><td rowspan="2">60</td><td rowspan="2">10</td><td rowspan="2">20.00</td><td rowspan="2">18.00</td><td rowspan="6">6.25</td><td rowspan="6"></td><td>0.76</td></tr><tr><td>74057-9007</td><td>1.27</td></tr><tr><td>74057-9502</td><td rowspan="2">15</td><td rowspan="2">90</td><td rowspan="2">15</td><td rowspan="2">30.00</td><td rowspan="2">28.00</td><td>0.76</td></tr><tr><td>74057-9507</td><td>1.27</td></tr><tr><td>74057-8502</td><td rowspan="2">25</td><td rowspan="2">150</td><td rowspan="2">25</td><td rowspan="2">50.00</td><td rowspan="2">48.00</td><td>0.76</td></tr><tr><td>74057-8507</td><td>1.27</td></tr><tr><td>74057-9003</td><td rowspan="2">10</td><td rowspan="2">60</td><td rowspan="2">10</td><td rowspan="2">20.00</td><td rowspan="2">18.00</td><td rowspan="6">4.25</td><td rowspan="6"></td><td>0.76</td></tr><tr><td>74057-9008</td><td>1.27</td></tr><tr><td>74057-9503</td><td rowspan="2">15</td><td rowspan="2">90</td><td rowspan="2">15</td><td rowspan="2">30.00</td><td rowspan="2">28.00</td><td>0.76</td></tr><tr><td>74057-9508</td><td>1.27</td></tr><tr><td>74057-8503</td><td rowspan="2">25</td><td rowspan="2">150</td><td rowspan="2">25</td><td rowspan="2">50.00</td><td rowspan="2">48.00</td><td>0.76</td></tr><tr><td>74057-8508</td><td>1.27</td></tr><tr><td>74057-9004</td><td rowspan="2">10</td><td rowspan="2">60</td><td rowspan="2">10</td><td rowspan="2">20.00</td><td rowspan="2">18.00</td><td rowspan="6">5.15</td><td rowspan="6"></td><td>0.76</td></tr><tr><td>74057-9009</td><td>1.27</td></tr><tr><td>74057-9504</td><td rowspan="2">15</td><td rowspan="2">90</td><td rowspan="2">15</td><td rowspan="2">30.00</td><td rowspan="2">28.00</td><td>0.76</td></tr><tr><td>74057-9509</td><td>1.27</td></tr><tr><td>74057-8504</td><td rowspan="2">25</td><td rowspan="2">150</td><td rowspan="2">25</td><td rowspan="2">50.00</td><td rowspan="2">48.00</td><td>0.76</td></tr><tr><td>74057-8509</td><td>1.27</td></tr></table>								PART NUMBER	COLUMN	NUMBER OF SIGNAL	NUMBER OF PIN	NUMBER OF SHIELD	A	B	M	Au (um) THICKNESS	74057-9001	10	60	10	20.00	18.00	4.75		0.76	74057-9006	1.27	74057-9501	15	90	15	30.00	28.00	0.76	74057-9506	1.27	74057-8501	25	150	25	50.00	48.00	0.76	74057-8501	1.27	74057-9002	10	60	10	20.00	18.00	6.25		0.76	74057-9007	1.27	74057-9502	15	90	15	30.00	28.00	0.76	74057-9507	1.27	74057-8502	25	150	25	50.00	48.00	0.76	74057-8507	1.27	74057-9003	10	60	10	20.00	18.00	4.25		0.76	74057-9008	1.27	74057-9503	15	90	15	30.00	28.00	0.76	74057-9508	1.27	74057-8503	25	150	25	50.00	48.00	0.76	74057-8508	1.27	74057-9004	10	60	10	20.00	18.00	5.15		0.76	74057-9009	1.27	74057-9504	15	90	15	30.00	28.00	0.76	74057-9509	1.27	74057-8504	25	150	25	50.00	48.00	0.76	74057-8509	1.27	F
PART NUMBER	COLUMN	NUMBER OF SIGNAL	NUMBER OF PIN	NUMBER OF SHIELD	A	B	M	Au (um) THICKNESS																																																																																																																																																																																																																																																																	
74057-1001	10	60	10	20.00	18.00	4.75		0.76																																																																																																																																																																																																																																																																	
74057-1006								1.27																																																																																																																																																																																																																																																																	
74057-1501	15	90	15	30.00	28.00			0.76																																																																																																																																																																																																																																																																	
74057-1506								1.27																																																																																																																																																																																																																																																																	
74057-2501	25	150	25	50.00	48.00			0.76																																																																																																																																																																																																																																																																	
74057-2501								1.27																																																																																																																																																																																																																																																																	
74057-1002	10	60	10	20.00	18.00	0.76																																																																																																																																																																																																																																																																			
74057-1007						1.27																																																																																																																																																																																																																																																																			
74057-1502	15	90	15	30.00	28.00	0.76																																																																																																																																																																																																																																																																			
74057-1507						1.27																																																																																																																																																																																																																																																																			
74057-2502	25	150	25	50.00	48.00	0.76																																																																																																																																																																																																																																																																			
74057-2507						1.27																																																																																																																																																																																																																																																																			
74057-1003	10	60	10	20.00	18.00	4.25		0.76																																																																																																																																																																																																																																																																	
74057-1008								1.27																																																																																																																																																																																																																																																																	
74057-1503	15	90	15	30.00	28.00			0.76																																																																																																																																																																																																																																																																	
74057-1508								1.27																																																																																																																																																																																																																																																																	
74057-2503	25	150	25	50.00	48.00			0.76																																																																																																																																																																																																																																																																	
74057-2508								1.27																																																																																																																																																																																																																																																																	
74057-1004	10	60	10	20.00	18.00	5.15		0.76																																																																																																																																																																																																																																																																	
74057-1009								1.27																																																																																																																																																																																																																																																																	
74057-1504	15	90	15	30.00	28.00			0.76																																																																																																																																																																																																																																																																	
74057-1509								1.27																																																																																																																																																																																																																																																																	
74057-2504	25	150	25	50.00	48.00			0.76																																																																																																																																																																																																																																																																	
74057-2509								1.27																																																																																																																																																																																																																																																																	
PART NUMBER	COLUMN	NUMBER OF SIGNAL	NUMBER OF PIN	NUMBER OF SHIELD	A	B	M	Au (um) THICKNESS																																																																																																																																																																																																																																																																	
74057-9001	10	60	10	20.00	18.00	4.75		0.76																																																																																																																																																																																																																																																																	
74057-9006								1.27																																																																																																																																																																																																																																																																	
74057-9501	15	90	15	30.00	28.00			0.76																																																																																																																																																																																																																																																																	
74057-9506								1.27																																																																																																																																																																																																																																																																	
74057-8501	25	150	25	50.00	48.00			0.76																																																																																																																																																																																																																																																																	
74057-8501								1.27																																																																																																																																																																																																																																																																	
74057-9002	10	60	10	20.00	18.00	6.25		0.76																																																																																																																																																																																																																																																																	
74057-9007								1.27																																																																																																																																																																																																																																																																	
74057-9502	15	90	15	30.00	28.00			0.76																																																																																																																																																																																																																																																																	
74057-9507								1.27																																																																																																																																																																																																																																																																	
74057-8502	25	150	25	50.00	48.00			0.76																																																																																																																																																																																																																																																																	
74057-8507								1.27																																																																																																																																																																																																																																																																	
74057-9003	10	60	10	20.00	18.00	4.25		0.76																																																																																																																																																																																																																																																																	
74057-9008								1.27																																																																																																																																																																																																																																																																	
74057-9503	15	90	15	30.00	28.00			0.76																																																																																																																																																																																																																																																																	
74057-9508								1.27																																																																																																																																																																																																																																																																	
74057-8503	25	150	25	50.00	48.00			0.76																																																																																																																																																																																																																																																																	
74057-8508								1.27																																																																																																																																																																																																																																																																	
74057-9004	10	60	10	20.00	18.00	5.15		0.76																																																																																																																																																																																																																																																																	
74057-9009								1.27																																																																																																																																																																																																																																																																	
74057-9504	15	90	15	30.00	28.00			0.76																																																																																																																																																																																																																																																																	
74057-9509								1.27																																																																																																																																																																																																																																																																	
74057-8504	25	150	25	50.00	48.00			0.76																																																																																																																																																																																																																																																																	
74057-8509								1.27																																																																																																																																																																																																																																																																	
E									E																																																																																																																																																																																																																																																																
D									D																																																																																																																																																																																																																																																																
C									C																																																																																																																																																																																																																																																																
B	TIN/LEAD CHART								LEAD FREE CHART								B																																																																																																																																																																																																																																																								
A	<table><tr><td rowspan="10">ADDED 15 COLUMN EC NO: UCP2006-1491 DRWN: JJONIAK 2006/01/19 CHKD: JJONIAK 2006/01/19 APPR: CBI XLER 2006/01/23</td><td rowspan="10">QUALITY SYMBOLS ▽=0 ▽=0</td><td colspan="2">GENERAL TOLERANCES (UNLESS SPECIFIED)</td><td colspan="2">DIMENSION STYLE MM ONLY</td><td>SCALE ---</td><td>DESIGN UNITS METRIC</td><td colspan="2">THIRD ANGLE PROJECTION</td></tr><tr><td rowspan="4">4 PLACES 3 PLACES 2 PLACES 1 PLACE</td><td>±---</td><td>±---</td><td rowspan="4">DRAWN BY JJONIAK 2006/01/10 CHECKED BY JJONIAK 2006/01/10 APPROVED BY JJONIAK 2006/01/10</td><td rowspan="4">DATE 2006/01/10</td><td rowspan="4">TITLE VHDM 6 ROW OPEN END BACKPLANE SALES ASSEMBLY</td></tr><tr><td>mm</td><td>INCH</td></tr><tr><td>±---</td><td>±---</td></tr><tr><td>±---</td><td>±---</td></tr><tr><td colspan="2">ANGULAR ±1/2°</td><td colspan="2">MATERIAL NO. SEE CHARTS</td><td colspan="2">DOCUMENT NO. SD-74057-002</td><td colspan="2">SHEET NO. 3 OF 3</td></tr><tr><td colspan="2">DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS</td><td colspan="6">THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION</td></tr><tr><td>K</td><td>REV</td><td colspan="10"></td></tr></table>										ADDED 15 COLUMN EC NO: UCP2006-1491 DRWN: JJONIAK 2006/01/19 CHKD: JJONIAK 2006/01/19 APPR: CBI XLER 2006/01/23	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		4 PLACES 3 PLACES 2 PLACES 1 PLACE	±---	±---	DRAWN BY JJONIAK 2006/01/10 CHECKED BY JJONIAK 2006/01/10 APPROVED BY JJONIAK 2006/01/10	DATE 2006/01/10	TITLE VHDM 6 ROW OPEN END BACKPLANE SALES ASSEMBLY	mm	INCH	±---	±---	±---	±---	ANGULAR ±1/2°		MATERIAL NO. SEE CHARTS		DOCUMENT NO. SD-74057-002		SHEET NO. 3 OF 3		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION						K	REV																					A																																																																																																																																																																																																		
ADDED 15 COLUMN EC NO: UCP2006-1491 DRWN: JJONIAK 2006/01/19 CHKD: JJONIAK 2006/01/19 APPR: CBI XLER 2006/01/23	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION																																																																																																																																																																																																																																																																	
		4 PLACES 3 PLACES 2 PLACES 1 PLACE	±---	±---	DRAWN BY JJONIAK 2006/01/10 CHECKED BY JJONIAK 2006/01/10 APPROVED BY JJONIAK 2006/01/10	DATE 2006/01/10	TITLE VHDM 6 ROW OPEN END BACKPLANE SALES ASSEMBLY																																																																																																																																																																																																																																																																		
			mm	INCH																																																																																																																																																																																																																																																																					
			±---	±---																																																																																																																																																																																																																																																																					
			±---	±---																																																																																																																																																																																																																																																																					
		ANGULAR ±1/2°		MATERIAL NO. SEE CHARTS		DOCUMENT NO. SD-74057-002		SHEET NO. 3 OF 3																																																																																																																																																																																																																																																																	
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																																																																																																																																																																																																																																																																					
		K	REV																																																																																																																																																																																																																																																																						
			ib_frame_B_P_ME_T Rev. D 2004/04/02	9	8	7	6	5	4	3			2	1																																																																																																																																																																																																																																																											



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.