

# SEALED, ILLUMINATED ROCKER SWITCHES

**K3**  
SEALED  
ROCKERS

ATTRACTIVE & RUGGED FOR WET & DUSTY ENVIRONMENTS

The OTTO K3 rocker switch is a quality, precision switch designed to comply with standards established for appliance, marine (ignition protection) and off-road vehicles along with other demanding applications where rugged rocker switches are required.

K3 sealed rocker switches snap into industry-standard panel cutouts. Choose illuminated and printed legends, thru-panel drain option and switching compatibility from low level to 20 amps.

The K3 offers a choice of LED, incandescent and neon illumination. Legends can be stamped onto a non-illuminated button, stamped onto an illuminated lens or laser etched into the lens and backlit.

Available in standard and low level contact ratings, the K3 rockers will fit a wide range of applications. Expect a minimum of 25,000 cycles at a full rated load of 20 amps resistive or 15 amps inductive. 100,000 cycles mechanical. A full complement of switch operation is available including momentary and maintained action in 2 or 3-position switches in SPST, SPDT, SPTT, DPST and DPDT circuit arrangements.

OTTO can provide custom colors upon request. Value-added assemblies with wire leads are also available. Please consult the factory for assistance.

## Features:

- **Sealed watertight per IP68S**
- **Snap-in panel mounting into industry standard panel cutout**
- **Optional panel seal gasket**
- **Thru-panel drain option**
- **LED, neon & incandescent lighting**
- **0.250" Quick Connect terminals**
- **Optional one-piece connector**
- **Optional terminal barriers**
- **Low level up to 20 amp switch**
- **Configurable Single Pole Triple Throw (SPTT) with external jumpers**
- **RoHS/WEEE/Reach compliant**



| Standard Characteristics/Ratings: |                                                                                                          |                             |
|-----------------------------------|----------------------------------------------------------------------------------------------------------|-----------------------------|
| ELECTRICAL RATINGS:               |                                                                                                          |                             |
| Load                              | Sea Level<br>@ 12/28VDC                                                                                  | Sea Level<br>@ 125VAC, 60Hz |
| Resistive                         | 20A                                                                                                      | 16A                         |
| Inductive                         | 15A                                                                                                      | 15A                         |
| Lamp                              | 5A                                                                                                       | 5A                          |
| Motor                             | 0.5HP @ 110VAC                                                                                           |                             |
| DWV                               | 1050Vrms except across light terminals                                                                   |                             |
| Low Level                         | 10mA @ 30mV                                                                                              |                             |
| Electrical Life:                  | 25,000 cycles                                                                                            |                             |
| LIGHTING:                         |                                                                                                          |                             |
| Light Source                      | Rating                                                                                                   |                             |
| Incandescent                      | (VDC) 6V, 12V, 24V                                                                                       |                             |
| Neon                              | (VAC) 125V, 250V                                                                                         |                             |
| LED                               | (VDC) 2V, 6V, 12V, 24V                                                                                   |                             |
| Mechanical Life:                  | 100,000 cycles                                                                                           |                             |
| Seal:                             | IP68S                                                                                                    |                             |
| Operating Temp Range:             | -40°C to +85°C                                                                                           |                             |
| MATERIALS:                        |                                                                                                          |                             |
| Case:                             | Thermoplastic, black                                                                                     |                             |
| Button:                           | Thermoplastic                                                                                            |                             |
| Terminals/Contact:                | Brass, silver alloy with silver plate, gold flash for low level                                          |                             |
| Terminal Hardware:                | K3 series recommended Quick Connect terminals:<br>AMP 60253-2 for 12-16 AWG<br>AMP 42100-2 for 14-18 AWG |                             |
| Mounting Hardware:                | None provided                                                                                            |                             |

## K3 SERIES PART NUMBER CODE

Part Number Code Continued Below

**K3**      **X**      **X**

### Base Options

- A.** With Keying Pin Only  
Standard Rating  
Silver Plate
- B.** Without Barriers or Pin  
Standard Rating  
Silver Plate
- C.** With Terminal Barriers Only  
Standard Rating  
Silver Plate
- D.** With Keying Pin Only  
Low Level Rating  
Gold Plate
- E.** Without Barriers or Pin  
Low Level Rating  
Gold Plate
- F.** With Terminal Barriers Only  
Low Level Rating  
Gold Plate
- G.** With Keying Pin Only  
Standard Rating  
No Plate
- H.** Without Barriers or Pin  
Standard Rating  
No Plate
- J.** With Terminal Barriers Only  
Standard Rating  
No Plate

### Case Style/Button Color

- A.** Case With Drain Holes  
Button Color: Black
  - B.** Case Without Drain Holes  
Button Color: Black
  - C.** Case With Drain Holes  
Button Color: Red
  - D.** Case Without Drain Holes  
Button Color: Red
  - E.** Case With Drain Holes  
Button Color: White
  - F.** Case Without Drain Holes  
Button Color: White
- NOTE: Switch case is black for all options below:
- Case With Drain Holes  
Button Not Included
  - Case Without Drain Holes  
Button Not Included

### Switch Action/Circuit

|            | Position<br>"A" | Position<br>"B" | Position<br>"C" | Circuit |
|------------|-----------------|-----------------|-----------------|---------|
| <b>1A.</b> | 3-4             | NONE            | OFF             | SPST    |
| <b>2A.</b> | 3-4/8-9         | NONE            | OFF             | DPST    |
| <b>1B.</b> | 3-4             | NONE            | 3-2             | SPDT    |
| <b>2B.</b> | 3-4/8-9         | NONE            | 3-2/8-7         | DPDT    |
| <b>1C.</b> | (3-4)           | NONE            | OFF             | SPST    |
| <b>2C.</b> | (3-4)/(8-9)     | NONE            | OFF             | DPST    |
| <b>1D.</b> | (3-4)           | NONE            | 3-2             | SPDT    |
| <b>2D.</b> | (3-4)/(8-9)     | NONE            | 3-2/8-7         | DPDT    |
| <b>1E.</b> | (3-4)           | OFF             | (3-2)           | SPDT    |
| <b>2E.</b> | (3-4)/(8-9)     | OFF             | (3-2)/(8-7)     | DPDT    |
| <b>1F.</b> | 3-4             | OFF             | 3-2             | SPDT    |
| <b>2F.</b> | 3-4/8-9         | OFF             | 3-2/8-7         | DPDT    |
| <b>1G.</b> | (3-4)           | OFF             | 3-2             | SPDT    |
| <b>2G.</b> | (3-4)/(8-9)     | OFF             | 3-2/8-7         | DPDT    |

### Special Circuits

|            | Position<br>"A" | Position<br>"B" | Position<br>"C" | Special<br>Circuits |
|------------|-----------------|-----------------|-----------------|---------------------|
| <b>1H.</b> | 3-4/8-9         | 8-9             | OFF             | ON/ON/OFF           |
| <b>1J.</b> | 3-4/8-9         | 8-9             | NONE            | ON/ON/NONE          |
| <b>1K.</b> | (3-4)/(8-9)     | 8-9             | OFF             | (ON)/ON/OFF         |
| <b>1L.</b> | (3-4)/(8-9)     | 8-9             | NONE            | (ON)/ON/NONE        |
| <b>1M.</b> | 3-4/8-9         | 3-2/8-9         | 3-2/8-7         | ON/ON/ON            |
| <b>1N.</b> | (3-4)/(8-9)     | 3-2/8-9         | 3-2/8-7         | (ON)/ON/ON          |
| <b>1P.</b> | (3-4)/(8-9)     | 3-2/8-9         | (3-2)/(8-7)     | (ON)/ON/(ON)        |
| <b>2R.</b> | 3-4/8-9         | OFF/8-9         | OFF/OFF         | ON/OFF/OFF          |
| <b>2S.</b> | (3-4)/8-9       | OFF/8-9         | OFF/OFF         | (ON)/OFF/OFF        |

NOTE: ( ) denotes momentary action.


### Light Source Type

- A.** No Illumination
- B.** 6V Incandescent
- C.** 12V Incandescent
- D.** 24V Incandescent
- E.** 125VAC Neon
- F.** 250VAC Neon
- G.** 2V Red LED
- H.** 2V Green LED
- J.** 2V Amber LED
- K.** 6V Red LED
- L.** 6V Green LED
- M.** 6V Amber LED
- N.** 12V Red LED
- P.** 12V Green LED
- Q.** 12V Amber LED
- R.** 24V Red LED
- S.** 24V Green LED
- T.** 24V Amber LED

### Light Circuit

| Circuit               | Terminal<br>Connections |
|-----------------------|-------------------------|
| <b>A.</b> None        | None                    |
| <b>B.</b> Dep. in "A" | 1(-) & 4(+)             |
| <b>C.</b> Dep. in "C" | 2(+) & 5(-)             |
| <b>D.</b> Ind. in "A" | 1(-) & 6(+)             |
| <b>E.</b> Ind. in "C" | 5(-) & 10(+)            |
| <b>F.</b> Dep. in "A" | 1(-) & 4(+)             |
| <b>J.</b> Dep. in "C" | 2(+) & 5(-)             |
| <b>G.</b> Dep. in "A" | 1(-) & 4(+)             |
| <b>L.</b> Ind. in "C" | 5(-) & 10(+)            |
| <b>H.</b> Ind. in "A" | 1(-) & 6(+)             |
| <b>N.</b> Dep. in "C" | 2(+) & 5(-)             |
| <b>J.</b> Ind. in "A" | 1(-) & 6(+)             |
| <b>Q.</b> Ind. in "C" | 5(-) & 10(+)            |

NOTE: Polarity only applies to LED circuits.



## K3 PART NUMBER CODE - CONTINUED FROM ABOVE

**X**

### Lens Color

- Position "A"**
- 1. Transparent Red
- 2. Transparent Green
- 3. Transparent Amber ①
- 4. Clear ①
- 5. Translucent White ②
- Z. No Lens ③

NOTE: It is not recommended to use green LEDs with translucent white lenses. This will reduce light intensity. Use clear lenses with green LEDs for maximum light intensity.

- ① Recommended for neon lamps.
- ② Special Order: Ultra bright green LED to be used with translucent white lenses.
- ③ Legend colors "B" & "D" are only available on lens color "Z".

**STOP HERE** for  
lighted switches  
without legends.

Example: K3AAIFNH-44

### Legend Style

- Position "A"**
  - ZZ. No Legend
- NOTE: For all other legend options, refer to the legend table on page 162, find the two digit code and enter the code in the appropriate position(s).

### Legend Color

- Position "A"**
- 1. Red
- 2. Black
- 9. White
- B. Backlight/Daylight White ④
- D. Backlight/Deadfront ④
- Z. No Legend

④ For legend color "B" and "D", please use button color "A" & "B" and lens color "Z" for each position.

### Legend Orientation

- Position "A"**
- Position "C"**
- 1. Std. 

|   |   |
|---|---|
| A | C |
|---|---|
- 2. 90° 



|   |   |
|---|---|
| ⤵ | ⤴ |
|---|---|
- 3. 180° 

|   |   |
|---|---|
| ⤵ | ⤴ |
|---|---|
- 4. 270° 

|   |   |
|---|---|
| ⤵ | ⤴ |
|---|---|

**STOP HERE** for  
unlighted switches  
without legends.

Example: K3AAIFAA



**K3 Connector**  
P/N 801775-2A Without Latches  
P/N 801775-2B With Latches

**Panel Seal Gasket**  
P/N 807037

Order separately for use with switches without drain holes.

**Panel Plug**  
See Panel Plug (PP) page 167.

• K3 panel plugs available as shown on page 160.


Recommended Quick Connect Terminals:  
AMP 60253-2 for 12-16 AWG  
AMP 42100-2 for 14-18 AWG

# SEALED, ILLUMINATED ROCKER SWITCHES

**K3**  
SEALED  
ROCKERS

SNAP-IN PANEL MOUNTING, ATTRACTIVE & RUGGED FOR WET & DUSTY ENVIRONMENTS

ROCKER SWITCHES



|                                                                                                                                                                                                                                                                                                         |  |                                                                              |  |                                                                                       |  |                                                                                                            |  |                                                                                                          |  |                                                                                         |  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|------------------------------------------------------------------------------|--|---------------------------------------------------------------------------------------|--|------------------------------------------------------------------------------------------------------------|--|----------------------------------------------------------------------------------------------------------|--|-----------------------------------------------------------------------------------------|--|
| <p>K3...1M...--</p> <p>POS "A"      POS "B"      POS "C"</p> <p>SPECIAL CIRCUIT - ON-ON-ON SCHEMATIC</p>                                                                                                                                                                                                |  | <p>K3...2A...--</p> <p>DPST-ON-NONE-OFF SCHEMATIC</p>                        |  | <p>K3...2B...--</p> <p>DPDT-ON-NONE-ON SCHEMATIC</p>                                  |  | <p>K3...2C...--</p> <p>DPST-(ON)-NONE-OFF SCHEMATIC</p>                                                    |  | <p>K3...2D...--</p> <p>DPDT-(ON)-NONE-ON SCHEMATIC</p>                                                   |  |                                                                                         |  |
| <p>GENERAL SCHEMATIC INFORMATION</p> <p>○—○ INDICATES MAINTAIN ACTION (FIXED POSITION)</p> <p>▼—○ INDICATES MOMENTARY ACTION (AUTOMATIC RETURN ACTION)</p> <p>FOR OTHER LIGHTING SCHEMATICS REPLACE FOLLOWING SYMBOLS:</p> <p> INCANDESCENT (REPLACE RESISTOR &amp; LED)</p> <p> NEON (REPLACE LED)</p> |  | <p>K3...2E...--</p> <p>DPDT-(ON)-OFF-(ON) SCHEMATIC</p>                      |  | <p>K3...2F...--</p> <p>DPDT-ON-OFF-ON SCHEMATIC</p>                                   |  | <p>K3...2G...--</p> <p>DPDT-(ON)-OFF-ON SCHEMATIC</p>                                                      |  | <p>K3...2BNC-Z</p> <p>DPDT-ON-NONE-ON SCHEMATIC W/DEPENDENT LED IN "A"</p>                               |  | <p>K3...2BNC-Z</p> <p>DPDT-ON-NONE-ON SCHEMATIC W/DEPENDENT LED IN "C"</p>              |  |
| <p>K3...2BND-Z</p> <p>DPDT-ON-NONE-ON SCHEMATIC W/INDEPENDENT LED IN "A"</p>                                                                                                                                                                                                                            |  | <p>K3...2BNE-Z</p> <p>DPDT-ON-NONE-ON SCHEMATIC W/INDEPENDENT LED IN "C"</p> |  | <p>K3...2BNF...</p> <p>DPDT-ON-NONE-ON SCHEMATIC W/DEPENDENT LED IN "A" &amp; "C"</p> |  | <p>K3...2BNG...</p> <p>DPDT-ON-NONE-ON SCHEMATIC W/INDEPENDENT LED IN "A" &amp; INDEPENDENT LED IN "C"</p> |  | <p>K3...2BNH...</p> <p>DPDT-ON-NONE-ON SCHEMATIC W/INDEPENDENT LED IN "A" &amp; DEPENDENT LED IN "C"</p> |  | <p>K3...2BNJ...</p> <p>DPDT-ON-NONE-ON SCHEMATIC W/INDEPENDENT LED IN "A" &amp; "C"</p> |  |



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.