High SPL Microphone with Bottom Port and Analog Output

Data Sheet

ADMP411

FEATURES

4.72 mm × 3.76 mm × 1.0 mm surface mount package
131 dB SPL acoustic overload point
Sensitivity of −46 dBV
±2 dB sensitivity tolerance
Omnidirectional response
High SNR of 62 dBA
Extended frequency response from 28 Hz to 20 kHz
Low current consumption: <250 µA
Single-ended analog output
High PSR of −80 dBV
Compatible with Sn/Pb and Pb-free solder processes
RoHS/WEEE compliant

APPLICATIONS

Fire and safety radios
Safety masks
Smartphones and feature phones
Tablet computers
Teleconferencing systems
Digital still and video cameras
Studio microphones
Bluetooth headsets
Security and surveillance

FUNCTIONAL BLOCK DIAGRAM




Figure 1.




Figure 2. Isometric Views of Microphone Package

GENERAL DESCRIPTION

The ADMP411[1] is a high performance, high SPL, low noise, low power, analog output bottom ported, omnidirectional MEMS microphone. The ADMP411 consists of a MEMS microphone element and an impedance converter amplifier. The ADMP411 sensitivity specification makes it an excellent choice for both near field and far field applications. The ADMP411 is pin compatible with the ADMP401 microphone, providing an easy upgrade path.

The ADMP411 has a linear response up to 131 dB SPL. It offers high SNR and extended wideband frequency response resulting in natural sound with high intelligibility. Low current consumption enables long battery life for portable applications.

The ADMP411 is available in a miniature 4.72 mm × 3.76 mm × 1.0 mm surface-mount package. It is reflow solder compatible with no sensitivity degradation.

[1] Protected by U.S. Patents 7,449,356; 7,825,484; 7,885,423; 7,961,897. Other patents are pending.

Rev. 0 **Document Feedback**
Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.
Tel: 781.329.4700 **©2013 Analog Devices, Inc. All rights reserved.**
Technical Support **www.analog.com**

TABLE OF CONTENTS

Features 1
Applications 1
Functional Block Diagram 1
General Description 1
Revision History 2
Specifications 3
Absolute Maximum Ratings 4
ESD Caution 4
Pin Configuration and Function Descriptions 5
Typical Performance Characteristics 6
Applications Information 7
Codec Connections 7
Dynamic Range Considerations 7
Supporting Documents 7
Handling Instructions 8
Pick and Place Equipment 8
Reflow Solder 8
Board Wash 8
PCB Land Pattern Layout 9
Outline Dimensions 10
Ordering Guide 10

REVISION HISTORY

4/13—Revision 0: Initial Version

SPECIFICATIONS

T_A = 25°C, V_{DD} = 1.8 V, unless otherwise noted. All minimum and maximum specifications are guaranteed. Typical specifications are not guaranteed.

Table 1.

Parameter	Test Conditions/Comments	Min	Typ	Max	Unit
PERFORMANCE					
Directionality			Omni		
Sensitivity	1 kHz, 94 dB SPL	−48	−46	−44	dBV
Signal-to-Noise Ratio (SNR)	20 Hz to 20 kHz, A-weighted		62		dBA
Equivalent Input Noise (EIN)	20 Hz to 20 kHz, A-weighted		32		dBA SPL
Dynamic Range	Derived from EIN and maximum acoustic input		99		dB
Frequency Response[1]	Low frequency −3 dB point		28		Hz
	High frequency −3 dB point		>20		kHz
Total Harmonic Distortion (THD)	105 dB SPL		0.2	1	%
Power Supply Rejection (PSR)	217 Hz, 100 mV p-p square wave superimposed on V_{DD} = 1.8 V		−80		dBV
Power Supply Rejection Ratio (PSRR)	1 kHz, 100 mV p-p sine wave superimposed on V_{DD} = 1.8 V		−46		dB
Acoustic Overload Point	10% THD		131		dB SPL
POWER SUPPLY					
Supply Voltage (V_{DD})		1.5		3.63	V
Supply Current (I_S)	V_{DD} = 1.8 V		180	220	µA
	V_{DD} = 3.3 V		210	250	µA
OUTPUT CHARACTERISTICS					
Output Impedance (Z_{OUT})			200		Ω
Output DC Offset			0.8		V
Maximum Output Voltage	131 dB SPL input		0.355		V rms
Noise Floor	20 Hz to 20 kHz, A-weighted, rms		−108		dBV

[1] See Figure 5 and Figure 6.

ABSOLUTE MAXIMUM RATINGS

Table 2.

Parameter	Rating
Supply Voltage	−0.3 V to +3.63 V
Sound Pressure Level (SPL)	160 dB
Mechanical Shock	10,000 *g*
Vibration	Per MIL-STD-883 Method 2007, Test Condition B
Storage Temperature Range	−40°C to +150°C
Operating Temperature Range	−40°C to +85°C

Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only; functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ESD CAUTION



ESD (electrostatic discharge) sensitive device. Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.




Figure 3. Recommended Soldering Profile Limits

Table 3. Recommended Soldering Profile Limits

Profile Feature	Sn63/Pb37	Pb-Free
Average Ramp Rate (T_L to T_P)	1.25°C/sec maximum	1.25°C/sec maximum
Preheat		
Minimum Temperature (T_{SMIN})	100°C	150°C
Maximum Temperature (T_{SMAX})	150°C	200°C
Time (T_{SMIN} to T_{SMAX}), t_S	60 sec to 75 sec	60 sec to 75 sec
Ramp-Up Rate (T_{SMAX} to T_L)	1.25°C/sec	1.25°C/sec
Time Maintained Above Liquidous (t_L)	45 sec to 75 sec	~50 sec
Liquidous Temperature (T_L)	183°C	217°C
Peak Temperature (T_P)	215°C + 3°C/−3°C	260°C + 0°C/−5°C
Time Within 5°C of Actual Peak Temperature (t_P)	20 sec to 30 sec	20 sec to 30 sec
Ramp-Down Rate	3°C/sec maximum	3°C/sec maximum
Time 25°C to Peak Temperature	5 minute maximum	5 minute maximum

PIN CONFIGURATION AND FUNCTION DESCRIPTIONS




Figure 4. Pin Configuration

Table 4. Pin Function Descriptions

Pin No.	Mnemonic	Description
1	OUTPUT	Analog Output Signal
2	GND	Ground
3	GND	Ground
4	GND	Ground
5	V_{DD}	Power Supply
6	GND	Ground

TYPICAL PERFORMANCE CHARACTERISTICS




Figure 5. Frequency Response Mask




Figure 8. THD + N vs. Input Level




Figure 6. Typical Frequency Response (Measured)




Figure 9. Linearity




Figure 7. Typical Power Supply Rejection Ratio vs. Frequency




Figure 10. Clipping Characteristics

APPLICATIONS INFORMATION

CODEC CONNECTIONS

The ADMP411 output can be connected to a dedicated codec microphone input (see Figure 11) or to a high input impedance gain stage (see Figure 12). A 0.1 µF ceramic capacitor placed close to the ADMP411 supply pin is used for testing and is recommended to adequately decouple the microphone from noise on the power supply. A dc blocking capacitor is required at the output of the microphone. This capacitor creates a high-pass filter with a corner frequency at

$$f_C = 1/(2\pi \times C \times R)$$

where R is the input impedance of the codec.

A minimum value of 4.7 µF is recommended in Figure 11 because the ADAU1761/ADAU1361 input impedance can be as low as 2 kΩ at its highest PGA gain setting, which results in a high-pass filter corner frequency at 17 Hz.

Figure 12 shows the ADMP411 connected to an ADA4075-2 op amp configured as a noninverting preamplifier. The AN-1165 Application Note describes using op amps for microphone preamp circuits and includes a list of recommended Analog Devices, Inc., op amps.




Figure 11. ADMP411 Connected to the Analog Devices ADAU1761 or ADAU1361 Codec




Figure 12. ADMP411 Connected to the ADA4075-2 Op Amp

DYNAMIC RANGE CONSIDERATIONS

To fully utilize the 99 dB dynamic range of the ADMP411 in a design, the preamp, ADC, or codec circuit following it must be chosen carefully. For example, the ADAU1761 has a 98 dB dynamic range with V_{DD} = 3.3 V. To match the dynamic ranges between the microphone and the ADC input of the codec, some gain must be added to the ADMP411 output. For example, at the 131 dB SPL maximum acoustic input, the ADMP411 outputs a −13 dBV rms signal. The full-scale input voltage of the ADAU1761 ADC is 0 dBV; therefore, 13 dB of gain must be added to the signal to match the dynamic range of the microphone with the dynamic range of the codec.

SUPPORTING DOCUMENTS

Evaluation Board User Guide

UG-445, *EVAL-ADMP411Z-FLEX: Bottom-Ported Analog Output MEMS Microphone Evaluation Board*

Application Notes

AN-1003, *Recommendations for Mounting and Connecting Analog Devices, Inc., Bottom-Ported MEMS Microphones*

AN-1068, *Reflow Soldering of the MEMS Microphone*

AN-1112, *Microphone Specifications Explained*

AN-1124, *Recommendations for Sealing Analog Devices, Inc., Bottom-Port MEMS Microphones from Dust and Liquid Ingress*

AN-1140, *Microphone Array Beamforming*

AN-1165, *Op Amps for MEMS Microphone Preamp Circuits*

AN-1181, *Using a MEMS Microphone in a 2-Wire Microphone Circuit*

HANDLING INSTRUCTIONS

PICK AND PLACE EQUIPMENT

The MEMS microphone can be handled using standard pick and place and chip shooting equipment. Take care to avoid damage to the MEMS microphone structure as follows:

- Use a standard pickup tool to handle the microphone. Because the microphone hole is on the bottom of the package, the pickup tool can make contact with any part of the lid surface.
- Do not pick up the microphone with a vacuum tool that makes contact with the bottom side of the microphone.
- Do not pull air out or blow air into the microphone port.
- Do not use excessive force to place the microphone on the PCB.

REFLOW SOLDER

For best results, the soldering profile should be in accordance with the recommendations of the manufacturer of the solder paste used to attach the MEMS microphone to the PCB. It is recommended that the solder reflow profile not exceed the limit conditions specified in Figure 3 and Table 3. For more detailed recommendations, see the AN-1068 Application Note, *Reflow Soldering of the MEMS Microphone*.

BOARD WASH

When washing the PCB, ensure that water does not make contact with the microphone port. Blowoff procedures and ultrasonic cleaning must not be used.

PCB LAND PATTERN LAYOUT

The recommended PCB land pattern for the ADMP411 is laid out to a 1:1 ratio to the solder pads on the microphone package, as shown in Figure 13. Take care to avoid applying solder paste to the sound hole in the PCB. A suggested solder paste stencil pattern layout is shown in Figure 14. The diameter of the sound hole in the PCB should be larger than the diameter of the sound port of the microphone. A minimum diameter of 0.5 mm is recommended.




Figure 13. PCB Land Pattern Layout (Dimensions Shown in Millimeters)




Figure 14. Suggested Solder Paste Stencil Pattern Layout

OUTLINE DIMENSIONS




Figure 15. 6-Terminal Chip Array Small Outline No Lead Cavity [LGA_CAV]
4.72 mm × 3.76 mm Body
(CE-6-1)
Dimensions shown in millimeters

ORDERING GUIDE

Model[1]	Temperature Range	Package Description	Package Option	Ordering Quantity
ADMP411ACEZ-RL	−40°C to +85°C	6-Terminal LGA_CAV, 13" Tape and Reel	CE-6-1	4,500
ADMP411ACEZ-RL7	−40°C to +85°C	6-Terminal LGA_CAV, 7" Tape and Reel	CE-6-1	1,000
EVAL-ADMP411Z-FLEX		Flex Evaluation Board		

[1] Z = RoHS Compliant Part.

NOTES

NOTES

©2013 Analog Devices, Inc. All rights reserved. Trademarks and registered trademarks are the property of their respective owners.
D10913-0-4/13(0)


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.