

	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1																																																																																																																																																																																																																																																																																																																																																																																														
M	<table><tr><td rowspan="2">X*NOT TOOLED</td><td rowspan="2">ASSEMBLY NUMBER</td><td colspan="4">PART CHARACTERISTICS</td></tr><tr><td>EXTERNAL CONNECTOR SIZE</td><td>NUMBER OF POSITIONS</td><td>P. C. BOARD THICKNESS</td><td>MOUNTING EARS OPTION</td></tr><tr><td rowspan="6">L</td><td>42878-4216</td><td>4 POS. BODY</td><td>4</td><td>.062</td><td>YES</td></tr><tr><td>42878-4218</td><td>↑</td><td>4</td><td>.062</td><td>NO</td></tr><tr><td>42878-4264</td><td></td><td>4</td><td>.125</td><td>YES</td></tr><tr><td>42878-4266</td><td></td><td>4</td><td>.125</td><td>NO</td></tr><tr><td>42878-4360</td><td></td><td>2</td><td>.062</td><td>YES</td></tr><tr><td>42878-4362</td><td></td><td>2</td><td>.062</td><td>NO</td></tr><tr><td rowspan="6">K</td><td>42878-4408</td><td>↓</td><td>2</td><td>.125</td><td>YES</td></tr><tr><td>42878-4410</td><td>4 POS. BODY</td><td>2</td><td>.125</td><td>NO</td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">J</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">I</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">H</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">G</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">F</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">E</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">D</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">C</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">B</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">A</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr></table>																				X*NOT TOOLED	ASSEMBLY NUMBER	PART CHARACTERISTICS				EXTERNAL CONNECTOR SIZE	NUMBER OF POSITIONS	P. C. BOARD THICKNESS	MOUNTING EARS OPTION	L	42878-4216	4 POS. BODY	4	.062	YES	42878-4218	↑	4	.062	NO	42878-4264		4	.125	YES	42878-4266		4	.125	NO	42878-4360		2	.062	YES	42878-4362		2	.062	NO	K	42878-4408	↓	2	.125	YES	42878-4410	4 POS. BODY	2	.125	NO																					J																															I																															H																															G																															F																															E																															D																															C																															B																															A																														
X*NOT TOOLED	ASSEMBLY NUMBER	PART CHARACTERISTICS																																																																																																																																																																																																																																																																																																																																																																																																																
		EXTERNAL CONNECTOR SIZE	NUMBER OF POSITIONS	P. C. BOARD THICKNESS	MOUNTING EARS OPTION																																																																																																																																																																																																																																																																																																																																																																																																													
L	42878-4216	4 POS. BODY	4	.062	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-4218	↑	4	.062	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-4264		4	.125	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-4266		4	.125	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-4360		2	.062	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-4362		2	.062	NO																																																																																																																																																																																																																																																																																																																																																																																																													
K	42878-4408	↓	2	.125	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-4410	4 POS. BODY	2	.125	NO																																																																																																																																																																																																																																																																																																																																																																																																													
J																																																																																																																																																																																																																																																																																																																																																																																																																		
I																																																																																																																																																																																																																																																																																																																																																																																																																		
H																																																																																																																																																																																																																																																																																																																																																																																																																		
G																																																																																																																																																																																																																																																																																																																																																																																																																		
F																																																																																																																																																																																																																																																																																																																																																																																																																		
E																																																																																																																																																																																																																																																																																																																																																																																																																		
D																																																																																																																																																																																																																																																																																																																																																																																																																		
C																																																																																																																																																																																																																																																																																																																																																																																																																		
B																																																																																																																																																																																																																																																																																																																																																																																																																		
A																																																																																																																																																																																																																																																																																																																																																																																																																		
<table><tr><td rowspan="2">X*NOT TOOLED</td><td rowspan="2">ASSEMBLY ITEM NUMBER</td><td colspan="4">PART CHARACTERISTICS</td></tr><tr><td>EXTERNAL CONNECTOR SIZE</td><td>NUMBER OF POSITIONS</td><td>P. C. BOARD THICKNESS</td><td>MOUNTING EARS OPTION</td></tr><tr><td rowspan="12"></td><td>42878-6216</td><td>6 POS. BODY</td><td>6</td><td>.062</td><td>YES</td></tr><tr><td>42878-6218</td><td>↑</td><td>6</td><td>.062</td><td>NO</td></tr><tr><td>42878-6264</td><td></td><td>6</td><td>.125</td><td>YES</td></tr><tr><td>42878-6266</td><td></td><td>6</td><td>.125</td><td>NO</td></tr><tr><td>42878-6360</td><td></td><td>4</td><td>.062</td><td>YES</td></tr><tr><td>42878-6362</td><td></td><td>4</td><td>.062</td><td>NO</td></tr><tr><td>42878-6408</td><td></td><td>4</td><td>.125</td><td>YES</td></tr><tr><td>42878-6410</td><td></td><td>4</td><td>.125</td><td>NO</td></tr><tr><td>42878-6504</td><td></td><td>2</td><td>.062</td><td>YES</td></tr><tr><td>42878-6506</td><td></td><td>2</td><td>.062</td><td>NO</td></tr><tr><td>42878-6552</td><td>↓</td><td>2</td><td>.125</td><td>YES</td></tr><tr><td>42878-6554</td><td>6 POS. BODY</td><td>2</td><td>.125</td><td>NO</td></tr><tr><td rowspan="6"></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr></table>																				X*NOT TOOLED	ASSEMBLY ITEM NUMBER	PART CHARACTERISTICS				EXTERNAL CONNECTOR SIZE	NUMBER OF POSITIONS	P. C. BOARD THICKNESS	MOUNTING EARS OPTION		42878-6216	6 POS. BODY	6	.062	YES	42878-6218	↑	6	.062	NO	42878-6264		6	.125	YES	42878-6266		6	.125	NO	42878-6360		4	.062	YES	42878-6362		4	.062	NO	42878-6408		4	.125	YES	42878-6410		4	.125	NO	42878-6504		2	.062	YES	42878-6506		2	.062	NO	42878-6552	↓	2	.125	YES	42878-6554	6 POS. BODY	2	.125	NO																																																																																																																																																																																																																																																																																																																								
X*NOT TOOLED	ASSEMBLY ITEM NUMBER	PART CHARACTERISTICS																																																																																																																																																																																																																																																																																																																																																																																																																
		EXTERNAL CONNECTOR SIZE	NUMBER OF POSITIONS	P. C. BOARD THICKNESS	MOUNTING EARS OPTION																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6216	6 POS. BODY	6	.062	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6218	↑	6	.062	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6264		6	.125	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6266		6	.125	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6360		4	.062	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6362		4	.062	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6408		4	.125	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6410		4	.125	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6504		2	.062	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6506		2	.062	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6552	↓	2	.125	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6554	6 POS. BODY	2	.125	NO																																																																																																																																																																																																																																																																																																																																																																																																													
<table><tr><td colspan="5">CHARACTERISTICS LEGEND</td></tr><tr><td colspan="5">EXTERNAL CONNECTOR BODY DIMENSIONS: AVAILABLE IN 4, 6, AND 8 POSITION BODY</td></tr><tr><td colspan="5">NUMBER OF CONTACT POSITIONS: CONNECTOR SIZE 4 ACCOMMODATES 2, 4, OR 6 TERMINALS, CONNECTOR SIZE 6 ACCOMMODATES 2, 4, OR 6 TERMINALS, CONNECTOR SIZE 8 ACCOMMODATES 2, 4, 6, 8, OR 10 TERMINALS</td></tr><tr><td colspan="5">POLARIZATION OPTION: (AVAILABLE ON CONNECTOR SIZE 8 ONLY) "NO"= WITHOUT KEYING SLOT "YES"= WITH KEYING SLOT</td></tr><tr><td colspan="5">MOUNTING EARS OPTION: "YES"= PART WITH MOUNTING EARS "NO"= PART WITHOUT MOUNTING EARS</td></tr><tr><td colspan="5">(SEE SHEET 1 & 2 FOR PART DESCRIPTIONS AND DIMENSIONS)</td></tr></table>																				CHARACTERISTICS LEGEND					EXTERNAL CONNECTOR BODY DIMENSIONS: AVAILABLE IN 4, 6, AND 8 POSITION BODY					NUMBER OF CONTACT POSITIONS: CONNECTOR SIZE 4 ACCOMMODATES 2, 4, OR 6 TERMINALS, CONNECTOR SIZE 6 ACCOMMODATES 2, 4, OR 6 TERMINALS, CONNECTOR SIZE 8 ACCOMMODATES 2, 4, 6, 8, OR 10 TERMINALS					POLARIZATION OPTION: (AVAILABLE ON CONNECTOR SIZE 8 ONLY) "NO"= WITHOUT KEYING SLOT "YES"= WITH KEYING SLOT					MOUNTING EARS OPTION: "YES"= PART WITH MOUNTING EARS "NO"= PART WITHOUT MOUNTING EARS					(SEE SHEET 1 & 2 FOR PART DESCRIPTIONS AND DIMENSIONS)																																																																																																																																																																																																																																																																																																																																																																					
CHARACTERISTICS LEGEND																																																																																																																																																																																																																																																																																																																																																																																																																		
EXTERNAL CONNECTOR BODY DIMENSIONS: AVAILABLE IN 4, 6, AND 8 POSITION BODY																																																																																																																																																																																																																																																																																																																																																																																																																		
NUMBER OF CONTACT POSITIONS: CONNECTOR SIZE 4 ACCOMMODATES 2, 4, OR 6 TERMINALS, CONNECTOR SIZE 6 ACCOMMODATES 2, 4, OR 6 TERMINALS, CONNECTOR SIZE 8 ACCOMMODATES 2, 4, 6, 8, OR 10 TERMINALS																																																																																																																																																																																																																																																																																																																																																																																																																		
POLARIZATION OPTION: (AVAILABLE ON CONNECTOR SIZE 8 ONLY) "NO"= WITHOUT KEYING SLOT "YES"= WITH KEYING SLOT																																																																																																																																																																																																																																																																																																																																																																																																																		
MOUNTING EARS OPTION: "YES"= PART WITH MOUNTING EARS "NO"= PART WITHOUT MOUNTING EARS																																																																																																																																																																																																																																																																																																																																																																																																																		
(SEE SHEET 1 & 2 FOR PART DESCRIPTIONS AND DIMENSIONS)																																																																																																																																																																																																																																																																																																																																																																																																																		
<table><tr><td rowspan="2">SEE SHEET ONE EC NO: UCP2004-1617 DRWNLSCHMDT 2004/03/03 CHKDLSCHMDT 2004/03/03 APPR.FSMTH 2004/03/03</td><td rowspan="2">DESCRIPTION (REV)</td><td>QUALITY SYMBOLS</td><td>GENERAL TOLERANCES (UNLESS SPECIFIED)</td><td>SCALE ---</td><td>DESIGN UNITS INCH</td><td>THIRD ANGLE PROJECTION</td><td>REVISE ON CAD ONLY</td></tr><tr><td>4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± --- ± --- 1 PLACE ± --- ± --- ANGULAR ±1/2° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS</td><td>mm INCH IN/MM</td><td>DIMENSION STYLE</td><td>DRAWN BY DATE BAP 1992/04/09 CHECKED BY DATE BAP 1992/04/09 APPROVED BY DATE RAS 1992/04/09</td><td>TITLE ASSEMBLY, VERTICAL LOW PROFILE MODULAR JACKS (CONNECTOR SIZE 4 & 6) MOLEX INCORPORATED</td><td>MATERIAL NO. DOCUMENT NO. SHEET NO. 4 OF 5</td></tr></table>																				SEE SHEET ONE EC NO: UCP2004-1617 DRWNLSCHMDT 2004/03/03 CHKDLSCHMDT 2004/03/03 APPR.FSMTH 2004/03/03	DESCRIPTION (REV)	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	SCALE ---	DESIGN UNITS INCH	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY	4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± --- ± --- 1 PLACE ± --- ± --- ANGULAR ±1/2° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	mm INCH IN/MM	DIMENSION STYLE	DRAWN BY DATE BAP 1992/04/09 CHECKED BY DATE BAP 1992/04/09 APPROVED BY DATE RAS 1992/04/09	TITLE ASSEMBLY, VERTICAL LOW PROFILE MODULAR JACKS (CONNECTOR SIZE 4 & 6) MOLEX INCORPORATED	MATERIAL NO. DOCUMENT NO. SHEET NO. 4 OF 5																																																																																																																																																																																																																																																																																																																																																																																	
SEE SHEET ONE EC NO: UCP2004-1617 DRWNLSCHMDT 2004/03/03 CHKDLSCHMDT 2004/03/03 APPR.FSMTH 2004/03/03	DESCRIPTION (REV)	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	SCALE ---	DESIGN UNITS INCH	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY																																																																																																																																																																																																																																																																																																																																																																																																											
		4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± --- ± --- 1 PLACE ± --- ± --- ANGULAR ±1/2° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	mm INCH IN/MM	DIMENSION STYLE	DRAWN BY DATE BAP 1992/04/09 CHECKED BY DATE BAP 1992/04/09 APPROVED BY DATE RAS 1992/04/09	TITLE ASSEMBLY, VERTICAL LOW PROFILE MODULAR JACKS (CONNECTOR SIZE 4 & 6) MOLEX INCORPORATED	MATERIAL NO. DOCUMENT NO. SHEET NO. 4 OF 5																																																																																																																																																																																																																																																																																																																																																																																																											
<table><tr><td>to frame D.P.M.E.T Rev. C 2002/05/05</td><td>19</td><td>18</td><td>17</td><td>16</td><td>15</td><td>14</td><td>13</td><td>12</td><td>11</td><td>10</td><td>9</td><td>8</td><td>7</td><td>6</td><td>5</td><td>4</td><td>3</td><td>2</td><td>1</td></tr></table>																				to frame D.P.M.E.T Rev. C 2002/05/05	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1																																																																																																																																																																																																																																																																																																																																																																											
to frame D.P.M.E.T Rev. C 2002/05/05	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1																																																																																																																																																																																																																																																																																																																																																																																															



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.