



For more Information
please call

1-800-Belden1



General Description:

Belden's .050" pitch, color-coded PVC flat cable allows for quick identification and circuit tracing, along with easy breakouts for circuit routing, and is designed for mass-termination with standard IDC connectors.

Physical Characteristics (Overall)

Conductor

AWG:

| # Conductors | AWG | Stranding | Conductor Material |
|--------------|-----|-----------|--------------------|
| 40 | 28 | 7x36 | TC - Tinned Copper |

Total Number of Conductors: 40

Conductor Spacing Center to Center: .050

Insulation

Insulation Material:

| Insulation Material | Wall Thickness (in.) |
|--------------------------|----------------------|
| PVC - Polyvinyl Chloride | 0.010 |

Insulation Resistance: >10,000 Mega Ohms

Insulation Color Code Chart:

| Number | Color |
|--------------------|--------------------|
| 1 | Brown |
| 2 | Red |
| 3 | Orange |
| 4 | Yellow |
| 5 | Green |
| 6 | Blue |
| 7 | Purple |
| 8 | Gray |
| 9 | White |
| 10 | Black |
| Over 10 conductors | Repeat as required |

Outer Shield

Outer Shield Material:

| Outer Shield Material |
|-----------------------|
| Unshielded |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material |
|-----------------------|
| Clear PVC |

Overall Cable

Overall Nominal Thickness: .036

Overall Nominal Width: 2.00

Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +105°C

Bulk Cable Weight: 44 lbs/1000 ft.

Min. Bend Radius/Minor Axis: 0.500 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

UL Rating: AWM 20932

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

| | |
|---------------------------------------|------------|
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 10/01/2005 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MIL Order #39 (China RoHS): | Yes |

Flame Test

| | |
|----------------|------|
| UL Flame Test: | VW-1 |
|----------------|------|

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

| Description | Impedance (Ohm) |
|-------------|-----------------|
| (GS) | 150 |
| (GSG) | 105 |

Nom. Inductance:

| Description | Inductance (µH/ft) |
|---------------|--------------------|
| @ 1 MHz (GS) | .29 |
| @ 1 MHz (GSG) | .20 |

Nom. Capacitance Conductor to Conductor:

| Description | Capacitance (pF/ft) |
|---------------|---------------------|
| @ 1 kHz (GSG) | 18 |
| @ 1 MHz (GS) | 10 |
| @ 1 MHz (GSG) | 15 |

Nominal Velocity of Propagation:

| Description | VP (%) |
|-------------|--------|
| | 72 |

Nominal Delay:

| Delay (ns/ft) |
|-------------------|
| 1.40 NS/FT. (GSG) |

Nom. Conductor DC Resistance:

| DCR @ 20°C (Ohm/1000 ft) |
|--------------------------|
| 68.2 OHMS/1000 FT. MAX. |

Nom. Attenuation:

| Freq. (MHz) | Attenuation (dB/100 ft.) |
|-------------|--------------------------|
| 10 | 2.8 |
| 20 | 4.8 |
| 30 | 6.5 |
| 40 | 8.3 |
| 50 | 9.8 |
| 60 | 12 |
| 70 | 13 |
| 80 | 14 |
| 90 | 15.8 |
| 100 | 17 |

Max. Operating Voltage - UL:

| Voltage |
|-----------|
| 300 V RMS |

Max. Recommended Current:

| Current |
|----------------------------|
| 1 Amp per conductor @ 20°C |

Dielectric Withstand Voltage: 2,000 V RMS

Typical Unbalanced Crosstalk:

| Description | Pulse Rise Time (NS) (MHz) | Near End % (MHz) | Far End % (MHz) |
|----------------------|----------------------------|------------------|-----------------|
| 10 ft. sample length | 3 | 4.8 | 7 |
| 10 ft. sample length | 5 | 3.5 | 4.7 |
| 10 ft. sample length | 7 | 3 | 3 |

Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

9R28040 Flat - Rainbow 9R280XX Series

Notes (Overall)

Notes: GS=Ground-Signal Mode; GSG=Ground-Signal-Ground Mode

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|----------------|--------|-------------|-------|-------|--------------------|
| 9R28040 000100 | 100 FT | 4.800 LB | NONE | | 40 #28 PVC RAINBOW |

Revision Number: 3 Revision Date: 10-02-2012

© 2015 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.