



| PC BOARD VERSIONS | | |
|---|---|---|
| PRODUCTNR: | PCB THICKNESS | DIM"A" |
| 70229-X01/X01LF | 1.6 | 2.90 |
| 70229-X11/X11LF | 2.4 | 3.53 |








RECOMMENDED HOLE PATTERN,
COMPONENT SIDE.




PRODUCT AFTER HOT RIVETTING.




NOTES:

1 BODY MAT'L: LIQUID CRYSTAL POLYMER 30% GLASS FLAME RETARDANT ACC. UL 94-V0
2 TERMINAL MATERIAL: PHOSPHOR BRONZE.
3 PLATING SOLDERTAILS 2-8 μm SnPb 90-97 OR 2-8 鎗 PURE Sn
4 INDICATED HOLES ARE UNPLATED.
5 PRODUCTMARKING: PARTNUMBER & BATCH ID.
6 THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008 .
7 THE HOUSING WILL WITHSTAND EXPOSURE TO 260DEGREE PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION.
8. DIAMOND LOCATION PEG ARE ONLY EXISTED ON THE BOTH SIDES OF PRODUCT.

| PLATING CONTACT AREA: | |
|---|---|
| PRODUCT NR: | PERFORMANCE LEVEL: |
| 70229-1YZ/1YZLF | TELCORDIA CO |
| 70229-2YZ/2YZLF | CUSTOMER SPECIAL |
| 70229-3YZ/3YZLF | CUSTOMER SPECIAL |

| ltr | ecn | aadr | date |
|---|---|---|---|
| K | DG04-0104 | CLu | 041221 |
| L | DG06-0477 | Cenh | 11/20/06 |
| M | DG07-0168 | Cenh | 05/08/07 |
| N | DG09-0068 | Cenh | 06/06/09 |
| H | V00578 | LLA | 000316 |
| J | V00847 | LLA | 000530 |

| | | |
|---|---|---|
| dr | A.van Zanten | 900918 |
| engr | H. Bouwknegt | 940308 |
| chn | A van Zanten | 900918 |
| appd | H van Woensel | 900918 |

| sheet | revision | N | N | N |
|---|---|---|---|---|
| index | sheet | 1 | 2 | 3 |

mat'l code
tolerances unless otherwise specified
linear
angles
mm
scale 5:1
CUSTOMER COPY
projection
www.fciconnect.com
title: RA FEMALE SIGNAL STB 48 mm VERSION
product family: METRAL(tm)
code 213
size A2
dwg no 70229
sheet 1 of3


All rights strictly reserved. Reproduction or issue to third parties in any form whatsoever is not permitted without written authority from the proprietor.
Property of FCI b.v.
©FCI b.v.


Tous droits strictement reserves. Reproduction ou communication a des tiers interdite sous quelque forme que ce soit sans autorisation ecrite du proprietaire.
Propriete de FCI b.v.
©FCI b.v.


form A2


PDM: Rev:N STATUS: Released Printed: May 19, 2011


| PC BOARD VERSIONS | | |
|---|---|---|
| PRODUCTNR: | PCB THICKNESS | DIM"A" |
| 70229-X02/X02LF | 1.6 | 2.90 |
| 70229-X12/X12LF | 2.4 | 3.53 |







RECOMMENDED HOLE PATTERN,
COMPONENT SIDE.

NOTES:

1 BODY MAT'L: LIQUID CRYSTAL POLYMER 30% GLASS FLAME RETARDANT ACC. UL 94-V0
2 TERMINAL MATERIAL: PHOSPHOR BRONZE.
3 PLATING SOLDERTAILS 2-8 μm SnPb 90-97 OR 2-8 鍍 PURE Sn
4 INDICATED HOLES ARE UNPLATED.
5 PRODUCTMARKING: PARTNUMBER & BATCH ID.
6 SET BACK FOR PRESS BLOCK.
7 TOP SURFACE OF PRESS BLOCK MAY EXTEND UP TO 0.4MM HIGHER THAN HOUSING. THIS MAY AFFECT THE TAIL LENGTH BEFORE APPLICATION TO A BOARD
8 THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008 .
9 THE HOUSING WILL WITHSTAND EXPOSURE TO 260DEGREE PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION.
10. DIAMOND LOCATION PEG ARE ONLY EXISTED ON THE BOTH SIDES OF PRODUCT.

| PLATING CONTACT AREA: | |
|---|---|
| PRODUCT NR: | PERFORMANCE LEVEL: |
| 70229-1YZ/1YZLF | TELCORDIA CO |
| 70229-2YZ/2YZLF | CUSTOMER SPECIAL |
| 70229-3YZ/3YZLF | CUSTOMER SPECIAL |

| | | | |
|---|---|---|---|
| mat'l code | tolerances unless otherwise specified | CUSTOMER COPY | FCI www.fciconnect.com |
| ltr ecn nodr date: N | linear | projectiontitle | RA FEMALE SIGNAL STB 48 mm VERSION |
| | angles | | |
| | dr D. de Bil 970529 | mm | product family METRAL(tm) code |
| | engr P. Schalk 970529 | | size dwg no 213 |
| | chr P. Schalk 970529 | scale 5:1 | A2 70229 sheet 2 of- |
| | appd H. Cooijmans 970529 | | |
| sheet revision index sheet | | | |


Tous droits strictement reservés. Reproduction ou communication à des tiers interdite sous quelque forme que ce soit sans autorisation écrite du propriétaire. Propriété de F C I b.v. ©F C I b.v.


All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of F C I b.v. ©F C I b.v.





PDM: Rev:N STATUS: Released Printed: May 19, 2011

| PC BOARD VERSIONS | | |
|---|---|---|
| PRODUCTNR: | PCB THICKNESS | DIM"A" |
| 70229-X03/X03LF | 1.6 | 2.90 |
| 70229-X13/X13LF | 2.4 | 3.53 |





PRODUCT AFTER HOT RIVETTING.




RECOMMENDED HOLE PATTERN,
COMPONENT SIDE.

NOTES:

1 BODY MAT'L: LIQUID CRYSTAL POLYMER 30% GLASS FLAME RETARDANT ACC. UL 94-V0
2 TERMINAL MATERIAL: PHOSPHOR BRONZE.
3 PLATING SOLDERTAILS 2-8 um SnPb 90-97 OR 2-8 um PURE Sn
4 INDICATED HOLES ARE UNPLATED.
5 PRODUCTMARKING: PARTNUMBER & BATCH ID.
6 THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008 .
7 THE HOUSING WILL WITHSTAND EXPOSURE TO 260DEGREE PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION.
8. DIAMOND LOCATION PEG ARE ONLY EXISTED ON THE BOTH SIDES OF PRODUCT.

| PLATING CONTACT AREA: | |
|---|---|
| PRODUCT NR: | PERFORMANCE LEVEL: |
| 70229-1YZ/1YZLF | TELCORDIA CO |
| 70229-2YZ/2YZLF | CUSTOMER SPECIAL |
| 70229-3YZ/3YZLF | CUSTOMER SPECIAL |

mat'l code | tolerances unless otherwise specified | CUSTOMER COPY | FCI www.fciconnect.com

| ltr | ecn | nodr | date |
|---|---|---|---|
| N | | | |

linear
angles
projection
title: RA FEMALE SIGNAL STB 48 mm VERSION
mm
scale 5:1
product family METRAL(tm)
code 213
size A2
dwg no 70229
sheet 3 of-

| | | | |
|---|---|---|---|
| dr | Heaven Cen | 11/20/06 | |
| engr | Collins Lu | 11/20/06 | |
| chr | Beer Fu | 11/20/06 | |
| appd | Joseph Hsia | 11/20/06 | |

sheet index | revision sheet

Form A2


Tous droits strictement reserves. Reproduction ou communication a des tiers interdites sous quelque forme que ce soit sans autorisation ecrite du proprietaire. Propriete de F C I b.v. © F C I b.v.

All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of F C I b.v. © F C I b.v.


PDM: Rev:N STATUS: Released Printed: May 19, 2011


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.




**Как с нами связаться**

**Телефон:** 8 (812) 309 58 32 (многоканальный)
**Факс:** 8 (812) 320-02-42
**Электронная почта:** org@eplast1.ru
**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.