# Thin Film Mini-MELF Resistors

SMM 0204 thin film MELF resistors are the perfect choice for most fields of modern professional electronics where reliability and stability are of major concern. The typical applications in the fields of automotive, industrial and medical equipment reflect the outstanding level of proven reliability.

## FEATURES

- Advanced metal film technology
- AEC-Q200 qualified
- Approval acc. EN 140401-803 available on request
- Excellent stability in different environmental conditions
- Best in class pulse load capability
- Sulfur resistance verified according to ASTM B 809
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

AUTOMOTIVE GRADE

Pb-free

RoHS COMPLIANT

HALOGEN FREE

GREEN (5-2008)

## APPLICATIONS

- Automotive
- Telecommunication
- Industrial
- Medical equipment

## TECHNICAL SPECIFICATIONS

| DESCRIPTION | SMM0204 |
|---|---|
| DIN size | 0204 |
| Metric CECC size | RC 3715M |
| Resistance range | 0.22 Ω to 10 MΩ |
| Resistance tolerance | ± 5 %; ± 1 %; ± 0.5 %; ± 0.25 %; ± 0.1 % |
| Temperature coefficient | ± 100 ppm/K; ± 50 ppm/K; ± 25 ppm/K; ± 15 ppm/K |
| Rated dissipation $P_{70}$ (1) | 0.4 W |
| Operating voltage, $U_{max.}$ AC/DC | 200 V |
| Operating temperature range | -55 °C to 155 °C |
| Permissible voltage against ambient (insulation): 1 min; $U_{ins}$ | 300 V |
| Failure rate: $FIT_{observed}$ | ≤ 0.1 x $10^{-9}$/h |
| Zero-Ohm-Resistor: OMM0204 | $R_{max.}$ = 10 mΩ; $I_{max.}$ = 3 A |

**Notes**

- The IECQ-CECC approved product versions SMM0204 EN803 E0 and OMM0204 EN803 E0 respectively feature a quality factor $\pi_Q$ = 3 for the purpose of system MTBF calculations, compared with $\pi_Q$ = 10 for the standard versions.

(1) Please refer to APPLICATION INFORMATION below.

## APPLICATION INFORMATION

The power dissipation on the resistor generates a temperature rise against the local ambient, depending on the heat flow support of the printed-circuit board (thermal resistance). The rated dissipation applies only if the permitted film temperature is not exceeded. Furthermore, a high level of ambient temperature or of power dissipation may raise the temperature of the solder joint, hence special solder alloys or board materials may be required to maintain the reliability of the assembly.

These resistors do not feature a limited lifetime when operated within the permissible limits. However, resistance value drift increasing over operating time may result in exceeding a limit acceptable to the specific application, thereby establishing a functional lifetime. At the maximum permissible film temperature of 155 °C the useful lifetime is specified for 8000 h. The designer may estimate the performance of the particular resistor application or set certain load and temperature limits in order to maintain a desired stability.



For technical questions, contact: melf@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

| MAXIMUM RESISTANCE CHANGE AT RATED DISSIPATION | | | | |
|---|---|---|---|---|
| **OPERATION MODE** | | **PRECISION** | **STANDARD** | **POWER** |
| Rated dissipation, $P_{70}$ | SMM0204 | 0.07 W | 0.25 W | 0.4 W |
| Operating temperature range | | -10 °C to 85 °C | -55 °C to 125 °C | -55 °C to 155 °C |
| Permissible film temperature, $\vartheta_{F\ max.}$ | | 85 °C | 125 °C | 155 °C |
| Max. resistance change at $P_{70}$ for resistance range, $\Delta R/R$ after: | SMM0204 | 10 Ω to 1 MΩ | 0.22 Ω to 1 MΩ | 0.22 Ω to 10 MΩ |
| | 1000 h | ≤ 0.05 % | ≤ 0.15 % | ≤ 0.25 % |
| | 8000 h | ≤ 0.1 % | ≤ 0.3 % | ≤ 0.5 % |
| | 225 000 h | ≤ 0.25 % | ≤ 0.75 % | - |

| TEMPERATURE COEFFICIENT AND RESISTANCE RANGE | | | | |
|---|---|---|---|---|
| **TYPE / SIZE** | **TCR** | **TOLERANCE** | **RESISTANCE** | **E-SERIES** |
| SMM0204 | ± 100 ppm/K | ± 5 % | 0.22 Ω to 10 MΩ | E24 |
| | ± 50 ppm/K | ± 1 % | 0.82 Ω to 10 MΩ | E24; E96 |
| | | ± 0.5 % | 10 Ω to 1 MΩ | E24; E96; E192 |
| | ± 25 ppm/K | ± 0.5 % | 10 Ω to 1 MΩ | E24; E96; E192 |
| | | ± 0.25 % | 22 Ω to 511 kΩ | |
| | | ± 0.1 % | 43 Ω to 511 kΩ | |
| | ± 15 ppm/K | ± 0.5 % | 10 Ω to 221 kΩ | E24; E96; E192 |
| | | ± 0.25 % | 22 Ω to 221 kΩ | |
| | | ± 0.1 % | 43 Ω to 221 kΩ | |
| | Jumper | ≤ 10 mΩ; $I_{max.}$ = 3 A | | |

**Notes**

- The color of the body coating is light green for jumpers and for a temperature coefficient of ± 50 ppm/K or of ± 100 ppm/K, pink for ± 25 ppm/K, or violet for ± 15 ppm/K.
- Zero ohm jumper are marked with one centered black band.

| PACKAGING | | | | | | |
|---|---|---|---|---|---|---|
| **TYPE / SIZE** | **CODE** | **QUANTITY** | **CARRIER TAPE** | **WIDTH** | **PITCH** | **REEL DIAMETER** |
| SMM0204<br>OMM0204 | B1 (1) | 1000 (1) | Antistatic blister tape acc. IEC 60286-3 Type 2a | 8 mm | 4 mm | 180 mm/7" |
| | B3 | 3000 | | | | |
| | B0 | 10 000 | | | | 330 mm/13" |
| SMM0204 EN803 E0<br>OMM0204 EN803 E0 | B1 | 1000 | Antistatic blister tape acc. IEC 60286-3 Type 2a | 8 mm | 4 mm | 180 mm/7" |
| | B3 | 3000 | | | | |
| | B0 | 10 000 | | | | 330 mm/13" |

**Note**

(1) Package of 1000 pieces, code B1, is available only for products with TCR ± 25 ppm/K or ± 15 ppm/K, and with tolerance ± 0.25 % or ± 0.1 %. Bulk case acc. IEC 60286-6 available on request.


For technical questions, contact: melf@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

## PART NUMBER AND PRODUCT DESCRIPTION

**Part Number: SMM02040C5620FB000**
**Part Number: SMM0204VC5620FB000**
**Part Number: OMM02040000000B000**

| S | M | M | 0 | 2 | 0 | 4 | 0 | C | 5 | 6 | 2 | 0 | F | B | 0 | 0 | 0 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| O | M | M | 0 | 2 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | B | 0 | 0 | 0 |

| TYPE / SIZE | VERSION | TCR | RESISTANCE | TOLERANCE | PACKAGING |
|---|---|---|---|---|---|
| **SMM0204**<br>**OMM0204** | **0** = Neutral<br>**V** = EN 140401-803, version A, nominal failure rate level E0 | **E** = ± 15 ppm/K<br>**D** = ± 25 ppm/K<br>**C** = ± 50 ppm/K<br>**B** = ± 100 ppm/K<br>**0** = Jumper | **3 digit value**<br>**1 digit multiplier**<br>**0000** = Jumper<br>MULTIPLIER<br>**7** = $*10^{-3}$ **2** = $*10^{2}$<br>**8** = $*10^{-2}$ **3** = $*10^{3}$<br>**9** = $*10^{-1}$ **4** = $*10^{4}$<br>**0** = $*10^{0}$ **5** = $*10^{5}$<br>**1** = $*10^{1}$ | **B** = ± 0.1 %<br>**C** = ± 0.25 %<br>**D** = ± 0.5 %<br>**F** = ± 1 %<br>**J** = ± 5 %<br>**0** = Jumper | **B1**<br>**B3**<br>**B0** |

**Product Description: SMM0204 50 562R 1 % B0**
**Product Description: SMM0204 50 562R 1 % B0 EN803 E0**
**Product Description: OMM0204 0R0 B0**

| | | | | | |
|---|---|---|---|---|---|
| **SMM0204** | **50** | **562R** | **1 %** | **B0** | - |
| **OMM0204** | - | **0R0** | - | **B0** | - |
| TYPE / SIZE | TCR | RESISTANCE | TOLERANCE | PACKAGING | VERSION |
| **SMM0204**<br>**OMM0204** | ± **15** ppm/K<br>± **25** ppm/K<br>± **50** ppm/K<br>± **100** ppm/K | **100R** = 100 Ω<br>**2M21** = 2.21 MΩ<br>**0R0** = JUMPER | **± 0.1 %**<br>**± 0.25 %**<br>**± 0.5 %**<br>**± 1 %**<br>**± 5 %** | **B1**<br>**B3**<br>**B0** | |

**Notes**

- Products can be ordered using either the PART NUMBER or the PRODUCT DESCRIPTION.
- Products according to EN 140401-803 can be ordered by usng the related ordering code "SMM0204V...".



For technical questions, contact: melf@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

## DESCRIPTION

Production is strictly controlled and follows an extensive set of instructions established for reproducibility. A homogeneous film of metal alloy is deposited on a high grade ceramic body ($Al_2O_3$) and conditioned to achieve the desired temperature coefficient. Nickel plated steel termination caps are firmly pressed on the metallized rods. A special laser is used to achieve the target value by smoothly cutting a helical groove in the resistive layer without damaging the ceramic. The resistor elements are covered by a protective coating designed for electrical, mechanical and climatic protection. The terminations receive a final pure tin on nickel and copper plating for enhanced temperature cycling stability. Four or five color code rings designate the resistance value and tolerance in accordance with **IEC 60062** (1).

The result of the determined production is verified by an extensive testing procedure performed on 100 % of the individual resistors. This includes full screening for the elimination of products with a potential risk of early field failures (feasible for $R \geq 10\ \Omega$) according to EN 140401-803, 2.1.2.2. Only accepted products are laid directly into the blister tape in accordance with **IEC 60286-3, Type 2a** (1).

## ASSEMBLY

The resistors are suitable for processing on automatic SMD assembly systems. They are suitable for automatic soldering using wave, reflow or vapor phase as shown in **IEC 61760-1** (1). The encapsulation is resistant to all cleaning solvents commonly used in the electronics industry, including alcohols, esters and aqueous solutions. The suitability of conformal coatings, potting compounds and their processes, if applied, shall be qualified by appropriate means to ensure the long-term stability of the whole system.

The resistors are completely lead (Pb)-free, the pure tin plating provides compatibility with lead (Pb)-free and lead containing soldering processes. Solderability is specified for 2 years after production or requalification, however, excellent solderability is proven after extended storage in excess of 10 years. The permitted storage time is 20 years. The immunity of the plating against tin whisker growth has been proven under extensive testing.

All products comply with the **IEC 62474**, Material Declaration for Products of and for the Electrotechnical Industry.

The dedicated database (2), that list declarable substances, ensures full compliance with the following directives:

- 2000/53/EC End of Life Vehicle Directive (ELV) and Annex II (ELV II)
- 2011/65/EU Restriction of the use of Hazardous Substances Directive (RoHS)
- 2012/19/EU Waste Electrical and Electronic Equipment Directive (WEEE)

## APPROVALS

The resistors are qualified according to AEC-Q200. Resistors approved according to EN 140401-803 are available by using the related ordering code.

## RELATED PRODUCTS

MELF resistors of other sizes are available:

Thin Fim Micro-MELF Resistors SMM0102
(www.vishay.com/doc?20003)

Thin Fim MELF Resistors SMM0207
(www.vishay.com/doc?20005)

Resistors are available with established reliability in accordance with **EN 140401-803 Version E**. Please refer to datasheet “MELF Resistors with Established Reliability” (www.vishay.com/doc?28707).

MS1 .... ESCC high-reliability thin film MINI-MELF resistors are the premium choice for design and manufacture of equipment, where matured technology and proven reliability are of utmost importance. They are regularly used in communication and research satellites and fit equally well into aircraft and military electronic systems.

Approval of the MS1 .... ESCC products is granted by the European Space Components Coordination and registered in the ESCC Qualified Parts List, REP005.
(www.vishay.com/doc?28790).

**Notes**

(1) The quoted IEC standards are also released as EN standards with the same number and identical contents.

(2) IEC 62474 database can be found at: http://std.iec.ch/iec62474.



For technical questions, contact: melf@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

## FUNCTIONAL PERFORMANCE




**Temperature Rise**




**Derating**




**Non-linearity**




**Current Noise - $A_1$**




**HF - Performance**




**HF - Performance**



For technical questions, contact: melf@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

## FUNCTIONAL PERFORMANCE




**Single pulse high voltage overload capability 1.2/50 acc. EN 60115-1, 4.27**




**Single pulse high voltage overload capability 10/700 acc. EN 60115-1, 4.27**




Maximum pulse load, single pulse; applicable if $\bar{P} \rightarrow 0$ and $n \leq 1000$ and $\hat{U} \leq \hat{U}_{max.}$;
for permissible resistance change equivalent to 8000 h operation in power operation mode

**Single Pulse**




Maximum pulse load, continuous pulses; applicable if $\bar{P} \leq P\ (\vartheta_{amb})$ and $\hat{U} \leq \hat{U}_{max.}$;
for permissible resistance change equivalent to 8000 h operation in power operation mode

**Continuous Pulse**



For technical questions, contact: melf@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000




Maximum pulse voltage, single and continuous pulses; applicable if $\hat{P} \leq \hat{P}_{max.}$;
for permissible resistance change equivalent to 8000 h operation in power operation mode

**Pulse Voltage**

## TESTS AND REQUIREMENTS

All tests are carried out in accordance with the following specifications:

EN 60115-1, generic specification

EN 60115-8 (successor of EN 140400), sectional specification

EN 140401-803, detail specification

IEC 60068-2-xx, test methods

The parameters stated in the Test Procedures and Requirements table are based on the required tests and permitted limits of EN 140401-803. The table presents only the most important tests, for the full test schedule refer to the documents listed above. However, some additional tests and a number of improvements against those minimum requirements have been included.

The testing also covers most of the requirements specified by EIA/ECA-703 and JIS-C-5201-1.

The tests are carried out under standard atmospheric conditions in accordance with IEC 60068-1, 4.3, whereupon the following values are applied:

Temperature: 15 °C to 35 °C

Relative humidity: 45 % to 75 %

Air pressure: 86 kPa to 106 kPa (860 mbar to 1060 mbar).

A climatic category LCT / UCT / 56 is applied, defined by the lower category temperature (LCT), the upper category temperature (UCT), and the duration of exposure in the damp heat, steady state test (56 days).

The components are mounted for testing on printed circuit boards in accordance with EN 60115-8, 2.4.2, unless otherwise specified.

**TEST PROCEDURES AND REQUIREMENTS**

| EN 60115-1 CLAUSE | IEC 60068-2 (1) TEST METHOD | TEST | PROCEDURE | REQUIREMENTS PERMISSIBLE CHANGE ($\Delta R$) | | | |
|---|---|---|---|---|---|---|---|
| | | | SMM0204 | < 1 Ω | 1 Ω to < 10 Ω | 10 Ω to ≤ 1 MΩ | > 1 MΩ |
| 4.8.4.2 | - | Temperature coefficient (1) | At (20 / -55 / 20) °C and (20 / 125 / 20) °C | ± 100 ppm/K, ± 50 ppm/K, ± 25 ppm/K, ± 15 ppm/K | | | |
| 4.25.1 | - | Endurance at 70 °C: precision operation mode | $U = \sqrt{P_{70} \times R} \leq U_{max.}$; 1.5 h on; 0.5 h off; 70 °C; 1000 h | | | ± (0.05 % $R$ + 0.005 Ω) | |
| | | | 70 °C; 8000 h | | | ± (0.1 % $R$ + 0.005 Ω) | |
| | | Endurance at 70 °C: standard operation mode | $U = \sqrt{P_{70} \times R} \leq U_{max.}$; 1.5 h on; 0.5 h off; 70 °C; 1000 h | ± (0.15 % $R$ + 0.01 Ω) | | ± (0.1 % $R$ + 0.005 Ω) | ± (0.25 % $R$) |
| | | | 70 °C; 8000 h | ± (0.3 % $R$ + 0.01 Ω) | | ± (0.2 % $R$ + 0.005 Ω) | ± (0.5 % $R$) |


For technical questions, contact: melf@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

## TEST PROCEDURES AND REQUIREMENTS

| EN 60115-1 CLAUSE | IEC 60068-2 (1) TEST METHOD | TEST | PROCEDURE | REQUIREMENTS PERMISSIBLE CHANGE ($\Delta R$) | | | |
|---|---|---|---|---|---|---|---|
| | | | SMM0204 | < 1 Ω | 1 Ω to < 10 Ω | 10 Ω to ≤ 1 MΩ | > 1 MΩ |
| 4.25.1 | - | Endurance at 70 °C: power operation mode | $U = \sqrt{P_{70} \times R}$ ≤ $U_{max.}$; 1.5 h on; 0.5 h off; 70 °C; 1000 h<br>70 °C; 8000 h | ± (0.25 % $R$ + 0.01 Ω)<br>± (0.5 % $R$ + 0.01 Ω) | | | |
| 4.25.3 | - | Endurance at upper category temperature | 125 °C; 1000 h | ± (0.15 % $R$ + 0.01 Ω) | | ± (0.1 % $R$ + 0.005 Ω) | ± (0.25 % $R$) |
| | | | 155 °C; 1000 h | ± (0.3 % $R$ + 0.01 Ω) | | ± (0.2 % $R$ + 0.005 Ω) | ± (0.5 % $R$) |
| 4.24 | 78 (Cab) | Damp heat, steady state | (40 ± 2) °C; 56 days; (93 ± 3) % RH | ± (0.15 % $R$ + 0.01 Ω) | | | ± (0.25 % $R$) |
| 4.39 | 67 (Cy) | Damp heat, steady state, accelerated | (85 ± 2) °C (85 ± 5) % RH $U = \sqrt{0.3 \times P_{70} \times R}$ ≤ 100 V and $U$ = 0.3 x $U_{max.}$; (the smaller value is valid) 1000 h | ± (0.25 % $R$ + 0.01 Ω) | | | ± (2 % $R$) |
| - | - | Cold | -55 °C; 2000 h | ± (0.1 % $R$ + 0.01 Ω) | | | |
| 4.19 | 14 (Na) | Rapid change of temperature | 30 min at LCT and 30 min at UCT; LCT = -55 °C; UCT = 125 °C; 1000 cycles | ± (0.15 % $R$ + 0.01 Ω) | | | ± (0.25 % $R$) |
| | | | LCT = -55 °C; UCT = 155 °C; 1000 cycles | ± (0.5 % $R$ + 0.01 Ω) | | | |
| 4.13 | - | Short time overload: standard operation mode | $U = 2.5 \times \sqrt{P_{70} \times R}$ ≤ 2 x $U_{max.}$; 5 s | ± (0.03 % $R$ + 0.01 Ω) | | | ± (0.1 % $R$) |
| | | Short time overload: power operation mode | | ± (0.05 % $R$ + 0.01 Ω) | | | ± (0.1 % $R$) |
| 4.27 | - | Single pulse high voltage overload: standard operation mode | Severity no. 4: $U = 10 \times \sqrt{P_{70} \times R}$ ≤ 2 x $U_{max.}$; 10 pulses 10 µs/700 µs | ± (0.15 % $R$ + 0.01 Ω) | | | |
| | | Single pulse high voltage overload: power peration mode | | ± (0.15 % $R$ + 0.01 Ω) | | | |


For technical questions, contact: melf@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

## TEST PROCEDURES AND REQUIREMENTS

| EN 60115-1 CLAUSE | IEC 60068-2 [1] TEST METHOD | TEST | PROCEDURE | REQUIREMENTS PERMISSIBLE CHANGE ($\Delta R$) | | | |
|---|---|---|---|---|---|---|---|
| | | | SMM0204 | < 1 Ω | 1 Ω to < 10 Ω | 10 Ω to ≤ 1 MΩ | > 1 MΩ |
| 4.37 | - | Periodic electric overload: standard operation mode | $U = \sqrt{15 \times P_{70} \times R}$ ≤ 2 x $U_{max.}$; 0.1 s on; 2.5 s off; 1000 cycles | ± (0.15 % $R$ + 0.01 Ω) | | | |
| | | Periodic electric overload: power operation mode | | ± (0.3 % $R$ + 0.01 Ω) | | | |
| 4.22 | 6 (Fc) | Vibration | Endurance by sweeping; 10 Hz to 2000 Hz; no resonance; amplitude ≤ 1.5 mm or ≤ 200 m/s$^2$; 7.5 h | ± (0.05 % $R$ + 0.01 Ω) | | | ± (0.1 % $R$) |
| 4.38 | - | Electrostatic discharge (Human Body Model) | IEC 61340-3-1 [1]; 3 pos. + 3 neg. discharges SMM 0204: 2 kV | ± (0.5 % $R$ + 0.05 Ω) | | | |
| 4.17.2 | 58 (Td) | Solderability | Solder bath method; SnPb40; non-activated flux (215 ± 3) °C; (3 ± 0.3) s | Good tinning (≥ 95% covered); no visible damage | | | |
| | | | Solder bath method; SnAg3Cu0.5 or SnAg3.5; non-activated flux; (235 ± 3) °C; (2 ± 0.2) s | Good tinning (≥ 95% covered); no visible damage | | | |
| 4.18.2 | 58 (Td) | Resistance to soldering heat | Solder bath method; (260 ± 5) °C; (10 ± 1) s | ± (0.1 % $R$ + 0.01 Ω) | | ± (0.05 % $R$ + 0.01 Ω) | |
| | | | Reflow method 2 (IR/forced gas convection); (260 ± 5) °C; (10 ± 1) s | ± (0.05 % $R$ + 0.01 Ω) | | ± (0.02 % $R$ + 0.01 Ω) | |
| 4.29 | 45 (XA) | Component solvent resistance | Isopropyl alcohol; 50 °C; method 2 | No visible damage | | | |
| 4.30 | 45 (XA) | Solvent resistance of marking | Isopropyl alcohol; 50 °C; method 1, toothbrush | Marking visible, no visible damage | | | |
| 4.32 | 21 ($Ue_3$) | Shear (adhesion) | 45 N | No visible damage | | | |
| 4.33 | 21 ($Ue_1$) | Substrate bending | Depth 2 mm, 3 times | No visible damage, no open circuit in bent position ± (0.05 % + 0.005 Ω) | | | |
| 4.7 | - | Voltage proof | $U_{RMS} = U_{ins}$; 60 s | No flashover or breakdown | | | |
| 4.35 | - | Flammability | IEC 60695-11-5 [1]; needle flame test; 10 s | No burning after 30s | | | |

**Note**

[1] The quoted IEC standards are also released as EN standards with the same number and identical contents.



For technical questions, contact: melf@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

## DIMENSIONS




| DIMENSIONS AND MASS | | | | | | |
|---|---|---|---|---|---|---|
| TYPE / SIZE | L (mm) | D (mm) | $L_{1\ min.}$ (mm) | $D_1$ (mm) | K (mm) | MASS (mg) |
| SMM0204<br>OMM0204 | 3.6 + 0/- 0.2 | 1.4 + 0/- 0.1 | 1.8 | D + 0/- 0.15 | 0.8 ± 0.1 | 22 |

**Notes**

- Color code marking is applied according to IEC 60062 (1) in four bands (E24 series) for 5 % tolerance, or in five bands (E96 or E192 series). Each color band appears as a single solid line, voids are permissible if at least $^2/_3$ of the band is visible from each radial angle of view. The last color band for tolerance is approximately 50 % wider than the other bands.

## PATTERN STYLES FOR MELF RESISTORS




| RECOMMENDED SOLDER PAD DIMENSIONS | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| TYPE / SIZE | WAVE SOLDERING | | | | REFLOW SOLDERING | | | |
| | G (mm) | Y (mm) | X (mm) | Z (mm) | G (mm) | Y (mm) | X (mm) | Z (mm) |
| SMM0204<br>OMM0204 | 1.5 | 1.5 | 1.8 | 4.5 | 1.7 | 1.2 | 1.6 | 4.1 |

**Notes**

- The rated dissipation applies only if the permitted film temperature is not exceeded. Furthermore, a high level of ambient temperature or of power dissipation may raise the temperature of the solder joint, hence special solder alloys or board materials may be required to maintain the reliability of the assembly. Specified power rating above standard operation mode requires dedicated heat-sink pads, which to a great extend depend on board materials and design. The given solder pad dimensions reflect the considerations for board design and assembly as outlined e.g. in standards IEC 61188-5-x (1), or in publication IPC-7351. They do not guarantee any supposed thermal properties, particularly as these are also strongly influenced by many other parameters.
  Please note however that applications for "power operation mode" require special considerations for the design of solder pads and adjacent conductor areas.

(1) The quoted IEC standards are also released as EN standards with the same number and identical contents.



For technical questions, contact: melf@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

# Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay’s knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer’s responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer’s technical experts. Product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

# Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.




**Как с нами связаться**

**Телефон:** 8 (812) 309 58 32 (многоканальный)
**Факс:** 8 (812) 320-02-42
**Электронная почта:** org@eplast1.ru
**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.