



Is Now Part of



ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at
www.onsemi.com

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild_questions@onsemi.com.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.



June 2015

LM431SA / LM431SB / LM431SC

Programmable Shunt Regulator

Features

- Programmable Output Voltage to 36 V
- Low Dynamic Output Impedance: 0.2 Ω (Typical)
- Sink Current Capability: 1.0 to 100 mA
- Equivalent Full-Range Temperature Coefficient of 50 ppm/ $^{\circ}\text{C}$ (Typical)
- Temperature Compensated for Operation Over Full Rated Operating Temperature Range
- Low Output Noise Voltage
- Fast Turn-on Response

Description

The LM431SA / LM431SB / LM431SC are three-terminal the output adjustable regulators with thermal stability over operating temperature range. The output voltage can be set any value between V_{REF} (approximately 2.5 V) and 36 V with two external resistors. These devices have a typical dynamic output impedance of 0.2 Ω . Active output circuit provides a sharp turn-on characteristic, making these devices excellent replacement for zener diodes in many applications.

SOT-89

1. Ref 2. Anode 3. Cathode

SOT-23F

1. Cathode 2. Ref 3. Anode

SOT-23M32 - 1. Ref 2. Cathode 3. Anode
M3 - 1. Cathode 2. Ref 3. Anode

Ordering Information

Product Number	Output Voltage Tolerance	Operating Temperature	Top Mark ⁽¹⁾	Package	Packing Method
LM431SACMFX	2%	-25 to +85°C	43A □	SOT-23F 3L	Tape and Reel
LM431SACM3X			43L	SOT-23 3L	
LM431SACM32X			43G	SOT-23 3L	
LM431SBCMLX	43B		SOT-89 3L		
LM431SBCMFX	43B □		SOT-23F 3L		
LM431SBCM3X	43M		SOT-23 3L		
LM431SBCM32X	43H		SOT-23 3L		
LM431SCCMLX	43C		SOT-89 3L		
LM431SCCMFX	43C □		SOT-23F 3L		
LM431SCCM3X	43N		SOT-23 3L		
LM431SCCM32X	43J		SOT-23 3L		
LM431SAIMFX	2%	-40 to +85°C	43AI	SOT-23F 3L	

Note:

1. SOT-23 and SOT-23F have basically four-character marking except LM431SAIMFX.

(3 letters for device code + 1 letter for date code)

SOT-23F date code is composed of 1 digit numeric or alphabetic week code adding bar-type year code.

> Week code: Change in every two weeks

> Year code (additional bar): Rotate in three year cycle

Week	01-02	03-04	05-06	07-08	09-10	11-12	13-14	15-16	17-18	19-20	21-22	23-24	25-26
Code	1	2	3	4	5	6	7	8	9	A	D	E	F
Week	27-28	29-30	31-32	33-34	35-36	37-38	39-40	41-42	43-44	45-46	47-48	49-50	51-52
Code	H	J	K	L	N	O	P	R	S	T	U	V	X

Year	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018
Code	□	□	□	□	□	□	□	□	□	□	□

Block Diagram




Figure 1. Block Diagram

Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only. Values are at $T_A = 25^\circ\text{C}$ unless otherwise noted.

Symbol	Parameter		Value	Unit
V_{KA}	Cathode Voltage		37	V
I_{KA}	Cathode current Range (Continuous)		-100 to +150	mA
I_{REF}	Reference Input Current Range		-0.05 to +10.00	mA
$R_{\theta JA}$	Thermal Resistance Junction-Air ^(2,3)	ML Suffix Package (SOT-89)	220	$^\circ\text{C/W}$
		MF Suffix Package (SOT-23F)	350	
		M32, M3 Suffix Package (SOT-23)	400	
P_D	Power Dissipation ^(4,5)	ML Suffix Package (SOT-89)	560	mW
		MF Suffix Package (SOT-23F)	350	
		M32, M3 Suffix Package (SOT-23)	310	
T_J	Junction Temperature		150	$^\circ\text{C}$
T_{OPR}	Operating Temperature Range	All products except LM431SAIMFX	-25 to +85	$^\circ\text{C}$
		LM431SAIMFX	-40 to +85	
T_{STG}	Storage Temperature Range		-65 to +150	$^\circ\text{C}$

Notes:

- Thermal resistance test board
Size: 1.6 mm x 76.2 mm x 114.3 mm (1S0P)
JEDEC Standard: JESD51-3, JESD51-7.
- Assume no ambient airflow.
- $T_{JMAX} = 150^\circ\text{C}$; ratings apply to ambient temperature at 25°C .
- Power dissipation calculation: $P_D = (T_J - T_A) / R_{\theta JA}$.

Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. Fairchild does not recommend exceeding them or designing to Absolute Maximum Ratings.

Symbol	Parameter	Min.	Max.	Unit
V_{KA}	Cathode Voltage	V_{REF}	36	V
I_{KA}	Cathode Current	1	100	mA

Electrical Characteristics⁽⁶⁾Values are at $T_A = 25^\circ\text{C}$ unless otherwise noted.

Symbol	Parameter	Conditions	LM431SA			LM431SB			LM431SC			Unit
			Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	
V_{REF}	Reference Input Voltage	$V_{KA} = V_{REF}$, $I_{KA} = 10\text{ mA}$	2.450	2.500	2.550	2.470	2.495	2.520	2.482	2.495	2.508	V
$\Delta V_{REF} / \Delta T$	Deviation of Reference Input Voltage Over-Temperature	$V_{KA} = V_{REF}$, $I_{KA} = 10\text{ mA}$, $T_{MIN} \leq T_A \leq T_{MAX}$	SOT-89 SOT-23F				4.5	17.0		4.5	17.0	mV
			SOT-23				6.6	24		6.6	24	mV
$\Delta V_{REF} / \Delta V_{KA}$	Ratio of Change in Reference Input Voltage to the Change in Cathode Voltage	$I_{KA} = 10\text{ mA}$	$\Delta V_{KA} = 10\text{ V} - V_{REF}$				-1.0	-2.7		-1.0	-2.7	mV/V
			$\Delta V_{KA} = 36\text{ V} - 10\text{ V}$				-0.5	-2.0		-0.5	-2.0	
I_{REF}	Reference Input Current	$I_{KA} = 10\text{ mA}$, $R_1 = 10\text{ K}\Omega$, $R_2 = \infty$		1.5	4.0		1.5	4.0		1.5	4.0	μA
$\Delta I_{REF} / \Delta T$	Deviation of Reference Input Current Over Full Temperature Range	$I_{KA} = 10\text{ mA}$, $R_1 = 10\text{ K}\Omega$, $R_2 = \infty$, $T_A = \text{Full Range}$	SOT-89 SOT-23F				0.4	1.2		0.4	1.2	μA
			SOT-23				0.8	2.0		0.8	2.0	μA
$I_{KA(MIN)}$	Minimum Cathode Current for Regulation	$V_{KA} = V_{REF}$		0.45	1.00		0.45	1.00		0.45	1.00	mA
$I_{KA(OFF)}$	Off -Stage Cathode Current	$V_{KA} = 36\text{ V}$, $V_{REF} = 0$		0.05	1.00		0.05	1.00		0.05	1.00	μA
Z_{KA}	Dynamic Impedance	$V_{KA} = V_{REF}$, $I_{KA} = 1\text{ to }100\text{ mA}$, $f \geq 1.0\text{ kHz}$		0.15	0.50		0.15	0.50		0.15	0.50	Ω


Note:6. $T_{MIN} = -25^\circ\text{C}$, $T_{MAX} = +85^\circ\text{C}$.

Electrical Characteristics^(7, 8) (Continued)Values are at $T_A = 25^\circ\text{C}$ unless otherwise noted.

Symbol	Parameter	Conditions	LM431SAI			Unit
			Min.	Typ.	Max.	
V_{REF}	Reference Input Voltage	$V_{\text{KA}} = V_{\text{REF}}, I_{\text{KA}} = 10 \text{ mA}$	2.450	2.500	2.550	V
$V_{\text{REF(dev)}}$	Deviation of Reference Input Voltage Over-Temperature	$V_{\text{KA}} = V_{\text{REF}}, I_{\text{KA}} = 10 \text{ mA}, T_{\text{MIN}} \leq T_A \leq T_{\text{MAX}}$		5	20	mV
$\Delta V_{\text{REF}}/\Delta V_{\text{KA}}$	Ratio of Change in Reference Input Voltage to Change in Cathode Voltage	$I_{\text{KA}} = 10 \text{ mA}$		-1.0	-2.7	mV/V
		$\Delta V_{\text{KA}} = 36 \text{ V} - 10 \text{ V}$		-0.5	-2.0	
I_{REF}	Reference Input Current	$I_{\text{KA}} = 10 \text{ mA}, R_1 = 10 \text{ K}\Omega, R_2 = \infty$		1.5	4.0	μA
$I_{\text{REF(dev)}}$	Deviation of Reference Input Current Over Full Temperature Range	$I_{\text{KA}} = 10 \text{ mA}, R_1 = 10 \text{ K}\Omega, R_2 = \infty, T_{\text{MIN}} \leq T_A \leq T_{\text{MAX}}$		0.8	2.0	μA
$I_{\text{KA(MIN)}}$	Minimum Cathode Current for Regulation	$V_{\text{KA}} = V_{\text{REF}}$		0.45	1.00	mA
$I_{\text{KA(OFF)}}$	Off -Stage Cathode Current	$V_{\text{KA}} = 36 \text{ V}, V_{\text{REF}} = 0$		0.05	1.00	μA
Z_{KA}	Dynamic Impedance	$V_{\text{KA}} = V_{\text{REF}}, I_{\text{KA}} = 1 \text{ to } 100 \text{ mA}, f \geq 1.0 \text{ kHz}$		0.15	0.50	Ω

Notes:7. $T_{\text{MIN}} = -40^\circ\text{C}$, $T_{\text{MAX}} = +85^\circ\text{C}$.8. The deviation parameters $V_{\text{REF(dev)}}$ and $I_{\text{REF(dev)}}$ are defined as the differences between the maximum and minimum values obtained over the rated temperature range. The average full-range temperature coefficient of the reference input voltage, αV_{REF} , is defined as:

$$|\alpha V_{\text{REF}}| \left(\frac{\text{ppm}}{^\circ\text{C}} \right) = \frac{\left(\frac{V_{\text{REF(dev)}}}{V_{\text{REF(at } 25^\circ\text{C)}}} \right) \cdot 10^6}{T_{\text{MAX}} - T_{\text{MIN}}}$$

where $T_{\text{MAX}} - T_{\text{MIN}}$ is the rated operating free-air temperature range of the device. αV_{REF} can be positive or negative, depending on whether minimum V_{REF} or maximum V_{REF} , respectively, occurs at the lower temperature.Example: $V_{\text{REF(dev)}} = 4.5 \text{ mV}$, $V_{\text{REF}} = 2500 \text{ mV}$ at 25°C , $T_{\text{MAX}} - T_{\text{MIN}} = 125^\circ\text{C}$ for LM431SAI.

$$|\alpha V_{\text{REF}}| = \frac{\left(\frac{4.5 \text{ mV}}{2500 \text{ mV}} \right) \cdot 10^6}{125^\circ\text{C}} = 14.4 \text{ ppm}/^\circ\text{C}$$

Because minimum V_{REF} occurs at the lower temperature, the coefficient is positive.

Test Circuits




Figure 2. Test Circuit for $V_{KA} = V_{REF}$




Figure 3. Test Circuit for $V_{KA} \geq V_{REF}$




Figure 4. Test Circuit for $I_{KA(OFF)}$

Typical Applications

$$V_O = \left(1 + \frac{R_1}{R_2}\right) V_{\text{ref}}$$




Figure 5. Shunt Regulator

$$V_O = V_{\text{ref}} \left(1 + \frac{R_1}{R_2}\right)$$




Figure 6. Output Control for Three-Terminal Fixed Regulator

$$V_O = \left(1 + \frac{R_1}{R_2}\right) V_{\text{ref}}$$




Figure 7. High Current Shunt Regulator




Figure 8. Current Limit or Current Source




Figure 9. Constant-Current Sink

Typical Performance Characteristics




Figure 10. Cathode Current vs. Cathode Voltage




Figure 11. Cathode Current vs. Cathode Voltage




Figure 12. OFF-State Cathode Current vs. Ambient Temperature




Figure 13. Reference Input Current vs. Ambient Temperature




Figure 14. Frequency vs. Small Signal Voltage Amplification




Figure 15. Pulse Response

Typical Performance Characteristics (Continued)




Figure 16. Stability Boundary Conditions




Figure 17. Anode-Reference Diode Curve




Figure 18. Reference-Cathode Diode Curve





Figure 19. Reference Input Voltage vs. Ambient Temperature

Physical Dimensions



NOTES: UNLESS OTHERWISE SPECIFIED.

A. REFERENCE TO JEDEC TO-243 VARIATION AA.
B. ALL DIMENSIONS ARE IN MILLIMETERS.

C. DOES NOT COMPLY JEDEC STANDARD VALUE.
D. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH AND TIE BAR PROTRUSION.
E. DIMENSION AND TOLERANCE AS PER ASME Y14.5-1994.
F. DRAWING FILE NAME: MA03CREV3

Figure 20. 3-LEAD, SOT-89, JEDEC TO-243, OPTION AA

Physical Dimensions (Continued)




Figure 21. 3-LEAD, SOT23F, FLAT LEAD, LOW PROFILE

Technical drawing of a component with dimensions and callouts. The drawing includes a top view, a side view, and a detail view (DETAIL A).

Top View Dimensions:

- Overall width: 2.92 ± 0.20
- Overall height: $1.30^{+0.20}_{-0.15}$
- Feature 1 width: 0.95
- Feature 2 width: 0.60
- Feature 3 width: 0.37
- Feature 4 width: 0.20
- Feature 5 width: 0.20
- Feature 6 width: 0.20
- Feature 7 width: 0.20
- Feature 8 width: 0.20
- Feature 9 width: 0.20
- Feature 10 width: 0.20
- Feature 11 width: 0.20
- Feature 12 width: 0.20
- Feature 13 width: 0.20
- Feature 14 width: 0.20
- Feature 15 width: 0.20
- Feature 16 width: 0.20
- Feature 17 width: 0.20
- Feature 18 width: 0.20
- Feature 19 width: 0.20
- Feature 20 width: 0.20
- Feature 21 width: 0.20
- Feature 22 width: 0.20
- Feature 23 width: 0.20
- Feature 24 width: 0.20
- Feature 25 width: 0.20
- Feature 26 width: 0.20
- Feature 27 width: 0.20
- Feature 28 width: 0.20
- Feature 29 width: 0.20
- Feature 30 width: 0.20
- Feature 31 width: 0.20
- Feature 32 width: 0.20
- Feature 33 width: 0.20
- Feature 34 width: 0.20
- Feature 35 width: 0.20
- Feature 36 width: 0.20
- Feature 37 width: 0.20
- Feature 38 width: 0.20
- Feature 39 width: 0.20
- Feature 40 width: 0.20
- Feature 41 width: 0.20
- Feature 42 width: 0.20
- Feature 43 width: 0.20
- Feature 44 width: 0.20
- Feature 45 width: 0.20
- Feature 46 width: 0.20
- Feature 47 width: 0.20
- Feature 48 width: 0.20
- Feature 49 width: 0.20
- Feature 50 width: 0.20
- Feature 51 width: 0.20
- Feature 52 width: 0.20
- Feature 53 width: 0.20
- Feature 54 width: 0.20
- Feature 55 width: 0.20
- Feature 56 width: 0.20
- Feature 57 width: 0.20
- Feature 58 width: 0.20
- Feature 59 width: 0.20
- Feature 60 width: 0.20
- Feature 61 width: 0.20
- Feature 62 width: 0.20
- Feature 63 width: 0.20
- Feature 64 width: 0.20
- Feature 65 width: 0.20
- Feature 66 width: 0.20
- Feature 67 width: 0.20
- Feature 68 width: 0.20
- Feature 69 width: 0.20
- Feature 70 width: 0.20
- Feature 71 width: 0.20
- Feature 72 width: 0.20
- Feature 73 width: 0.20
- Feature 74 width: 0.20
- Feature 75 width: 0.20
- Feature 76 width: 0.20
- Feature 77 width: 0.20
- Feature 78 width: 0.20
- Feature 79 width: 0.20
- Feature 80 width: 0.20
- Feature 81 width: 0.20
- Feature 82 width: 0.20
- Feature 83 width: 0.20
- Feature 84 width: 0.20
- Feature 85 width: 0.20
- Feature 86 width: 0.20
- Feature 87 width: 0.20
- Feature 88 width: 0.20
- Feature 89 width: 0.20
- Feature 90 width: 0.20
- Feature 91 width: 0.20
- Feature 92 width: 0.20
- Feature 93 width: 0.20
- Feature 94 width: 0.20
- Feature 95 width: 0.20
- Feature 96 width: 0.20
- Feature 97 width: 0.20
- Feature 98 width: 0.20
- Feature 99 width: 0.20
- Feature 100 width: 0.20

Side View Dimensions:

- Overall height: 1.20 MAX
- Feature 1 height: 0.93
- Feature 2 height: 0.10
- Feature 3 height: 0.00
- Feature 4 height: 0.10
- Feature 5 height: 0.00
- Feature 6 height: 0.10
- Feature 7 height: 0.00
- Feature 8 height: 0.10
- Feature 9 height: 0.00
- Feature 10 height: 0.10
- Feature 11 height: 0.00
- Feature 12 height: 0.10
- Feature 13 height: 0.00
- Feature 14 height: 0.10
- Feature 15 height: 0.00
- Feature 16 height: 0.10
- Feature 17 height: 0.00
- Feature 18 height: 0.10
- Feature 19 height: 0.00
- Feature 20 height: 0.10
- Feature 21 height: 0.00
- Feature 22 height: 0.10
- Feature 23 height: 0.00
- Feature 24 height: 0.10
- Feature 25 height: 0.00
- Feature 26 height: 0.10
- Feature 27 height: 0.00
- Feature 28 height: 0.10
- Feature 29 height: 0.00
- Feature 30 height: 0.10
- Feature 31 height: 0.00
- Feature 32 height: 0.10
- Feature 33 height: 0.00
- Feature 34 height: 0.10
- Feature 35 height: 0.00
- Feature 36 height: 0.10
- Feature 37 height: 0.00
- Feature 38 height: 0.10
- Feature 39 height: 0.00
- Feature 40 height: 0.10
- Feature 41 height: 0.00
- Feature 42 height: 0.10
- Feature 43 height: 0.00
- Feature 44 height: 0.10
- Feature 45 height: 0.00
- Feature 46 height: 0.10
- Feature 47 height: 0.00
- Feature 48 height: 0.10
- Feature 49 height: 0.00
- Feature 50 height: 0.10
- Feature 51 height: 0.00
- Feature 52 height: 0.10
- Feature 53 height: 0.00
- Feature 54 height: 0.10
- Feature 55 height: 0.00
- Feature 56 height: 0.10
- Feature 57 height: 0.00
- Feature 58 height: 0.10
- Feature 59 height: 0.00
- Feature 60 height: 0.10
- Feature 61 height: 0.00
- Feature 62 height: 0.10
- Feature 63 height: 0.00
- Feature 64 height: 0.10
- Feature 65 height: 0.00
- Feature 66 height: 0.10
- Feature 67 height: 0.00
- Feature 68 height: 0.10
- Feature 69 height: 0.00
- Feature 70 height: 0.10
- Feature 71 height: 0.00
- Feature 72 height: 0.10
- Feature 73 height: 0.00
- Feature 74 height: 0.10
- Feature 75 height: 0.00
- Feature 76 height: 0.10
- Feature 77 height: 0.00
- Feature 78 height: 0.10
- Feature 79 height: 0.00
- Feature 80 height: 0.10
- Feature 81 height: 0.00
- Feature 82 height: 0.10
- Feature 83 height: 0.00
- Feature 84 height: 0.10
- Feature 85 height: 0.00
- Feature 86 height: 0.10
- Feature 87 height: 0.00
- Feature 88 height: 0.10



TRADEMARKS

The following includes products registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

AccuPower™
AttitudeEngine™
Awinda®
AX-CAP®
BitSiC™
Build it Now™
CorePLUS™
CorePOWER™
CROSSVOLT™
CTL™
Current Transfer Logic™
DEUXPEED®
Dual Cool™
EcoSPARK®
EfficientMax™
ESBC™
F®
Fairchild®
Fairchild Semiconductor®
FACT Quiet Series™
FACT®
FAST®
FastvCore™
FETBench™
FPS™

F-PFS™
FRFET®
Global Power ResourceSM
GreenBridge™
Green FPS™
Green FPS™ e-Series™
Gmax™
GTO™
IntelliMAX™
ISOPLANAR™
Making Small Speakers Sound Louder and Better™
MegaBuck™
MICROCOUPLER™
MicroFET™
MicroPak™
MicroPak2™
MillerDrive™
MotionMax™
MotionGrid®
MTi®
MTx®
MVN®
mWSaver®
OptoHiT™
OPTOLOGIC®

OPTOPLANAR®

Power Supply WebDesigner™
PowerTrench®
PowerXS™
Programmable Active Droop™
QFET®
QS™
Quiet Series™
RapidConfigure™

Saving our world, 1mW/W/kW at a time™
SignalWise™
SmartMax™
SMART START™
Solutions for Your Success™
SPM®
STEALTH™
SuperFET®
SuperSOT™-3
SuperSOT™-6
SuperSOT™-8
SupreMOS®
SyncFET™
Sync-Lock™

 SYSTEM GENERAL®
TinyBoost®
TinyBuck®
TinyCalc™
TinyLogic®
TINYOPTO™
TinyPower™
TinyPWM™
TinyWire™
TranSiC™
TriFault Detect™
TRUECURRENT®
µSerDes™
 SerDes™
UHC®
Ultra FRFET™
UniFET™
VCX™
VisualMax™
VoltagePlus™
XS™
Xsens™
仙童™

* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. TO OBTAIN THE LATEST, MOST UP-TO-DATE DATASHEET AND PRODUCT INFORMATION, VISIT OUR WEBSITE AT <http://www.fairchildsemi.com>. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.

Rev. 174

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada

Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910

Japan Customer Focus Center
Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local
Sales Representative

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ON Semiconductor:](#)

[LM431SBCM32X](#) [LM431SBCMFX](#) [LM431SBCMLX](#) [LM431SBCM3X](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.