

## 1.8V, 7MHz, 90dB CMRR, SINGLE-SUPPLY, RAIL-TO-RAIL I/O OPERATIONAL AMPLIFIER

### FEATURES

- 1.8V OPERATION
- *Micro*SIZE PACKAGES
- BANDWIDTH: 7MHz
- CMRR: 90dB (typical)
- SLEW RATE: 5V/ $\mu$ s
- LOW OFFSET: 500 $\mu$ V (max)
- QUIESCENT CURRENT: 750 $\mu$ A/Channel (max)
- SHUTDOWN MODE: < 1 $\mu$ A/Channel

### APPLICATIONS

- SIGNAL CONDITIONING
- DATA ACQUISITION
- PROCESS CONTROL
- ACTIVE FILTERS
- TEST EQUIPMENT

### DESCRIPTION

The OPA363 and OPA364 families are high-performance CMOS operational amplifiers optimized for very low voltage, single-supply operation. These miniature, low-cost amplifiers are designed to operate on single supplies from 1.8V ( $\pm 0.9$ V) to 5.5V ( $\pm 2.75$ V). Applications include sensor amplification and signal conditioning in battery-powered systems.

The OPA363 and OPA364 families offer excellent CMRR without the crossover associated with traditional complementary input stages. This results in excellent performance for driving Analog-to-Digital (A/D) converters without degradation of differential linearity and THD. The input common-mode range includes both the negative and positive supplies. The output voltage swing is within 10mV of the rails.

The OPA363 family includes a shutdown mode. Under logic control, the amplifiers can be switched from normal operation to a standby current that is less than 1 $\mu$ A.

The single version is available in the *Micro*SIZE SOT23-5 (SOT23-6 for shutdown) and SO-8. The dual version is available in MSOP-8, MSOP-10, and SO-8 packages. Quad packages are available in TSSOP-14 and SO-14 packages. All versions are specified for operation from  $-40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ .

|          | OPA363 | OPA364 | OPA2363 | OPA2364 | OPA4364 |
|----------|--------|--------|---------|---------|---------|
| SOT23-5  |        | x      |         |         |         |
| SOT23-6  | x      |        |         |         |         |
| MSOP-8   |        |        |         | x       |         |
| MSOP-10  |        |        | x       |         |         |
| SO-8     | x      | x      |         | x       |         |
| TSSOP-14 |        |        |         |         | x       |
| SO-14    |        |        |         |         | x       |



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

## ABSOLUTE MAXIMUM RATINGS<sup>(1)</sup>

|                                                      |                      |
|------------------------------------------------------|----------------------|
| Supply Voltage .....                                 | +5.5V                |
| Signal Input Terminals, Voltage <sup>(2)</sup> ..... | –0.5V to (V+) + 0.5V |
| Current <sup>(2)</sup> .....                         | ±10mA                |
| Enable Input .....                                   | (V–) – 0.5V to 5.5V  |
| Output Short-Circuit <sup>(3)</sup> .....            | Continuous           |
| Operating Temperature .....                          | –40°C to +150°C      |
| Storage Temperature .....                            | –65°C to +150°C      |
| Junction Temperature .....                           | +150°C               |
| Lead Temperature (soldering, 10s) .....              | +300°C               |

NOTES: (1) Stresses above these ratings may cause permanent damage. Exposure to absolute maximum conditions for extended periods may degrade device reliability. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those specified is not implied. (2) Input terminals are diode-clamped to the power-supply rails. Input signals that can swing more than 0.5V beyond the supply rails should be current limited to 10mA or less. (3) Short-circuit to ground one amplifier per package.



## ELECTROSTATIC DISCHARGE SENSITIVITY

This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.








## PACKAGE/ORDERING INFORMATION

| PRODUCT        | PACKAGE-LEAD  | PACKAGE DESIGNATOR <sup>(1)</sup> | SPECIFIED TEMPERATURE RANGE | PACKAGE MARKING | ORDERING NUMBER                | TRANSPORT MEDIA, QUANTITY                 |
|----------------|---------------|-----------------------------------|-----------------------------|-----------------|--------------------------------|-------------------------------------------|
| OPA363I<br>"   | SOT23-6<br>"  | DBV<br>"                          | –40°C to +125°C<br>"        | A40<br>"        | OPA363IDBVT<br>OPA363IDBVR     | Tape and Reel, 250<br>Tape and Reel, 3000 |
| OPA363I<br>"   | SO-8<br>"     | D<br>"                            | –40°C to +125°C<br>"        | OPA363<br>"     | OPA363ID<br>OPA363IDR          | Rails, 100<br>Tape and Reel, 2500         |
| OPA2363I<br>"  | MSOP-10<br>"  | DGS<br>"                          | –40°C to +125°C<br>"        | BHK<br>"        | OPA2363IDGST<br>OPA2363IDGSR   | Tape and Reel, 250<br>Tape and Reel, 2500 |
| OPA364I<br>"   | SOT23-5<br>"  | DBV<br>"                          | –40°C to +125°C<br>"        | A41<br>"        | OPA364IDBVT<br>OPA364IDBVR     | Tape and Reel, 250<br>Tape and Reel, 3000 |
| OPA364I<br>"   | SO-8<br>"     | D<br>"                            | –40°C to +125°C<br>"        | OPA364<br>"     | OPA364ID<br>OPA364IDR          | Rails, 100<br>Tape and Reel, 2500         |
| OPA2364I<br>"  | MSOP-8<br>"   | DGK<br>"                          | –40°C to +125°C<br>"        | BHL<br>"        | OPA2364IDGKT<br>OPA2364IDGKR   | Tape and Reel, 250<br>Tape and Reel, 2500 |
| OPA2364I<br>"  | SO-8<br>"     | D<br>"                            | –40°C to +125°C<br>"        | OPA2364<br>"    | OPA2364ID<br>OPA2364IDR        | Rails, 100<br>Tape and Reel, 2500         |
| OPA363AI<br>"  | SOT23-6<br>"  | DBV<br>"                          | –40°C to +125°C<br>"        | A40<br>"        | OPA363AIDBVT<br>OPA363AIDBVR   | Tape and Reel, 250<br>Tape and Reel, 3000 |
| OPA363AI<br>"  | SO-8<br>"     | D<br>"                            | –40°C to +125°C<br>"        | OPA363A<br>"    | OPA363AID<br>OPA363AIDR        | Rails, 100<br>Tape and Reel, 2500         |
| OPA2363AI<br>" | MSOP-10<br>"  | DGS<br>"                          | –40°C to +125°C<br>"        | BHK<br>"        | OPA2363AIDGST<br>OPA2363AIDGSR | Tape and Reel, 250<br>Tape and Reel, 2500 |
| OPA364AI<br>"  | SOT23-5<br>"  | DBV<br>"                          | –40°C to +125°C<br>"        | A41<br>"        | OPA364AIDBVT<br>OPA364AIDBVR   | Tape and Reel, 250<br>Tape and Reel, 3000 |
| OPA364AI<br>"  | SO-8<br>"     | D<br>"                            | –40°C to +125°C<br>"        | OPA364A<br>"    | OPA364AID<br>OPA364AIDR        | Rails, 100<br>Tape and Reel, 2500         |
| OPA2364AI<br>" | SO-8<br>"     | D<br>"                            | –40°C to +125°C<br>"        | OPA2634A<br>"   | OPA2364AID<br>OPA2364AIDR      | Rails, 100<br>Tape and Reel, 2500         |
| OPA2364AI<br>" | MSOP-8<br>"   | DGK<br>"                          | –40°C to +125°C<br>"        | BHL<br>"        | OPA2364AIDGKT<br>OPA2364AIDGKR | Tape and Reel, 250<br>Tape and Reel, 2500 |
| OPA4364AI<br>" | SO-14<br>"    | D<br>"                            | –40°C to +125°C<br>"        | OPA4364A<br>"   | OPA4364AID<br>OPA4364AIDR      | Rails, 58<br>Tape and Reel, 2500          |
| OPA4364AI<br>" | TSSOP-14<br>" | PW<br>"                           | –40°C to +125°C<br>"        | OPA4364A<br>"   | OPA4364AIPWT<br>OPA4364AIPWR   | Tape and Reel, 250<br>Tape and Reel, 2500 |

NOTES: (1) For the most current specifications and package information, refer to our web site at [www.ti.com](http://www.ti.com).

## PIN CONFIGURATIONS

### Top View



NOTE: (1) Orient according to marking.

NC = No Internal Connection.

# ELECTRICAL CHARACTERISTICS: $V_S = +1.8V$ to $+5.5V$

**Boldface** limits apply over the specified temperature range,  $T_A = -40^{\circ}C$  to  $+125^{\circ}C$ .







At  $T_A = +25^{\circ}C$ ,  $R_L = 10k\Omega$  connected to  $V_S/2$ , and  $V_{OUT} = V_S/2$ ,  $V_{CM} = V_S/2$ , unless otherwise noted.

| PARAMETER                                                                                                                                                                                                        | CONDITION                                                                                        | OPAx363, OPAx364                                                                                                                                                                          |                                                                  |                                                    | UNITS                                                                                        |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------|----------------------------------------------------|----------------------------------------------------------------------------------------------|
|                                                                                                                                                                                                                  |                                                                                                  | MIN                                                                                                                                                                                       | TYP                                                              | MAX                                                |                                                                                              |
| <b>OFFSET VOLTAGE</b><br>Input Offset Voltage, OPA363I, OPA364I<br>OPA2363I, OPA2364I<br>OPA363AI, OPA364AI, OPA2363AI, OPA2364AI, OPA4364AI<br><b>Drift</b><br><b>vs Power Supply</b><br>Channel Separation, dc | $V_{OS}$<br><br><br><br>$dV_{OS}/dT$<br><b>PSRR</b><br><br>$V_S = 1.8V$ to $5.5V$ , $V_{CM} = 0$ |                                                                                                                                                                                           |                                                                  | 500<br>900<br>2.5<br><br><b>80</b><br><b>330</b>   | $\mu V$<br>$\mu V$<br>mV<br>$\mu V/^{\circ}C$<br>$\mu V/V$<br>$\mu V/V$                      |
| <b>INPUT BIAS CURRENT</b><br>Input Bias Current<br><b>over Temperature</b><br>Input Offset Current                                                                                                               | $I_B$<br><br><br>$I_{OS}$                                                                        |                                                                                                                                                                                           | $\pm 1$<br>See Typical Characteristics<br>$\pm 1$                | $\pm 10$<br><br>$\pm 10$                           | pA<br><br>pA                                                                                 |
| <b>NOISE</b><br>Input Voltage Noise, $f = 0.1Hz$ to $10Hz$<br>Input Voltage Noise Density, $f = 10kHz$<br>Input Current Noise Density, $f = 10kHz$                                                               | $e_n$<br>$e_n$<br>$i_n$                                                                          |                                                                                                                                                                                           | 10<br>17<br>0.6                                                  |                                                    | $\mu Vp-p$<br>$nV/\sqrt{Hz}$<br>$fA/\sqrt{Hz}$                                               |
| <b>INPUT VOLTAGE RANGE</b><br>Common-Mode Voltage Range<br><b>Common-Mode Rejection Ratio</b>                                                                                                                    | $V_{CM}$<br><b>CMRR</b><br>$(V-) - 0.1V < V_{CM} < (V+) + 0.1V$                                  | $(V-) - 0.1$<br><b>74</b>                                                                                                                                                                 | <b>90</b>                                                        | $(V+) + 0.1$                                       | V<br>dB                                                                                      |
| <b>INPUT CAPACITANCE</b><br>Differential<br>Common-Mode                                                                                                                                                          |                                                                                                  |                                                                                                                                                                                           | 2<br>3                                                           |                                                    | pF<br>pF                                                                                     |
| <b>OPEN-LOOP GAIN</b><br>Open-Loop Voltage Gain<br>OPA4364AI<br><b>over Temperature</b>                                                                                                                          | $A_{OL}$<br><br><br>$V_S = +1.8V$ to $+5.5V$                                                     | $R_L = 10k\Omega$ , $100mV < V_O < (V+) - 100mV$<br><br><br><b>86</b>                                                                                                                     | 94<br>90<br><b>86</b>                                            | 100                                                | dB<br>dB<br>dB                                                                               |
| <b>FREQUENCY RESPONSE</b><br>Gain Bandwidth Product<br>Slew Rate<br>Settling Time, 0.1%<br>0.01%<br>Overload Recovery Time<br>Total Harmonic Distortion + Noise                                                  | GBW<br><br>SR<br>$t_S$<br><br>THD+N                                                              | $C_L = 100pF$<br><br>$G = +1$<br>$V_S = +5V$ , 4V Step, $G = +1$<br>$V_S = +5V$ , 4V Step, $G = +1$<br>$V_{IN} \cdot \text{Gain} > V_S$<br>$V_S = +5V$ , $G = +1$ , $f = 20Hz$ to $20kHz$ | <br>7<br>5<br>1<br>1.5<br>0.8<br>0.002                           |                                                    | MHz<br>V/ $\mu s$<br>$\mu s$<br>$\mu s$<br>$\mu s$<br>%                                      |
| <b>OUTPUT</b><br>Voltage Output Swing from Rail<br><b>over Temperature</b><br>Short-Circuit Current<br>Capacitive Load Drive                                                                                     | <br><br>$I_{SC}$<br>$C_{LOAD}$                                                                   | $R_L = 10k\Omega$<br><b><math>R_L = 10k\Omega</math></b>                                                                                                                                  | 10<br>See Typical Characteristics<br>See Typical Characteristics | 20<br><b>20</b>                                    | mV<br>mV<br>mA                                                                               |
| <b>SHUTDOWN (for OPAx363)</b><br>$t_{OFF}$<br>$t_{ON}^{(1)}$<br>$V_L$ (shutdown)<br>$V_H$ (amplifier is active)<br>$I_{QSD}$                                                                                     |                                                                                                  | 0.75 (V+)                                                                                                                                                                                 | 1<br>20                                                          | $(V-) + 0.8$<br>5.5<br>0.9                         | $\mu s$<br>$\mu s$<br>V<br>V<br>$\mu A$                                                      |
| <b>POWER SUPPLY</b><br>Specified Voltage Range<br>Operating Voltage Range<br>Quiescent Current (per amplifier)                                                                                                   | $V_S$<br><br>$I_Q$                                                                               | $V_S = +1.8V$<br>$V_S = +3.6V$<br>$V_S = +5.5V$                                                                                                                                           | 1.8<br><br>1.8 to 5.5<br><b>650</b><br><b>850</b><br><b>1.1</b>  | 5.5<br><br><b>750</b><br><b>1000</b><br><b>1.4</b> | V<br>V<br>$\mu A$<br>$\mu A$<br>mA                                                           |
| <b>TEMPERATURE RANGE</b><br>Specified Range<br>Operating Range<br>Storage Range<br>Thermal Resistance<br>SOT23-5, SOT23-6<br>MSOP-8, MSOP-10, SO-8<br>TSSOP-14, SO-14                                            | <br><br><br>$\theta_{JA}$                                                                        | <br><br><br>-40<br>-40<br>-65                                                                                                                                                             | <br><br><br>200<br>150<br>100                                    | +125<br>+150<br>+150                               | $^{\circ}C$<br>$^{\circ}C$<br>$^{\circ}C$<br>$^{\circ}C/W$<br>$^{\circ}C/W$<br>$^{\circ}C/W$ |

NOTE: (1) Part is considered enabled when input offset voltage returns to specified range.







# TYPICAL CHARACTERISTICS

At  $T_{CASE} = +25^{\circ}\text{C}$ ,  $R_L = 10\text{k}\Omega$ , and connected to  $V_S/2$ ,  $V_{OUT} = V_S/2$ ,  $V_{CM} = V_S/2$ , unless otherwise noted.









# TYPICAL CHARACTERISTICS (Cont.)

At  $T_{CASE} = +25^{\circ}\text{C}$ ,  $R_L = 10\text{k}\Omega$ , and connected to  $V_S/2$ ,  $V_{OUT} = V_S/2$ ,  $V_{CM} = V_S/2$ , unless otherwise noted.





# TYPICAL CHARACTERISTICS (Cont.)

At  $T_{CASE} = +25^{\circ}\text{C}$ ,  $R_L = 10\text{k}\Omega$ , and connected to  $V_S/2$ ,  $V_{OUT} = V_S/2$ ,  $V_{CM} = V_S/2$ , unless otherwise noted.



# TYPICAL CHARACTERISTICS (Cont.)

At  $T_{CASE} = +25^{\circ}C$ ,  $R_L = 10k\Omega$ , and connected to  $V_S/2$ ,  $V_{OUT} = V_S/2$ ,  $V_{CM} = V_S/2$ , unless otherwise noted.



## APPLICATIONS INFORMATION

The OPA363 and OPA364 series op amps are rail-to-rail operational amplifiers with excellent CMRR, low noise, low offset, and wide bandwidth on supply voltages as low as  $\pm 0.9V$ . The OPA363 features an additional pin for shutdown/enable function. These families do not exhibit phase reversal and are unity-gain stable. Specified over the industrial temperature range of  $-40^{\circ}C$  to  $+125^{\circ}C$ , the OPA363 and OPA364 families offer precision performance for a wide range of applications.

### RAIL-TO-RAIL INPUT

The OPA363 and OPA364 feature excellent rail-to-rail operation, with supply voltages as low as  $\pm 0.9V$ . The input common-mode voltage range of the OPA363 and OPA364 family extends 100mV beyond supply rails. The unique input topology of the OPA363 and OPA364 eliminates the input offset transition region typical of most rail-to-rail complimentary stage operational amplifiers, allowing the OPA363 and OPA364 to provide superior common-mode performance over the entire common-mode input range, as seen in Figure 1. This feature prevents degradation of the differential linearity error and THD when driving A/D converters. A simplified schematic of the OPA363 and OPA364 is shown in Figure 2.




FIGURE 1. OPA363 and OPA364 have Linear Offset Over Entire Common-Mode Range.




FIGURE 2. Simplified Schematic.

### OPERATING VOLTAGE

The OPA363 and OPA364 series op amp parameters are fully specified from  $+1.8V$  to  $+5.5V$ . Single  $0.1\mu F$  bypass capacitors should be placed across supply pins and as close to the part as possible. Supply voltages higher than  $5.5V$  (absolute maximum) may cause permanent damage to the amplifier. Many specifications apply from  $-40^{\circ}C$  to  $+125^{\circ}C$ . Parameters that vary significantly with operating voltages or temperature are shown in the Typical Characteristics.

## ENABLE FUNCTION

The shutdown (enable) function of the OPA363 is referenced to the negative supply voltage of the operational amplifier. A logic level HIGH enables the op amp. A valid logic HIGH is defined as voltage  $> 75\%$  of the positive supply applied to the enable pin. The valid logic HIGH signal can be as much as 5.5V above the negative supply, independent of the positive supply voltage. A valid logic LOW is defined as  $< 0.8\text{V}$  above the negative supply pin. If dual or split power supplies are used, care should be taken to ensure logic input signals are properly referred to the negative supply voltage. This pin should be connected to a valid high or low voltage or driven, not left open circuit.

The logic input is a high-impedance CMOS input. Dual op amps are provided separate logic inputs. For battery-operated applications, this feature may be used to greatly reduce the average current and extend battery life. The enable time is  $20\mu\text{s}$ ; disable time is  $1\mu\text{s}$ . When disabled, the output assumes a high-impedance state. This allows the OPA363 to be operated as a “gated” amplifier, or to have its output multiplexed onto a common analog output bus.

## CAPACITIVE LOAD

The OPA363 and OPA364 series op amps can drive a wide range of capacitive loads. However, all op amps under certain conditions may become unstable. Op amp configuration, gain, and load value are just a few of the factors to consider when determining stability. An op amp in unity-gain configuration is the most susceptible to the effects of capacitive load. The capacitive load reacts with the output resistance of the op amp to create a pole in the small-signal response, which degrades the phase margin.

In unity gain, the OPA363 and OPA364 series op amps perform well with a pure capacitive load up to approximately  $1000\text{pF}$ . The ESR (Equivalent Series Resistance) of the loading capacitor may be sufficient to allow the OPA363 and OPA364 to directly drive very large capacitive loads ( $> 1\mu\text{F}$ ). Increasing gain enhances the amplifier's ability to drive more capacitance. See the typical characteristic “Small-Signal Overshoot vs Capacitive Load.”

One method of improving capacitive load drive in the unity-gain configuration is to insert a  $10\Omega$  to  $20\Omega$  resistor in series with the output, as shown in Figure 3. This significantly reduces ringing with large capacitive loads. However, if there is a resistive load in parallel with the capacitive load, it creates a voltage divider introducing a dc error at the output and slightly reduces output swing. This error may be insignificant. For instance, with  $R_L = 10\text{k}\Omega$  and  $R_S = 20\Omega$ , there is only about a 0.2% error at the output.




FIGURE 3. Improving Capacitive Load Drive.

## INPUT AND ESD PROTECTION

All OPA363 and OPA364 pins are static protected with internal ESD protection diodes tied to the supplies. These diodes will provide overdrive protection if the current is externally limited to  $10\text{mA}$ , as stated in the absolute maximum ratings and shown in Figure 4.




FIGURE 4. Input Current Protection.

## ACHIEVING OUTPUT SWING TO THE OP AMP'S NEGATIVE RAIL

Some applications require an accurate output voltage swing from  $0\text{V}$  to a positive full-scale voltage. A good single supply op amp may be able to swing within a few mV of single supply ground, but as the output is driven toward  $0\text{V}$ , the output stage of the amplifier will prevent the output from reaching the negative supply rail of the amplifier.

The output of the OPA363 or OPA364 can be made to swing to ground, or slightly below, on a single supply power source. To do so requires use of another resistor and an additional, more negative power supply than the op amp's negative supply. A pull-down resistor may be connected between the output and the additional negative supply to pull the output down below the value that the output would otherwise achieve as shown in Figure 5.




FIGURE 5. OPA363 and OPA364 Swing to Ground.

This technique will not work with all op amps. The output stage of the OPA363 and OPA364 allows the output voltage to be pulled below that of most op amps, if approximately  $500\mu\text{A}$  is maintained through the output stage. To calculate the appropriate value load resistor and negative supply,  $R_L = -V/500\mu\text{A}$ . The OPA363 and OPA364 have been characterized to perform well under the described conditions, maintaining excellent accuracy down to  $0\text{V}$  and as low as  $-10\text{mV}$ . Limiting and nonlinearity occur below  $-10\text{mV}$ , with linearity returning as the output is again driven above  $-10\text{mV}$ .

## BUFFERED REFERENCE VOLTAGE

Many single-supply applications require a mid-supply reference voltage. The OPA363 and OPA364 offer excellent capacitive load drive capability, and can be configured to provide a 0.9V reference voltage, as can be seen in Figure 6. For appropriate loading considerations, see the “Capacitive Load” section.




FIGURE 6. The OPA363 and OPA364 Provide a Stable Reference Voltage.

## DIRECTLY DRIVING THE ADS8324 AND THE MSP430

The OPA363 and OPA364 series op amps are optimized for driving medium speed (up to 100kHz) sampling A/D converters. However, they also offer excellent performance for higher speed converters. The no crossover input stage of the OPA363 and OPA364 directly drive A/D converters without degradation of differential linearity and THD. They provide an effective means of buffering the A/D converters input capacitance and resulting charge injection while providing signal gain. Figure 7 and Figure 8 show the OPA363 and OPA364 configured to drive the ADS8324 and the 12-bit A/D converter on the MSP430.




FIGURE 7. The OPA363 and OPA364 Directly Drive the ADS8324.




FIGURE 8. Driving the 12-Bit A/D Converter on the MSP430.

## AUDIO APPLICATIONS

The OPA363 and OPA364 op amp family has linear offset voltage over the entire input common-mode range. Combined with low-noise, this feature makes the OPA363 and OPA364 suitable for audio applications. Single supply 1.8V operation allows the OPA2363 and OPA2364 to be optimal candidates for dual stereo-headphone drivers and microphone pre-amplifiers in portable stereo equipment, see Figures 9 and 10.




FIGURE 9. OPA2363 Configured as Half of a Dual Stereo Headphone Driver.




FIGURE 10. Microphone Preamplifier.

## ACTIVE FILTERING

Low harmonic distortion and noise specifications plus high gain and slew rate make the OPA363 and OPA364 optimal candidates for active filtering. Figure 11 shows the OPA2363 configured as a low-distortion, 3rd-order GIC (General Immitance Converter) filter. Figure 12 shows the implementation of a Sallen-Key, 3-pole, low-pass Bessel filter.




FIGURE 11. The OPA2363 as a 3rd-Order, 40kHz, Low-Pass GIC Filter.




FIGURE 12. The OPA363 or OPA364 Configured as a 3-Pole, 20kHz, Sallen-Key Filter.

**PACKAGING INFORMATION**

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package Qty | Eco Plan<br>(2)            | Lead/Ball Finish | MSL Peak Temp<br>(3) | Op Temp (°C) | Top-Side Markings<br>(4) | Samples                 |
|------------------|---------------|--------------|--------------------|------|-------------|----------------------------|------------------|----------------------|--------------|--------------------------|-------------------------|
| OPA2363AIDGSR    | ACTIVE        | VSSOP        | DGS                | 10   | 2500        | Green (RoHS<br>& no Sb/Br) | CU NIPDAUAG      | Level-2-260C-1 YEAR  | -40 to 125   | BHK                      | <a href="#">Samples</a> |
| OPA2363AIDGSRG4  | ACTIVE        | VSSOP        | DGS                | 10   | 2500        | Green (RoHS<br>& no Sb/Br) | CU NIPDAUAG      | Level-2-260C-1 YEAR  | -40 to 125   | BHK                      | <a href="#">Samples</a> |
| OPA2363AIDGST    | ACTIVE        | VSSOP        | DGS                | 10   | 250         | Green (RoHS<br>& no Sb/Br) | CU NIPDAUAG      | Level-2-260C-1 YEAR  | -40 to 125   | BHK                      | <a href="#">Samples</a> |
| OPA2363AIDGSTG4  | ACTIVE        | VSSOP        | DGS                | 10   | 250         | Green (RoHS<br>& no Sb/Br) | CU NIPDAUAG      | Level-2-260C-1 YEAR  | -40 to 125   | BHK                      | <a href="#">Samples</a> |
| OPA2363IDGSR     | ACTIVE        | VSSOP        | DGS                | 10   | 2500        | Green (RoHS<br>& no Sb/Br) | CU NIPDAUAG      | Level-2-260C-1 YEAR  | -40 to 125   | BHK                      | <a href="#">Samples</a> |
| OPA2363IDGSRG4   | ACTIVE        | VSSOP        | DGS                | 10   | 2500        | Green (RoHS<br>& no Sb/Br) | CU NIPDAUAG      | Level-2-260C-1 YEAR  | -40 to 125   | BHK                      | <a href="#">Samples</a> |
| OPA2363IDGST     | ACTIVE        | VSSOP        | DGS                | 10   | 250         | Green (RoHS<br>& no Sb/Br) | CU NIPDAUAG      | Level-2-260C-1 YEAR  | -40 to 125   | BHK                      | <a href="#">Samples</a> |
| OPA2363IDGSTG4   | ACTIVE        | VSSOP        | DGS                | 10   | 250         | Green (RoHS<br>& no Sb/Br) | CU NIPDAUAG      | Level-2-260C-1 YEAR  | -40 to 125   | BHK                      | <a href="#">Samples</a> |
| OPA2364AID       | ACTIVE        | SOIC         | D                  | 8    | 75          | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>2364<br>A         | <a href="#">Samples</a> |
| OPA2364AIDG4     | ACTIVE        | SOIC         | D                  | 8    | 75          | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>2364<br>A         | <a href="#">Samples</a> |
| OPA2364AIDGKR    | ACTIVE        | VSSOP        | DGK                | 8    | 2500        | Green (RoHS<br>& no Sb/Br) | CU NIPDAUAG      | Level-2-260C-1 YEAR  | -40 to 125   | BHL                      | <a href="#">Samples</a> |
| OPA2364AIDGKRG4  | ACTIVE        | VSSOP        | DGK                | 8    | 2500        | Green (RoHS<br>& no Sb/Br) | CU NIPDAUAG      | Level-2-260C-1 YEAR  | -40 to 125   | BHL                      | <a href="#">Samples</a> |
| OPA2364AIDGKT    | ACTIVE        | VSSOP        | DGK                | 8    | 250         | Green (RoHS<br>& no Sb/Br) | CU NIPDAUAG      | Level-2-260C-1 YEAR  | -40 to 125   | BHL                      | <a href="#">Samples</a> |
| OPA2364AIDGKTG4  | ACTIVE        | VSSOP        | DGK                | 8    | 250         | Green (RoHS<br>& no Sb/Br) | CU NIPDAUAG      | Level-2-260C-1 YEAR  | -40 to 125   | BHL                      | <a href="#">Samples</a> |
| OPA2364AIDR      | ACTIVE        | SOIC         | D                  | 8    | 2500        | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>2364<br>A         | <a href="#">Samples</a> |
| OPA2364AIDRG4    | ACTIVE        | SOIC         | D                  | 8    | 2500        | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>2364              | <a href="#">Samples</a> |

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package Qty | Eco Plan<br>(2)            | Lead/Ball Finish | MSL Peak Temp<br>(3) | Op Temp (°C) | Top-Side Markings<br>(4) | Samples                 |
|------------------|---------------|--------------|--------------------|------|-------------|----------------------------|------------------|----------------------|--------------|--------------------------|-------------------------|
|                  |               |              |                    |      |             |                            |                  |                      |              | A                        |                         |
| OPA2364ID        | ACTIVE        | SOIC         | D                  | 8    | 75          | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>2364              | <a href="#">Samples</a> |
| OPA2364IDG4      | ACTIVE        | SOIC         | D                  | 8    | 75          | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>2364              | <a href="#">Samples</a> |
| OPA2364IDGKR     | ACTIVE        | VSSOP        | DGK                | 8    | 2500        | Green (RoHS<br>& no Sb/Br) | CU NIPDAUAG      | Level-2-260C-1 YEAR  | -40 to 125   | BHL                      | <a href="#">Samples</a> |
| OPA2364IDGKRG4   | ACTIVE        | VSSOP        | DGK                | 8    | 2500        | Green (RoHS<br>& no Sb/Br) | CU NIPDAUAG      | Level-2-260C-1 YEAR  | -40 to 125   | BHL                      | <a href="#">Samples</a> |
| OPA2364IDGKT     | ACTIVE        | VSSOP        | DGK                | 8    | 250         | Green (RoHS<br>& no Sb/Br) | CU NIPDAUAG      | Level-2-260C-1 YEAR  | -40 to 125   | BHL                      | <a href="#">Samples</a> |
| OPA2364IDGKTG4   | ACTIVE        | VSSOP        | DGK                | 8    | 250         | Green (RoHS<br>& no Sb/Br) | CU NIPDAUAG      | Level-2-260C-1 YEAR  | -40 to 125   | BHL                      | <a href="#">Samples</a> |
| OPA2364IDR       | ACTIVE        | SOIC         | D                  | 8    | 2500        | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>2364              | <a href="#">Samples</a> |
| OPA2364IDRG4     | ACTIVE        | SOIC         | D                  | 8    | 2500        | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>2364              | <a href="#">Samples</a> |
| OPA363AID        | ACTIVE        | SOIC         | D                  | 8    | 75          | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>363<br>A          | <a href="#">Samples</a> |
| OPA363AIDBVR     | ACTIVE        | SOT-23       | DBV                | 6    | 3000        | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | A40                      | <a href="#">Samples</a> |
| OPA363AIDBVRG4   | ACTIVE        | SOT-23       | DBV                | 6    | 3000        | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | A40                      | <a href="#">Samples</a> |
| OPA363AIDBVT     | ACTIVE        | SOT-23       | DBV                | 6    | 250         | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | A40                      | <a href="#">Samples</a> |
| OPA363AIDBVTG4   | ACTIVE        | SOT-23       | DBV                | 6    | 250         | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | A40                      | <a href="#">Samples</a> |
| OPA363AIDG4      | ACTIVE        | SOIC         | D                  | 8    | 75          | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>363<br>A          | <a href="#">Samples</a> |
| OPA363ID         | ACTIVE        | SOIC         | D                  | 8    | 75          | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>363               | <a href="#">Samples</a> |
| OPA363IDBVR      | ACTIVE        | SOT-23       | DBV                | 6    | 3000        | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | A40                      | <a href="#">Samples</a> |
| OPA363IDBVRG4    | ACTIVE        | SOT-23       | DBV                | 6    | 3000        | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | A40                      | <a href="#">Samples</a> |

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package Qty | Eco Plan<br>(2)            | Lead/Ball Finish | MSL Peak Temp<br>(3) | Op Temp (°C) | Top-Side Markings<br>(4) | Samples                 |
|------------------|---------------|--------------|--------------------|------|-------------|----------------------------|------------------|----------------------|--------------|--------------------------|-------------------------|
| OPA363IDBVT      | ACTIVE        | SOT-23       | DBV                | 6    | 250         | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | A40                      | <a href="#">Samples</a> |
| OPA363IDBVTG4    | ACTIVE        | SOT-23       | DBV                | 6    | 250         | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | A40                      | <a href="#">Samples</a> |
| OPA363IDG4       | ACTIVE        | SOIC         | D                  | 8    | 75          | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>363               | <a href="#">Samples</a> |
| OPA364AID        | ACTIVE        | SOIC         | D                  | 8    | 75          | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>364<br>A          | <a href="#">Samples</a> |
| OPA364AIDBVR     | ACTIVE        | SOT-23       | DBV                | 5    | 3000        | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | A41                      | <a href="#">Samples</a> |
| OPA364AIDBVRG4   | ACTIVE        | SOT-23       | DBV                | 5    | 3000        | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | A41                      | <a href="#">Samples</a> |
| OPA364AIDBVT     | ACTIVE        | SOT-23       | DBV                | 5    | 250         | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | A41                      | <a href="#">Samples</a> |
| OPA364AIDBVTG4   | ACTIVE        | SOT-23       | DBV                | 5    | 250         | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | A41                      | <a href="#">Samples</a> |
| OPA364AIDG4      | ACTIVE        | SOIC         | D                  | 8    | 75          | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>364<br>A          | <a href="#">Samples</a> |
| OPA364AIDR       | ACTIVE        | SOIC         | D                  | 8    | 2500        | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>364<br>A          | <a href="#">Samples</a> |
| OPA364AIDRG4     | ACTIVE        | SOIC         | D                  | 8    | 2500        | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>364<br>A          | <a href="#">Samples</a> |
| OPA364ID         | ACTIVE        | SOIC         | D                  | 8    | 75          | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>364               | <a href="#">Samples</a> |
| OPA364IDBVR      | ACTIVE        | SOT-23       | DBV                | 5    | 3000        | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | A41                      | <a href="#">Samples</a> |
| OPA364IDBVRG4    | ACTIVE        | SOT-23       | DBV                | 5    | 3000        | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | A41                      | <a href="#">Samples</a> |
| OPA364IDBVT      | ACTIVE        | SOT-23       | DBV                | 5    | 250         | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | A41                      | <a href="#">Samples</a> |
| OPA364IDBVTG4    | ACTIVE        | SOT-23       | DBV                | 5    | 250         | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | A41                      | <a href="#">Samples</a> |

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package Qty | Eco Plan<br>(2)            | Lead/Ball Finish | MSL Peak Temp<br>(3) | Op Temp (°C) | Top-Side Markings<br>(4) | Samples                 |
|------------------|---------------|--------------|--------------------|------|-------------|----------------------------|------------------|----------------------|--------------|--------------------------|-------------------------|
| OPA364IDG4       | ACTIVE        | SOIC         | D                  | 8    | 75          | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>364               | <a href="#">Samples</a> |
| OPA364IDR        | ACTIVE        | SOIC         | D                  | 8    | 2500        | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>364               | <a href="#">Samples</a> |
| OPA364IDRG4      | ACTIVE        | SOIC         | D                  | 8    | 2500        | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>364               | <a href="#">Samples</a> |
| OPA4364AID       | ACTIVE        | SOIC         | D                  | 14   | 50          | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA4364A                 | <a href="#">Samples</a> |
| OPA4364AIDG4     | ACTIVE        | SOIC         | D                  | 14   | 50          | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA4364A                 | <a href="#">Samples</a> |
| OPA4364AIDR      | ACTIVE        | SOIC         | D                  | 14   | 2500        | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA4364A                 | <a href="#">Samples</a> |
| OPA4364AIDRG4    | ACTIVE        | SOIC         | D                  | 14   | 2500        | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA4364A                 | <a href="#">Samples</a> |
| OPA4364AIPWR     | ACTIVE        | TSSOP        | PW                 | 14   | 2500        | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>4364A             | <a href="#">Samples</a> |
| OPA4364AIPWRG4   | ACTIVE        | TSSOP        | PW                 | 14   | 2500        | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>4364A             | <a href="#">Samples</a> |
| OPA4364AIPWT     | ACTIVE        | TSSOP        | PW                 | 14   | 250         | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>4364A             | <a href="#">Samples</a> |
| OPA4364AIPWTG4   | ACTIVE        | TSSOP        | PW                 | 14   | 250         | Green (RoHS<br>& no Sb/Br) | CU NIPDAU        | Level-2-260C-1 YEAR  | -40 to 125   | OPA<br>4364A             | <a href="#">Samples</a> |

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

(2) Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

**TBD:** The Pb-Free/Green conversion plan has not been defined.

**Pb-Free (RoHS):** TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

**Pb-Free (RoHS Exempt):** This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

---

**Green (RoHS & no Sb/Br):** TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

<sup>(3)</sup> MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

<sup>(4)</sup> Only one of markings shown within the brackets will appear on the physical device.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.


In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**OTHER QUALIFIED VERSIONS OF OPA4364 :**

- Automotive: [OPA4364-Q1](#)

NOTE: Qualified Version Definitions:

- Automotive - Q100 devices qualified for high-reliability automotive applications targeting zero defects


**TAPE AND REEL INFORMATION**


\*All dimensions are nominal

| Device        | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|---------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| OPA2363AIDGSR | VSSOP        | DGS             | 10   | 2500 | 330.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| OPA2363AIDGST | VSSOP        | DGS             | 10   | 250  | 180.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| OPA2363IDGSR  | VSSOP        | DGS             | 10   | 2500 | 330.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| OPA2363IDGST  | VSSOP        | DGS             | 10   | 250  | 180.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| OPA2364AIDGKR | VSSOP        | DGK             | 8    | 2500 | 330.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| OPA2364AIDGKT | VSSOP        | DGK             | 8    | 250  | 180.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| OPA2364AIDR   | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| OPA2364IDGKR  | VSSOP        | DGK             | 8    | 2500 | 330.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| OPA2364IDGKT  | VSSOP        | DGK             | 8    | 250  | 180.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| OPA2364IDR    | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| OPA363AIDBVR  | SOT-23       | DBV             | 6    | 3000 | 180.0              | 8.4                | 3.2     | 3.1     | 1.39    | 4.0     | 8.0    | Q3            |
| OPA363AIDBVT  | SOT-23       | DBV             | 6    | 250  | 180.0              | 8.4                | 3.2     | 3.1     | 1.39    | 4.0     | 8.0    | Q3            |
| OPA363IDBVR   | SOT-23       | DBV             | 6    | 3000 | 180.0              | 8.4                | 3.2     | 3.1     | 1.39    | 4.0     | 8.0    | Q3            |
| OPA363IDBVT   | SOT-23       | DBV             | 6    | 250  | 180.0              | 8.4                | 3.2     | 3.1     | 1.39    | 4.0     | 8.0    | Q3            |
| OPA364AIDBVR  | SOT-23       | DBV             | 5    | 3000 | 180.0              | 8.4                | 3.2     | 3.1     | 1.39    | 4.0     | 8.0    | Q3            |
| OPA364AIDBVT  | SOT-23       | DBV             | 5    | 250  | 180.0              | 8.4                | 3.2     | 3.1     | 1.39    | 4.0     | 8.0    | Q3            |
| OPA364AIDR    | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| OPA364IDBVR   | SOT-23       | DBV             | 5    | 3000 | 180.0              | 8.4                | 3.2     | 3.1     | 1.39    | 4.0     | 8.0    | Q3            |

| Device       | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|--------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| OPA364IDBVT  | SOT-23       | DBV             | 5    | 250  | 180.0              | 8.4                | 3.2     | 3.1     | 1.39    | 4.0     | 8.0    | Q3            |
| OPA364IDR    | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| OPA4364AIPWR | TSSOP        | PW              | 14   | 2500 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| OPA4364AIPWT | TSSOP        | PW              | 14   | 250  | 180.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS




\*All dimensions are nominal

| Device        | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|---------------|--------------|-----------------|------|------|-------------|------------|-------------|
| OPA2363AIDGSR | VSSOP        | DGS             | 10   | 2500 | 367.0       | 367.0      | 35.0        |
| OPA2363AIDGST | VSSOP        | DGS             | 10   | 250  | 210.0       | 185.0      | 35.0        |
| OPA2363IDGSR  | VSSOP        | DGS             | 10   | 2500 | 367.0       | 367.0      | 35.0        |
| OPA2363IDGST  | VSSOP        | DGS             | 10   | 250  | 210.0       | 185.0      | 35.0        |
| OPA2364AIDGKR | VSSOP        | DGK             | 8    | 2500 | 367.0       | 367.0      | 35.0        |
| OPA2364AIDGKT | VSSOP        | DGK             | 8    | 250  | 210.0       | 185.0      | 35.0        |
| OPA2364AIDR   | SOIC         | D               | 8    | 2500 | 367.0       | 367.0      | 35.0        |
| OPA2364IDGKR  | VSSOP        | DGK             | 8    | 2500 | 367.0       | 367.0      | 35.0        |
| OPA2364IDGKT  | VSSOP        | DGK             | 8    | 250  | 210.0       | 185.0      | 35.0        |
| OPA2364IDR    | SOIC         | D               | 8    | 2500 | 367.0       | 367.0      | 35.0        |
| OPA363AIDBVR  | SOT-23       | DBV             | 6    | 3000 | 210.0       | 185.0      | 35.0        |
| OPA363AIDBVT  | SOT-23       | DBV             | 6    | 250  | 210.0       | 185.0      | 35.0        |
| OPA363IDBVR   | SOT-23       | DBV             | 6    | 3000 | 210.0       | 185.0      | 35.0        |

| Device       | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|--------------|--------------|-----------------|------|------|-------------|------------|-------------|
| OPA363IDBVT  | SOT-23       | DBV             | 6    | 250  | 210.0       | 185.0      | 35.0        |
| OPA364AIDBVR | SOT-23       | DBV             | 5    | 3000 | 210.0       | 185.0      | 35.0        |
| OPA364AIDBVT | SOT-23       | DBV             | 5    | 250  | 210.0       | 185.0      | 35.0        |
| OPA364AIDR   | SOIC         | D               | 8    | 2500 | 367.0       | 367.0      | 35.0        |
| OPA364IDBVR  | SOT-23       | DBV             | 5    | 3000 | 210.0       | 185.0      | 35.0        |
| OPA364IDBVT  | SOT-23       | DBV             | 5    | 250  | 210.0       | 185.0      | 35.0        |
| OPA364IDR    | SOIC         | D               | 8    | 2500 | 367.0       | 367.0      | 35.0        |
| OPA4364AIPWR | TSSOP        | PW              | 14   | 2500 | 367.0       | 367.0      | 35.0        |
| OPA4364AIPWT | TSSOP        | PW              | 14   | 250  | 210.0       | 185.0      | 35.0        |

## DBV (R-PDSO-G5)

## PLASTIC SMALL-OUTLINE PACKAGE



4073253-4/K 03/2006

- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Body dimensions do not include mold flash or protrusion. Mold flash and protrusion shall not exceed 0.15 per side.
  - D. Falls within JEDEC MO-178 Variation AA.

DBV (R-PDSO-G5)


PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Customers should place a note on the circuit board fabrication drawing not to alter the center solder mask defined pad.
  - D. Publication IPC-7351 is recommended for alternate designs.
  - E. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Example stencil design based on a 50% volumetric metal load solder paste. Refer to IPC-7525 for other stencil recommendations.

## DBV (R-PDSO-G6)

## PLASTIC SMALL-OUTLINE PACKAGE




4073253-5/K 03/2006

- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Body dimensions do not include mold flash or protrusion. Mold flash and protrusion shall not exceed 0.15 per side.
  - D. Leads 1,2,3 may be wider than leads 4,5,6 for package orientation.
- $\triangle$  Falls within JEDEC MO-178 Variation AB, except minimum lead width.

DBV (R-PDSO-G6)

PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Customers should place a note on the circuit board fabrication drawing not to alter the center solder mask defined pad.
  - D. Publication IPC-7351 is recommended for alternate designs.
  - E. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Example stencil design based on a 50% volumetric metal load solder paste. Refer to IPC-7525 for other stencil recommendations.

## DGK (S-PDSO-G8)


## PLASTIC SMALL-OUTLINE PACKAGE



4073329/E 05/06

## DGS (S-PDSO-G10)

## PLASTIC SMALL-OUTLINE PACKAGE




4073272/C 02/04

- NOTES:
- All linear dimensions are in millimeters.
  - This drawing is subject to change without notice.
  - Body dimensions do not include mold flash or protrusion.
  - Falls within JEDEC MO-187 variation BA.

D (R-PDSO-G14)

PLASTIC SMALL OUTLINE



4040047-5/M 06/11

NOTES:

- A. All linear dimensions are in inches (millimeters).
- B. This drawing is subject to change without notice.
- C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.006 (0,15) each side.
- D. Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
- E. Reference JEDEC MS-012 variation AB.

D (R-PDSO-G14)


PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Publication IPC-7351 is recommended for alternate designs.
  - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

PW (R-PDSO-G14)

PLASTIC SMALL OUTLINE




4040064-3/G 02/11

- NOTES:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
  - B. This drawing is subject to change without notice.
  - C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0,15 each side.
  - D. Body width does not include interlead flash. Interlead flash shall not exceed 0,25 each side.
  - E. Falls within JEDEC MO-153

PW (R-PDSO-G14)

PLASTIC SMALL OUTLINE



4211284-2/F 12/12

- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Publication IPC-7351 is recommended for alternate designs.
  - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

D (R-PDSO-G8)

PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - $\triangle C$  Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.006 (0,15) each side.
  - $\triangle D$  Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
  - E. Reference JEDEC MS-012 variation AA.

D (R-PDSO-G8)

PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Publication IPC-7351 is recommended for alternate designs.
  - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

### Products

|                              |                                                                                      |
|------------------------------|--------------------------------------------------------------------------------------|
| Audio                        | <a href="http://www.ti.com/audio">www.ti.com/audio</a>                               |
| Amplifiers                   | <a href="http://amplifier.ti.com">amplifier.ti.com</a>                               |
| Data Converters              | <a href="http://dataconverter.ti.com">dataconverter.ti.com</a>                       |
| DLP® Products                | <a href="http://www.dlp.com">www.dlp.com</a>                                         |
| DSP                          | <a href="http://dsp.ti.com">dsp.ti.com</a>                                           |
| Clocks and Timers            | <a href="http://www.ti.com/clocks">www.ti.com/clocks</a>                             |
| Interface                    | <a href="http://interface.ti.com">interface.ti.com</a>                               |
| Logic                        | <a href="http://logic.ti.com">logic.ti.com</a>                                       |
| Power Mgmt                   | <a href="http://power.ti.com">power.ti.com</a>                                       |
| Microcontrollers             | <a href="http://microcontroller.ti.com">microcontroller.ti.com</a>                   |
| RFID                         | <a href="http://www.ti-rfid.com">www.ti-rfid.com</a>                                 |
| OMAP Applications Processors | <a href="http://www.ti.com/omap">www.ti.com/omap</a>                                 |
| Wireless Connectivity        | <a href="http://www.ti.com/wirelessconnectivity">www.ti.com/wirelessconnectivity</a> |

### Applications

|                               |                                                                                          |
|-------------------------------|------------------------------------------------------------------------------------------|
| Automotive and Transportation | <a href="http://www.ti.com/automotive">www.ti.com/automotive</a>                         |
| Communications and Telecom    | <a href="http://www.ti.com/communications">www.ti.com/communications</a>                 |
| Computers and Peripherals     | <a href="http://www.ti.com/computers">www.ti.com/computers</a>                           |
| Consumer Electronics          | <a href="http://www.ti.com/consumer-apps">www.ti.com/consumer-apps</a>                   |
| Energy and Lighting           | <a href="http://www.ti.com/energy">www.ti.com/energy</a>                                 |
| Industrial                    | <a href="http://www.ti.com/industrial">www.ti.com/industrial</a>                         |
| Medical                       | <a href="http://www.ti.com/medical">www.ti.com/medical</a>                               |
| Security                      | <a href="http://www.ti.com/security">www.ti.com/security</a>                             |
| Space, Avionics and Defense   | <a href="http://www.ti.com/space-avionics-defense">www.ti.com/space-avionics-defense</a> |
| Video and Imaging             | <a href="http://www.ti.com/video">www.ti.com/video</a>                                   |

### TI E2E Community

[e2e.ti.com](http://e2e.ti.com)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.