

Chronos 2 timers

→ 17.5 mm DIN rail mounting


- Relay or solid state output
- Multi-function or mono-function
- Multi-range
- Multi-voltage
- Screw or spring terminals
- LED status indicator (relay version)
- Option of connecting an external power supply to the control input
- 3-wire sensor control option



Part numbers


Type	Functions	Timing	Output	Nominal rating	Connections	Supply voltage	Code
MUR1	A - At - B - C - H - Ht - Di - D - Ac - Bw	0.1 s→100h	1 changeover relay	8 A	Screw terminals	24 V  / 24 → 240 V 	88 827 105
MAR1	A - At	0.1s→100h	1 changeover relay	8 A	Screw terminals	24 V  / 24 → 240 V 	88 827 115
MBR1	B	0.1s→100h	1 changeover relay	8 A	Screw terminals	24 V  / 24 → 240 V 	88 827 125
MCR1	C	0.1s→100h	1 changeover relay	8 A	Screw terminals	24 V  / 24 → 240 V 	88 827 135
MHR1	H - Ht	0.1s→100h	1 changeover relay	8 A	Screw terminals	24 V  / 24 → 240 V 	88 827 145
MLR4	Li - L	0.1s→100h	1 changeover relay	8 A	Screw terminals	12 V  / 	88 827 150
MLR1	Li - L	0.1s→100h	1 changeover relay	8 A	Screw terminals	24 V  / 24 → 240 V 	88 827 155
MUR4	A - At - B - C - H - Ht - Di - D - Ac - Bw	0.1s→100h	1 changeover relay	8 A	Screw terminals	12 V  / 	88 827 100
MUR3	A - At - B - C - H - Ht - Di - D - Ac - Bw	0.1s→100h	1 changeover relay	8 A	Screw terminals	12→240 V  / 	88 827 103
MURc3	A - At - B - C - H - Ht - Di - D - Ac - Bw	0.1s→100h	1 changeover relay	8 A	Spring terminals	12 →240 V  / 	88 827 503
MXR1	Ad - Ah - N - O - P - Pt - TL - Tt - W	0.1s→100h	1 changeover relay	8 A	Screw terminals	24 V  / 24 → 240 V 	88 827 185
MUS2	A - At - B - C - H - Ht - Di - D - Ac - Bw	0.1s→100h	Solid state	0.7 A	Screw terminals	24 →240 V 	88 827 004
MAS5	A	0.1s→100h	Solid state	0.7 A	Screw terminals	24 →240 V  / 	88 827 014
MHS2	H	0.1s→100h	Solid state	0.7 A	Screw terminals	24 →240 V 	88 827 044
MLS2	Li - L	0.1s→100h	Solid state	0.7 A	Screw terminals	24 →240 V 	88 827 054

Dimensions (mm)




Connections

1 changeover relay output




A-At / H-Ht / B / C / Di-D / Ac / BW
Ad - Ah - N - O - P - Pt - Tl - Tt - W

Solid state output




A / H

1 changeover relay output




Li - L

Solid state output



L / Li

Solid state output



A-At / H-Ht / B / C / Di-D / Ac / BW
Ad - Ah - N - O - P - Pt - Tl - Tt - W

Curves

Function A




Delay on energisation

Function B




Timing on impulse one short

Function D



Flip-flop Pause start

Function Ht



Delay on energisation with memory

Function Ac




Timing after closing and opening of control contact

Function Bw



Pulse output (adjustable)

Function Di




Flip-flop Pulse start

Function L



Double temporisation

Function At



Timing on energisation with memory

Function C - 1 changeover relay



Timing after impulse

Function H




Timing on energisation

Function Li




Asymmetrical recycler
Pulse start

Function Ad



Delay on energisation by switch
(non resettable)

Function O




Delayed safe-guard

Function TI




Impulse relay

Function Ah



Flashing single cycle by switch
(non resettable)

Function P



Delayed fixed-length pulse

Function Tt




Timed impulse relay

Function N



Safe-guard

Function Pt



Impulse counter (delay on)

Function W



Timing after pulse on control contact

Chronos 2 timers

→ 17.5 mm DIN rail mounting

Timing

Timing ranges (7 ranges)	1 s - 10 s - 1 min - 10 min - 1 h - 10 h - 100 h
Repetition accuracy with constant parameters	± 0.5 % (IEC/EN 61812-1)
Drift Temperature	± 0.05 % / °C
Drift Voltage	± 0.2 % / V
Display accuracy according to IEC/EN 61812-1	± 10 % / 25 °C
Minimum pulse duration typically (relay version)	30 ms
Minimum pulse duration typically (solid state version)	50 ms
Minimum pulse duration typically (relay version under load)	100 ms
Maximum reset time by de-energisation typically (relay version)	120 ms
Maximum reset time by de-energisation typically (solid state version)	350 ms
Immunity from micro power cuts : typical	< 10 ms

Supply

Multi-voltage power supply	Depending on version
Frequency (Hz)	50 / 60
Operating range	85 → 110 % Un 85 → 120 % Un for 12 V ~ / ---
Operator factor	100 %
Max. absorbed power	32 VA (240 V ~) 1.5 W (240 V ---) 0.6 W (24 V ---) 0.7 VA (12 V ~) 0.7 W (12 V ---)

Output specification

1 or 2 changeover relays, AgNi (cadmium-free)	1 C/O
Rated power	2000 VA/80 W
Maximum breaking current	8 A ~ / 250 V ~ resistive 8 A --- / 30 V --- resistive
Minimum breaking current	10 mA / 5 V ---
Voltage breaking capacity	250 V ~ / 8 A ~ resistive 250 V --- / 0.3 A resistive
Electrical life (operations)	10 ⁵ 8 A 250 V ~ resistive
Mechanical life (operations)	10 x 10 ⁶
Breakdown voltage acc. to IEC/EN 61812-1	2.5 kV / 1 min / 1 mA / 50 Hz
Impulse voltage acc. to IEC/EN 60664-1, IEC/EN 61812-1	5 kV wave 1.2 / 50 µs

Solid state output

Rated power	0.7 A ~ / --- 20 °C (0.5 A UL)
Derating	5 mA/ °C
Maximum admissible current	20 A ≤ 10 ms
Minimum breaking current	10 mA
Leakage current	< 5 mA
Voltage breaking capacity	250 V ~ / ---
Maximum voltage drop at terminals	3 wire 4V 2 wire 8V
Electrical life (operations)	10 ⁸
Breakdown voltage acc. to IEC/EN 60664-1, IEC 60255-5	2.5 kV to 1 mA / 1 min

Input type

Volt-free contact
3-wire PNP output control option
residual voltage : 0.4V whatever the timer power supply

General characteristics

Conformity to standards	IEC/EN 61812-1 IEC/EN 61000-6-1 IEC/EN 61000-6-2 IEC/EN 61000-6-3 IEC/EN 61000-6-4
Certifications	CE, UL, cUL, CSA, GL
Temperature limits use (°C)	-20 → +60
Temperature limits stored (°C)	-30 → +60
Installation category (acc. to IEC/EN 60664-1)	Voltage surge category III
Creepage distance and clearance acc. to IEC/EN 60664-1	4 kV / 3 mm
Protection (IEC/EN 60529)	IP20
Degree of protection acc. to IEC/EN 60529 Front face	IP50
Vibration resistance acc. to IEC/EN 60068-2-6	20 m/s ² 10 Hz → 150 Hz
Relative humidity no condensation acc. to IEC/EN 60068-2-30	93 % non-condensing
Electromagnetic compatibility - Immunity to electrostatic discharges acc. to IEC/EN 61000-4-2	Level III (Air 8 kV / Contact 6 kV)
Immunity to radiated, radio-frequency, electromagnetic field acc. CE/EN 61000-4-3	Level I (1 V/m : 2.0 G Hz → 2.7 G Hz) Level II (3 V/m : 1.4 G Hz → 2.0 G Hz) Level III (10 V/m : 80 M Hz → 1 G Hz)
Immunity to rapid transient bursts acc. to IEC/EN 61000-4-4	Level III (direct 2 kV / Capacitive coupling clamp 1 kV)
Immunity to shock waves on power supply acc. to IEC/EN 61000-4-5	Level III (2 kV / common mode 2 kV/ residual current mode 1 kV)
Immunity to radio frequency in common mode acc. to IEC/EN 61000-4-6	Level III (10V rms : 0.15 M Hz to 80 M Hz)
Immunity to voltage dips and breaks acc. to IEC/EN 61000-4-11	0 % residual voltage, 1 cycle 70 % residual voltage, 25/30 cycles
Mains-borne and radiated emissions acc. to EN 55022 (CISPR22), EN55011 (CISPR11)	Class B
Fixing : Symmetrical DIN rail	35 mm
Terminal capacity Single-wire without ferrule	1 x 0.5 → 3.3 mm ² (AWG 20 → AWG 12) 2 x 0.5 → 2.5 mm ² (AWG 20 → AWG 14)
Terminal capacity Multi-wire with ferrule	1 x 0.2 → 2.5 mm ² (AWG 24 → AWG 14) 2 x 0.2 → 1.5 mm ² (AWG 24 → AWG 16)
Spring terminals, 2 terminals per connection point - flexible wire	2 x 0.2 → 1.5 mm ² (AWG 24 → AWG 16)
Spring terminals, 2 terminals per connection point - rigid wire	2 x 0.2 → 1.5 mm ² (AWG 24 → AWG 16)
Housing material	Self-extinguishing

Weight : casing 17.5 mm

88827105 (MUR1) : 63 g
88827115 (MAR1) : 63 g
88827125 (MBR1) : 63 g
88827135 (MCR1) : 62 g
88827145 (MHR1) : 63 g
88827150 (MLR4) : 63 g
88827155 (MLR1) : 64 g
88827100 (MUR4) : 62 g
88827103 (MUR3) : 66 g
88827503 (MURc3) : 59 g
88827150 (MLR4) : 63 g
88827185 (MXR1) : 63 g
88827004 (MUS2) : 55 g
88827014 (MAS5) : 53 g
88827044 (MHS2) : 53 g
88827054 (MLS2) : 56 g

Shock test IEC/EN 60068-2-27

15 g - 11 ms

Short interruption on power line
acc to IEC61000-4-11

0 % residual voltage,
250/300 cycles

Insulation resistance according
to IEC/EN 60664-1

100 MΩ (500 V_{DC})



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.