



For more Information  
please call

1-800-Belden1



### Description:

22 AWG Bare copper conductors, PP insulation, PVC jacket with ripcord. Sequential footage marking every two feet.

### Usage (Overall)

**Suitable Applications:**

Security Systems, Intercom/PA Systems, Sound/Audio Systems, Power Limited Controls, and Single Line Telephone.

### Physical Characteristics (Overall)

#### Conductor

**AWG:**

# Conductors	AWG	Stranding	Conductor Material
6	22	7x30	BC - Bare Copper

#### Insulation

**Insulation Material:**

Insulation Material	Wall Thickness (mm)
PP - Polypropylene	0.178

#### Outer Shield

**Outer Shield Material:**

Outer Shield Material
Unshielded

#### Outer Jacket

**Outer Jacket Material:**

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.432

**Outer Jacket Ripcord:**

Yes

#### Overall Cabling

**Overall Cabling Lay Length & Direction:**

Length (mm)	Twists (m.)
63.500	1.463

**Overall Cabling Color Code Chart:**

Number	Color
1	Black
2	Red
3	White
4	Green
5	Brown
6	Blue

**Overall Nominal Diameter:**

4.064 mm

### Mechanical Characteristics (Overall)

**Operating Temperature Range:**

-20°C To +75°C

**UL Temperature Rating:**

75°C

**Bulk Cable Weight:**

37.354 Kg/Km

## 5504UE Multi-Conductor - Commercial Applications

Max. Recommended Pulling Tension:	242.872 N
Min. Bend Radius (Install)/Minor Axis:	41.275 mm

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMR
NEC Articles:	800
CEC/C(UL) Specification:	CMG
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

#### Flame Test

UL Flame Test:	UL1666 Vertical Shaft
C(UL) Flame Test:	FT4

#### Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	6504UE

### Surface Printing (Overall)

#### Electrical Characteristics (Overall)

##### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
65.620

##### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
53.1522

##### Max. Operating Voltage - UL:

Voltage
300 V RMS

##### Max. Recommended Current:

Current
2 Amps per conductor @ 25°C

#### Related Documents:

No related documents are available for this product

#### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
5504UE 008U1000	305 MT	9.072 KG	GRAY		6 #22 PP FRPVC
5504UE 0081000	305 MT	9.072 KG	GRAY	C	6 #22 PP FRPVC
5504UE 008500	152 MT	4.536 KG	GRAY		6 #22 PP FRPVC
5504UE 009C500	152 MT	5.670 KG	WHITE		6 #22 PP FRPVC
5504UE 009U1000	305 MT	9.072 KG	WHITE		6 #22 PP FRPVC
5504UE 009U500	152 MT	4.763 KG	WHITE		6 #22 PP FRPVC

## 5504UE Multi-Conductor - Commercial Applications

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 2    Revision Date: 06-02-2008

© 2011 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.