

P993

Low Range Differential Pressure PCB Mount Sensor



Typical Applications

- Variable Air Volume Systems (VAV)
- Filter Pressure Monitoring
- Duct Air Flow
- Modulated Furnace Controls
- Combustion Air Flow
- Gaseous Leak Detection

Standard Full Scale Pressure Ranges

1, 2, 5, 10, ± 1 , ± 2 , and ± 5 inches of H₂O

Features

- Rugged PCB Mount Package
- Amplified Temperature Compensated Linear Output
- No Position Sensitivity
- EMI/RFI & ESD Protected
- Superior Output Signal Stability

Description

The P993 series of pressure sensors incorporates a silicon capacitive sensing element in a compact package.

Using a 5 Vdc input, the sensors provide a 0.25 to 4.0 Vdc output proportional to pressure. Internal temperature compensation provides an accurate, easy to use device.

The innovative design eliminates mounting position effects found on other low pressure differential sensors currently available in the market.

Technical Specifications

Note: Performance Specifications with 5 Vdc supply at 25°C

Differential Pressure Ranges

(inches of H ₂ O):	1, 2, 5, 10, ±1, ±2, and ±5
Proof Pressure:	1.0 PSI (either port)
Burst Pressure:	1.5 PSI (either port)
Supply Voltage:	5.0 ± 0.25 Vdc
Supply Current:	4mA Max.
Output Voltage (Ratiometric):	0.25 to 4.0 Vdc
Calibration Tolerance (at 5.0 Vdc supply and no load):	
Zero/Null Pressure:	0.25 Vdc ± 60 mV
Span:	3.75 Vdc ± 60 mV
Voltage Ratiometricity:	±1.5% of span Max. 4.75 to 5.25 Vdc supply

Total Error Band

(10° to 40°C):	±2% of span Max. (±3% for 0-1" range)
Output Impedance:	100 Ω Max.
Service Life:	10,000,000 cycles Min.
Shock:	10 g's at 6ms duration
Vibration:	1 g from 20 Hz to 1200 Hz
Operating Temperature:	0°C to 60°C
Storage Temperature:	-40°C to +95°C
Humidity:	95% RH, non-condensing
Weight:	20 grams Max.
Electrical Termination:	3 solderable pins, tin plated
Preferred Mounting Position:	None
Pressure Connection:	1/8" diameter tube fitting with barb for 3/16 ID tubing

Recommended Interface

Impedance:	25 kΩ Min. resistance between transducer output and ground, in parallel with 0.2 uF Max. capacitance
------------	--

Over-Voltage Protection: 16 Vdc

Reverse Polarity Protection: -6 Vdc



Before installation and operation, ensure that the appropriate pressure sensor has been selected in terms of pressure range, design and specific measuring conditions. Non-compliance can result in serious injury and/or damage to the equipment.

Warning: The product information contained in this catalogue is given purely as information and does not constitute a representation, warranty or any form of contractual commitment. Kavlico reserve the right to modify their products without notice. It is imperative that we should be consulted over any particular use or application of our products and it is the responsibility of the buyer to establish, particularly through all the appropriate tests, that the product is suitable for the use or application. Under no circumstances will our warranty apply, nor shall we be held responsible for any application (such as any modification, addition, deletion, use in conjunction with other electrical or electronic components, circuits or assemblies, or any other unsuitable material or substance) which has not been expressly agreed by us prior to the sale of our products.

© 2013 Kavlico. All rights reserved.

How to Order

Use this diagram, working top to bottom and left to right to construct your model number. An example is shown below. Custom OEM options are also available.

P993 Low Range Differential Pressure PCB Mount Sensor



Pressure Range

1	0 - 1.0" H ₂ O
1B	±1" H ₂ O
2	0 - 2.0" H ₂ O
2B	±2" H ₂ O
5	0 - 5.0" H ₂ O
5B	±5" H ₂ O
10	0 - 10" H ₂ O

P993 - 5B

Example: P993 - 5B

Description: P993 Pressure Sensor, ±5" H₂O



Dimensions in: mm [inches]

Don't see what you want?

Call us at +1 (619) 710-2068 to customize this product to meet your application-specific needs!



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.