

ETX® Module

High graphics performance with low power consumption

conga-EAF

Based on AMD Embedded G-Series Processors

Best price/performance ratio

High performance graphics


ETX®



AMD Fusion
FAMILY OF APUS
EMBEDDED TECHNOLOGY

Formfactor	ETX® Spec 3.02
CPU	AMD Embedded G-Series Processors AMD G-T56N 1.6 GHz Dual Core (L2 cache 512kB x2, 18 W) AMD G-T40N 1.0 GHz Dual Core (L2 cache 512kB x2, 9W) AMD G-T40R 1.0 GHz Single Core (L2 cache 512kB, 5.5 W) AMD G-T40E 1.0 GHz Dual Core (L2 cache 512kB x2, 6.5 W) AMD G-T16R 615 MHz Single Core (L2 cache 512kB, 4.5 W)
DRAM	Single channel up to one 4 GB DDR3 SO-DIMM memory (up to 1066 MHz)
Chipset	AMD A55E Controller Hub
Ethernet	10/100M Fast Ethernet, Realtek RTL8105E
I/O Interfaces	2x Serial ATA*, 2x EIDE (up to UDMA-66/100), 4x USB 2.0, PCI Bus (Rev. 2.3), ISA Bus, I2C (Fast Mode, 400 kHz, Multi Master), Floppy, LPT, 2x COM, PS/2
Sound	High Definition Audio Interface and Analog MIC, Line In, Line Out by on-module HDA codec
Graphics	Integrated High Performance Video, DirectX®11 graphics with UVD 3.0, Integrated VGA DAC, Dual Simultaneous Display Support, no PEG support
LVDS	2x24 Bit, 800x600 to 1920x1200@60Hz; VESA standard or JEDIA data mapping; Automatic Panel Detection via EDID/EPI
CRT	400 MHz RAMDAC, resolutions up to 2560x1600 - 18W APU, 1920x1200 - 9W APU
DisplayPort	1x DisplayPort 1.1a shared with HDMI port, resolutions up to 2560x1600 - 18W APU, 1920x1200 - 9W APU
HDMI or DVI	1x HDMI 1.3 Port, shared with DisplayPort, resolutions up to 1920x1080 / 1920x1200 for DVI mode
congatec Board Controller	Multi Stage Watchdog, non-volatile User Data Storage, Manufacturing and Board Information, Board Statistics, BIOS Setup Data, Backup, I²C bus (fast mode, 400 kHz, multi-master), Power Loss Control
Embedded BIOS Features	AMI-Aptio UEFI BIOS with congatec Embedded BIOS features
Security	The conga-EAF can be optionally equipped with a discrete "Trusted Platform Module" (TPM). It is capable of calculating efficient hash and RSA algorithms with key lengths up to 2,048 bits and includes a real random number generator. Security sensitive applications such as gaming and e-commerce will benefit also with improved authentication, integrity and confidence levels.
Power Management	ACPI 3.0 with battery support
Operating Systems	Microsoft® Windows8, Microsoft® Windows7, Microsoft® Windows XP, Microsoft® Windows® embedded Standard, Microsoft® Windows CE 6.0, Windows Embedded Compact 7, Linux
Power Consumption	Typ. application: 9 .. 18 W., see manual for full details, CMOS Battery Backup
Temperature	Operating: 0 .. +60°C Storage: -20 .. +80°C
Humidity	Operating: 10 - 90% r. H. non cond. Storage: 5 - 95% r. H. non cond.
Size	95 x 114 mm (3.7" x 4.5")

Block Diagram conga-EAF



Order Information conga-EAF

Article	PN	Description
conga-EAF/T56N	041071	AMD Dual Core Processor T56N with 1.6GHz, 1MB L2 cache and 1066MT/s DDR3 SODIMM memory interface for up to 4GB.
conga-EAF/T40N	041073	AMD Dual Core Processor T40N with 1.0GHz, 1MB L2 cache and 1066MT/s DDR3 SODIMM memory interface for up to 4GB.
conga-EAF/T16R	041078	Standard ETX module with AMD Ontario™ Single Core Processor T16R with 615MHz, 4.5W, 512kB L2 cache and 1066MT/s DDR3 SODIMM memory interface for up to 4GB.
conga-EAF/T40R	041076	AMD Ontario™ Single Core Processor T40R 1.0GHz, 1MByte L2 cache and 1066MT/s DDR3 SODIMM memory interface for up to 4GB
conga-EAF/T40E	041077	AMD Ontario™ Dual Core Processor T40E 1.0GHz, 1MByte L2 cache and 1066MT/s DDR3 SODIMM memory interface for up to 4GB.
conga-XAF/HSP-B	041050	Standard Heatspreader. All stand-offs are with 2.7mm bore hole.
conga-XAF/HSP-T	041051	Standard Heatspreader. All stand-offs are M2.5mm threaded.
conga-XAF/CSP-B	041055	Standard passive cooling solution for modules conga-XAF and EAF. All standoffs are with 2.7mm bore hole.
conga-XAF/CSP-T	041056	Standard passive cooling solution for modules conga-XAF and EAF. All standoffs are M2.5mm thread.
conga- XAF/CSA-B	041057	Standard active cooling solution for modules conga-XAF and EAF. Integrated 12V fan. All standoffs are with 2.7mm bore hole.
conga-XAF/CSA-T	041058	Standard active cooling solution for modules conga-XAF and EAF. Integrated 12V fan. All standoffs are M2.5mm thread.
DDR3-SODIMM-1333 (1GB)	068751	DDR3 SODIMM memory module with 1333 MT/s (PC3-10600) and 1GB RAM
DDR3-SODIMM-1333 (2GB)	068761	DDR3 SODIMM memory module with 1333 MT/s (PC3-10600) and 2GB RAM
DDR3-SODIMM-1333 (4GB)	068764	DDR3 SODIMM memory module with 1333 MT/s (PC3-10600) and 4GB RAM

Engineering Tools / Accessories for ETX®

conga-EEVAL	033269	Evaluation carrier board for ETX-modules
conga-FPA2	047250	Flatpanel prototype adapter to develop your own flatpanel adapter including cables set.
XTX/ETX-carrierboard-socket-3	400006	Connector for ETX and XTX carrier boards, height 3.0 mm, packing unit 8 pieces
XTX/ETX-carrierboard-socket-9.5	400009	Connector for ETX and XTX carrier boards, height 9.5 mm, packing unit 8 pieces



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.