

## Description

The 74LVC273A provides eight positive-edge-triggered D-type flip-flops with a direct clear (CLR) input.


The device is designed for operation with a power supply range of 1.65V to 3.6V. The device is fully specified for partial power down applications using I<sub>OFF</sub>. The I<sub>OFF</sub> circuitry disables the output preventing damaging current backflow when the device is powered down.

## Features

- Supply Voltage Range from 1.65V to 3.6V
- Sinks or Sources 24mA at V<sub>CC</sub> = 3V
- CMOS Low Power Consumption
- I<sub>OFF</sub> Supports Partial Power Down Operation
- Inputs or Outputs accept up to 5.5V
- Inputs Can Be Driven by 3.3V or 5V Allowing for Mixed Voltage Applications
- Schmitt Trigger Action at All Inputs
- Typical V<sub>OLP</sub> (Quiet Output Ground Bounce) less than 0.8V with V<sub>CC</sub> = 3.3V and T<sub>A</sub> = +25°C
- Typical V<sub>OHV</sub> (Quiet Output dynamic VOH) greater than 2.0V with V<sub>CC</sub> = 3.3V and T<sub>A</sub> = +25°C
- ESD Protection Tested per JESD 22
  - Exceeds 200-V Machine Model (A115-A)
  - Exceeds 2000-V Human Body Model (A114-A)
  - Exceeds 1000-V Charged Device Model (C101C)
- Latch-Up Exceeds 250mA per JESD 78, Class II
- All devices are:
  - **Totally Lead-Free & Fully RoHS compliant (Notes 1 & 2)**
  - **Halogen and Antimony Free. "Green" Device (Note 3)**

- Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant.
  2. See [http://www.diodes.com/quality/lead\\_free.html](http://www.diodes.com/quality/lead_free.html) for more information about Diodes Incorporated's definitions of Halogen and Antimony free, "Green" and Lead-Free.
  3. Halogen and Antimony free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.


## Pin Assignments



## Applications

- General Purpose Logic
- Bus Driving
- Power Down Signal Isolation
- Wide array of products such as:
  - PCs, Notebooks, Netbooks, Ultrabooks
  - Networking Computer Peripherals, Hard Drives, CD/DVD ROM
  - TV, DVD, DVR, Set Top Box

## Ordering Information




| Device          | Package Code | Package (Note 4 & 5) | Package Size                                 | 13" Tape and Reel |                    |
|-----------------|--------------|----------------------|--|-------------------|--------------------|
|                 |              |                      |  | Quantity          | Part Number Suffix |
| 74LVC273AT20-13 | T20          | TSSOP-20             | 6.4mm X 6.5mm X 1.2mm<br>0.65 mm lead pitch  | 2500/Tape & Reel  | -13                |
| 74LVC273AQ20-13 | Q20          | V-QFN4525-20         | 2.5mm X 4.5mm X 0.95mm<br>0.50 mm lead pitch | 2500/Tape & Reel  | -13                |

- Notes:
4. Pad layout as shown on Diodes Inc. suggested pad layout document AP02001, which can be found on our website at <http://www.diodes.com/datasheets/ap02001.pdf>.
  5. V-QFN4525-20 is a JEDEC recognized naming convention that specifies the package thickness category as V and the number 4525 describes the package as 4.5mm X 2.5mm.

## Pin Descriptions

| Pin Number | Pin Name                | Description    |
|------------|-------------------------|----------------|
| 1          | $\overline{\text{CLR}}$ | Clear          |
| 2          | Q1                      | Latch Output   |
| 3          | D1                      | Data Input     |
| 4          | D2                      | Data Input     |
| 5          | Q2                      | Latch Output   |
| 6          | Q3                      | Latch Output   |
| 7          | D3                      | Data Input     |
| 8          | D4                      | Data Input     |
| 9          | Q4                      | Latch Output   |
| 10         | GND                     | Ground         |
| 11         | CLK                     | Clock          |
| 12         | Q5                      | Latch Output   |
| 13         | D5                      | Data Input     |
| 14         | D6                      | Data Input     |
| 15         | Q6                      | Latch Output   |
| 16         | Q7                      | Latch Output   |
| 17         | D7                      | Data Input     |
| 18         | D8                      | Data Input     |
| 19         | Q8                      | Latch Output   |
| 20         | Vcc                     | Supply Voltage |

## Logic Diagram



## Function Table

| (Each Flip-Flop)        |     |   |                |
|-------------------------|-----|---|----------------|
| INPUTS                  |     |   | OUTPUT         |
| $\overline{\text{CLR}}$ | CLK | D | Q              |
| L                       | X   | X | L              |
| H                       | ↑   | H | H              |
| H                       | ↑   | L | L              |
| H                       | L   | X | Q <sub>0</sub> |

**Absolute Maximum Ratings** (Notes 6 & 7)

| Symbol           | Description   | Rating       | Unit |
|------------------|---|--------------|------|
| ESD HBM          | Human Body Model ESD Protection   | 2            | kV   |
| ESD CDM          | Charged Device Model ESD Protection                                       | 1            | kV   |
| ESD MM           | Machine Model ESD Protection  | 200          | V    |
| V <sub>CC</sub>  | Supply Voltage Range  | -0.5 to +7.0 | V    |
| V <sub>I</sub>   | Input Voltage Range   | -0.5 to +7.0 | V    |
| I <sub>IK</sub>  | Input Clamp Current V <sub>I</sub> < 0V                                   | -20          | mA   |
| I <sub>OK</sub>  | Output Clamp Current V <sub>O</sub> < 0V                                  | -50          | mA   |
| I <sub>O</sub>   | Continuous output current -0.5V < V <sub>O</sub> < V <sub>CC</sub> + 0.5V | ±50          | mA   |
| I <sub>CC</sub>  | Continuous Current Through V <sub>CC</sub>                                | 100          | mA   |
| I <sub>GND</sub> | Continuous Current Through GND  | -100         | mA   |
| T <sub>J</sub>   | Operating Junction Temperature  | -40 to +150  | °C   |
| T <sub>STG</sub> | Storage Temperature   | -65 to +150  | °C   |
| P <sub>TOT</sub> | Total Power Dissipation   | 500          | mW   |

- Notes:
- Stresses beyond the absolute maximum may result in immediate failure or reduced reliability. These are stress values and device operation should be within recommend values.
  - Forcing the maximum allowed voltage could cause a condition exceeding the maximum current or conversely forcing the maximum current could cause a condition exceeding the maximum voltage. The ratings of both current and voltage must be maintained within the controlled range.

**Recommended Operating Conditions** (Note 8)

| Symbol          | Parameter                          | Conditions              | Min  | Max             | Unit |
|-----------------|------------------------------------|-------------------------|------|-----------------|------|
| V <sub>CC</sub> | Supply Voltage                     | Operating               | 1.65 | 3.6             | V    |
|                 |                                    | Data Retention Only     | 1.5  | —               | V    |
| V <sub>I</sub>  | Input Voltage                      | —                       | 0    | 5.5             | V    |
| V <sub>O</sub>  | Output Voltage                     | —                       | 0    | V <sub>CC</sub> | V    |
| I <sub>OH</sub> | High-Level Output Current          | V <sub>CC</sub> = 1.65V | —    | -4              | mA   |
|                 |                                    | V <sub>CC</sub> = 2.3V  | —    | -8              |      |
|                 |                                    | V <sub>CC</sub> = 2.7V  | —    | -12             |      |
|                 |                                    | V <sub>CC</sub> = 3.0V  | —    | -24             |      |
| I <sub>OL</sub> | Low-Level Output Current           | V <sub>CC</sub> = 1.65V | —    | 4               | mA   |
|                 |                                    | V <sub>CC</sub> = 2.3V  | —    | 8               |      |
|                 |                                    | V <sub>CC</sub> = 2.7V  | —    | 12              |      |
|                 |                                    | V <sub>CC</sub> = 3.0V  | —    | 24              |      |
| Δt/ΔV           | Input Transition Rise or Fall Rate |                         | —    | 10              | ns/V |
| T <sub>A</sub>  | Operating Free-Air Temperature     |                         | -40  | +125            | °C   |

- Note: 8. Unused inputs should be held at V<sub>CC</sub> or ground.

**Electrical Characteristics**

| Symbol           | Parameter                  | Test Conditions  | V <sub>CC</sub>                         | T <sub>A</sub> = -40°C to +85°C |                        | T <sub>A</sub> = +85°C to +125°C |                        | Unit |    |
|------------------|----------------------------|--|---|---------------------------------|------------------------|----------------------------------|------------------------|------|----|
|                  |                            |  |   | Min                             | Max                    | Min                              | Max                    |      |    |
| V <sub>IH</sub>  | High-Level Input Voltage   |  | 1.65V to 1.95V                          | V <sub>CC</sub> X 0.65          |                        | V <sub>CC</sub> X 0.65           |                        | V    |    |
|                  |                            |  | 2.3V to 2.7V                            | 1.7                             |                        | 1.7                              |                        |      |    |
|                  |                            |  | 3.0V to 3.6V                            | 2                               |                        | 2                                |                        |      |    |
| V <sub>IL</sub>  | Low-Level Input voltage    |  | 1.65V to 1.95V                          |                                 | V <sub>CC</sub> X 0.35 |                                  | V <sub>CC</sub> X 0.35 | V    |    |
|                  |                            |  | 2.3V to 2.7V                            |                                 | 0.7                    |                                  | 0.7                    |      |    |
|                  |                            |  | 3.0V to 3.6V                            |                                 | 0.8                    |                                  | 0.8                    |      |    |
| V <sub>OH</sub>  | High-Level Output Voltage  | I <sub>OH</sub> = -50μA                                      | 1.65V to 3.6V                           | V <sub>CC</sub> -0.2            |                        | V <sub>CC</sub> -0.3             |                        | V    |    |
|                  |                            | I <sub>OH</sub> = -4mA                                       | 1.65V                                   | 1.2                             |                        | 1.05                             |                        |      |    |
|                  |                            | I <sub>OH</sub> = -8mA                                       | 2.3V                                    | 1.7                             |                        | 1.65                             |                        |      |    |
|                  |                            | I <sub>OH</sub> = -12mA                                      | 2.7V                                    | 2.2                             |                        | 2.05                             |                        |      |    |
|                  |                            | I <sub>OH</sub> = -24mA                                      | 3.0V                                    | 2.4                             |                        | 2.48                             |                        |      |    |
| V <sub>OL</sub>  | Low-Level Output Voltage   | I <sub>OL</sub> = 100μA                                      | 1.65V to 3.6V                           |                                 | 0.2                    |                                  | 0.3                    | V    |    |
|                  |                            | I <sub>OL</sub> = 4mA  | 1.65V                                   |                                 | 0.45                   |                                  | 0.65                   |      |    |
|                  |                            | I <sub>OL</sub> = 8mA  | 2.3V                                    |                                 | 0.60                   |                                  | 0.80                   |      |    |
|                  |                            | I <sub>OL</sub> = 12mA                                       | 2.7V                                    |                                 | 0.40                   |                                  | 0.60                   |      |    |
|                  |                            | I <sub>OL</sub> = 24mA                                       | 3.0V                                    |                                 | 0.55                   |                                  | 0.80                   |      |    |
| I <sub>OFF</sub> | Power Down Leakage Current | V <sub>I</sub> or V <sub>O</sub> = 0 or 5.5V                 | 0V                                      |                                 | ±10                    |                                  | 20                     | μA   |    |
| I <sub>I</sub>   | Input Current Control Pins | V <sub>I</sub> = GND or 5.5V                                 | 0 to 3.6V                               |                                 | ±5                     |                                  | ± 20                   | μA   |    |
| I <sub>CC</sub>  | Supply Current             | V <sub>I</sub> = GND or V <sub>CC</sub> , I <sub>O</sub> = 0 | 6.0V                                    |                                 | 10                     |                                  | 40                     | μA   |    |
| ΔI <sub>CC</sub> | Additional Supply Current  | One input at V <sub>CC</sub> -0.6V<br>I <sub>O</sub> = 0A    | 2.7V to 3.6V                            |                                 | 500                    |                                  | 5000                   | μA   |    |
| C <sub>i</sub>   | Input Capacitance          | Control Pins   | V <sub>I</sub> = GND or V <sub>CC</sub> | 0V to 3.6V                      | 4.0 typical            |                                  | 4.0 typical            |      | pF |
|                  |                            | I/O Pins   |   |                                 | 5.5 typical            |                                  | 5.5 typical            |      |    |

### Switching Characteristics

| Symbol           | Parameter                                  | Test Conditions | V <sub>CC</sub> | T <sub>A</sub> = +25°C |     |      | -40°C to +85°C |     | +85°C to +125°C |                 | Unit |
|------------------|--|-----------------|-----------------|------------------------|-----|------|----------------|-----|-----------------|-----------------|------|
|                  |  |                 |                 | Min                    | Typ | Max  | Min            | Max | Min             | Max             |      |
| f <sub>MAX</sub> | Maximum Frequency                          | Figure 1        | 1.8V ± 0.15V    | 35                     | 40  |      | 35             |     | 30              |                 | Mhz  |
|                  |  |                 | 2.5V ± 0.3V     | 75                     | 60  |      | 50             |     | 45              |                 |      |
|                  |  |                 | 2.7V            | 150                    | 175 |      | 150            |     | 100             |                 |      |
|                  |  |                 | 3.3V ± 0.3      | 150                    | 230 |      | 150            |     | 125             |                 |      |
| t <sub>w</sub>   | Pulse Width<br>CLK<br>High or Low          | Figure 1        | 1.8V ± 0.15V    | 5.0                    | 2.5 |      | 5.0            |     | 5.5             |                 | ns   |
|                  |  |                 | 2.5V ± 0.3V     | 4.0                    | 2.0 |      | 4.0            |     | 4.5             |                 |      |
|                  |  |                 | 2.7V            | 3.3                    | 1.7 |      | 3.3            |     | 3.5             |                 |      |
|                  |  |                 | 3.3V ± 0.3V     | 3.0                    | 1.5 |      | 3.0            |     | 3.5             |                 |      |
| t <sub>w</sub>   | Pulse Width<br>CLR Low                     | Figure 1        | 1.8V ± 0.15V    | 5.0                    | 2.5 |      | 5.0            |     | 5.5             |                 | ns   |
|                  |  |                 | 2.5V ± 0.3V     | 4.0                    | 2.0 |      | 4.0            |     | 4.5             |                 |      |
|                  |  |                 | 2.7V            | 3.3                    | 1.7 |      | 3.3            |     | 3.5             |                 |      |
|                  |  |                 | 3.3V ± 0.3V     | 3.0                    | 1.5 |      | 3.0            |     | 3.5             |                 |      |
| t <sub>SU</sub>  | Set-up Time D <sub>N</sub><br>to CLK       | Figure 1        | 1.8V ± 0.15V    | 4.0                    | 2.0 |      | 4.0            |     | 4.5             | t <sub>SU</sub> | ns   |
|                  |  |                 | 2.5V ± 0.3V     | 3.0                    | 1.5 |      | 3.0            |     | 3.5             |                 |      |
|                  |  |                 | 2.7V            | 2.0                    | 1.0 |      | 2.0            |     | 2.5             |                 |      |
|                  |  |                 | 3.3V ± 0.3V     | 1.5                    | 1.0 |      | 1.5            |     | 2.0             |                 |      |
| t <sub>H</sub>   | Hold Time<br>D <sub>N</sub> to CLK         | Figure 1        | 1.8V ± 0.15V    | 3.0                    | 1.5 |      | 3.0            |     | 3.5             |                 | ns   |
|                  |  |                 | 2.5V ± 0.3V     | 2.0                    | 1.0 |      | 2.0            |     | 2.5             |                 |      |
|                  |  |                 | 2.7V            | 1.5                    | 1.0 |      | 1.5            |     | 2.0             |                 |      |
|                  |  |                 | 3.3V ± 0.3V     | 1.5                    | 1.0 |      | 1.5            |     | 2.0             |                 |      |
| t <sub>REM</sub> | Removal Time<br>CLR to CLK                 | Figure 1        | 1.8V ± 0.15V    | 1                      | 7.8 | 16.5 | 1              | 17  | 1               | 14.2            | ns   |
|                  |  |                 | 2.5V ± 0.3V     | 1                      | 4   | 9    | 1              | 9.5 | 1               | 8.2             |      |
|                  |  |                 | 2.7V            | 1                      | 4.4 | 8.3  | 1              | 8.5 | 1               | 10.0            |      |
|                  |  |                 | 3.3V ± 0.3V     | 1.7                    | 4.1 | 7.3  | 1.7            | 7.5 | 1.7             | 9.0             |      |
| t <sub>PD</sub>  | Propagation Delay<br>CLK to Q <sub>N</sub> | Figure 1        | 1.8V ± 0.15V    | 1                      | 7.8 | 16.5 | 1              | 17  | 1               | 14.2            | ns   |
|                  |  |                 | 2.5V ± 0.3V     | 1                      | 4   | 9    | 1              | 9.5 | 1               | 8.2             |      |
|                  |  |                 | 2.7V            | 1                      | 4.4 | 8.3  | 1              | 8.5 | 1               | 10.0            |      |
|                  |  |                 | 3.3V ± 0.3V     | 1.7                    | 4.1 | 7.3  | 1.7            | 7.5 | 1.7             | 9.0             |      |
| t <sub>PD</sub>  | Propagation Delay<br>CLR to Q <sub>N</sub> | Figure 1        | 1.8V ± 0.15V    | 1                      | 7.8 | 16.5 | 1              | 17  | 1               | 14.2            | ns   |
|                  |  |                 | 2.5V ± 0.3V     | 1                      | 4   | 9    | 1              | 9.5 | 1               | 8.2             |      |
|                  |  |                 | 2.7V            | 1                      | 4.4 | 8.3  | 1              | 8.5 | 1               | 10.0            |      |
|                  |  |                 | 3.3V ± 0.3V     | 1.7                    | 4.1 | 7.3  | 1.7            | 7.5 | 1.7             | 9.0             |      |
| tsk(0)           | Output Skew Time                           |                 | 3.3V ± 0.3V     |                        |     | 1.0  |                |     |                 | 1.5             | ns   |

### Operating Characteristics

T<sub>A</sub> = +25°C


| Symbol          | Parameter                              | Test Conditions | V <sub>CC</sub> | TYP  | Unit |
|-----------------|--|-----------------|-----------------|------|------|
| C <sub>pd</sub> | Power dissipation capacitance per gate | F = 10 MHz      | 1.8V ± 0.15V    | 9.9  | pF   |
|                 |  |                 | 2.5V ± 0.3V     | 10.2 |      |
|                 |  |                 | 3.3V ± 0.3V     | 10.6 |      |

### Package Characteristics

| Symbol          | Parameter                              | Package      | Test Conditions | Min | Typ | Max | Unit |
|-----------------|--|--------------|-----------------|-----|-----|-----|------|
| θ <sub>JA</sub> | Thermal Resistance Junction-to-Ambient | TSSOP-20     | (Note 9)        | —   | 74  | —   | °C/W |
| θ <sub>JC</sub> | Thermal Resistance Junction-to-Case    | TSSOP-20     | (Note 9)        | —   | 15  | —   | °C/W |
| θ <sub>JA</sub> | Thermal Resistance Junction-to-Ambient | V-QFN4525-20 | (Note 9)        | —   | 67  | —   | °C/W |
| θ <sub>JC</sub> | Thermal Resistance Junction-to-Case    | V-QFN4525-20 | (Note 9)        | —   | 20  | —   | °C/W |


Note: 9. Test conditions for TSSOP-20 and V-QFN4525-20: Devices mounted on 4 layer FR-4 substrate PC board, 2oz copper, with minimum recommended pad layout per JESD 51-7.

**Parameter Measurement Information**




| TEST              | S1   |
|-------------------|------|
| $t_{PLH}/t_{PHL}$ | Open |


| $V_{CC}$         | Inputs   |              | $V_M$      | $V_{LOAD}$        | $C_L$ | $R_L$        | $V_{\Delta}$ |
|------------------|----------|--------------|------------|-------------------|-------|--------------|--------------|
|                  | $V_i$    | $t_r/t_f$    |            |                   |       |              |              |
| $1.8V \pm 0.15V$ | $V_{CC}$ | $\leq 2ns$   | $V_{CC}/2$ | $2 \times V_{CC}$ | 30pF  | 1K $\Omega$  | 0.15V        |
| $2.5V \pm 0.2V$  | $V_{CC}$ | $\leq 2ns$   | $V_{CC}/2$ | $2 \times V_{CC}$ | 30pF  | 500 $\Omega$ | 0.15V        |
| 2.7V             | 2.7V     | $\leq 2.5ns$ | 1.5V       | 6V                | 50pF  | 500 $\Omega$ | 0.3V         |
| $3.3V \pm 0.3V$  | 2.7V     | $\leq 2.5ns$ | 1.5V       | 6V                | 50pF  | 500 $\Omega$ | 0.3V         |



**Voltage Waveform Pulse Duration**



**Voltage Waveform Set-up and Hold Times**




**Voltage Waveform Propagation Delay Times  
Inverting and Non Inverting Outputs**

- Notes:
- A. Includes test lead and test apparatus capacitance.
  - B. All pulses are supplied at pulse repetition rate  $\leq 10$  MHz.
  - C. Inputs are measured separately one transition per measurement.
  - D.  $t_{PLH}$  and  $t_{PHL}$  are the same as  $t_{PD}$ .

**Figure 1 Load Circuit and Voltage Waveforms**


**Marking Information**

(1) TSSOP20



| Part Number  | Package  |
|--------------|----------|
| 74LVC273AT20 | TSSOP-20 |

(2) QFN-20 (V-QFN4525-20)




| Part Number  | Package      |
|--------------|--------------|
| 74LVC273AQ20 | V-QFN4525-20 |

NEW PRODUCT

**Package Outline Dimensions (All Dimensions in mm)**


Please see AP02002 at <http://www.diodes.com/datasheets/ap02002.pdf> for the latest version.

(1) TSSOP-20



| TSSOP-20             |          |      |      |
|----------------------|----------|------|------|
| Dim                  | Min      | Max  | Typ  |
| A                    | -        | 1.20 | -    |
| A1                   | 0.05     | 0.15 | -    |
| A2                   | 0.80     | 1.05 | -    |
| b                    | 0.19     | 0.30 | -    |
| c                    | 0.09     | 0.20 | -    |
| D                    | 6.40     | 6.60 | 6.50 |
| E                    | 6.20     | 6.60 | 6.40 |
| E1                   | 4.30     | 4.50 | 4.40 |
| e                    | 0.65 BSC |      |      |
| L                    | 0.45     | 0.75 | 0.60 |
| L1                   | 1.0 REF  |      |      |
| theta1               | 0°       | 8°   | -    |
| theta2               | 10°      | 14°  | 12°  |
| theta3               | 10°      | 14°  | 12°  |
| All Dimensions in mm |          |      |      |

(2) QFN-20 (V-QFN4525-20)



| V-QFN4525-20         |         |      |       |
|----------------------|---------|------|-------|
| Dim                  | Min     | Max  | Typ   |
| A                    | 0.75    | 0.85 | 0.80  |
| A1                   | 0.00    | 0.05 | 0.02  |
| A3                   | -       | -    | 0.15  |
| b                    | 0.18    | 0.30 | 0.23  |
| D                    | 4.45    | 4.55 | 4.50  |
| D2                   | 2.85    | 3.15 | 3.00  |
| E                    | 2.45    | 2.55 | 2.50  |
| E2                   | 0.85    | 1.15 | 1.00  |
| e                    | 0.50BSC |      |       |
| L                    | 0.30    | 0.50 | 0.40  |
| Z                    | -       | -    | 0.385 |
| Z1                   | -       | -    | 0.885 |
| All Dimensions in mm |         |      |       |

NEW PRODUCT



## Suggested Pad Layout


Please see AP02001 at <http://www.diodes.com/datasheets/ap02001.pdf> for the latest version.

### (1) TSSOP-20



| Dimensions | Value (in mm) |
|------------|---------------|
| C          | 0.650         |
| X          | 0.420         |
| X1         | 6.270         |
| Y          | 1.789         |
| Y1         | 4.160         |
| Y2         | 7.720         |

### (2) QFN-20 (V-QFN4525-20)



| Dimensions | Value (in mm) |
|------------|---------------|
| C          | 0.500         |
| X          | 0.330         |
| X1         | 0.600         |
| X2         | 3.200         |
| X3         | 3.830         |
| X4         | 4.800         |
| Y          | 0.600         |
| Y1         | 1.200         |
| Y2         | 0.830         |
| Y3         | 2.800         |

**IMPORTANT NOTICE**

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

**LIFE SUPPORT**

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2014, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.