
Model 120E

Vishay Spectrol

Incremental Optical Encoder Contactless Technology (128 Pulses per Turn)



FEATURES

- Long life: 10 million revolutions minimum (contactless)
- Cost effective: Elimination of A/D converters
- Stainless steel shafts and nickel-plated bushing in various lengths
- Stability: - 40 °C to + 65 °C operating temperature
- Variability: Cable and printed circuit terminations available

RoHS COMPLIANT

The Model 120E is a light-duty optical encoder that can be manually. This unique device outputs two square waves at a maximum rate of 128 pulses in quadrature with other resolutions as low as 10 pulses available. Typical applications includes Motion sensing and control, Motor control, Flow control, Low-to-high input for test and measurement, Medical instrumentation, Robotics and Computer Peripherals.

ELECTRICAL SPECIFICATIONS

PARAMETER	MINIMUM	NOMINAL	MAXIMUM
VCC Range (V)	4.75	5	5.25
Supply Current (mA)	-	-	30
Voh (V)	2.4	-	-
Vol (V)	-	-	0.4
Pull-up Resistor (kΩ)	-	10	-
Output	Channel A leads channel B by 90° electrically, CCW direction		

MECHANICAL SPECIFICATIONS

PARAMETER		
Vibration		10 to 2000 Hz, 15 G mil std., - 202 method 204 test condition C
Shock		100 G at 6 ms mil std. 202, method 213 test condition C
Rotational Torque	Sleeve Bearing	1.5 oz. in **Other torque ranges available**
Operating Speed		300 RPM
Rotational Life		10 000 000 revolutions
Shaft End Play		0.005 maximum
Shaft Radial Play		0.010 at 1"
Shaft Axial Force		15 lbs. push/pull
Terminal Strength		2 lbs.

ORDERING INFORMATION/DESCRIPTION

120	E	N	128	CBL	BO100	e4
MODEL	PRODUCT ID	SHAFT AND BUSHING SIZE	PULSES PER RESOLUTION	TERMINATION	PACKAGING	LEAD FINISH
Sleeve-bearing construction with two channel quadrature output	**E** = Encoder	**N** = 1/4" (6.35 mm) diameter by 0.875" (22.23 mm) long shaft 3/8" (9.53 mm) diameter x 32 NEF 2A by 3/8" (9.53 mm) long bushing	Number of pulses per revolution	**B66** = PC terminal type B-66 horizontal mounting **C24** = PC terminal type C-24, vertical mounting **CBL** = 7.5" (190.5 mm) long cable **CN1** = Cable with connector	Box of 100 pieces	

SAP PART NUMBERING GUIDELINES

120EN	128	CBL	B30
MODEL	PULSES PER REVOLUTION	TERMINAL CONFIGURATION	PACKAGING


For technical questions, contact: sfer@vishay.com

Document Number: 57090
Revision: 20-Mar-07


DIMENSIONS in inches (millimeters)

120E SERIES


PC TERMINALS: TYPE C-24




BLOCK DIAGRAMM ONE OUTPUT



CABLE STYLE




OUTPUT WAVEFORM



*Channel A leads channel B by 90° electrically in CCW direction

PC TERMINALS: TYPE B-66



TERM #	FUNCTION
1	5 V_{DC} ± 5 % at 30 ma max.
2	"A" out
3	Ground
4	"B" out

"A" DIMENSIONS	
Standard	0.160
Special	0.400 max.

Dimension Tolerances, Unless Otherwise Specified

FRACTIONS = ± 1/64 (0.40 mm) DECIMALS = ± 0.005 GRDS = ± 0.010 (0.25 mm)

Notes:

(1) "A" cable length standard 7.50 ± 0.50. Other lengths available, specified by customer.

(2) "A" and "B" outputs are TTL compatible on all models.

COLOR	FUNCTION
Red	5V_{DC} ± 5 % at 30 ma max.
Green	Ground
Yellow	"A" out
Orange	"B" out

ENVIRONMENTAL SPECIFICATIONS			
PARAMETER	**MINIMUM**	**NOMINAL**	**MAXIMUM**
Operating Temperature (°C)	- 40 °C	-	+ 65 °C
Storage Temperature (°C)	- 55 °C	-	+ 110 °C
Humidity	85 % RH at 40 °C, 240 h	-	-

TERMINAL	
Terminal	B66: PC Terminals, horizontal mounting C24: PC Terminals, vertical mounting CBL: 7.5 including cable CN1: 7.5 including cable with connector

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.