



All dimensions are in mm; tolerances according to ISO 2768 m-H

**Interface**

According to IEC 61169-54

**Contents and Documentation**

This kit is delivered with

- **Standard Definitions Card**  
Printed Standard Definitions that can be used on nearly all Vector Network Analyzers
- **Test Results Documentation**
- **Lanyard**
- **Hard Shell Case**

**Material and plating**

**Connector parts**

Center conductor  
Outer conductor  
Coupling nut  
Body  
Dielectric  
Substrate

**Material**

Brass  
Stainless steel  
Brass  
Aluminum  
PTFE  
Al<sub>2</sub>O<sub>3</sub>

**Plating**

Gold, min. 1.27 µm, over nickel  
Passivated  
White bronze(e.g. Optalloy®)  
black anodized

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG  
RF\_35/09.14/6.2

**Electrical data**

Frequency range DC to 12 GHz

**Thru**

Return loss  $\geq 36$  dB, DC to 4 GHz  
 $\geq 30$  dB, 4 GHz to 6 GHz  
 $\geq 20$  dB, 6 GHz to 12 GHz

**Open**

Error from nominal phase<sup>1</sup>  
 $\leq 2.5^\circ$ , DC to 6 GHz  
 $\leq 3.0^\circ$ , 6 GHz to 12 GHz

**Short**

Error from nominal phase<sup>2</sup>  
 $\leq 2.5^\circ$ , DC to 6 GHz  
 $\leq 3.0^\circ$ , 6 GHz to 12 GHz

**Load**

Return loss  $\geq 40$  dB, DC to 4 GHz  
 $\geq 35$  dB, 4 GHz to 6 GHz  
 $\geq 25$  dB, 6 GHz to 12 GHz

DC-Resistance  $50 \Omega \pm 0.5 \Omega$

Power handling  $\leq 1.0$  W

<sup>1</sup> The nominal phase is defined by the Offset Delay, the Offset Loss and the Fringing Capacitances

<sup>2</sup> The nominal phase is defined by the Offset Delay, the Offset Loss and the Short Inductance

**Mechanical data**

Mating cycles  $\geq 100$   
 Maximum torque 5 Nm  
 Recommended torque 2 Nm  
 Gauge 2.75 mm to 2.90 mm

**General standard definitions**

For proper operation the vector network analyzer (VNA) needs a model describing the electrical behaviour of this calibration standard. The different models, units, and terms used will depend on the VNA type and they will have to be entered into the VNA. All values are based on typical geometry and plating.

**Thru**

Offset  $Z_0$  / Impedance /  $Z_0$  50  $\Omega$   
 Offset Delay 234.829 ps  
 Length (electrical) / Offset Length 70.40 mm  
 Offset Loss 2.50 G $\Omega$ /s  
 Loss 0.0510 dB/ $\sqrt{\text{GHz}}$   
 Line Loss 0.0007 dB/mm

**Open**

Offset  $Z_0$  / Impedance /  $Z_0$  50  $\Omega$   
 Offset Delay 80.823 ps  
 Length (electrical) / Offset Length 24.23 mm  
 Offset Loss 0.70 G $\Omega$ /s  
 Loss 0.0098 dB/ $\sqrt{\text{GHz}}$   
 Fringing Capacitances  
 $C_0 = -7.54000 \times 10^{-15}$  F / -7.54000 fF  
 $C_1 = -5810.00 \times 10^{-27}$  F/Hz / -5.81000 fF /GHz  
 $C_2 = 987.000 \times 10^{-36}$  F/Hz<sup>2</sup> / 0.98700 fF /GHz<sup>2</sup>  
 $C_3 = -45.5000 \times 10^{-45}$  F/Hz<sup>3</sup> / -0.04550 fF /GHz<sup>3</sup>

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF\_35/09\_14/6.2

**Short**

Offset $Z_o$ / Impedance / $Z_o$	50 $\Omega$
Offset Delay	80.823 ps
Length (electrical) / Offset Length	24.23 mm
Offset Loss	0.70 G $\Omega$ /s
Loss	0.0098 dB/ $\sqrt{\text{GHz}}$
Short Inductance	$L_0 = -15.900 \times 10^{-12} \text{ H} \quad / \quad -15.900 \text{ pH}$
	$L_1 = 9995.0 \times 10^{-24} \text{ H/Hz} \quad / \quad 9.9950 \text{ pH/GHz}$
	$L_2 = -2440.0 \times 10^{-33} \text{ H/Hz}^2 \quad / \quad -2.4400 \text{ pH/GHz}^2$
	$L_3 = 71.000 \times 10^{-42} \text{ H/Hz}^3 \quad / \quad 0.0710 \text{ pH/GHz}^3$

**Load**

Offset $Z_o$ / Impedance / $Z_o$	50 $\Omega$
Offset Delay	0.0000 ps
Length (electrical) / Offset Length	0.000 mm
Offset Loss	0.00 G $\Omega$ /s
Loss	0.0000 dB/ $\sqrt{\text{GHz}}$

**Environmental data**

Operating temperature range <sup>3</sup>	+20 °C to +26 °C
Rated temperature range of use <sup>4</sup>	0 °C to +50 °C
Storage temperature range	-40 °C to +85 °C
RoHS	compliant

<sup>3</sup> Temperature range over which these specifications are valid.

<sup>4</sup> This range is underneath and above the operating temperature range, within the calibration kit is fully functional and could be used without damage

**Declaration of documentation**

Standard delivery for this kit includes Test Results. The documentation issued reports which quantities were tested individually, traceable to national / international standards. Model based standard definitions of the calibration standards are reported in Agilent / Keysight, Rohde & Schwarz and Anritsu compatible VNA format.

**Inspection interval**

Recommendation	12 months
----------------	-----------

**Packing**

Standard	1 pce in bag
Weight	398 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Marcel Panicke	07.06.16	Herbert Babinger	19.10.17	e00	17-s336	M. Knoll	19.10.17

Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de				Tel. : +49 8684 18-0 Email : info@rosenberger.de			Page 3 / 3
--	--	--	--	---	--	--	---------------



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.