


# PD-9501G/24VDC

60W, Gigabit, Single-port PoE Midspan, 24VDC Input



## Overview

Microsemi's PD-9501G is a Best-of-Breed single port solution for remote powering of current in a 24VDC environment as well as high power applications.

It is designed specifically to power IEEE 802.11n and IEEE802.3at access points, pan-tilt-zoom (PTZ) and dome cameras, IP videophones, thin clients and other high power Ethernet end-terminals with 60W of power, and is also backward compatible and safe to use with any 802.3af terminal such as VoIP phones, IP cameras and wireless LAN access points.

It can power both existing 10/100Base-T devices and emerging wireless Gigabit devices such as WI-MAX and wireless IEEE 802.11n access points.

With the midspan's plug-and-play installation, they are easily and cost effectively implemented leveraging an existing Ethernet infrastructure while at the same time providing flexibility to assurance a future-proof scalable network.

## PD-9501G/24VDC Features

- Up to 60W of power over 4-pairs
- 24 VDC input voltage
- IEEE802.3at compliant
- Plug-and-play installation
- Guaranteed uptime

## PD-9501G/24VDC Specifications

|                                     |                                                                                                                                                                                                                                                                                                                                                            |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| No. of Ports                        | 1                                                                                                                                                                                                                                                                                                                                                          |
| Pass Through Data Rates             | 10/100/1000 Mbps                                                                                                                                                                                                                                                                                                                                           |
| Power over Ethernet Output          | Pin Assignment and Polarity:<br>Data Pairs 1/2 (-) and 3/6 (+)<br>Spare Pairs 7/8 (-) and 4/5 (+)<br>Output Power Voltage: 54-57 VDC<br>User Port Power: 60W Max.                                                                                                                                                                                          |
| Input Power Requirements            | DC Input Voltage: 20-36 VDC<br>Startup Voltage: 10.8 VDC<br>DC Input Current: 3.5A@24 VDC,                                                                                                                                                                                                                                                                 |
| Dimensions                          | 87 mm (W) x 43 mm (H) x 166 mm (L)<br>3.46 in. x 1.68 in. x 6.53 in.                                                                                                                                                                                                                                                                                       |
| Weight                              | .992 lbs (450g)                                                                                                                                                                                                                                                                                                                                            |
| Indicators                          | System Indicator:<br>Green—AC Power<br><br>Channel Power:<br>Green—Power delivered over 4 pairs                                                                                                                                                                                                                                                            |
| Connectors                          | Shielded RJ-45, EIA 568A and 568B                                                                                                                                                                                                                                                                                                                          |
| Environmental Conditions            | Operating Ambient Temperature:<br>-4° to 104°F (-20°C to 40°C) @60W<br>-4° to 122°F (-20°C to 50°C) @30W<br><br>Operating Humidity:<br>Maximum 90%, Non-condensing<br><br>Storage Temperature:<br>-4° to 158°F (-20° to 70°C)<br><br>Storage Humidity:<br>Maximum 95%, Non-condensing<br><br>Operating Altitude:<br>-1000 to 10,000 ft. (-304.8 to 3048 m) |
| Reliability                         | MTBF: 215,000 hrs. @25°C                                                                                                                                                                                                                                                                                                                                   |
| Thermal Rating                      | 40 BTU/Hr                                                                                                                                                                                                                                                                                                                                                  |
| Warranty                            | 1-year                                                                                                                                                                                                                                                                                                                                                     |
| Regulatory                          | IEEE 802.3af (PoE), IEEE 802.3at (including 2-event), RoHS Compliant, WEEE Compliant, CE                                                                                                                                                                                                                                                                   |
| Electromagnetic Emission & Immunity | FCC Part 15, Class B<br>EN 55022 Class B (Emissions)<br>EN 55024 (Immunity)                                                                                                                                                                                                                                                                                |
| Safety Approvals                    | GS Mark Per IEC60950                                                                                                                                                                                                                                                                                                                                       |

## Ordering Information

| Part Number    | Name                     | Ports  |
|----------------|--------------------------|--------|
| PD-9501G/24VDC | Microsemi PD-9501G 24VDC | 1-port |



Microsemi Corporate Headquarters  
One Enterprise, Aliso Viejo, CA 92656 USA  
Within the USA: +1 (800) 713-4113  
Outside the USA: +1 (949) 380-6100  
Sales: +1 (949) 380-6136  
Fax: +1 (949) 215-4996  
email: [sales.support@microsemi.com](mailto:sales.support@microsemi.com)  
[www.microsemi.com](http://www.microsemi.com)

Microsemi Corporation (Nasdaq: MSCC) offers a comprehensive portfolio of semiconductor and system solutions for communications, defense & security, aerospace and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; security technologies and scalable anti-tamper products; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, Calif., and has approximately 3,400 employees globally. Learn more at [www.microsemi.com](http://www.microsemi.com).

©2014 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.

MSC-PD-9501G/24VDC/6.2.2014



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.