

# NL17SG00

## Single 2-Input NAND Gate

The NL17SG00 MiniGate™ is an advanced high-speed CMOS 2-input NAND gate in ultra-small footprint.

The NL17SG00 input structures provides protection when voltages up to 4.6 V are applied.

### Features

- Wide Operating  $V_{CC}$  Range: 0.9 V to 3.6 V
- High Speed:  $t_{PD} = 2.5$  ns (Typ) at  $V_{CC} = 3.0$  V,  $C_L = 15$  pF
- Low Power Dissipation:  $I_{CC} = 0.5$   $\mu$ A (Max) at  $T_A = 25^\circ\text{C}$
- 4.6 V Overvoltage Tolerant (OVT) Input Pins
- Ultra-Small Packages
- These are Pb-Free and Halide-Free Devices




Figure 1. Pinout (Top View)




**ON Semiconductor®**

<http://onsemi.com>

### MARKING DIAGRAMS



**SOT-953**  
**CASE 527AE**




**UDFN6**  
**1.0 x 1.0**  
**CASE 517BX**



**UDFN6**  
**1.45 x 1.0**  
**CASE 517AQ**



**SC-88A**  
**DF SUFFIX**  
**CASE 419A**



M = Date Code\*  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*Date Code orientation and/or position may vary depending upon manufacturing location.

### PIN ASSIGNMENT

|   | SOT-953  | SC-88A   | UDFN6    |
|---|----------|----------|----------|
| 1 | IN A     | IN B     | IN A     |
| 2 | GND      | IN A     | IN B     |
| 3 | IN B     | GND      | GND      |
| 4 | OUT Y    | OUT Y    | OUT Y    |
| 5 | $V_{CC}$ | $V_{CC}$ | NC       |
| 6 |          |          | $V_{CC}$ |

### FUNCTION TABLE

| Input |   | Output |
|-------|---|--------|
| A     | B | Y      |
| L     | L | H      |
| L     | H | H      |
| H     | L | H      |
| H     | H | L      |

### ORDERING INFORMATION

See detailed ordering and shipping information on page 5 of this data sheet.

# NL17SG00

## MAXIMUM RATINGS

| Symbol        | Parameter                                                                             | Value                                  | Unit |
|---------------|---------------------------------------------------------------------------------------|----------------------------------------|------|
| $V_{CC}$      | DC Supply Voltage                                                                     | -0.5 to +5.5                           | V    |
| $V_{IN}$      | DC Input Voltage                                                                      | -0.5 to +4.6                           | V    |
| $V_{OUT}$     | DC Output Voltage<br>Output at High or Low State<br>Power-Down Mode ( $V_{CC} = 0$ V) | -0.5 to $V_{CC} + 0.5$<br>-0.5 to +4.6 | V    |
| $I_{IK}$      | DC Input Diode Current<br>$V_{IN} < GND$                                              | -20                                    | mA   |
| $I_{OK}$      | DC Output Diode Current<br>$V_{OUT} < GND$                                            | -20                                    | mA   |
| $I_{OUT}$     | DC Output Source/Sink Current                                                         | $\pm 20$                               | mA   |
| $I_{CC}$      | DC Supply Current per Supply Pin                                                      | $\pm 20$                               | mA   |
| $I_{GND}$     | DC Ground Current per Ground Pin                                                      | $\pm 20$                               | mA   |
| $T_{STG}$     | Storage Temperature Range                                                             | -65 to +150                            | °C   |
| $T_L$         | Lead Temperature, 1 mm from Case for 10 Seconds                                       | 260                                    | °C   |
| $T_J$         | Junction Temperature Under Bias                                                       | +150                                   | °C   |
| MSL           | Moisture Sensitivity                                                                  | Level 1                                |      |
| $F_R$         | Flammability Rating<br>Oxygen Index: 28 to 34                                         | UL 94 V-0 @ 0.125 in                   |      |
| $V_{ESD}$     | ESD Withstand Voltage<br>Human Body Model (Note 2)<br>Machine Model (Note 3)          | >1500<br>>100                          | V    |
| $I_{LATCHUP}$ | Latchup Performance Above $V_{CC}$ and Below GND at 125°C (Note 4)                    | $\pm 100$                              | mA   |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Measured with minimum pad spacing on an FR4 board, using 10 mm-by-1 inch, 2-ounce copper trace with no air flow.
2. Tested to EIA/JESD22-A114-A.
3. Tested to EIA/JESD22-A115-A.
4. Tested to EIA/JESD78.

## RECOMMENDED OPERATING CONDITIONS

| Symbol                | Characteristics                                                                    | Min        | Max             | Unit |
|-----------------------|------------------------------------------------------------------------------------|------------|-----------------|------|
| $V_{CC}$              | Positive DC Supply Voltage                                                         | 0.9        | 3.6             | V    |
| $V_{IN}$              | Digital Input Voltage                                                              | 0.0        | 3.6             | V    |
| $V_{OUT}$             | Output Voltage<br>Output at High or Low State<br>Power-Down Mode ( $V_{CC} = 0$ V) | 0.0<br>0.0 | $V_{CC}$<br>3.6 | V    |
| $T_A$                 | Operating Temperature Range                                                        | -55        | +125            | °C   |
| $\Delta t / \Delta V$ | Input Transition Rise or Fall Rate<br>$V_{CC} = 3.3 \text{ V} \pm 0.3 \text{ V}$   | 0          | 10              | ns/V |

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

# NL17SG00

## DC ELECTRICAL CHARACTERISTICS

| Symbol          | Parameter                 | Conditions                                           | V <sub>CC</sub> (V)       | T <sub>A</sub> = 25°C |                       | T <sub>A</sub> = -55°C to +125°C |                       | Unit |
|-----------------|---------------------------|------------------------------------------------------|---------------------------|-----------------------|-----------------------|----------------------------------|-----------------------|------|
|                 |                           |                                                      |                           | Min                   | Max                   | Min                              | Max                   |      |
| V <sub>IH</sub> | High-Level Input Voltage  |                                                      | 0.9                       | V <sub>CC</sub>       |                       | V <sub>CC</sub>                  |                       | V    |
|                 |                           |                                                      | 1.1 to 1.3                | 0.7xV <sub>CC</sub>   |                       | 0.7xV <sub>CC</sub>              |                       |      |
|                 |                           |                                                      | 1.4 to 1.6                | 0.65xV <sub>CC</sub>  |                       | 0.65xV <sub>CC</sub>             |                       |      |
|                 |                           |                                                      | 1.65 to 1.95              | 0.65xV <sub>CC</sub>  |                       | 0.65xV <sub>CC</sub>             |                       |      |
|                 |                           |                                                      | 2.3 to 2.7                | 1.7                   |                       | 1.7                              |                       |      |
|                 |                           |                                                      | 3.0 to 3.6                | 2.0                   |                       | 2.0                              |                       |      |
| V <sub>IL</sub> | Low-Level Input Voltage   |                                                      | 0.9                       |                       | GND                   |                                  | GND                   | V    |
|                 |                           |                                                      | 1.1 to 1.3                |                       | 0.3xV <sub>CC</sub>   |                                  | 0.3xV <sub>CC</sub>   |      |
|                 |                           |                                                      | 1.4 to 1.6                |                       | 0.35xV <sub>CC</sub>  |                                  | 0.35xV <sub>CC</sub>  |      |
|                 |                           |                                                      | 1.65 to 1.95              |                       | 0.35xV <sub>CC</sub>  |                                  | 0.35xV <sub>CC</sub>  |      |
|                 |                           |                                                      | 2.3 to 2.7                |                       | 0.7                   |                                  | 0.7                   |      |
|                 |                           |                                                      | 3.0 to 3.6                |                       | 0.8                   |                                  | 0.8                   |      |
| V <sub>OH</sub> | High-Level Output Voltage | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub> | I <sub>OH</sub> = -20 µA  | 0.9                   | 0.75                  |                                  | 0.75                  | V    |
|                 |                           |                                                      | I <sub>OH</sub> = -0.3 mA | 1.1 to 1.3            | 0.75xV <sub>CC</sub>  |                                  | 0.75xV <sub>CC</sub>  |      |
|                 |                           |                                                      | I <sub>OH</sub> = -1.7 mA | 1.4 to 1.6            | 0.75xV <sub>CC</sub>  |                                  | 0.75xV <sub>CC</sub>  |      |
|                 |                           |                                                      | I <sub>OH</sub> = -3.0 mA | 1.65 to 1.95          | V <sub>CC</sub> -0.45 |                                  | V <sub>CC</sub> -0.45 |      |
|                 |                           |                                                      | I <sub>OH</sub> = -4.0 mA | 2.3 to 2.7            | 2.0                   |                                  | 2.0                   |      |
|                 |                           |                                                      | I <sub>OH</sub> = -8.0 mA | 3.0 to 3.6            | 2.48                  |                                  | 2.48                  |      |
| V <sub>OL</sub> | Low-Level Output Voltage  | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub> | I <sub>OL</sub> = 20 µA   | 0.9                   |                       | 0.1                              | 0.1                   | V    |
|                 |                           |                                                      | I <sub>OL</sub> = 0.3 mA  | 1.1 to 1.3            |                       | 0.25xV <sub>CC</sub>             | 0.25xV <sub>CC</sub>  |      |
|                 |                           |                                                      | I <sub>OL</sub> = 1.7 mA  | 1.4 to 1.6            |                       | 0.25xV <sub>CC</sub>             | 0.25xV <sub>CC</sub>  |      |
|                 |                           |                                                      | I <sub>OL</sub> = 3.0 mA  | 1.65 to 1.95          |                       | 0.45                             | 0.45                  |      |
|                 |                           |                                                      | I <sub>OL</sub> = 4.0 mA  | 2.3 to 2.7            |                       | 0.4                              | 0.4                   |      |
|                 |                           |                                                      | I <sub>OL</sub> = 8.0 mA  | 3.0 to 3.6            |                       | 0.4                              | 0.4                   |      |
| I <sub>IN</sub> | Input Leakage Current     | 0 ≤ V <sub>IN</sub> ≤ 3.6 V                          | 0 to 3.6                  |                       | ±0.1                  |                                  | ±1.0                  | µA   |
| I <sub>CC</sub> | Quiescent Supply Current  | V <sub>IN</sub> = V <sub>CC</sub> or GND             | 3.6                       |                       | 0.5                   |                                  | 10.0                  | µA   |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

# NL17SG00


## AC ELECTRICAL CHARACTERISTICS (Input $t_r = t_f = 3.0$ ns)

| Symbol                   | Parameter                              | Test Condition                         | $V_{CC}$ (V) | $T_A = 25^\circ\text{C}$ |       |      | $T_A = -55^\circ\text{C to } +125^\circ\text{C}$ |      | Unit |
|--------------------------|----------------------------------------|----------------------------------------|--------------|--------------------------|-------|------|--------------------------------------------------|------|------|
|                          |                                        |                                        |              | Min                      | Typ   | Max  | Min                                              | Max  |      |
| $t_{PLH}$ ,<br>$t_{PHL}$ | Propagation Delay,<br>A or B to Y      | $C_L = 10$ pF,<br>$R_L = 1$ M $\Omega$ | 0.9          | -                        | 11.0  | 13.7 | -                                                | 19.6 | ns   |
|                          |                                        |                                        | 1.1 to 1.3   | -                        | 8.6   | 10.8 | -                                                | 17.1 |      |
|                          |                                        |                                        | 1.4 to 1.6   | -                        | 5.9   | 9.6  | -                                                | 11.3 |      |
|                          |                                        |                                        | 1.65 to 1.95 | -                        | 4.5   | 7.0  | -                                                | 7.5  |      |
|                          |                                        |                                        | 2.3 to 2.7   | -                        | 2.9   | 4.4  | -                                                | 4.9  |      |
|                          |                                        |                                        | 3.0 to 3.6   | -                        | 2.2   | 3.5  | -                                                | 4.1  |      |
|                          |                                        | $C_L = 15$ pF,<br>$R_L = 1$ M $\Omega$ | 0.9          | -                        | 13.75 | 16.7 | -                                                | 20.0 | ns   |
|                          |                                        |                                        | 1.1 to 1.3   | -                        | 9.0   | 11.2 | -                                                | 17.4 |      |
|                          |                                        |                                        | 1.4 to 1.6   | -                        | 6.5   | 10.5 | -                                                | 12.6 |      |
|                          |                                        |                                        | 1.65 to 1.95 | -                        | 5.0   | 7.7  | -                                                | 8.0  |      |
|                          |                                        |                                        | 2.3 to 2.7   | -                        | 3.2   | 4.9  | -                                                | 5.6  |      |
|                          |                                        |                                        | 3.0 to 3.6   | -                        | 2.5   | 3.8  | -                                                | 4.4  |      |
|                          |                                        | $C_L = 30$ pF,<br>$R_L = 1$ M $\Omega$ | 0.9          | -                        | 17.0  | 21.0 | -                                                | 24.4 | ns   |
|                          |                                        |                                        | 1.1 to 1.3   | -                        | 11.2  | 14.8 | -                                                | 20.5 |      |
|                          |                                        |                                        | 1.4 to 1.6   | -                        | 8.6   | 10.3 | -                                                | 17.9 |      |
|                          |                                        |                                        | 1.65 to 1.95 | -                        | 5.0   | 7.5  | -                                                | 10.8 |      |
|                          |                                        |                                        | 2.3 to 2.7   | -                        | 4.4   | 6.4  | -                                                | 6.8  |      |
|                          |                                        |                                        | 3.0 to 3.6   | -                        | 3.5   | 4.9  | -                                                | 5.4  |      |
| $C_{IN}$                 | Input Capacitance                      |                                        | 0 to 3.6     |                          | 3     | -    | -                                                | -    | pF   |
| $C_{PD}$                 | Power Dissipation Capacitance (Note 5) | $f = 10$ MHz                           | 0.9 to 3.6   | -                        | 4     | -    | -                                                | -    | pF   |


Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

5.  $C_{PD}$  is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load. Average operating current can be obtained by the equation:  $I_{CC(OPR)} = C_{PD} \cdot V_{CC} \cdot f_{in} + I_{CC}$ .  $C_{PD}$  is used to determine the no-load dynamic power consumption;  $P_D = C_{PD} \cdot V_{CC}^2 \cdot f_{in} + I_{CC} \cdot V_{CC}$ .

# NL17SG00



**Figure 2. Switching Waveforms**



\*Includes all probe and jig capacitance.  
A 1-MHz square input wave is recommended  
for propagation delay tests.

**Figure 3. Test Circuit**

## ORDERING INFORMATION

| Device          | Package                      | Shipping <sup>†</sup> |
|-----------------|------------------------------|-----------------------|
| NL17SG00P5T5G   | SOT-953<br>(Pb-Free)         | 8000 / Tape & Reel    |
| NL17SG00DFT2G   | SC-88A<br>(Pb-Free)          | 3000 / Tape & Reel    |
| NL17SG00AMUTCG* | UDFN6 1.45x1 mm<br>(Pb-Free) | 3000 / Tape & Reel    |
| NL17SG00CMUTCG* | UDFN6 1x1 mm<br>(Pb-Free)    | 3000 / Tape & Reel    |



<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

\*In Development.

# NL17SG00

## PACKAGE DIMENSIONS

**SOT-953**  
CASE 527AE  
ISSUE E




### NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF THE BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| DIM            | MILLIMETERS |      |      |
|----------------|-------------|------|------|
|                | MIN         | NOM  | MAX  |
| A              | 0.34        | 0.37 | 0.40 |
| b              | 0.10        | 0.15 | 0.20 |
| C              | 0.07        | 0.12 | 0.17 |
| D              | 0.95        | 1.00 | 1.05 |
| E              | 0.75        | 0.80 | 0.85 |
| e              | 0.35 BSC    |      |      |
| H <sub>E</sub> | 0.95        | 1.00 | 1.05 |
| L              | 0.175 REF   |      |      |
| L2             | 0.05        | 0.10 | 0.15 |
| L3             | ---         | ---  | 0.15 |

### SOLDERING FOOTPRINT\*




DIMENSIONS: MILLIMETERS

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# NL17SG00

## PACKAGE DIMENSIONS

UDFN6 1.0x1.0, 0.35P  
CASE 517BX  
ISSUE O




### NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.20 MM FROM TERMINAL TIP.
4. PACKAGE DIMENSIONS EXCLUSIVE OF BURRS AND MOLD FLASH.

| MILLIMETERS |      |      |
|-------------|------|------|
| DIM         | MIN  | MAX  |
| A           | 0.45 | 0.55 |
| A1          | 0.00 | 0.05 |
| A3          | 0.13 | REF  |
| b           | 0.12 | 0.22 |
| D           | 1.00 | BSC  |
| E           | 1.00 | BSC  |
| e           | 0.35 | BSC  |
| L           | 0.25 | 0.35 |
| L1          | 0.30 | 0.40 |

### RECOMMENDED SOLDERING FOOTPRINT\*





\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.


# NL17SG00

## PACKAGE DIMENSIONS

UDFN6 1.45x1.0, 0.5P  
CASE 517AQ  
ISSUE O



**DETAIL A**  
OPTIONAL  
CONSTRUCTIONS




**DETAIL B**  
OPTIONAL  
CONSTRUCTIONS

### NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 mm FROM THE TERMINAL TIP.

| MILLIMETERS |          |      |
|-------------|----------|------|
| DIM         | MIN      | MAX  |
| A           | 0.45     | 0.55 |
| A1          | 0.00     | 0.05 |
| A2          | 0.07 REF |      |
| b           | 0.20     | 0.30 |
| D           | 1.45 BSC |      |
| E           | 1.00 BSC |      |
| e           | 0.50 BSC |      |
| L           | 0.30     | 0.40 |
| L1          | ---      | 0.15 |

### MOUNTING FOOTPRINT




DIMENSIONS: MILLIMETERS

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# NL17SG00

## PACKAGE DIMENSIONS


### SC-88A (SC-70-5/SOT-353) CASE 419A-02 ISSUE L




#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. 419A-01 OBSOLETE. NEW STANDARD 419A-02.
4. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| DIM | INCHES    |       | MILLIMETERS |      |
|-----|-----------|-------|-------------|------|
|     | MIN       | MAX   | MIN         | MAX  |
| A   | 0.071     | 0.087 | 1.80        | 2.20 |
| B   | 0.045     | 0.053 | 1.15        | 1.35 |
| C   | 0.031     | 0.043 | 0.80        | 1.10 |
| D   | 0.004     | 0.012 | 0.10        | 0.30 |
| G   | 0.026 BSC |       | 0.65 BSC    |      |
| H   | ---       | 0.004 | ---         | 0.10 |
| J   | 0.004     | 0.010 | 0.10        | 0.25 |
| K   | 0.004     | 0.012 | 0.10        | 0.30 |
| N   | 0.008 REF |       | 0.20 REF    |      |
| S   | 0.079     | 0.087 | 2.00        | 2.20 |



### SOLDER FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

MiniGate is a trademark of Semiconductor Components Industries, LLC (SCILLC).

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada  
Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910  
Japan Customer Focus Center  
Phone: 81-3-5817-1050

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.