

Features

- Lead free as standard
- RoHS compliant*
- Leadless
- Low stored charge



CD0603/1005 Schottky Barrier Chip Diode Series

General Information


The markets of portable communications, computing and video equipment are challenging the semiconductor industry to develop increasingly smaller electronic components.

Bourns offers small-signal high-speed Schottky Barrier Diodes for switching and rectification applications, in compact chip package 0603 and 1005 size format, which offer PCB real estate savings and are considerably smaller than most competitive parts. The Schottky Barrier Diodes offer a forward current of 30 mA, 100 mA or 200 mA, a reverse voltage of 30 V and 40 V and also have a low forward voltage option. The diodes are lead free with Cu/Ni/Au plated terminations and are compatible with lead free manufacturing processes, conforming to many industry and government regulations on lead free components.

Bourns® Chip Diodes conform to JEDEC standards, easy to handle on standard pick and place equipment and their flat configuration makes roll away much more difficult.

Electrical Characteristics (@ TA = 25 °C Unless Otherwise Noted)

Parameter	Symbol	CDxxxx- B00340	CDxxxx- B0130L	CDxxxx- B0140L	CDxxxx- B0140R	CDxxxx- B0230	CDxxxx- B0240	Unit
Forward Voltage (Max.)	V _F	0.37 (I _f = 1 mA)	0.44 (I _f = 0.1 A)	0.55 (I _f = 0.1 A)	0.45 (I _f = 0.01 A)	0.50 (I _f = 0.2 A)	0.55 (I _f = 0.2 A)	V
Capacitance Between Terminals (Max.) (f = 1 MHz)	C _T	1.5 (V _r = 1 V)	9 (V _r = 10 V)	9 (V _r = 10 V)	9 (V _r = 10 V)	12 (V _r = 10 V)	12 (V _r = 10 V)	pF
Reverse Current (Max.)	I _R	1 (V _r = 40 V)	30 (V _r = 30 V)	30 (V _r = 10 V)	1 (V _r = 10 V)	30 (V _r = 30 V)	10 (V _r = 30 V)	μΑ





WARNING Cancer and Reproductive Harm - www.P65Warnings.ca.gov

BOURNS®

Absolute Ratings (@ T_A = 25 °C Unless Otherwise Noted)


Parameter	Symbol	CD0603- B00340	CD0603- B0130L	CD0603- B0140L	CD0603- B0140R	CD0603- B0230	CD0603- B0240	Unit
Repetitive Peak Reverse Voltage	V _{RRM}	45	35	45	45	35	45	V
Reverse Voltage	v _R	40	30	40	40	30	40	V
Average Forward Current	Io	30	100	100	100	200	200	mA
Forward Current, Surge Peak	I _{surge}	500*	1000*	1000*	1000*	2000*	2000*	mA
Power Dissipation	PD		150			mW		
Storage Temperature	T _{STG}		-40 to +125			°C		
Junction Temperature	Тј		-40 to +125			°C		


Parameter	Symbol	CD1005- B00340	CD1005- B0130L	CD1005- B0140L	CD1005- B0140R	CD1005- B0230	CD1005- B0240	Unit
Repetitive Peak Reverse Voltage	V _{RRM}	45	35	45	45	35	45	V
Reverse Voltage	٧ _R	40	30	40	40	30	40	V
Average Forward Current	I _O	30	100	100	100	200	200	mA
Forward Current, Surge Peak	I _{surge}	500*	1000*	1000*	1000*	3000*	3000*	mA
Power Dissipation	PD	200	250	250	250	250	250	mW
Storage Temperature	T _{STG}		-40 to +125			°C		
Junction Temperature	TJ				-40 to +125			°C


Condition: 8.3 ms single half sine-wave superimposed on rate load (JEDEC method).

BOURNS®

Product Dimensions








Dimension	0603	1005		
А	1.60 - 1.80	2.40 - 2.60		
A	(0.063 - 0.071)	(0.095 - 0.102)		
В	0.80 - 1.00	1.10 - 1.30		
_ B	(0.031 - 0.039)	(0.043 - 0.051)		
С	<u>0.45</u> (0.018) Typ.	<u>0.50</u> (0.020) Typ.		
	(0.018) ^{Typ.}	(0.020) Typ.		
D	0.70 - 0.85	0.70 - 0.90		
	(0.027 - 0.033)	(0.027 - 0.035)		
F	<u>0.70</u> (0.028) Typ.	1.00 Tvp		
E	$\frac{0.70}{(0.028)}$ Typ.	(0.039) Typ.		

DIMENSIONS: $\frac{MM}{(INCHES)}$

Recommended Pad Layout



Dimension	0603	1005		
A (Max.)	<u>1.25</u> (0.049)	<u>2.00</u> (0.079)		
B (Min.)	1.00	1.3		
. ,	(0.039) 0.6	(0.051)		
C (Min.)	(0.024)	(0.028)		

DIMENSIONS: $\frac{MM}{(INCHES)}$


Physical Specifications


Typical Part Marking

33
38
39
35
37
3


BOURNS

Rating and Characteristic Curves: CDxxxx-B00340







Reverse Characteristics



Derating Curve




Capacitance Between Terminals





Specifications are subject to change without notice. Users should verify actual device performance in their specific applications.


BOURNS®

Rating and Characteristic Curves: CDxxxx-B0130L











BOURNS®


Rating and Characteristic Curves: CDxxxx-B0140L






Derating Curve 120 Mounting on glass epoxy PCBs 100 80 40 20 0 25 50 75 100 125 150


Ambient Temperature (°C)





BOURNS®

Rating and Characteristic Curves: CDxxxx-B0140R













BOURNS

Rating and Characteristic Curves: CDxxxx-B0230













BOURNS®

Rating and Characteristic Curves: CDxxxx-B0240











BOURNS

Packaging Information

The product will be dispensed in Tape and Reel format (see diagram below).





Devices are packed in accordance with EIA standard RS-481-A and specifications shown here.

		1005
A	1.00 ± 0.10	1.55 ± 0.10
	(0.039 - 0.004)	(0.061 - 0.004)
В		$\frac{2.65 \pm 0.10}{2.000}$
_	,	(0.104 - 0.004)
С		$\frac{1.05 \pm 0.10}{(0.041 \pm 0.004)}$
		(0.041 - 0.004)
d		$\frac{1.55 \pm 0.10}{(0.061 - 0.004)}$
	, ,	178
D		(7.008)
	100	60.0
D ₁	(2.362) MIN.	$\frac{60.0}{(2.362)}$ MIN.
D ₂	_13.0 ± 0.20	13.0 ± 0.20
	, ,	(0.512 - 0.008)
E		1.75 ± 0.10
		(0.069 - 0.004)
F		3.50 ± 0.05
·		(0.138 - 0.002)
Р		$\frac{4.00 \pm 0.10}{(0.157 \pm 0.004)}$
		(0.157 - 0.004)
Po		$\frac{4.00 \pm 0.10}{(0.157 + 0.004)}$
-	,	(0.157 - 0.004) 2.00 ± 0.05
P ₁		$\frac{2.00 \pm 0.03}{(0.079 - 0.002)}$
		0.25 ± 0.05
Т		(0.010 - 0.002)
		8.00 ± 0.20
W	(0.315 - 0.008)	(0.315 - 0.008)
W ₁	13.5 MAX.	$\frac{13.5}{(0.531)}$ MAX.
1	(0.531)	(0.531) MAX.
	4,000	4,000
	d D D D D D E F P P D D T W W 1	$\begin{array}{c} B \\ \\ \\ \\ C \\ \\ \\ C \\ \\ D \\ D$

Legal Disclaimer Notice



This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain types of applications are based on Bourns' knowledge of typical requirements in generic applications. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Users should always verify the actual performance of the Bourns® product in their specific devices and applications, and make their own independent judgments regarding the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., ISO/TS 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification. Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in nuclear, lifesaving, life-critical or life-sustaining applications, nor in any other applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage. Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any Bourns® products in such unauthorized applications might not be safe and thus is at the user's sole risk. Life-critical applications include devices identified by the U.S. Food and Drug Administration as Class III devices and generally equivalent classifications outside of the United States.

Bourns expressly identifies those Bourns® standard products that are suitable for use in automotive applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard products in an automotive application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk. If Bourns expressly identifies a sub-category of automotive application in the data sheet for its standard products (such as infotainment or lighting), such identification means that Bourns has reviewed its standard product and has determined that if such Bourns® standard product is considered for potential use in automotive applications, it should only be used in such sub-category of automotive applications. Any reference to Bourns® standard product in the data sheet as compliant with the AEC-Q standard or "automotive grade" does not by itself mean that Bourns has approved such product for use in an automotive application.

Bourns® standard products are not tested to comply with United States Federal Aviation Administration standards generally or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aircraft or space applications. Bourns expressly identifies Bourns® standard products that are suitable for use in aircraft or space applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard product in an aircraft or space application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Users shall not sell, transfer, export or re-export any Bourns® products or technology for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology in any facility which engages in activities relating to such devices. The foregoing restrictions apply to all uses and applications that violate national or international prohibitions, including embargos or international regulations. Further, Bourns® products and Bourns technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products may not, without prior authorization from Bourns and/or the U.S. Government, be resold, transferred, or re-exported to any party not eligible to receive U.S. commodities, software, and technical data.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties, including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:

Web Page: http://www.bourns.com/legal/disclaimers-terms-and-policies

PDF: http://www.bourns.com/docs/Legal/disclaimer.pdf



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов:
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001:
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: <u>org@eplast1.ru</u>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина,

дом 2, корпус 4, литера А.