

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
© COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	RLSD; NPR NSD07-105	18JAN2008	GG	SJ
	B	REV PER ECO-14-004513	09APR2014	JB	MS





SUGGESTED MOUNTING PATTERN 4

1. ALL DIMENSIONS ARE NOMINAL UNLESS OTHERWISE SPECIFIED.
2. POWER STRIP IS WIRED PER ELECTRICAL SCHEMATIC.
3. MATERIAL:
   JUNCTION BOX HOUSINGS - POLYCARBONATE, UL 94V-0, BLACK.
   JUNCTION BOX DUST COVER - 6/6, UL 94V-0 RATED.
   JUNCTION BOX CONTACTS - COPPER ALLOY SELECTIVELY TIN-PLATED AND SILVER PLATED 0.00508 [.000200] MINIMUM THICKNESS.
   POWER STRIP BRACKET - ZINC PLATED CARBON STEEL.
4. APPLICATION:
   AMPINNERGY - MODULAR POWER DISTRIBUTION SYSTEM, A MANUFACTURED WIRING SYSTEM.
   THE POWER STRIP IS DESIGNED TO BE MOUNTED USING THE KEYHOLE PATTERN IN THE MOUNTING BRACKET WITH CUSTOMER SUPPLIED FASTENERS, 4 PLACES.

	LEFT SIDE LINE NUMBER	RIGHT SIDE LINE NUMBER	PART NUMBER
	BLANK	BLANK	9-1933414-9
OBSOLETE	LINE 3G	LINE 3	7-1933414-3
OBSOLETE	LINE 3G	LINE 2	7-1933414-2
OBSOLETE	LINE 3G	LINE 1	7-1933414-1
OBSOLETE	LINE 2G	LINE 3	6-1933414-3
OBSOLETE	LINE 2G	LINE 2	6-1933414-2
OBSOLETE	LINE 2G	LINE 1	6-1933414-1
OBSOLETE	LINE 1G	LINE 3	5-1933414-3
OBSOLETE	LINE 1G	LINE 2	5-1933414-2
OBSOLETE	LINE 1G	LINE 1	5-1933414-1
	LINE 2	LINE 3	2-1933414-3
	LINE 1	LINE 3	1-1933414-3
	LINE 1	LINE 2	1-1933414-2
OBSOLETE	LINE 3G	LINE 3G	1933414-7
OBSOLETE	LINE 2G	LINE 2G	1933414-6
OBSOLETE	LINE 1G	LINE 1G	1933414-5
	LINE 3	LINE 3	1933414-3
	LINE 2	LINE 2	1933414-2
	LINE 1	LINE 1	1933414-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: MM [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±-
1 PLC ±-
2 PLC ±-
3 PLC ±- 1
4 PLC ±-
ANGLES ±-

MATERIAL - 3
FINISH - 3

DWN G. GARRETT 18JAN2008
CHK S. JONES 18JAN2008
APVD S. JONES 18JAN2008
PRODUCT SPEC 108-1234
APPLICATION SPEC 114-6039
WEIGHT -

TE Connectivity

NAME POWER STRIP, KEYHOLE MOUNT, 2 PORT, 3-3-2
-


SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	-	C-1933414	-

CUSTOMER DRAWING | SCALE 1:1 | SHEET 1 OF 3 | REV B

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
© COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	--	SEE SHEET 1	-	-	-



ELECTRICAL SCHEMATIC FOR 8-WIRE, DEDICATED NEUTRAL (3-3-2) POWER STRIP 2

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: MM [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±-
1 PLC ±-
2 PLC ±-
3 PLC ±-
4 PLC ±-
ANGLES ±-

MATERIAL - -
FINISH - -

DWN G. GARRETT 18JAN2008
CHK S. JONES 18JAN2008
APVD S. JONES 18JAN2008
PRODUCT SPEC 108-1234
APPLICATION SPEC 114-6039
WEIGHT -

TE Connectivity

NAME POWER STRIP, KEYHOLE MOUNT, 2 PORT, 3-3-2

SIZE A1 | CAGE CODE - | DRAWING NO C-1933414 | RESTRICTED TO -

CUSTOMER DRAWING | SCALE 1:1 | SHEET 2 OF 3 | REV B

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
© COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	--	SEE SHEET 1	-	-	-

LEFT-SIDE DUPLEX RECEPTACLE CONNECTIONS				RIGHT-SIDE DUPLEX RECEPTACLE CONNECTIONS				PART NO.
GROUND TYPE	NEUTRAL NO./CONTACT NO.	LINE NO./CONTACT NO.	AMPERAGE	GROUND TYPE	NEUTRAL NO./CONTACT NO.	LINE NO./CONTACT NO.	AMPERAGE	
ISOLATED	N3/4	3G/8	15/20	STANDARD	N3/4	L3/8	15/20	9-1933414-9
ISOLATED	N3/4	3G/8	15/20	STANDARD	N2/3	L2/7	15/20	7-1933414-3
ISOLATED	N3/4	3G/8	15/20	STANDARD	N1/2	L1/6	15/20	7-1933414-2
ISOLATED	N2/3	2G/7	15/20	STANDARD	N3/4	L3/8	15/20	7-1933414-1
ISOLATED	N2/3	2G/7	15/20	STANDARD	N2/3	L2/7	15/20	6-1933414-3
ISOLATED	N2/3	2G/7	15/20	STANDARD	N1/2	L1/6	15/20	6-1933414-2
ISOLATED	N1/2	1G/6	15/20	STANDARD	N3/4	L3/8	15/20	6-1933414-1
ISOLATED	N1/2	1G/6	15/20	STANDARD	N2/3	L2/7	15/20	5-1933414-3
ISOLATED	N1/2	1G/6	15/20	STANDARD	N1/2	L1/6	15/20	5-1933414-2
STANDARD	N2/3	L2/7	15/20	STANDARD	N3/4	L3/8	15/20	5-1933414-1
STANDARD	N1/2	L1/6	15/20	STANDARD	N3/4	L3/8	15/20	2-1933414-3
STANDARD	N1/2	L1/6	15/20	STANDARD	N2/3	L2/7	15/20	1-1933414-3
ISOLATED	N3/4	3G/8	15/20	ISOLATED	N3/4	3G/8	15/20	1-1933414-2
ISOLATED	N2/3	2G/7	15/20	ISOLATED	N2/3	2G/7	15/20	1933414-7
ISOLATED	N1/2	1G/6	15/20	ISOLATED	N1/2	1G/6	15/20	1933414-6
STANDARD	N3/4	L3/8	15/20	STANDARD	N3/4	L3/8	15/20	1933414-5
STANDARD	N2/3	L2/7	15/20	STANDARD	N2/3	L2/7	15/20	1933414-3
STANDARD	N1/2	L1/6	15/20	STANDARD	N1/2	L1/6	15/20	1933414-2
								1933414-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: MM [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±-
1 PLC ±-
2 PLC ±-
3 PLC ±-
4 PLC ±-
ANGLES ±-

MATERIAL -
-

FINISH -
-

DWN G. GARRETT 18JAN2008
CHK S. JONES 18JAN2008
APVD S. JONES 18JAN2008

PRODUCT SPEC 108-1234
APPLICATION SPEC 114-6039
WEIGHT -

TE Connectivity

NAME POWER STRIP, KEYHOLE MOUNT, 2 PORT, 3-3-2
-

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	-	C-1933414	-

CUSTOMER DRAWING | SCALE 1:1 | SHEET 3 OF 3 | REV B


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.