

# MBC60 Series


## AC-DC Open Frame Power Supplies

### Medical

The MBC60 Series of open-frame medical power supplies, with its wide universal 90-264 VAC input range, is available at 60 W of output power and a variety of single and multiple output voltages.

The MBC series was designed to 4<sup>th</sup> edition medical approvals and provides 2x MOPP (Means of Patient Protection) isolation for Class I and Class II installations.

These medical power supplies are ideal for, monitoring, home health equipment as well as surgical devices.



#### Key Features & Benefits

- 50 - 65 W Single to Triple Outputs
- Ultra High Efficiency > 85%
- Form Factor 4 x 2 x 1.2 inches (101.6 x 50.8 x 30.48 mm)
- Low leakage current < 250  $\mu$ A
- No Load Power < 0.3 W
- Approved to EN/IEC 60601-1
- 2x MOPP
- IEC Protection Class Options:
  - Class I: Earth pin J4 (no suffix)
  - Class II: No Earth pin (-2 suffix)
- Conducted EMI EN 55022-B, FCC Part 15 Level B
- Medical Safety Agency Approvals
- RoHS Compliant
- Cover Kit Accessory Available

#### Applications

- Dialysis
- Monitoring
- Pumps
- Surgical Devices
- Home Health
- Ultrasound

## 1. MODEL SELECTION

| MODEL <sup>1</sup>        | OUTPUT VOLTAGE (VDC) <sup>2</sup> | OUTPUT CURRENT MAX (A) | MINIMUM LOAD (A) <sup>3</sup> | RIPPLE & NOISE <sup>4</sup> | TOTAL REGULATION |
|---------------------------|-----------------------------------|------------------------|-------------------------------|-----------------------------|------------------|
| MBC60-1005G               | 5.2                               | 10.0                   | 0.0                           | 1.25%                       | ± 0.8%           |
| MBC60-1012G               | 12                                | 5.4                    | 0.0                           | 1%                          | ± 0.8%           |
| MBC60-1015G               | 15                                | 4.33                   | 0.0                           | 1%                          | ± 0.8%           |
| MBC60-1024G               | 24                                | 2.7                    | 0.0                           | 1%                          | ± 0.8%           |
| MBC60-1048G               | 48                                | 1.35                   | 0.0                           | 1%                          | ± 0.8%           |
| MBC60-3000G               | 5.2                               | 8.0                    | 0.5                           | 1.25%                       | ± 0.8%           |
|                           | 12.5                              | 3.0                    | 0.1                           | 1%                          | ± 5.3%           |
|                           | -12.5                             | 0.5                    | 0.0                           | 1%                          | ± 5.3%           |
| MBC60-3001G               | 5.2                               | 8.0                    | 0.5                           | 1.25%                       | ± 0.8%           |
|                           | 23.8                              | 1.5                    | 0.1                           | 1%                          | ± 5.3%           |
|                           | -12.5                             | 0.5                    | 0.0                           | 1%                          | ± 5.3%           |
| MBC60-3002G               | 5.2                               | 8.0                    | 0.5                           | 1.25%                       | ± 0.8%           |
|                           | 14.6                              | 2.5                    | 0.1                           | 1%                          | ± 5.3%           |
|                           | -16.2                             | 0.5                    | 0.0                           | 1%                          | ± 5.3%           |
| MBC60-3003G               | 3.3                               | 6.0                    | 1.0                           | 1.5%                        | ± 0.8%           |
|                           | 5.2                               | 3.0                    | 0.1                           | 1%                          | ± 5.3%           |
|                           | -12.8                             | 0.5                    | 0.0                           | 1%                          | ± 5.3%           |
| Cover-60-XCB <sup>5</sup> | Metal cover kit accessory         |                        |                               |                             |                  |

## 2. INPUT SPECIFICATIONS

Specifications are for nominal input voltage, 25°C unless otherwise stated.

| PARAMETER                    | DESCRIPTION / CONDITION                     | SPECIFICATION             |
|------------------------------|---------------------------------------------|---------------------------|
| Input Voltage                | Universal                                   | 90 - 264 VAC              |
| Input Frequency <sup>6</sup> |                                             | 47 to 400 Hz              |
| Input Current                | 120 VAC:<br>230 VAC:                        | 1.5 A max.<br>0.75 A max. |
| No Load Power                | Single output models<br>Multi output models | < 0.3 W<br>< 0.5 W        |
| Inrush Current               | 120 VAC:<br>230 VAC:                        | 30 A max.<br>60 A max.    |
| Leakage Current              | 120 VAC:<br>230 VAC:                        | < 140 µA<br>< 250 µA      |
| Switching Frequency          | Typical                                     | 67 kHz                    |

<sup>1</sup> Single output models deliver 65 W, except MBC60-1005G (50 W). Triple output models deliver 60 W, except MBC60-3003G (45 W).

<sup>2</sup> Maximum outputs for each output. Max power rating should not be exceeded

<sup>3</sup> Minimum load specified to meet cross regulation.

<sup>4</sup> Ripple is peak to peak with 20 MHz bandwidth and 10 µF (Tantalum capacitor) in parallel with a 0.1 µF capacitor at rated line voltage and load ranges.

<sup>5</sup> When used in Cover Kit, de-rate output power to 70 % under all operating conditions.

<sup>6</sup> Safety Approved: 47 to 63 Hz

### 3. OUTPUT SPECIFICATIONS

| PARAMETER                 | DESCRIPTION / CONDITION                                           | SPECIFICATION                  |
|---------------------------|-------------------------------------------------------------------|--------------------------------|
| Efficiency <sup>7</sup>   | Typical                                                           | 85%                            |
| Hold Up Time              | @ 120 VAC typical                                                 | >10 ms                         |
| Output Power              | Derate output power linearly to 80% from 90 to 80 VAC input.      | 50 - 65 W                      |
| Line Regulation           |                                                                   | +/-0.3%                        |
| Load Regulation           | V1:<br>V2 & V3:                                                   | +/-0.5%<br>+/-5%               |
| Transient Response        | 50% to 100% load change, 50/60 Hz, 50% duty cycle, 0.1 A/ $\mu$ s | < 10%,<br>recovery time < 5 ms |
| Rise Time                 |                                                                   | < 100 ms                       |
| Set Point Tolerance       | V1:<br>V2 & V3:                                                   | $\pm$ 3%<br>$\pm$ 5%           |
| Output Voltage Adjustment | V1                                                                | $\pm$ 10%                      |
| Over Current Protection   | Typical above rating                                              | 130%                           |
| Over Voltage Protection   | Typical for V1 only                                               | 130%                           |
| Short Circuit Protection  | Short term, autorecovery                                          |                                |

### 4. ENVIRONMENTAL SPECIFICATIONS

| PARAMETER             | DESCRIPTION / CONDITION                                   | SPECIFICATION             |
|-----------------------|-----------------------------------------------------------|---------------------------|
| Operating Temperature | Refer to derating curve, Fig. 1<br>Start-up is guaranteed | -20 to 70°C<br>-20 to 0°C |
| Storage Temperature   |                                                           | -40 to +85°C              |
| Relative Humidity     | Non Condensing                                            | 95%                       |
| Altitude              | Operating:<br>Non-Operating:                              | 10,000 ft.<br>40,000 ft.  |
| Reliability           | MTBF according to Telcordia -SR332-Issue 3                | 1.87 million hours        |
| Cooling               | Convection                                                |                           |



Figure 1. Derating Curve

De-rate linearly from 100% at 50°C to 50% at 70°C

<sup>7</sup> For MBC60-3003G efficiency is 75% typical.

## 5. EMC SPECIFICATIONS

| PARAMETER                          | DESCRIPTION / CONDITION             | SPECIFICATION        |
|------------------------------------|-------------------------------------|----------------------|
| Conducted Emissions                | EN 55011-B, CISPR22-B, FCC PART15-B | Pass                 |
| Radiated Emissions                 | EN 55011                            | Pass                 |
| Input Current Harmonics            | EN 61000-3-2                        | Class D              |
| Voltage Fluctuation and Flicker    | EN 61000-3-3                        | Pass                 |
| ESD Immunity                       | EN 61000-4-2                        | Level 4, Criterion A |
| Radiated Field Immunity            | EN 61000-4-3                        | Level 3, Criterion A |
| Electrical Fast Transient Immunity | EN 61000-4-4                        | Level 3, Criterion A |
| Surge Immunity                     | EN 61000-4-5                        | Level 3, Criterion A |
| Conducted Immunity                 | EN 61000-4-6                        | Level 3, Criterion A |
| Magnetic Field Immunity            | EN 61000-4-8                        | Level 4, Criterion A |
| Voltage Dips, Interruptions        | EN 61000-4-11                       | Criterion A & B      |

## 6. SAFETY SPECIFICATIONS

| PARAMETER         | DESCRIPTION / CONDITION                                                                                | SPECIFICATION                        |
|-------------------|--------------------------------------------------------------------------------------------------------|--------------------------------------|
| Isolation Voltage | Input to Output, 2M0PP<br>Input to Ground, 1M0PP<br>Output to Ground                                   | Min. 5700 VDC<br>1500 VAC<br>500 VAC |
| Safety Standards  | Approved to the latest edition of the following standards:<br>CSA/UL60601-1, EN60601-1 and IEC60601-1. |                                      |
| Agency Approvals  | Nemko, UL, C-UL                                                                                        |                                      |
| CE mark           | Complies with LVD Directive                                                                            |                                      |

## 7. CONNECTOR & PIN DESCRIPTION

| CONNECTOR           | PIN | DESCRIPTION / CONDITION                           | MANUFACTURER / PN                                                       |
|---------------------|-----|---------------------------------------------------|-------------------------------------------------------------------------|
| AC Input Connector  | J1  | Pin 1 AC Line<br>Pin 2 AC Neutral                 | Molex: 26-60-4030 or equivalent<br>Mating: 09-50-3031; Pins: 08-50-0106 |
| DC Output Connector | J2  | Pin 1,2 V1<br>Pin 3,4 RTN<br>Pin 5 V3<br>Pin 6 V2 | Tyco: 640445-6 or equivalent<br>Mating: 647402-6; Pins: 3-647409-1      |
| Signal Connector    | J3  | Pin 1 +V1 Sense<br>Pin 2 -V1 Sense                | Molex: 22-23-2021 or equivalent<br>Mating: 22-01-2021                   |
| Earth               | J4  |                                                   | Molex: 19705-4301<br>Mating: 190030001                                  |

## 8. MECHANICAL SPECIFICATIONS

| PARAMETER  | DESCRIPTION / CONDITION                    |
|------------|--------------------------------------------|
| Weight     | 150 g (0.33 lbs.)                          |
| Dimensions | 101.6 x 50.8 x 30.48 mm (4 x 2 x 1.2 inch) |




Figure 2. Mechanical Drawing MBC60-1xxxG




Figure 3. Mechanical Drawing MBC60-3xxxG

**NOTES:** In case the PCB is mounted in a metal enclosure, using metal hardware ensure the following:

- 1 Stand off, used to mount PCB has OD of 5.4 mm max.
- 2 Screws, used to fix PCB on stand off, have head dia of 6.0 mm max.
- 3 Washer, if used, to have dia of 6.5 mm max.

**For more information on these products consult: [tech.support@psbel.com](mailto:tech.support@psbel.com)**

**NUCLEAR AND MEDICAL APPLICATIONS** - Products are not designed or intended for use as critical components in life support systems, equipment used in hazardous environments, or nuclear control systems.

**TECHNICAL REVISIONS** - The appearance of products, including safety agency certifications pictured on labels, may change depending on the date manufactured. Specifications are subject to change without notice.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.