

# MMBT2369L, MMBT2369AL

## Switching Transistors

NPN Silicon

### Features

- S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant\*

### MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector-Emitter Voltage	$V_{CEO}$	15	Vdc
Collector-Emitter Voltage	$V_{CES}$	40	Vdc
Collector-Base Voltage	$V_{CBO}$	40	Vdc
Emitter-Base Voltage	$V_{EBO}$	4.5	Vdc
Collector Current – Continuous	$I_C$	200	mAdc

### THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation FR-5 Board (Note 1) $T_A = 25^\circ\text{C}$ Derate above $25^\circ\text{C}$	$P_D$	225 1.8	mW mW/ $^\circ\text{C}$
Thermal Resistance, Junction-to-Ambient	$R_{\theta JA}$	556	$^\circ\text{C}/\text{W}$
Total Device Dissipation Alumina Substrate, (Note 2) $T_A = 25^\circ\text{C}$ Derate above $25^\circ\text{C}$	$P_D$	300 2.4	mW mW/ $^\circ\text{C}$
Thermal Resistance, Junction-to-Ambient	$R_{\theta JA}$	417	$^\circ\text{C}/\text{W}$
Junction and Storage Temperature	$T_J, T_{stg}$	-55 to +150	$^\circ\text{C}$


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. FR-5 =  $1.0 \times 0.75 \times 0.062$  in.
2. Alumina =  $0.4 \times 0.3 \times 0.024$  in. 99.5% alumina.




ON Semiconductor®


<http://onsemi.com>



SOT-23  
CASE 318  
STYLE 6



### MARKING DIAGRAM



xxx = M1J or 1JA  
M = Date Code\*  
■ = Pb-Free Package

(Note: Microdot may be in either location)

\*Date Code orientation and/or overbar may vary depending upon manufacturing location.

### ORDERING INFORMATION

Device	Package	Shipping <sup>†</sup>
MMBT2369LT1G	SOT-23 (Pb-Free)	3,000 / Tape & Reel
SMMBT2369LT1G	SOT-23 (Pb-Free)	3,000 / Tape & Reel
MMBT2369ALT1G	SOT-23 (Pb-Free)	3,000 / Tape & Reel
SMMBT2369ALT1G	SOT-23 (Pb-Free)	3,000 / Tape & Reel

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# MMBT2369L, MMBT2369AL

**ELECTRICAL CHARACTERISTICS** ( $T_A = 25^\circ\text{C}$  unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
<b>OFF CHARACTERISTICS</b>					
Collector–Emitter Breakdown Voltage (Note 3) ( $I_C = 10 \mu\text{Adc}$ , $I_B = 0$ )	$V_{(\text{BR})\text{CEO}}$	15	—	—	Vdc
Collector–Emitter Breakdown Voltage ( $I_C = 10 \mu\text{Adc}$ , $V_{BE} = 0$ )	$V_{(\text{BR})\text{CES}}$	40	—	—	Vdc
Collector–Base Breakdown Voltage ( $I_C = 10 \mu\text{Adc}$ , $I_E = 0$ )	$V_{(\text{BR})\text{CBO}}$	40	—	—	Vdc
Emitter–Base Breakdown Voltage ( $I_E = 10 \mu\text{Adc}$ , $I_C = 0$ )	$V_{(\text{BR})\text{EBO}}$	4.5	—	—	Vdc
Collector Cutoff Current ( $V_{CB} = 20 \text{ Vdc}$ , $I_E = 0$ ) ( $V_{CB} = 20 \text{ Vdc}$ , $I_E = 0$ , $T_A = 150^\circ\text{C}$ )	$I_{\text{CBO}}$	— —	— —	0.4 30	$\mu\text{Adc}$
Collector Cutoff Current MMBT2369A ( $V_{CE} = 20 \text{ Vdc}$ , $V_{BE} = 0$ )	$I_{\text{CES}}$	—	—	0.4	$\mu\text{Adc}$

## ON CHARACTERISTICS

DC Current Gain (Note 3) MMBT2369 ( $I_C = 10 \mu\text{Adc}$ , $V_{CE} = 1.0 \text{ Vdc}$ ) MMBT2369A ( $I_C = 10 \mu\text{Adc}$ , $V_{CE} = 1.0 \text{ Vdc}$ ) MMBT2369A ( $I_C = 10 \mu\text{Adc}$ , $V_{CE} = 0.35 \text{ Vdc}$ ) MMBT2369A ( $I_C = 10 \mu\text{Adc}$ , $V_{CE} = 0.35 \text{ Vdc}$ , $T_A = -55^\circ\text{C}$ ) MMBT2369A ( $I_C = 30 \mu\text{Adc}$ , $V_{CE} = 0.4 \text{ Vdc}$ ) MMBT2369 ( $I_C = 100 \mu\text{Adc}$ , $V_{CE} = 2.0 \text{ Vdc}$ ) MMBT2369A ( $I_C = 100 \mu\text{Adc}$ , $V_{CE} = 1.0 \text{ Vdc}$ )	$h_{FE}$	40 — 40 20 30 20 20	— — — — — — —	120 120 — — — — —	—
Collector–Emitter Saturation Voltage (Note 3) MMBT2369 ( $I_C = 10 \mu\text{Adc}$ , $I_B = 1.0 \mu\text{Adc}$ ) MMBT2369A ( $I_C = 10 \mu\text{Adc}$ , $I_B = 1.0 \mu\text{Adc}$ ) MMBT2369A ( $I_C = 10 \mu\text{Adc}$ , $I_B = 1.0 \mu\text{Adc}$ , $T_A = +125^\circ\text{C}$ ) MMBT2369A ( $I_C = 30 \mu\text{Adc}$ , $I_B = 3.0 \mu\text{Adc}$ ) MMBT2369A ( $I_C = 100 \mu\text{Adc}$ , $I_B = 10 \mu\text{Adc}$ )	$V_{CE(\text{sat})}$	— — — — —	— — — — —	0.25 0.20 0.30 0.25 0.50	Vdc
Base–Emitter Saturation Voltage (Note 3) MMBT2369/A ( $I_C = 10 \mu\text{Adc}$ , $I_B = 1.0 \mu\text{Adc}$ ) MMBT2369A ( $I_C = 10 \mu\text{Adc}$ , $I_B = 1.0 \mu\text{Adc}$ , $T_A = -55^\circ\text{C}$ ) MMBT2369A ( $I_C = 30 \mu\text{Adc}$ , $I_B = 3.0 \mu\text{Adc}$ ) MMBT2369A ( $I_C = 100 \mu\text{Adc}$ , $I_B = 10 \mu\text{Adc}$ )	$V_{BE(\text{sat})}$	0.7 — — —	— — — —	0.85 1.02 1.15 1.60	Vdc

## SMALL-SIGNAL CHARACTERISTICS

Output Capacitance ( $V_{CB} = 5.0 \text{ Vdc}$ , $I_E = 0$ , $f = 1.0 \text{ MHz}$ )	$C_{\text{obo}}$	—	—	4.0	pF
Small Signal Current Gain ( $I_C = 10 \mu\text{Adc}$ , $V_{CE} = 10 \text{ Vdc}$ , $f = 100 \text{ MHz}$ )	$h_{fe}$	5.0	—	—	—



## SWITCHING CHARACTERISTICS

Storage Time ( $I_{B1} = I_{B2} = I_C = 10 \mu\text{Adc}$ )	$t_s$	—	5.0	13	ns
Turn-On Time ( $V_{CC} = 3.0 \text{ Vdc}$ , $I_C = 10 \mu\text{Adc}$ , $I_{B1} = 3.0 \mu\text{Adc}$ )	$t_{on}$	—	8.0	12	ns
Turn-Off Time ( $V_{CC} = 3.0 \text{ Vdc}$ , $I_C = 10 \mu\text{Adc}$ , $I_{B1} = 3.0 \mu\text{Adc}$ , $I_{B2} = 1.5 \mu\text{Adc}$ )	$t_{off}$	—	10	18	ns



Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

3. Pulse Test: Pulse Width  $\leq 300 \mu\text{s}$ , Duty Cycle  $\leq 2.0\%$ .




## MMBT2369L, MMBT2369AL



\*Total shunt capacitance of test jig and connectors.



\*Total shunt capacitance of test jig and connectors.



**Figure 5. Turn-On and Turn-Off Time Test Circuit**

# MMBT2369L, MMBT2369AL




Figure 6. Junction Capacitance Variations




Figure 7. Typical Switching Times




Figure 8. Turn-Off Waveform




Figure 9. Storage Time Equivalent Test Circuit




Figure 10. Maximum Collector Saturation Voltage Characteristics

## MMBT2369L, MMBT2369AL




Figure 11. Minimum Current Gain Characteristics





Figure 12. Saturation Voltage Limits

# MMBT2369L, MMBT2369AL

## PACKAGE DIMENSIONS

### SOT-23 (TO-236) CASE 318-08 ISSUE AP



#### NOTES:


1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

DIM	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.89	1.00	1.11	0.035	0.040	0.044
A1	0.01	0.06	0.10	0.001	0.002	0.004
b	0.37	0.44	0.50	0.015	0.018	0.020
c	0.09	0.13	0.18	0.003	0.005	0.007
D	2.80	2.90	3.04	0.110	0.114	0.120
E	1.20	1.30	1.40	0.047	0.051	0.055
e	1.78	1.90	2.04	0.070	0.075	0.081
L	0.10	0.20	0.30	0.004	0.008	0.012
L1	0.35	0.54	0.69	0.014	0.021	0.029
H_E	2.10	2.40	2.64	0.083	0.094	0.104
$\theta$	0°	—	10°	0°	—	10°

#### STYLE 6:

1. BASE
2. Emitter
3. Collector

## SOLDERING FOOTPRINT



**ON Semiconductor** and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

#### Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помошь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помошь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: [org@eplast1.ru](mailto:org@eplast1.ru)

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.