


PRODUCT NUMBER	PLATING PERFORMANCE LEVEL	PRESS FIT PIN TO PCB	FOR REAR PLUG-UP APPLICATIONS USE SHROUD
74983-102ZZZ	TELCORDIA CO	STANDARD	74993-102
74983-102ZZZLF		LEAD FREE	74993-102
74983-302ZZZ	CUSTOMER SPECIAL	STANDARD	74993-302
74983-302ZZZLF		LEAD FREE	74993-302LF
74983-502ZZZ	TELCORDIA UE	STANDARD	74993-502
74983-502ZZZLF		LEAD FREE	74993-502LF
74983-A02ZZZ	CUSTOMER SPECIAL	STANDARD	74993-102
74983-A02ZZZLF		LEAD FREE	74993-102LF










EYE OF NEEDLE
PRESS FIT SECTION



BABY-H
PRESS FIT SECTION

DETAIL A
SCALE 4:1
SEE NOTE 16

mat'l code SEE NOTE 5				tolerances unless otherwise specified			CUSTOMER
ltr	ecn no.	dr	date				COPY
W	V06-0544	DCH	2006-06-12	linear	0.X ±0.3		projection
X	V07-0175	DCH	2007-04-16		0.XX ±0.13		
Y	V08-0024	HTB	2008-01-16		.XXX ±.051		
AA	V08-0130	LP	2008-03-25	angles	0° ±2°		MM
-	-	-	-	dr	E. KROPER.	2001-01-15	
U	V05-0192	DAI	2005-04-15	engr	J. VOLSTORF	2001-01-15	scale 1:1
V	V05-0735	TAB	2005-08-05	chr	J. VOLSTORF	2001-01-15	
				appd	J. VOLSTORF	2001-01-15	

sheet index	revision sheet								
		AA	AA	AA	AA	AA	AA	AA	AA
		1	2	3	4	5	6	7	

FCI www.fciconnect.com

title: VERTICAL SIGNAL HDR 8 ROW P.F. 96 POS. SPECIAL LOAD EXT.

product family: METRAL 1000 | code: 213

size: A | dwg no: 74983 | sheet: 1 of 7

cage code: 22526

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

REV E - 2006-04-18

Pro/E

PDM: Rev:AA STATUS: Released Printed: May 13, 2011

PIN NO.	DIM A MATING LENGTH	DIM B TAIL LENGTH	PCB THICKNESS RANGE ACCOMMODATED BY PIN'S TAIL LENGTH				
			WHEN MATING TO A 84854 SERIES METRAL 1000 RECEPTACLES		WHEN MATING TO A 52066 SERIES METRAL 4000 RECEPTACLE		
			ROWS A,B,C, D,E,F,G & H	GROUND ROW	ROWS:A,B,D,E,G & H	ROW C & F	GROUND ROW
01*	5.00	4.30	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN
22		12.20	2.95 - 3.80	2.95 - 4.20	2.95 - 3.80	2.95 - 3.80	2.95 - 4.20
30		12.95	2.95 - 4.55	3.25 - 4.95	2.95 - 4.55	2.95 - 4.55	3.25 - 4.95
05		13.70	2.95 - 5.30	4.00 - 5.70	3.30 - 5.30	2.95 - 5.30	4.00 - 5.70
35		14.45	3.05 - 6.05	4.75 - 6.45	4.05 - 6.05	3.05 - 6.05	4.75 - 6.45
48		15.20	3.80 - 6.80	5.50 - 7.20	4.80 - 6.80	3.80 - 6.80	5.50 - 7.20
40		15.70	4.30 - 7.30	6.00 - 7.70	5.30 - 7.30	4.30 - 7.30	6.00 - 7.70
65		16.40	5.00 - 8.00	6.70 - 8.40	6.00 - 8.00	5.00 - 8.00	6.70 - 8.40
09		17.10	5.70 - 8.70	7.40 - 9.10	6.70 - 8.70	5.70 - 8.70	7.40 - 9.10
02*	5.75	4.30	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN
44		12.20	2.95 - 3.80	2.95 - 4.20	2.95 - 3.80	2.95 - 3.80	2.95 - 4.20
31		12.95	2.95 - 4.55	3.25 - 4.95	2.95 - 4.55	2.95 - 4.55	3.25 - 4.95
06		13.70	2.95 - 5.30	4.00 - 5.70	3.30 - 5.30	2.95 - 5.30	4.00 - 5.70
36		14.45	3.05 - 6.05	4.75 - 6.45	4.05 - 6.05	3.05 - 6.05	4.75 - 6.45
49		15.20	3.80 - 6.80	5.50 - 7.20	4.80 - 6.80	3.80 - 6.80	5.50 - 7.20
25		15.70	4.30 - 7.30	6.00 - 7.70	5.30 - 7.30	4.30 - 7.30	6.00 - 7.70
66		16.40	5.00 - 8.00	6.70 - 8.40	6.00 - 8.00	5.00 - 8.00	6.70 - 8.40
10		17.10	5.70 - 8.70	7.40 - 9.10	6.70 - 8.70	5.70 - 8.70	7.40 - 9.10
03*	6.50	4.30	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN
45		12.20	2.95 - 3.80	2.95 - 4.20	2.95 - 3.80	2.95 - 3.80	2.95 - 4.20
32		12.95	2.95 - 4.55	3.25 - 4.95	2.95 - 4.55	2.95 - 4.55	3.25 - 4.95
07		13.70	2.95 - 5.30	4.00 - 5.70	3.30 - 5.30	2.95 - 5.30	4.00 - 5.70
37		14.45	3.05 - 6.05	4.75 - 6.45	4.05 - 6.05	3.05 - 6.05	4.75 - 6.45
50		15.20	3.80 - 6.80	5.50 - 7.20	4.80 - 6.80	3.80 - 6.80	5.50 - 7.20
41		15.70	4.30 - 7.30	6.00 - 7.70	5.30 - 7.30	4.30 - 7.30	6.00 - 7.70
24		16.40	5.00 - 8.00	6.70 - 8.40	6.00 - 8.00	5.00 - 8.00	6.70 - 8.40
11		17.10	5.70 - 8.70	7.40 - 9.10	6.70 - 8.70	5.70 - 8.70	7.40 - 9.10

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

mat'l code	SEE NOTE 5		
ltr	ecn no.	dr	date
AA			

tolerances unless otherwise specified		
linear	0.X ±0.3	
	0.XX ±0.13	
	.XXX ±.051	
angles	0° ±2°	
dr	E. KROPER.	2001-01-15
engr	J. VOLSTORF	2001-01-15
chr	J. VOLSTORF	2001-01-15
appd	J. VOLSTORF	2001-01-15

sheet index	revision sheet

CUSTOMER COPY

projection

MM

scale 1:1

www.fciconnect.com

title: VERTICAL SIGNAL HDR 8 ROW P.F. 96 POS. SPECIAL LOAD EXT.

product family: METRAL 1000 | code: 213

size: A | dwg no: 74983 | sheet: 2

cage code: 22526

REV E - 2006-04-18

Pro/E

PDM: Rev:AA STATUS: Released Printed: May 13, 2011

PIN NO.	DIM A MATING LENGTH	DIM B TAIL LENGTH	PCB THICKNESS RANGE ACCOMMODATED BY PIN LENGTH				
			WHEN MATING TO A 84854 SERIES METRAL 1000 RECEPTACLE		WHEN MATING TO A 52066 SERIES METRAL 4000 RECEPTACLE		
			ROWS A,B,C,D, E, F, G, & H	GROUND ROW	ROWS:A,B,D, E,G & H	ROW C & F	GROUND ROW
04*	7.25	4.30	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN
46		12.20	2.95 - 3.80	2.95 - 4.20	2.95 - 3.80	2.95 - 3.80	2.95 - 4.20
33		12.95	2.95 - 4.55	3.25 - 4.95	2.95 - 4.55	2.95 - 4.55	3.25 - 4.95
08		13.70	2.95 - 5.30	4.00 - 5.70	3.30 - 5.30	2.95 - 5.30	4.00 - 5.70
38		14.45	3.05 - 6.05	4.75 - 6.45	4.05 - 6.05	3.05 - 6.05	4.75 - 6.45
51		15.20	3.80 - 6.80	5.50 - 7.20	4.80 - 6.80	3.80 - 6.80	5.50 - 7.20
42		15.70	4.30 - 7.30	6.00 - 7.70	5.30 - 7.30	4.30 - 7.30	6.00 - 7.70
67		16.40	5.00 - 8.00	6.70 - 8.40	6.00 - 8.00	5.00 - 8.00	6.70 - 8.40
12		17.10	5.70 - 8.70	7.40 - 9.10	6.70 - 8.70	5.70 - 8.70	7.40 - 9.10
19*	8.00	4.30	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN
47		12.20	2.95 - 3.80	2.95 - 4.20	2.95 - 3.80	2.95 - 3.80	2.95 - 4.20
34		12.95	2.95 - 4.55	3.25 - 4.95	2.95 - 4.55	2.95 - 4.55	3.25 - 4.95
20		13.70	2.95 - 5.30	4.00 - 5.70	3.30 - 5.30	2.95 - 5.30	4.00 - 5.70
39		14.45	3.05 - 6.05	4.75 - 6.45	4.05 - 6.05	3.05 - 6.05	4.75 - 6.45
52		15.20	3.80 - 6.80	5.50 - 7.20	4.80 - 6.80	3.80 - 6.80	5.50 - 7.20
43		15.70	4.30 - 7.30	6.00 - 7.70	5.30 - 7.30	4.30 - 7.30	6.00 - 7.70
68		16.40	5.00 - 8.00	6.70 - 8.40	6.00 - 8.00	5.00 - 8.00	6.70 - 8.40
21		17.10	5.70 - 8.70	7.40 - 9.10	6.70 - 8.70	5.70 - 8.70	7.40 - 9.10

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

ltr	ecn no.	dr	date
AA			

sheet index	revision sheet

mat'l code SEE NOTE 5

tolerances unless otherwise specified

linear	0.X ±0.3	
	0.XX ±0.13	
	.XXX ±.051	
angles	0° ±2°	
dr	E. KROPER.	2001-01-15
engr	J. VOLSTORF	2001-01-15
chr	J. VOLSTORF	2001-01-15
appd	J. VOLSTORF	2001-01-15

CUSTOMER COPY

projection

MM

scale 1:1

www.fciconnect.com

title VERTICAL SIGNAL HDR 8 ROW P.F. 96 POS. SPECIAL LOAD EXT.

product family METRAL 1000

code 213

size A

dwg no 74983

sheet 3

cage code 22526

REV E - 2006-04-18


Pro/E

PDM: Rev:AA STATUS: Released Printed: May 13, 2011


PRODUCT NUMBER
SEE SHEET 1

PRESS-FIT HOLES	OPTION 1
HOLE DIAMETER AFTER PLATING	∅0.65-0.80
PRESS-FIT HOLES	∅0.81-0.86 (∅0.85 DRILL)
COPPER PLATING	0.025 MIN
SnPb PLATING	0.005-0.015


FOR OTHER OPTIONS SEE DRAWING 58351



REAR PLUG-UP



STUB MOUNT



RECOMMENDED PCB HOLE PATTERN
(COMPONENT SIDE)

mat'l code SEE NOTE 5				tolerances unless otherwise specified			CUSTOMER	FCI www.fciconnect.com
ltr	ecn no.	dr	date	linear	0.X ±0.3		COPY	
AA					0.XX ±0.13		projection	title VERTICAL SIGNAL HDR 8 ROW P.F. 96 POS. SPECIAL LOAD EXT.
					.XXX ±.051			
				angles	0° ±2°			
				dr	E. KROPER.	2001-01-15	MM	product family METRAL 1000 code 213
				engr	J. VOLSTORF	2001-01-15		size A dwg no 74983 sheet 4
				chr	J. VOLSTORF	2001-01-15	scale 1:1	
				appd	J. VOLSTORF	2001-01-15		
sheet index	revision sheet							cage code 22526

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

REV E - 2006-04-18

Pro/E

PDM: Rev:AA STATUS: Released Printed: May 13, 2011

SPECIAL LOAD PATTERNS

PRODUCT #	ROW	PIN CODES
74983-X02001 74983-X02001LF SEE NOTE 15	H	01
	G	
	F	
	E	
	D	
	C	
	B	
	A	
	GND	
74983-X02004 *RPU 74983-X02004LF *RPU SEE NOTE 15	H	05
	G	
	F	
	E	
	D	
	C	
	B	
	A	
	GND	
74983-X02011 74983-X02011LF SEE NOTE 15	H	02
	G	
	F	
	E	
	D	
	C	
	B	
	A	
	GND	01
74983-X02013 *RPU 74983-X02013LF *RPU SEE NOTE 15	H	06
	G	
	F	
	E	
	D	
	C	
	B	
	A	
	GND	30
74983-X02050 74983-X02050LF SEE NOTE 15	H	02
	G	
	F	04
	E	03
	D	
	C	04
	B	03
	A	
	GND	02

PCB THICKNESS RANGE FOR REAR PLUG UP APPLICATIONS: 4.00 - 5.30

PCB THICKNESS RANGE FOR REAR PLUG UP APPLICATIONS: 3.25 - 5.30

* REAR PLUG-UP PART NUMBERS

SPECIAL LOAD PATTERNS

PRODUCT #	ROW	PIN CODES
74983-X02051 74983-X02051LF SEE NOTE 15	H	03
	G	
	F	
	E	
	D	
	C	
	B	
	A	
	GND	02
74983-X02052 74983-X02052LF SEE NOTE 15	H	02
	G	
	F	04
	E	02
	D	
	C	04
	B	02
	A	
	GND	
74983-X02053 *RPU 74983-X02053LF *RPU SEE NOTE 15	H	06
	G	
	F	08
	E	06
	D	
	C	08
	B	06
	A	
	GND	
74983-X02054 74983-X02054LF SEE NOTE 15	H	02
	G	
	F	
	E	
	D	
	C	
	B	
	A	
	GND	

PCB THICKNESS RANGE FOR REAR PLUG UP APPLICATIONS: 4.00 - 5.30

mat'l code SEE NOTE 5				tolerances unless otherwise specified			CUSTOMER COPY	FCI www.fciconnect.com
ltr	ecn no.	dr	date	linear	0.X ±0.3		projection	title VERTICAL SIGNAL HDR 8 ROW P.F. 96 POS. SPECIAL LOAD EXT.
AA					0.XX ±0.13			
					.XXX ±.051			
				angles	0° ±2°			
				dr	E. KROPER.	2001-01-15	MM	product family METRAL 1000 code 213
				engr	J. VOLSTORF	2001-01-15		size A dwg no 74983 sheet 5
				chr	J. VOLSTORF	2001-01-15	scale 1:1	
				appd	J. VOLSTORF	2001-01-15		
sheet index	revision sheet							cage code 22526

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

REV E - 2006-04-18

Pro/E

PDM: Rev:AA STATUS: Released Printed: May 13, 2011

SPECIAL LOAD PATTERNS

PRODUCT #	ROW	PIN CODES
74983-X02056 *RPU 74983-X02056LF *RPU SEE NOTE 15	H	22
	G	
	F	
	E	
	D	
	C	
	B	
	A	
	GND	
74983-X02057 74983-X02057LF SEE NOTE 15	H	02
	G	
	F	
	E	
	D	
	C	
	B	
	A	
	GND	
74983-X02058 *RPU 74983-X02058LF *RPU SEE NOTE 15	H	06
	G	
	F	
	E	
	D	
	C	
	B	
	A	
	GND	
74983-X02059 ** 74983-X02059LF ** SEE NOTE 15	H	03
	G	
	F	19
	E	04
	D	
	C	19
	B	04
	A	
	GND	02
74983-X02060 74983-X02060LF SEE NOTE 15	H	03
	G	
	F	
	E	11
	D	41
	C	24
	B	41
	A	24
	GND	49

PCB THICKNESS RANGE FOR REAR PLUG UP APPLICATIONS: 2.95 - 3.80

PCB THICKNESS RANGE FOR REAR PLUG UP APPLICATIONS: 4.00 - 5.30

PCB THK RANGE FOR REAR PLUG UP APPLICATIONS: *2.30 - 6.70

* REAR PLUG-UP PART NUMBERS
** CANNOT BE MATED TO A METRAL 4000 RECEPTACLE

SPECIAL LOAD PATTERNS

PRODUCT #	ROW	PIN CODES
74983-X02061 *RPU 74983-X02061LF *RPU SEE NOTE 15	H	35
	G	
	F	
	E	
	D	
	C	
	B	
	A	
	GND	05

PCB THICKNESS RANGE FOR REAR PLUG UP APPLICATIONS: 4.05 - 5.70

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

mat'l code SEE NOTE 5				tolerances unless otherwise specified			CUSTOMER
ltr	ecn no.	dr	date				COPY
AA				linear	0.X ±0.3		projection
					0.XX ±0.13		
					.XXX ±.051		
				angles	0° ±2°		MM
				dr	E. KROPER.	2001-01-15	
				engr	J. VOLSTORF	2001-01-15	scale 1:1
				chr	J. VOLSTORF	2001-01-15	
				appd	J. VOLSTORF	2001-01-15	
sheet index	revision sheet						

www.fciconnect.com

title: VERTICAL SIGNAL HDR 8 ROW P.F. 96 POS. SPECIAL LOAD EXT.

product family: METRAL 1000 | code: 213

size: A | dwg no: 74983 | sheet: 6

cage code: 22526

REV E - 2006-04-18

Pro/E

PDM: Rev:AA STATUS: Released Printed: May 13, 2011

PRODUCT NUMBER
SEE SHEET 1

NOTES:

1. SEE APPLICATION SPECIFICATION GS-20-010 FOR INFORMATION ON AVAILABLE TOOLING, CURCUIT BOARD DESIGN CONSIDERATIONS, REPAIR PROCEDURES AND PRODUCT OFFERINGS.

2. SEE FCI PUBLICATION 95051I-028 FOR "ELECTRICAL PERFORMANCE DATA FOR DIFFERENTIAL APPLICATIONS."

3. SEE FCI PUBLICATION 95051I-028 FOR "ELECTRICAL PERFORMANCE DATA FOR SINGLE-ENDED APPLICATION."

4. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS AND TOLERANCES ARE IN ACCORDANCE WITH ASME Y14.5M, 1994

5. HOUSING MATERIAL: LIQUID CRYSTAL POLYMER, 30% GLASS FILLED, FLAME RETARDANT PER UL 94-V0.
   PIN MATERIAL: PHOSPHER BRONZE
   GROUND SPRING MATERIAL: PHOSPHER BRONZE

6. PLATING INFORMATION: PLATING ON CONTACT AREA MEETS THE PERFORMANCE LEVELS SHOWN IN TABLE ON SHEET 1.
   PLATING ON "LF" TAILS IS Sn. PLATING ON ALL OTHERS IS SnPb.

7. DIMENSIONAL RESTRICTIONS OF PINS IN HEADERS.
   FOR MATING WITH METRAL 1000 RECEPTACLES
   DIM A : 5.00mm MIN, 8.00mm MAX FOR ROWS A-H
   DIM A : 5.00mm MIN, 5.75mm MAX FOR ROW GND NEXT TO ROW A
   DIM C : 5.00mm MIN, 8.00mm MAX FOR ROWS A-H
   DIM C : 4.60mm MIN, 6.30mm MAX FOR ROW GND NEXT TO ROW A
   FOR MATING WITH METRAL 4000 RECEPTACLES
   DIM A : 5.00mm MIN, 6.50mm MAX FOR ROWS A, B, D, E, G & H
   DIM A : 5.00mm MIN, 8.00mm MAX FOR ROW C & F
   DIM A : 5.00mm MIN, 5.75mm MAX FOR ROW GND NEXT TO ROW A
   DIM C : 5.00mm MIN, 7.00mm MAX FOR ROWS A, B, D, E, G & H
   DIM C : 5.00mm MIN, 8.00mm MAX FOR ROW C & F
   DIM C : 4.60mm MIN, 6.30mm MAX FOR ROW GND NEXT TO ROW A

8. THE MIN PCB THICKNESS FOR REAR PLUG-UP APPLICATIONS IS 2.9mm SINCE THE COMPLIANT SECTIONS OF THE GROUND SPRING IN THE HEADER DIRECTLY OPPOSE THE GROUND SPRING OF THE SHROUD. THE MIN PCB THICKNESS FROM FRONT PLUG-UP ONLY APPLICATIONS IS 1.6mm.

9. THESE HOLES ARE NEEDED FOR REAR PLUG-UP DESIGNS USING A SHROUD AND MAY BE OMITTED FOR FRONT PLUG-UP ONLY DESIGNS.

10. THE 'CONNECTOR OUTLINE' IS THE MIN OUTLINE REQUIRED. TO DETERMINE THE OUTLINE NECESSARY TO PERMIT THE VARIOUS TYPES OF REPAIR OPERATIONS, SEE APPLICATION SPECIFICATION GS-20-010.

11. CURRENT RATING : 1 AMP PER PIN

12. TEMPERATURE RANGE : -55°C TO +105°C

13. P/N 73983-X02ZZZLF
    - LEAD FREE (OPTIONAL)
    - SPECIAL LOAD PATTERN
    - PLATING CODE

14. AFTER INSERTION INTO CIRCUIT BOARD WITH QUALIFIED TOOL.

15. THE PRODUCTS WHERE THE PART NUMBER ENDS IN LF MEET EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.

    ALL PRODUCTS WILL WITHSTAND EXPOSURE TO 240°C FOR 60 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN.

16. PIN TYPE IS AT THE MANUFACTURERS OPTION AND CAN BE EITHER BABY-H OR EYE OF THE NEEDLE STYLE

mat'l code SEE NOTE 5				tolerances unless otherwise specified			CUSTOMER	FCI www.fciconnect.com
ltr	ecn no.	dr	date				COPY	
AA				linear	0.X ±0.3		projection	title VERTICAL SIGNAL HDR 8 ROW P.F. 96 POS. SPECIAL LOAD EXT.
					0.XX ±0.13			
					.XXX ±.051			
				angles	0° ±2°			
				dr	E. KROPER.	2001-01-15	MM	product family METRAL 1000 code 213
				engr	J. VOLSTORF	2001-01-15		
				chr	J. VOLSTORF	2001-01-15	scale 1:1	size A dwg no 74983 sheet 7
				appd	J. VOLSTORF	2001-01-15		
sheet index	revision sheet							cage code 22526

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

REV E - 2006-04-18

Pro/E


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.