

30A BIDIRECTIONAL SURFACE MOUNT THYRISTOR SURGE PROTECTIVE DEVICE

Features

- 30A Peak Pulse Current @ 10/1000µs
- 150A Peak Pulse Current @ 8/20µs
- 58 - 320V Stand-Off Voltages
- Oxide-Glass Passivated Junction
- Bidirectional Protection In a Single Device
- High Off-State impedance and Low On-State Voltage
- Helps Equipment Meet GR-1089-CORE, IEC 61000-4-5, FCC Part 68, ITU-T K.20/K.21, and UL497B
- UL Listed Under Recognized Component Index, File Number 156346
- **Lead Free Finish/RoHS Compliant (Note 1)**
- **Green Molding Compound (No Halogen and Antimony) (Note 2)**

Mechanical Data

- Case: SMB
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Lead Free Plating (Matte Tin Finish). Solderable per MIL-STD-202, Method 208
- Polarity: None; Bidirectional Devices Have No Polarity Indicator
- Weight: 0.093 grams (approximate)



Top View



Bottom View

Ordering Information (Note 3)

| Part Number | Case | Packaging |
|--------------|------|------------------|
| TB0640L-13-F | SMB | 3000/Tape & Reel |
| TB0720L-13-F | SMB | 3000/Tape & Reel |
| TB0900L-13-F | SMB | 3000/Tape & Reel |
| TB1100L-13-F | SMB | 3000/Tape & Reel |
| TB1300L-13-F | SMB | 3000/Tape & Reel |
| TB1500L-13-F | SMB | 3000/Tape & Reel |
| TB1800L-13-F | SMB | 3000/Tape & Reel |
| TB2300L-13-F | SMB | 3000/Tape & Reel |
| TB2600L-13-F | SMB | 3000/Tape & Reel |
| TB3100L-13-F | SMB | 3000/Tape & Reel |
| TB3500L-13-F | SMB | 3000/Tape & Reel |

- Notes:
1. EU Directive 2002/95/EC (RoHS). All applicable RoHS exemptions applied, see EU Directive 2002/95/EC Annex Notes.
 2. Product manufactured with Data Code 0924 (week 24, 2009) and newer are built with Green Molding Compound.
 3. For packaging details, go to our website at <http://www.diodes.com>.

Marking Information



xxxxx = Product type marking code (See Table on Page 2)
 DII = Manufacturers' code marking
 YWW = Date code marking
 Y = Last digit of year (ex: 2 for 2002)
 WW = Week code (01 ~ 53)

Maximum Ratings @T_A = 25°C unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load.
For capacitance load, derate current by 20%.

| Characteristic | Symbol | Value | Unit |
|--|----------------------|-------|------|
| Non-Repetitive Peak Impulse Current @10/1000us | I _{pp} | 30 | A |
| Non-Repetitive Peak On-State Current @8.3ms (one-half cycle) | I _{TSM} | 15 | A |
| Typical Positive Temperature Coefficient for Breakdown Voltage | ΔVBR/ΔT _J | 0.1 | %/°C |


Thermal Characteristics

| Characteristic | Symbol | Value | Unit |
|---|------------------|-------------|------|
| Thermal Resistance, Junction to Lead | R _{θJL} | 30 | °C/W |
| Thermal Resistance, Junction to Ambient | R _{θJA} | 120 | °C/W |
| Junction Temperature Range | T _J | -40 to +150 | °C |
| Storage Temperature Range | T _{STG} | -55 to +150 | °C |

Maximum Rated Surge Waveform

| Waveform | Standard | I _{pp} (A) |
|--------------------|------------------|---------------------|
| 2/10 us | GR-1089-CORE | 200 |
| 8/20 us | IEC 61000-4-5 | 150 |
| 10/160 us | FCC Part 68 | 100 |
| 10/700 us (Note 4) | ITU-T, K.20/K.21 | 60 |
| 10/560 us | FCC Part 68 | 50 |
| 10/1000 us | GR-1089-CORE | 30 |

Notes: 4. Applied 2kV, 10/700 us waveform



Electrical Characteristics @T_A = 25°C unless otherwise specified

| Part Number | Maximum Rated Repetitive Off-State Voltage | Maximum Off-State Leakage Current @ V _{DRM} | Maximum Breakover Voltage | Maximum On-State Voltage @ I _T = 1A | Breakover Current I _{BO} | | Holding Current I _H | | Typical Off-State Capacitance | Marking Code |
|-------------|--|--|---------------------------|--|-----------------------------------|----------|--------------------------------|----------|-------------------------------|--------------|
| | V _{DRM} (V) | I _{DRM} (uA) | V _{BO} (V) | V _T (V) | Min (mA) | Max (mA) | Min (mA) | Max (mA) | C _O (pF) | |
| TB0640L | 58 | 5 | 77 | 3.5 | 50 | 800 | 150 | 800 | 100 | T064L |
| TB0720L | 65 | 5 | 88 | 3.5 | 50 | 800 | 150 | 800 | 100 | T072L |
| TB0900L | 75 | 5 | 98 | 3.5 | 50 | 800 | 150 | 800 | 100 | T090L |
| TB1100L | 90 | 5 | 130 | 3.5 | 50 | 800 | 150 | 800 | 60 | T110L |
| TB1300L | 120 | 5 | 160 | 3.5 | 50 | 800 | 150 | 800 | 60 | T130L |
| TB1500L | 140 | 5 | 180 | 3.5 | 50 | 800 | 150 | 800 | 60 | T150L |
| TB1800L | 160 | 5 | 220 | 3.5 | 50 | 800 | 150 | 800 | 60 | T180L |
| TB2300L | 190 | 5 | 265 | 3.5 | 50 | 800 | 150 | 800 | 40 | T230L |
| TB2600L | 220 | 5 | 300 | 3.5 | 50 | 800 | 150 | 800 | 40 | T260L |
| TB3100L | 275 | 5 | 350 | 3.5 | 50 | 800 | 150 | 800 | 40 | T310L |
| TB3500L | 320 | 5 | 400 | 3.5 | 50 | 800 | 150 | 800 | 40 | T350L |

Electrical Characteristics @ $T_A = 25^\circ\text{C}$ unless otherwise specified

| Symbol | Parameter |
|------------------|--------------------------------------|
| V_{DRM} | Stand-off Voltage |
| I_{DRM} | Leakage current at stand-off voltage |
| V_{BR} | Breakdown voltage |
| I_{BR} | Breakdown current |
| V_{BO} | Breakover voltage |
| I_{BO} | Breakover current |
| I_{H} | Holding current (Note 5) |
| V_{T} | On state voltage |
| I_{PP} | Peak pulse current |
| C_{O} | Off-state capacitance (Note 6) |

Notes: 5. $I_{\text{H}} > (V_{\text{T}}/R_{\text{f}})$ If this criterion is not obeyed, the TSPD triggers but does not return correctly to high-resistance state. The surge recovery time does not exceed 30ms.
6. Off-state capacitance measured at $f = 1.0\text{MHz}$, $1.0V_{\text{RMS}}$ signal, $V_{\text{R}} = 2V_{\text{DC}}$ bias.




Fig. 1 Off-State Current vs. Junction Temperature




Fig. 2 Relative Variation of Breakdown Voltage vs. Junction Temperature



Fig. 3 Relative Variation of Breakover Voltage vs. Junction Temperature



Fig. 4 On-State Current vs. On-State Voltage



Fig. 5 Relative Variation of Holding Current vs. Junction Temperature



Fig. 6 Relative Variation of Junction Capacitance vs. Reverse Voltage Bias

Package Outline Dimensions



| SMB | | |
|-----|------|------|
| Dim | Min | Max |
| A | 3.30 | 3.94 |
| B | 4.06 | 4.57 |
| C | 1.96 | 2.21 |
| D | 0.15 | 0.31 |
| E | 5.00 | 5.59 |
| G | 0.05 | 0.20 |
| H | 0.76 | 1.52 |
| J | 2.00 | 2.50 |

All Dimensions in mm

Suggested Pad Layout



| SMB Dimensions | Value (in mm) |
|----------------|---------------|
| Z | 6.8 |
| G | 1.8 |
| X | 2.3 |
| Y | 2.5 |
| C | 4.3 |

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2011, Diodes Incorporated

www.diodes.com



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.