







HOLD DOWN TYPE

mat'l. code —				surface 58 ✓ tolerance ISO 1302 ISO 406 ISO 1101				projection 		product family PCI_EXPRESS															
ltr	ecn no	dr	date	tolerances unless otherwise specified						 MM		title PCI_EXPRESS_CARD_EDGE POST-FREE_ASSEMBLY(SMT)													
A	T04-0004	RC	02/05/'07	angles	linear	.X±.3																			
B	T07-1083	RC	05/25/'07			.XX±.20																			
C	DG-007885	HT	11/14/'11			0°±2'						XXX±.10				scale 1									
D	DG-009560	HT	01/16/'12	dr	RICHARD_CHIU		01/30/'07				dwg no						sheet 1 of 6				size				
E	ELX-DG-13973	WL	01/31/'13	engr	RICHARD_CHIU		01/30/'07				10076266						A4								
				chr	PAUL_WANG		01/30/'07																		
				appd	JOSEPH_HSIA		01/30/'07																		
sheet index		revision		E	A	A	E	A	A																
		sheet		1	2	3	4	5	6																



ADD-IN CARD EDGE-FINGER DIMENSIONS


mat'l. code -				surface 58 ISO 1302	tolerance ISO 406 ISO 101	projection 101	product family PCI_EXPRESS	
ltr	ecn no	dr	date	tolerances unless otherwise specified			title PCI_EXPRESS_CARD_EDGE POST-FREE_ASSEMBLY(SMT)	
A	-	-	-	angles	.X±.2	MM		
				linear	.XX±.13	scale 2		
				0°±2°	XXX±.05		dwg no sheet 2 of 6 size	
				dr	RICHARD_CHIU	1/30/'07	10076266 A4	
				engr	RICHARD_CHIU	1/30/'07	type CUSTOMER Drawing	
				chr	PAUL_WANG	1/30/'07		
				appd	JOSEPH_HSIA	1/30/'07		
sheet index	revision	A						
	sheet	2						



RECOMMENDED PCB LAYOUT, PAD TYPE

DIMENSIONS							
POSITION	A	B ± 0.15 ± 0.05	C ± 0.20	D ± 0.23	E ± 0.20	H ± 0.10	J
36	6.00	7.65	9.15	25.00	27.00	28.00	6.00
64	20.00	21.65	23.15	39.00	41.00	42.00	20.00
98	37.00	38.65	40.15	56.00	58.00	59.00	37.00
164	70.00	71.65	73.15	89.00	91.00	92.00	70.00

POSITION OF CAP



mat'l. code				surface 58	tolerance	projection	product family	
-				ISO 1302	ISO 406 ISO 1101		PCI_EXPRESS	
ltr	ecn no	dr	date	tolerances unless otherwise specified			title	
A	-	-	-	angles	.X $\pm$.2	MM	PCI_EXPRESS_CARD_EDGE	
				linear	.XX $\pm$.13		POST-FREE_ASSEMBLY(SMT)	
				0° $\pm$ 2°	XXX $\pm$.05			
				dr	RICHARD_CHIU 1/30/'07	FCI	dwg no	sheet 3 of 6
				engr	RICHARD_CHIU 1/30/'07		10076266	
				chr	PAUL_WANG 1/30/'07		A4	
				appd	JOSEPH_HSIA 1/30/'07		CUSTOMER Drawing	
sheet index	revision sheet	A	3					

NOTES:

1.MATERIAL:

HOUSING: NYLON, GLASS FILLED UL94V-0 RATE, SUITABLE FOR IR SOLDERING.

TERMINAL: COPPER ALLOY

PLATING: 50u" NICKEL UNDERPLATE ALL OVER

CONTACT AREA PLATING - SEE PRODUCT NUMBER CODE

SOLDER TAIL: TIN 100u" OVER 50u" NICKEL

METAL PADS: COPPER ALLOY

FINISH: 100u" TIN OVER 50u" NICKEL

2.PRODUCT SPECIFICATION: GS-12-390

③THE HORIZONTAL AXIS FOR THE PAD PATTERN IS ESTABLISHED BY

THE CENTER LINE OF THE PAD LENGTH.

THE VERTICAL AXIS IS 90° TO THE HORIZONTAL AXIS, THROUGH THE CENTER OF DATUM $\begin{matrix} - \\ Z \\ - \end{matrix}$

④NO TIE BAR PERMITTED FROM CARD EDGE TO LEADING EDGE OF PAD FOR PINS A1.

⑤CHAMFER EDGES MUST BE FREE OF CUTTING BURRS.

7.RoHS COMPATIBLE PRODUCT SPECIFICATIONS

a - PLATING:

- "LF" MEANS THE PRODUCT IS LEAD-FREE, 2um MINIMUM MATTE TIN OVER 1.27um MINIMUM NICKEL UNDERPLATE.

b - MANUFACTURING PROCESS COMPATIBILITY

- THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C±5°C PEAK TEMPERATURE FOR 5 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN.

PRODUCT NUMBER CODE

10076266-X X X X L F

HOUSING COLOR OPTIONS

1-BLACK

LEAD FREE

PACKAGING OPTIONS

T-TRAY PACKAGING WITHOUT CAP

R-TAPE & REEL PACKING WITHOUT CAP (FOR 36P&64P OPTIONS ONLY)

P-TAPE & REEL PACKING WITH CAP (FOR 36P&64P OPTIONS ONLY)

C-TRAY PACKAGING WITH CAP

M-TAPE&REEL WITH MYLAR(36P&64P OPTION ONLY)

F-HARD TRAY PACKAGING WITH CAP (164P ONLY)

TERMINAL PLATING OPTIONS

0-50u" Ni UNDERPLATE

30u" Au CONTACT AREA

100u" TIN TAIL AREA ----- COMPATIBLE RoHS

1-50u" Ni UNDERPLATE

15u" Au CONTACT AREA

100u" TIN TAIL AREA ----- COMPATIBLE RoHS

2-50u" Ni UNDERPLATE

GOLD FLASH CONTACT AREA

100u" TIN TAIL AREA ----- COMPATIBLE RoHS



POS OPTIONS




0-36

1-64

2-98

3-164

mat'l. code —				surface 58/ISO 1302			tolerance ISO 406 ISO 101			projection 		product family PCI_EXPRESS										
ltr	ecn no	dr	date	tolerances unless otherwise specified									title									
E	—	—	—	angles	linear	.X±.2					PCI_EXPRESS_CARD_EDGE POST—FREE_ASSEMBLY(SMT)											
						.XX±.13																
						XXX±.05																
				0°±2°			scale 2															
				dr	RICHARD_CHIU	1/30/'07																
				engr	RICHARD_CHIU	1/30/'07																
				chr	PAUL_WANG	1/30/'07																
				app	JOSEPH_HSIA	1/30/'07																
sheet index		revision sheet		C	4							type CUSTOMER Drawing										



TAPE AND REEL
PACKING
RECOMMENDED FOR
36PINS ONLY

mat'l. code				surface 58		tolerance		projection		product family										
-				ISO 1302		ISO 406 ISO 101				PCI_EXPRESS										
ltr	ecn no	dr	date	tolerances unless otherwise specified						title										
A	-	-	-	angles	linear	.X±.3				PCI_EXPRESS_CARD_EDGE										
						.XX±.20				POST-FREE_ASSEMBLY(SMT)										
						XXX±.10				scale 1										
				dr	RICHARD_CHIU		1/30/'07				dwg no						sheet 5 of 6		size	
				engr	RICHARD_CHIU		1/30/'07				10076266						A4			
				chr	PAUL_WANG		1/30/'07													
				appd	JOSEPH_HSIA		1/30/'07													
sheet index		revision sheet		A	5															

1 For PCI EXPRESS SMT TYPE 36P ONLY.

2. Material :

2.1 Reel :

2.1.1 Plastic hub : High Impact Polystyrene

2.1.2 Cover tape : PE

2.1.3 Carrier tape : ABS

2.2 Waterproof bag : PE

2.3 Desiccative : Silica Gel

2.4 Carton : Corrugated paper

2.5 Baffle : E.P.E

2.6 Angle paperboard : Corrugated paper

3. Dimension :

3.1 Reel :

3.1.1 Plastic hub : $\varnothing 330 \times T50.5$ mm

3.1.2 Cover tape : $5690(L) \times 37.4(W)$ mm

3.1.3 Carrier tape : $5640(L) \times 44(W)$ mm

3.2 Waterproof bag : $600(H) \times 465(W) \times 0.06(T)$ mm

3.3 Desiccative : 25 gram / Package

3.4 Carton : $380(L) \times 380(W) \times 300(H)$ mm

3.5 Baffle (1): $370(L) \times 370(W) \times 15(H)$ mm

3.6 Baffle (2): $355(L) \times 252(W) \times 15(H)$ mm

3.7 Angle paperboard : 252(H)

4. Quantity :


4.1 250 Pcs / Reel

4.2 1250 Pcs / Carton

5. Weight :

5.1 N/W :

5.2 G/W :



mat'l. code —				surface 58 ISO 1302 ✓	tolerance ISO 406 ISO 1101	projection 1101	product family PCI_EXPRESS			
ltr	ecn no	dr	date	tolerances unless otherwise specified			title			
A	—	—	—	angles	.X±.3	MM	PCI_EXPRESS_CARD_EDGE			
				linear	.XX±.20	scale 1	POST-FREE_ASSEMBLY(SMT)			
				0°±2°	XXX±.10					
				dr	RICHARD_CHIU	1/30/'07	dwg no		sheet 6 of 6	size
				engr	RICHARD_CHIU	1/30/'07	10076266			A4
				chr	PAUL_WANG	1/30/'07				
				appd	JOSEPH_HSIA	1/30/'07	type		CUSTOMER Drawing	
sheet index	revision	A								
	sheet	6								



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.