

## 1874A Multi-Conductor - Enhanced Category 6 Bonded-Pair Cable



For more Information  
please call

1-800-Belden1



### General Description:

CAT6+ (350MHz), 4-Bonded-Pairs, U/UTP-Unshielded, Plenum-CMP, Premise Horizontal Cable, 23 AWG Solid Bare Copper Conductor, FEP Insulation, Ripcord, Flamarrest® Jacket

### Usage (Overall)

**Suitable Applications:** Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU, Digital Video, RS-422, Noisy Environments

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
4	23	Solid	BC - Bare Copper

**Total Number of Conductors:** 8

#### Insulation

Insulation Material:

Insulation Material
FEP - Fluorinated Ethylene Propylene

#### Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

Outer Jacket Diameter:

Nom. Dia. (in.)
0.365
0.165

**Outer Jacket Ripcord:** Yes

#### Overall Cable

**Overall Nominal Diameter:** 0.365 x 0.165 in.

#### Pair

Pair Color Code Chart:

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

### Mechanical Characteristics (Overall)

**Operating Temperature Range:** -20°C To +80°C

**Bulk Cable Weight:** 31 lbs/1000 ft.

**Max. Recommended Pulling Tension:** 45 lbs.

**Min. Bend Radius/Minor Axis:** 0.500 in.

**Min. Bend/Installation:** 1.500 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

**NEC/(UL) Specification:** CMP

## 1874A Multi-Conductor - Enhanced Category 6 Bonded-Pair Cable

CEC/C(UL) Specification:	CMP
EU Directive 2011/65/EU (ROHS II):	Yes
Other Standards:	ISO/IEC 11801 ed 2.1 (2008) Class E
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2006
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Telecommunications Standards:	Category 6 - TIA 568.C.2

**Applicable Patents:**

Country
www.belden.com/p

**Flame Test**

UL Flame Test:	NFPA 262 Plenum Flame Test (UL910)(FT6)
CSA Flame Test:	FT6

**Plenum/Non-Plenum**

Plenum (Y/N):	Yes
Non-Plenum Number:	1872A

### Electrical Characteristics (Overall)

**Nom. Mutual Capacitance:**

Capacitance (pF/ft)
15.0

Maximum Capacitance Unbalance (pF/100 m):	49
---	----

**Nominal Velocity of Propagation:**

VP (%)
72

**Maximum Delay:**

Delay (ns/100 m)
510 @ 100MHz

**Max. Delay Skew:**

Delay Skew (ns/100 m)
25

**Maximum Conductor DC Resistance:**

DCR @ 20°C (Ohm/100 m)
7.500

**Max. Operating Voltage - UL:**

Voltage
300 V RMS

**Maximum DCR Unbalanced:**

DCR Unbalance @ 20°C (%)
3

### Electrical Characteristics-Premise (Overall)

**Premise Cable Electrical Table 1:**

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min RL (dB)
1	1.900	75.3	75.3	73.4	73.4	20.000
4	3.700	66.3	66.3	62.6	62.6	23.000
8	5.300	61.8	61.8	56.5	56.5	24.500
10	5.900	60.3	60.3	54.4	54.4	25.000
16	7.500	57.2	57.2	49.7	49.7	25.000
20	8.400	55.8	55.8	47.3	47.3	25.000
25	9.500	54.3	54.3	44.9	44.9	24.300
31.25	10.600	52.9	52.9	42.2	42.2	23.600
62.5	15.400	48.4	48.4	33.0	33.0	21.500
100	19.800	45.3	45.3	25.5	25.5	21.000
155	25.100	42.4	42.4	17.3	17.3	21.000

## 1874A Multi-Conductor - Enhanced Category 6 Bonded-Pair Cable

200	29.000	40.8	40.8	11.8	11.8	21.000
250	32.800	39.3	39.3	6.5	6.5	18.000
300	36.400	38.1	38.1	1.7	1.7	18.000
350	39.800	37.1	37.1	-2.6	-2.6	17.000
400	43.000	36.3	36.3			14.000
450	46.900	35.5	35.5			14.000
500	48.900	34.8	34.8			14.000
550	51.800	34.2	34.2			14.000

Premise Cable Electrical Table 2:

Freq. (MHz)	Input (Unfitted) Imp. (Ohms)	Fitted Impedance	Min. ACRF (dB)	Min. PSACRF (dB)
1	100 ± 12	100 ± 15	67.8	64.8
4	100 ± 12	100 ± 15	55.7	52.8
8	100 ± 12	100 ± 15	49.7	46.7
10	100 ± 12	100 ± 15	47.8	44.8
16	100 ± 12	100 ± 8	43.7	40.7
20	100 ± 12	100 ± 8	41.8	38.8
25	100 ± 15	100 ± 8	39.8	36.8
31.25	100 ± 15	100 ± 8	37.9	34.9
62.5	100 ± 15	100 ± 8	31.8	28.9
100	100 ± 15	100 ± 8	27.8	24.8
155	100 ± 15	100 ± 8	24.0	21.0
200	100 ± 15	100 ± 8	21.7	18.8
250	100 ± 20	100 ± 8	19.8	16.8
300	100 ± 20	100 ± 8	18.3	15.3
350	100 ± 22	100 ± 8	16.9	13.9
400	100 ± 32	100 ± 8	15.8	12.8
450	100 ± 32	100 ± 8	14.7	11.7
500	100 ± 32	100 ± 8	13.8	10.8
550	100 ± 32	100 ± 8	13.0	10.0

### Notes (Overall)

**Notes:** Belden IBDN. Jacket sequentially marked at 2 ft. intervals. Values above 350 MHz are information only. Third party verified to ANSI/TIA-568-C.2 Category 6.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1874A D15A1000	1,000 FT	39.000 LB	BLUE		CAT6+ 4PRB U/UTP CMP RIB
1874A D15I1000	1,000 FT	37.000 LB	BLUE	C	CAT6+ 4PRB U/UTP CMP REEL
1874A F6HA1000	1,000 FT	39.000 LB	GRAY, DARK PEARL		CAT6+ 4PRB U/UTP CMP RIB
1874A F6H1000	1,000 FT	37.000 LB	GRAY, DARK PEARL	C	CAT6+ 4PRB U/UTP CMP REEL
1874A 002A1000	1,000 FT	39.000 LB	RED		CAT6+ 4PRB U/UTP CMP RIB
1874A 003A1000	1,000 FT	39.000 LB	ORANGE		CAT6+ 4PRB U/UTP CMP RIB
1874A 004A1000	1,000 FT	39.000 LB	YELLOW		CAT6+ 4PRB U/UTP CMP RIB
1874A 005A1000	1,000 FT	39.000 LB	GREEN, DARK		CAT6+ 4PRB U/UTP CMP RIB
1874A 007A1000	1,000 FT	39.000 LB	VIOLET		CAT6+ 4PRB U/UTP CMP RIB
1874A 007I1000	1,000 FT	37.000 LB	VIOLET	C	CAT6+ 4PRB U/UTP CMP REEL
1874A 009A1000	1,000 FT	39.000 LB	WHITE		CAT6+ 4PRB U/UTP CMP RIB
1874A 009I1000	1,000 FT	37.000 LB	WHITE	C	CAT6+ 4PRB U/UTP CMP REEL
1874A 010I1000	1,000 FT	37.000 LB	BLACK	C	CAT6+ 4PRB U/UTP CMP REEL
1874A 877A1000	1,000 FT	39.000 LB	NATURAL		CAT6+ 4PRB U/UTP CMP RIB
1874A 877I1000	1,000 FT	37.000 LB	NATURAL	C	CAT6+ 4PRB U/UTP CMP REEL

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 8 Revision Date: 02-28-2014

© 2014 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.