



# Chip Inductors – 1008LS (2520)

- Lower DCR than other 1008 inductors
- Ferrite construction for high current handling
- Inductance values: 1.0 – 100  $\mu$ H

Request free evaluation samples by contacting Coilcraft or visiting [www.coilcraft.com](http://www.coilcraft.com).

| Part number <sup>1</sup> | Inductance <sup>2</sup><br>( $\mu$ H) | Percent tolerance | Q min <sup>3</sup> | SRF min <sup>4</sup><br>(MHz) | DCR max <sup>5</sup><br>(Ohms) | Irms <sup>6</sup><br>(mA) | Color code <sup>7</sup> |
|--------------------------|---------------------------------------|-------------------|--------------------|-------------------------------|--------------------------------|---------------------------|-------------------------|
| 1008LS-102XJL_           | 1.0 @ 7.9 MHz                         | 5                 | 48 @ 50 MHz        | 230                           | 0.62                           | 700                       | Black                   |
| 1008LS-122XJL_           | 1.2 @ 7.9 MHz                         | 5                 | 37 @ 50 MHz        | 210                           | 0.68                           | 650                       | Red                     |
| 1008LS-152XJL_           | 1.5 @ 7.9 MHz                         | 5                 | 37 @ 50 MHz        | 190                           | 0.76                           | 630                       | Green                   |
| 1008LS-182XJL_           | 1.8 @ 7.9 MHz                         | 5                 | 37 @ 50 MHz        | 170                           | 0.84                           | 600                       | Gray                    |
| 1008LS-222XJL_           | 2.2 @ 7.9 MHz                         | 5                 | 37 @ 50 MHz        | 150                           | 1.10                           | 520                       | Red                     |
| 1008LS-272XJL_           | 2.7 @ 7.9 MHz                         | 5                 | 37 @ 50 MHz        | 135                           | 1.28                           | 490                       | Violet                  |
| 1008LS-332XJL_           | 3.3 @ 7.9 MHz                         | 5                 | 37 @ 50 MHz        | 120                           | 1.46                           | 450                       | Orange                  |
| 1008LS-392XJL_           | 3.9 @ 7.9 MHz                         | 5                 | 37 @ 7.9 MHz       | 105                           | 1.56                           | 420                       | White                   |
| 1008LS-432XJL_           | 4.3 @ 7.9 MHz                         | 5                 | 30 @ 7.9 MHz       | 85                            | 1.70                           | 400                       | Orange                  |
| 1008LS-472XJL_           | 4.7 @ 7.9 MHz                         | 5                 | 32 @ 7.9 MHz       | 90                            | 1.68                           | 400                       | Violet                  |
| 1008LS-502XJL_           | 5.0 @ 7.9 MHz                         | 5                 | 25 @ 7.9 MHz       | 30                            | 2.20                           | 360                       | Black                   |
| 1008LS-562XJL_           | 5.6 @ 7.9 MHz                         | 5                 | 37 @ 7.9 MHz       | 80                            | 1.82                           | 380                       | Blue                    |
| 1008LS-622XJL_           | 6.2 @ 7.9 MHz                         | 5                 | 32 @ 7.9 MHz       | 75                            | 2.50                           | 330                       | Red                     |
| 1008LS-682XJL_           | 6.8 @ 7.9 MHz                         | 5                 | 37 @ 7.9 MHz       | 70                            | 2.00                           | 360                       | Gray                    |
| 1008LS-822XJL_           | 8.2 @ 7.9 MHz                         | 5                 | 37 @ 7.9 MHz       | 65                            | 2.65                           | 330                       | Red                     |
| 1008LS-912XJL_           | 9.1 @ 7.9 MHz                         | 5                 | 37 @ 7.9 MHz       | 57                            | 2.90                           | 310                       | Brown                   |
| 1008LS-103XJL_           | 10 @ 7.9 MHz                          | 5                 | 37 @ 7.9 MHz       | 60                            | 2.95                           | 300                       | Black                   |
| 1008LS-123XJL_           | 12 @ 2.5 MHz                          | 5                 | 28 @ 2.5 MHz       | 38                            | 3.30                           | 290                       | Red                     |
| 1008LS-153XJL_           | 15 @ 2.5 MHz                          | 5                 | 34 @ 2.5 MHz       | 30                            | 3.70                           | 280                       | Green                   |
| 1008LS-183XJL_           | 18 @ 2.5 MHz                          | 5                 | 28 @ 2.5 MHz       | 26                            | 4.00                           | 160                       | Gray                    |
| 1008LS-223XJL_           | 22 @ 2.5 MHz                          | 5                 | 20 @ 2.5 MHz       | 22                            | 6.14                           | 270                       | Red                     |
| 1008LS-273XJL_           | 27 @ 2.5 MHz                          | 5                 | 24 @ 2.5 MHz       | 12                            | 6.45                           | 210                       | Violet                  |
| 1008LS-333XJL_           | 33 @ 2.5 MHz                          | 5                 | 22 @ 2.5 MHz       | 19                            | 7.00                           | 200                       | Orange                  |
| 1008LS-393XJL_           | 39 @ 2.5 MHz                          | 5                 | 33 @ 2.5 MHz       | 26                            | 10.0                           | 170                       | White                   |
| 1008LS-473XJL_           | 47 @ 2.5 MHz                          | 5                 | 20 @ 2.5 MHz       | 12                            | 10.7                           | 160                       | Violet                  |
| 1008LS-563XJL_           | 56 @ 2.5 MHz                          | 5                 | 20 @ 2.5 MHz       | 8.0                           | 10.0                           | 170                       | Blue                    |
| 1008LS-683XJL_           | 68 @ 0.79 MHz                         | 5                 | 14 @ 0.79 MHz      | 5.7                           | 13.5                           | 145                       | Gray                    |
| 1008LS-104XJL_           | 100 @ 0.79 MHz                        | 5                 | 13 @ 0.79 MHz      | 4.5                           | 20.5                           | 120                       | Black                   |

1. When ordering, please specify **termination** and **packaging** codes:

1008LS-103XJLC

**Termination:** L = RoHS compliant silver-palladium-platinum-glass frit.

E = Halogen free component. RoHS compliant silver-palladium-platinum-glass frit terminations.  
Special order: T = RoHS tin-silver-copper (95.5/4/0.5) or S = non-RoHS tin-lead (63/37).

**Packaging:** C = 7" machine-ready reel. EIA-481 embossed plastic tape (2000 parts per full reel).

B = Less than full reel. In tape, but not machine ready. To have a leader and trailer added (\$25 charge), use code letter C instead.

D = 13" machine-ready reel. EIA-481 embossed plastic tape. Factory order only, not stocked (7500 parts per full reel).

- Inductance measured using a Coilcraft SMD-A fixture in an Agilent/HP 4286A impedance analyzer with Coilcraft-provided correlation pieces.
- Q measured using an Agilent/HP 4291A with an Agilent/HP 16193 test fixture.
- SRF measured using an Agilent/HP 8753D network analyzer with a Coilcraft SMD-D fixture.
- DCR measured on a Cambridge Technology Micro-ohmmeter.
- Current that causes a 15°C temperature rise from 25°C. Because of their open construction, these parts will not saturate.
- Current production parts are marked with one dot. Prior production parts were marked with three dots. Part marking does not indicate polarity.
- Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.

**Designer's Kit C336** contains 10 of each stocked value

**Core material** Ceramic/Ferrite

**Environmental** RoHS compliant, halogen free optional

**Terminations** RoHS compliant silver-palladium-platinum-glass frit. Other terminations available at additional cost.

**Weight** 38.3 – 41.0 mg

**Ambient temperature** –40°C to +85°C with Irms current, +85°C to +100°C with derated current

**Storage temperature** Component: –40°C to +100°C.  
Tape and reel packaging: –40°C to +80°C

**Resistance to soldering heat** Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

**Temperature Coefficient of Inductance (TCL)** +100 to +350 ppm/°C

**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at <30°C / 85% relative humidity)

**Failures in Time (FIT) / Mean Time Between Failures (MTBF)**

One per billion hours / one billion hours, calculated per Telcordia SR-332

**Packaging** 2000/7" reel Plastic tape: 8 mm wide, 0.3 mm thick, 4 mm pocket spacing, 2.0 mm pocket depth

**PCB washing** Tested with pure water or alcohol only. For other solvents, see Doc787\_PCB\_Washing.pdf



[www.coilcraft.com](http://www.coilcraft.com)

**US** +1-847-639-6400 [sales@coilcraft.com](mailto:sales@coilcraft.com)

**UK** +44-1236-730595 [sales@coilcraft-europe.com](mailto:sales@coilcraft-europe.com)

**Taiwan** +886-2-2264 3646 [sales@coilcraft.com.tw](mailto:sales@coilcraft.com.tw)

**China** +86-21-6218 8074 [sales@coilcraft.com.cn](mailto:sales@coilcraft.com.cn)

**Singapore** + 65-6484 8412 [sales@coilcraft.com.sg](mailto:sales@coilcraft.com.sg)

Document 103-1 Revised 01/21/13


© Coilcraft Inc. 2013

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.





# 1008LS Series (2520)

## Typical Q vs Frequency



## Typical L vs Frequency



| A     | B     | C     | D     | E     | F     | G     | H     | I     | J     |
|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| max   | max   | max   | ref   |       |       |       |       |       |       |
| 0.115 | 0.110 | 0.080 | 0.020 | 0.080 | 0.020 | 0.060 | 0.100 | 0.040 | 0.050 |
| 2,92  | 2,79  | 2,03  | 0,51  | 2,03  | 0,51  | 1,52  | 2,54  | 1,02  | 1,27  |

**Note:** Height dimension is before optional solder application. For maximum height dimension including solder, add 0.006 in / 0,152 mm.

**S-Parameter files**  
ON OUR WEB SITE  
**SPICE models**  
ON OUR WEB SITE

**COILCRAFT** ACCURATE  
**PRECISION** REPEATABLE  
MEASUREMENTS  
SEE WEB SITE **TEST FIXTURES**



**US** +1-847-639-6400 sales@coilcraft.com  
**UK** +44-1236-730595 sales@coilcraft-europe.com  
**Taiwan** +886-2-2264 3646 sales@coilcraft.com.tw  
**China** +86-21-6218 8074 sales@coilcraft.com.cn  
**Singapore** + 65-6484 8412 sales@coilcraft.com.sg

Document 103-2 Revised 01/21/13  
© Coilcraft Inc. 2013  
This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.