


## Catalyst LP

- Dual core for high-speed applications
- 400MHz graphics engine
- High bandwidth I/O
- Eurotech's Everyware Software Framework helps speed up development time while making application development portable and robust
- Full-featured, application-ready development kits



### FEATURES

**CPU** – Intel Atom N450 and D510 with Intel ICH8M companion chip

**Memory/boot options** – Up to 2GB of DDR2 SDRAM, SD/MMC slots, dual SATA, and SSD Flash support up to 32GB

**Multimedia** – VGA, 18-bit color LVDS, dual display, Intel® HD Audio

**Mechanical** – Fanless 67 x 100 mm form factor

**Power management** – Power management across operating systems with consumption specs at 7W – 9W typical for single core and 11W – 13W typical for dual core

**Connectivity & I/O** – PCIe, Gigabit Ethernet and USB 2.0

**Operating system** – Pre-loaded Windows Embedded Standard or Wind River Linux

**Software framework** – Eurotech's Everyware™ Software Framework based on Java VME, with simplified foundation bundles supported allowing for fast application-specific code development.

The Catalyst LP, based on the Intel Atom N450 and D510 processors and the Intel ICH8M companion chip, offers dual core processing, high end graphics, rich high speed I/O, and more. All of this capability is brought out in the fanless 67 x 100 mm form factor typical of the Catalyst product family.

With a 400MHz graphics engine, the Catalyst LP offers high-performance graphics with 2-D and 3-D visualization for markets where high-resolution displays are critical, such as in digital signage. In addition, high bandwidth I/O capability and data storage interfaces like SATA make the Catalyst LP ideal for applications requiring extensive data retrieval and processing such as those in the industrial, medical, or human-machine interface markets. The compact, fanless design is well suited for devices both small and powerful.

The Catalyst LP supports Windows Embedded Standard and Wind River Linux 3.0. Support for Eurotech's Everyware™ Software Framework (ESF) and Eurotech Device Cloud (EDC) are coming soon. Contact us for availability.

### System Architecture

PROCESSOR	<ul style="list-style-type: none"> <li>Intel® Atom™ Processor N450 (single core)</li> <li>Intel® Atom™ Processor D510 (single core)</li> <li>Intel® ICH8M companion chip</li> </ul>
RAM MEMORY	Up to 2GB DDR2 SDRAM at 667MHz
FLASH MEMORY	Optional on-board SSD Flash support up to 32GB
OPERATING SYSTEM	<ul style="list-style-type: none"> <li>Windows Embedded Standard</li> <li>Wind River Linux</li> <li>Other RTOS (contact for details)</li> </ul>
SOFTWARE FRAMEWORK	Everyware™ Software Framework
NETWORK	10/100/1000 BASE-T Ethernet (magnetic only resident on carrier board)
USB	<ul style="list-style-type: none"> <li>9x USB 2.0 ports</li> <li>USB port disable capability</li> </ul>
I2C	I2C bus
LPC	LPC bus
SM Bus	SM Bus interface
VIDEO	<ul style="list-style-type: none"> <li>1x LVDS interface with 18-bit color</li> <li>1x VGA interface</li> <li>Dual independent display output capability</li> </ul>
AUDIO	Intel® High Definition Audio
TRUSTED PLATFORM MODULE	TPM available on set configurations
EXPANSION BUSES	<ul style="list-style-type: none"> <li>4x one-lane PCIe interfaces or optionally 1x four-lane</li> <li>2x SATA interface</li> <li>2x SD/MMC interfaces</li> </ul>
POWER	3.3V and 5.0V (± 5%)
TEMPERATURE	Operating: 0°C to +70°C
PHYSICAL	Dimensions: 67 x 100 mm
ADAPTER BOARD EXPANDABILITY	Customization options include: Serial ports (RS-232, RS-485, optically isolated) 4/5/8-wire touchscreen interface Parallel port Digital I/O Analog I/O CanBUS Microphone and speaker audio
ORDER CODES	<ul style="list-style-type: none"> <li>900125-1006R: Catalyst LP Module Intel Atom D510 (dual core), C Temp, 1.6GHz, 1GB DRAM</li> <li>900125-1007R: Catalyst LP Module Intel Atom D510 (dual core), C Temp, 1.6GHz, 2GB DRAM, 8GB Flash SSD, TPM</li> <li>900125-1008R: Catalyst LP Module Intel Atom N450 (single core), C Temp, 1.6GHz, 1GB DRAM</li> <li>CTLP1007: Catalyst LP Development Kit, Catalyst LP Module Intel Atom D510 (dual core), C Temp, 1.6GHz, 2GB DRAM, 8GB MMC, 4GB CompactFlash®, TPM</li> <li>CTLP1008: Catalyst LP Development Kit, Catalyst LP Module Intel Atom N450 (single core), C Temp, 1.6GHz, 1GB DRAM, 4GB CompactFlash®</li> </ul>

Note: The information in this document is subject to change without notice and should not be construed as a commitment by EUROTECH. While reasonable precautions have been taken, EUROTECH assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective companies.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.