


VECTOR

- Fanless EPIC form factor
- Wide range input power supply
- Rich set of expansion buses
- Multiple boot options
- Industrial and commercial temperature



FEATURES

Intel Architecture – Vector is based on the powerful Intel Atom X5xx processor family with CPU speeds from 1.1GHz up to 1.6GHz and low heat dissipation.

Low Power Design – Eurotech's low power design expertise allows Vector to deliver extensive capability with 7W typical of power consumption.

Expandability – Expansion buses such as MiniPCIe, SATA, SD, CF, or SSD allow flexibility in boot-media options and configurations.

Application-ready Development Kits – Eurotech's full-featured and application-ready development kits help customer begin application development quickly.

- Medical
- Industrial
- Transportation
- Infotainment

Eurotech's Vector delivers the power of Intel Atom in a low-cost, integrated single board computer (SBC) design. Supporting CPU speeds up to 1.6GHz and a rich suite of multimedia and I/O capabilities, the Vector is a flexible embedded solution for all markets where low power and high performance in a robust SBC design are a requirement.

Vector is available in a range of standardized configurations which support a comprehensive set of I/O connections including Gigabit Ethernet, dual CAN 2.0, high speed USB host and client ports, serial ports, and much more. A wide range PSU makes it ideal for industrial or automotive applications. Expansion interfaces such as Mini-PCIe, SATA, CompactFlash®, and on-board SSD allow flexibility in boot options and configuration choices. The Vector supports commercial and industrial temperatures and, with no fans, is extremely reliable and efficient.

Vector runs Windows Embedded Standard, Windows CE, or Wind River Linux. Eurotech's Everyware™ Software Framework (ESF), is available on Vector, allowing OEMs to focus on application-specific development. Optionally, Eurotech delivers also industry-specific ESF bundles, helping bring designs to market quickly with optimized costs.

Vector also supports Everyware Device Cloud (EDC), Eurotech end-to-end solution to bring data from distributed devices to business applications.



System Architecture

PROCESSOR	<ul style="list-style-type: none"> • Intel® Atom™ Z5xxP • 1.1GHz to 1.6GHz CPU Speed • Intel® System Controller Hub US15WP (SCH US15WP)
RAM MEMORY	512MB / 2GB DDR2 SDRAM SODIMM
SOLID STATE DISK	Optional on-board 2GB/4GB/8GB support
OPERATING SYSTEM	<ul style="list-style-type: none"> • Windows Embedded Standard • Windows CE • Wind River Linux • Other RTOS (contact for details)
EXPANSION INTERFACES	<ul style="list-style-type: none"> • 1x MiniPCIe socket • CompactFlash socket • Optional SecureDigital interface (mutually exclusive of CompactFlash socket) • Optional SATA controller • Optional on-board Solid State Disk 2GB/4GB/8GB
NETWORK	1x 10/100/1000 BASE-T Ethernet interface with RJ-45 connector
SERIAL	<ul style="list-style-type: none"> • 1x configurable RS-232/485 serial port • Optional 1x RS-232/485 serial port
USB	<ul style="list-style-type: none"> • 5x USB 2.0 host ports • 1x USB 2.0 client port (configurable as host port)
CAN	2x CAN 2.0 interfaces
I2C	1x I2C interface
GPIO	18x GPIO/8x8 keyboard scanning inputs
ANALOG	2x Analog inputs
VIDEO	<ul style="list-style-type: none"> • Dual display support • 1x VGA interface • 1x LVDS interface with 18-bit or 24-bit color support • Optional S-Video interface • 4/5/8-wire touchscreen • Backlight inverter
AUDIO	Intel® High Definition Audio with: <ul style="list-style-type: none"> • 2W amplified speaker output • Microphone input • Line input
TPM	Optional Trusted Platform Module
RTC	Battery backed Real Time Clock
POWER	• 7 to 25 VDC input
TEMPERATURE	Operating: Up to -40°C to +85°C (-40°F to +185°F)
PHYSICAL	• Dimensions: EPIC form factor with 4.5 x 6.5 inches (115 x 165 mm)
ORDER CODES	<ul style="list-style-type: none"> • 900124-7001R: Vector SBC, Intel Atom Z510P, 1.1GHz, C Temp, 1x GigE, 1x CF, 2x Serial, 5x USB host, 1x USB client, 1x PCIe, LVDS • 900124-7003R: Vector SBC, Intel Atom Z530P, 1.6GHz, C Temp, 1x GigE, 1x CF, 1x Serial, 5x USB host, 1x USB client, 1x PCIe, 2x CAN, 1x SATA, LVDS, Touchscreen, Audio, VGA • 900124-7004R: Vector SBC, Intel Atom Z520PT, 1.3GHz, I Temp, 1x GigE, 1x CF, 1x Serial, 5x USB host, 1x USB client, 1x PCIe, 2x CAN, 1x SATA, LVDS, Touchscreen, Audio • VEC7000: Vector SBC Development Kit, Intel Atom Z520P, 1.6GHz, C Temp, GigE, CF, Serial, USB, PCIe, CAN, SATA, LVDS display, Touchscreen, Audio, VGA, with OS WES, Win CE, and Wind River Linux

Note: The information in this document is subject to change without notice and should not be construed as a commitment by EUROTECH. While reasonable precautions have been taken, EUROTECH assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective companies.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.