



SIGN	DATE	DESCRIPTION	APPROVER
Δ	3/22'06	Hole size changed from 0.5mm to 1.3mm	Tony
Δ	01/12'07	Soldering temperature changed from 245° to 250°	Tason
Δ	01/12'07	Part NO is Changed	Tason
Δ	07/20'09	The shape of digging hele is Changed	Aaron
Δ	07/20'09	Operating temperature is Changed	Aaron
Δ	10/26'09	Wire guard solder pin is Changed from Brass to Copper	Aaron
Δ	11/09'10	Add is " VDE "	Aaron

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

DIMENSION

Dim A	N×7.5
Dim B	(N-1)×7.5

N=Number of contacts

Poles	Tolerance
2p-6p	±0.15
7p-12p	±0.25
13p-16p	±0.35

- Material:
- Item 1 Terminal housing:Thermoplastic (UL 94V-0)
 - Item 2 Clamp: Brass Ni plated
 - Δ ● Item 3 Wire guard solder pin:Copper Tin plated
 - Item 4 Terminal screw: Steel Zinc plating"- "slot type

- Δ Electrical cULus VDE
- Voltage rating: 300VAC 750V
 - Current rating: 20A 24A
 - Wire range : 0.2-2.5mm²
 - Solid wire(AWG): 12-30
 - Stranded wire(AWG): 12-30
 - Torque(Lb-In): 3.5 0.5 N.m
 - Screw: M3
 - Wire strip length: 6-7mm
 - Withstanding Voltage: 1.6KV 3KV
 - Δ ● Operating temperature: -40°C to +115°C
 - Δ ● Soldering temperature: 250°C±10°C/5 Sec
 - Safety Approval:

- Δ VJ xx 41 x 0 xxxx G
- RoHS
Pb<40,000ppm
- | | | |
|-----------------------------------|---------------------|--|
| No. of poles end stackable desgin | 0 Black (RAL9005) | 0000:"@"/Logo (Standard) |
| | 2 Red (RAL3001/D) | 000A:"ANYTEK"/Logo |
| 02 2 CONTACTS | 3 Orange(RAL2011/P) | Any special item by customer request, please contact sales department. |
| 03 3 CONTACTS | 4 Yellow(RAL1018/A) | |
| ... | 5 Green(RAL6018/T) | |
| ... | 6 Blue (RAL5015/A) | |
| 16 16 CONTACTS | 8 Grey(RAL7035/D) | |

ANYTEK			CUSTOMER COPY		
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD					
TITLE	VJ-7.5 Series 2P-16P Vertical (90D wire inlet)				
PART NO.	VJxx41x0xxxxG		DWG NO.	8VJ0202	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance
					X. ±0.50
Aaron		Aaron			UNIT: mm
2010.11.09		2009.10.26	SHEET: 01/01		SCALE: NONE
			REV.: H		X.XX ±0.30
					X.XX ±0.10
					X* ±1°



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.