

Descriptions

This series of fixed-voltage monolithic integrated-circuit voltage regulators is designed for a wide range of applications. These applications include on-card regulation for elimination of Noise and distribution problems associated with single-point regulation. In addition, they can be used with power-pass elements to make high-current voltage regulators. Each of these regulators can deliver up to 100mA of output current. The internal limiting and thermal shutdown features of these regulators make them essentially immune to overload. When used as a replacement for a Zener diode-resistor combination, an effective improvement in output impedance can be obtained together with lower-bias current.

Features


- 3-Terminal Regulators
- Output Current of 100mA
- Thermal Shutdown Protection
- Short-Circuit Limit Protection

Ordering Information


Type NO.	Marking	Package Code
S78LxxF	□□	SOT-89

□□: Voltage Code (05:5V, 06:6V, 08:8V, 09:9V, 10:10V, 12:12V, 15:15V, 18:18V, 24:24V)

Outline Dimensions (Unit : mm)



BLOCK DIAGRAM



PIN Connections

1. Output
- 2,4. GND
3. Input

Absolute maximum ratings

[Ta=25°C]

Characteristics	Symbol	Rating		Unit
Input Voltage	V _I	S78L05F Thru S78L10F	30	V
		S78L12F Thru S78L18F	35	
		S78L24F	40	
Power Dissipation	P _D [*]	500		mW
Junction Temperature	T _J	150		°C
Operating temperature range	T _{opr}	-40 ~ +85		°C
Storage temperature range	T _{stg}	-55 ~ +150		°C

* With PCB(50mm² copper area) at glass epoxy board (t=1.7mm, area=50×50mm)

Device Selection Guide

Device	Output Voltage
S78L05F	5.0V
S78L06F	6.0V
S78L08F	8.0V
S78L09F	9.0V
S78L10F	10V
S78L12F	12V
S78L15F	15V
S78L18F	18V
S78L24F	24V

Electrical Characteristics

(Electrical Characteristics at $V_I=10V$, $I_O=40mA$, $C_I=0.33\mu F$, $C_O=0.1\mu F$, $0^\circ C \leq T_J \leq 125^\circ C$, Unless otherwise specified)

Parameter	Symbol	Test Condition*		S78L05F			Unit
				Min.	Typ.	Max.	
Output Voltage**	V_O		$T_J=25^\circ C$	4.80	5.00	5.20	V
		$I_O=1mA \sim 40mA$ $V_I=7V \sim 20V$		4.75	-	5.25	
		$I_O=1mA \sim 70mA$ $V_I=10V$		4.75	-	5.25	
Line Regulation	$\Delta V_{O(\Delta V_I)}$	$V_I=7V \sim 20V$	$T_J=25^\circ C$	-	32	150	mV
		$V_I=8V \sim 20V$		-	26	100	
Load Regulation	$\Delta V_{O(\Delta I_L)}$	$I_O=1mA \sim 100mA$	$T_J=25^\circ C$	-	15	60	mV
		$I_O=1mA \sim 40mA$		-	8	30	
Quiescent Current	I_{QC}		$T_J=25^\circ C$	-	3.8	6	mA
Quiescent Current Change	ΔI_{QC}	$V_I=8V \sim 20V$		-	-	1.5	mA
		$I_O=1mA \sim 40mA$		-	-	0.1	
Dropout Voltage	V_{DROP}		$T_J=25^\circ C$	-	1.7	-	V
Ripple Rejection	RR	$V_I=8V \sim 18V$, $f=120Hz$		41	49	-	dB

Electrical Characteristics

(Electrical Characteristics at $V_I=11V$, $I_O=40mA$, $C_I=0.33\mu F$, $C_O=0.1\mu F$, $0^\circ C \leq T_J \leq 125^\circ C$, Unless otherwise specified)

Parameter	Symbol	Test Condition*		S78L06F			Unit
				Min.	Typ.	Max.	
Output Voltage**	V_O		$T_J=25^\circ C$	5.75	6.00	6.25	V
		$I_O=1mA \sim 40mA$ $V_I=8V \sim 20V$		5.70	-	6.30	
		$I_O=1mA \sim 70mA$ $V_I=11V$		5.70	-	6.30	
Line Regulation	$\Delta V_{O(\Delta V_I)}$	$V_I=8V \sim 20V$	$T_J=25^\circ C$	-	35	175	mV
		$V_I=9V \sim 20V$		-	29	125	
Load Regulation	$\Delta V_{O(\Delta I_L)}$	$I_O=1mA \sim 100mA$	$T_J=25^\circ C$	-	16	80	mV
		$I_O=1mA \sim 40mA$		-	9	40	
Quiescent Current	I_{QC}		$T_J=25^\circ C$	-	3.9	6	mA
Quiescent Current Change	ΔI_{QC}	$V_I=9V \sim 20V$		-	-	1.5	mA
		$I_O=1mA \sim 40mA$		-	-	0.1	
Dropout Voltage	V_{DROP}		$T_J=25^\circ C$	-	1.7	-	V
Ripple Rejection	RR	$V_I=9V \sim 19V$, $f=120Hz$		40	48	-	dB

Electrical Characteristics

(Electrical Characteristics at $V_I=14V$, $I_O=40mA$, $C_I=0.33\mu F$, $C_O=0.1\mu F$, $0^\circ C \leq T_J \leq 125^\circ C$, Unless otherwise specified)

Parameter	Symbol	Test Condition*		S78L08F			Unit
				Min.	Typ.	Max.	
Output Voltage**	V_O		$T_J=25^\circ C$	7.7	8.0	8.3	V
		$I_O=1mA \sim 40mA$ $V_I=10.5V \sim 23V$		7.6	-	8.4	
		$I_O=1mA \sim 70mA$ $V_I=14V$		7.6	-	8.4	
Line Regulation	$\Delta V_{O(\Delta V_I)}$	$V_I=10.5V \sim 23V$	$T_J=25^\circ C$	-	42	175	mV
		$V_I=11V \sim 23V$		-	36	125	
Load Regulation	$\Delta V_{O(\Delta I_L)}$	$I_O=1mA \sim 100mA$	$T_J=25^\circ C$	-	18	80	mV
		$I_O=1mA \sim 40mA$		-	10	40	
Quiescent Current	I_{QC}		$T_J=25^\circ C$	-	4	6	mA
Quiescent Current Change	ΔI_{QC}	$V_I=11V \sim 23V$		-	-	1.5	mA
		$I_O=1mA \sim 40mA$		-	-	0.1	
Dropout Voltage	V_{DROP}		$T_J=25^\circ C$	-	1.7	-	V
Ripple Rejection	RR	$V_I=13V \sim 23V$, $f=120Hz$		37	46	-	dB

Electrical Characteristics

(Electrical Characteristics at $V_I=16V$, $I_O=40mA$, $C_I=0.33\mu F$, $C_O=0.1\mu F$, $0^\circ C \leq T_J \leq 125^\circ C$, Unless otherwise specified)

Parameter	Symbol	Test Condition*		S78L09F			Unit
				Min.	Typ.	Max.	
Output Voltage**	V_O		$T_J=25^\circ C$	8.60	9.00	9.40	V
		$I_O=1mA \sim 40mA$ $V_I=12V \sim 24V$		8.55	-	9.45	
		$I_O=1mA \sim 70mA$ $V_I=16V$		8.55	-	9.45	
Line Regulation	$\Delta V_{O(\Delta V_I)}$	$V_I=12V \sim 24V$	$T_J=25^\circ C$	-	45	175	mV
		$V_I=13V \sim 24V$		-	40	125	
Load Regulation	$\Delta V_{O(\Delta I_L)}$	$I_O=1mA \sim 100mA$	$T_J=25^\circ C$	-	19	90	mV
		$I_O=1mA \sim 40mA$		-	11	40	
Quiescent Current	I_{QC}		$T_J=25^\circ C$	-	4.1	6	mA
Quiescent Current Change	ΔI_{QC}	$V_I=13V \sim 24V$		-	-	1.5	mA
		$I_O=1mA \sim 40mA$		-	-	0.1	
Dropout Voltage	V_{DROP}		$T_J=25^\circ C$	-	1.7	-	V
Ripple Rejection	RR	$V_I=15V \sim 25V$, $f=120Hz$		38	45	-	dB

Electrical Characteristics

(Electrical Characteristics at $V_I=17V$, $I_O=40mA$, $C_I=0.33\mu F$, $C_O=0.1\mu F$, $0^\circ C \leq T_J \leq 125^\circ C$, Unless otherwise specified)

Parameter	Symbol	Test Condition*		S78L10F			Unit
				Min.	Typ.	Max.	
Output Voltage**	V_O		$T_J=25^\circ C$	9.6	10.0	10.4	V
		$I_O=1mA \sim 40mA$ $V_I=13V \sim 25V$		9.5	-	10.5	
		$I_O=1mA \sim 70mA$ $V_I=17V$		9.5	-	10.5	
Line Regulation	$\Delta V_{O(\Delta V_I)}$	$V_I=13V \sim 25V$	$T_J=25^\circ C$	-	51	175	mV
		$V_I=14V \sim 25V$		-	42	125	
Load Regulation	$\Delta V_{O(\Delta I_L)}$	$I_O=1mA \sim 100mA$	$T_J=25^\circ C$	-	20	90	mV
		$I_O=1mA \sim 40mA$		-	11	40	
Quiescent Current	I_{QC}		$T_J=25^\circ C$	-	4.2	6	mA
Quiescent Current Change	ΔI_{QC}	$V_I=14V \sim 25V$		-	-	1.5	mA
		$I_O=1mA \sim 40mA$		-	-	0.1	
Dropout Voltage	V_{DROP}		$T_J=25^\circ C$	-	1.7	-	V
Ripple Rejection	RR	$V_I=15V \sim 25V$, $f=120Hz$		37	44	-	dB

Electrical Characteristics

(Electrical Characteristics at $V_I=19V$, $I_O=40mA$, $C_I=0.33\mu F$, $C_O=0.1\mu F$, $0^\circ C \leq T_J \leq 125^\circ C$, Unless otherwise specified)

Parameter	Symbol	Test Condition*		S78L12F			Unit
				Min.	Typ.	Max.	
Output Voltage**	V_O		$T_J=25^\circ C$	11.5	12.0	12.5	V
		$I_O=1mA \sim 40mA$ $V_I=14V \sim 27V$		11.4	-	12.5	
		$I_O=1mA \sim 70mA$ $V_I=19V$		11.4	-	12.6	
Line Regulation	$\Delta V_{O(\Delta V_I)}$	$V_I=14.5V \sim 27V$	$T_J=25^\circ C$	-	55	250	mV
		$V_I=16V \sim 27V$		-	49	200	
Load Regulation	$\Delta V_{O(\Delta I_L)}$	$I_O=1mA \sim 100mA$	$T_J=25^\circ C$	-	22	100	mV
		$I_O=1mA \sim 40mA$		-	13	50	
Quiescent Current	I_{QC}		$T_J=25^\circ C$	-	4.3	6.5	mA
Quiescent Current Change	ΔI_{QC}	$V_I=16V \sim 27V$		-	-	1.5	mA
		$I_O=1mA \sim 40mA$		-	-	0.1	
Dropout Voltage	V_{DROP}		$T_J=25^\circ C$	-	1.7	-	V
Ripple Rejection	RR	$V_I=15V \sim 25V$, $f=120Hz$		37	42	-	dB

Electrical Characteristics

(Electrical Characteristics at $V_I=23V$, $I_O=40mA$, $C_I=0.33\mu F$, $C_O=0.1\mu F$, $0^\circ C \leq T_J \leq 125^\circ C$, Unless otherwise specified)

Parameter	Symbol	Test Condition*		S78L15F			Unit
				Min.	Typ.	Max.	
Output Voltage**	V_O		$T_J=25^\circ C$	14.40	15.0	15.60	V
		$I_O=1mA \sim 40mA$ $V_I=17.5V \sim 30V$		14.25	-	15.75	
		$I_O=1mA \sim 70mA$ $V_I=23V$		14.25	-	15.75	
Line Regulation	$\Delta V_{O(\Delta V_I)}$	$V_I=17.5V \sim 30V$	$T_J=25^\circ C$	-	65	300	mV
		$V_I=19V \sim 30V$		-	58	250	
Load Regulation	$\Delta V_{O(\Delta I_L)}$	$I_O=1mA \sim 100mA$	$T_J=25^\circ C$	-	25	150	mV
		$I_O=1mA \sim 40mA$		-	15	75	
Quiescent Current	I_{QC}		$T_J=25^\circ C$	-	4.6	6.5	mA
Quiescent Current Change	ΔI_{QC}	$V_I=19V \sim 30V$		-	-	1.5	mA
		$I_O=1mA \sim 40mA$		-	-	0.1	
Dropout Voltage	V_{DROP}		$T_J=25^\circ C$	-	1.7	-	V
Ripple Rejection	RR	$V_I=18.5V \sim 28.5V$, $f=120Hz$		34	39	-	dB

Electrical Characteristics

(Electrical Characteristics at $V_I=26V$, $I_O=40mA$, $C_I=0.33\mu F$, $C_O=0.1\mu F$, $0^\circ C \leq T_J \leq 125^\circ C$, Unless otherwise specified)

Parameter	Symbol	Test Condition*		S78L18F			Unit
				Min.	Typ.	Max.	
Output Voltage**	V_O		$T_J=25^\circ C$	17.3	18.0	18.7	V
		$I_O=1mA \sim 40mA$ $V_I=20.5V \sim 33V$		17.1	-	18.9	
		$I_O=1mA \sim 70mA$ $V_I=26V$		17.1	-	18.9	
Line Regulation	$\Delta V_{O(\Delta V_I)}$	$V_I=20.5V \sim 33V$	$T_J=25^\circ C$	-	70	360	mV
		$V_I=22V \sim 33V$		-	64	300	
Load Regulation	$\Delta V_{O(\Delta I_L)}$	$I_O=1mA \sim 100mA$	$T_J=25^\circ C$	-	27	180	mV
		$I_O=1mA \sim 40mA$		-	19	90	
Quiescent Current	I_{QC}		$T_J=25^\circ C$	-	4.7	6.5	mA
Quiescent Current Change	ΔI_{QC}	$V_I=22V \sim 33V$		-	-	1.5	mA
		$I_O=1mA \sim 40mA$		-	-	0.1	
Dropout Voltage	V_{DROP}		$T_J=25^\circ C$	-	1.7	-	V
Ripple Rejection	RR	$V_I=21.5V \sim 31.5V$, $f=120Hz$		32	36	-	dB

Electrical Characteristics

(Electrical Characteristics at $V_I=32V$, $I_O=40mA$, $C_I=0.33\mu F$, $C_O=0.1\mu F$, $0^\circ C \leq T_J \leq 125^\circ C$, Unless otherwise specified)

Parameter	Symbol	Test Condition*		S78L24F			Unit
				Min.	Typ.	Max.	
Output Voltage**	V_O		$T_J=25^\circ C$	23.0	24.0	25.0	V
		$I_O=1mA \sim 40mA$ $V_I=26.5V \sim 39V$		22.8	-	25.2	
		$I_O=1mA \sim 70mA$ $V_I=32V$		22.8	-	25.2	
Line Regulation	$\Delta V_{O(\Delta V_I)}$	$V_I=26.5V \sim 39V$	$T_J=25^\circ C$	-	95	480	mV
		$V_I=29V \sim 39V$		-	78	400	
Load Regulation	$\Delta V_{O(\Delta I_L)}$	$I_O=1mA \sim 100mA$	$T_J=25^\circ C$	-	41	240	mV
		$I_O=1mA \sim 40mA$		-	28	120	
Quiescent Current	I_{QC}		$T_J=25^\circ C$	-	4.8	6.5	mA
Quiescent Current Change	ΔI_{QC}	$V_I=28V \sim 39V$		-	-	1.5	mA
		$I_O=1mA \sim 40mA$		-	-	0.1	
Dropout Voltage	V_{DROP}		$T_J=25^\circ C$	-	1.7	-	V
Ripple Rejection	RR	$V_I=27.5V \sim 37.5V$, $f=120Hz$		30	33	-	dB

* Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible.

Thermal effects must be taken into account separately. All characteristics are measured with a $0.33\mu F$ capacitor across the input and a $0.1\mu F$ capacitor across the output.

** This specification applies only for dc power dissipation permitted by absolute maximum ratings.

Electrical Characteristics Curve

Fig.1 V_O vs. T_J




Fig.2 I_{QC} vs. T_J




Fig.3 V_O vs. I_O




Fig.4 V_O vs. V_I




Fig.5 I_{QC} vs. V_I





Fig.6 P_D vs. T_a



⌋ The AUK Corp. products are intended for the use as components in general electronic
⌋ equipment (Office and communication equipment, measuring equipment, home
⌋ appliance, etc.). ⌋

⌋ Please make sure that you consult with us before you use these AUK Corp. products
⌋ in equipments which require high quality and / or reliability, and in equipments which
⌋ could have major impact to the welfare of human life(atomic energy control, airplane,
⌋ spaceship, transportation, combustion control, all types of safety device, etc.). AUK
⌋ Corp. cannot accept liability to any damage which may occur in case these AUK Corp.
⌋ products were used in the mentioned equipments without prior consultation with AUK
⌋ Corp..⌋

⌋ Specifications mentioned in this publication are subject to change without notice.⌋



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.