

# AC/DC Current Measurement Systems

## TCPA300, TCP312A, TCP305A, TCP303, TCPA400, TCP404XL Datasheet



The TCP300 and TCP400 Series AC/DC current measurement family is a highly advanced current measurement system for today's current measurement needs. When connected to Tektronix oscilloscopes with TEKPROBE Level II, TekConnect (w/ TCA-BNC), or TekVPI (w/ TPA-BNC) interfaces, current measurements and calculations are simple and easy.

### Key performance specifications

- DC - 100 MHz, Current Probe Amplifier (TCPA300) uses:
    - DC - 100 MHz, 30 A DC (TCP312A)
    - DC - 50 MHz, 50 A DC (TCP305A)
    - DC - 15 MHz, 150 A DC (TCP303)
  - DC - 50 MHz, Current Probe Amplifier (TCPA400) Uses:
    - DC - 2 MHz, 750 A DC<sup>1</sup> (TCP404XL) (500 A DC Continuous)
- <sup>1</sup>Derated with duty cycle

### Key features

- Automatic scaling and units<sup>2</sup> - Oscilloscope on-screen readout of magnitude and amps reduces measurement errors with no more hand calculations
- AC/DC input coupling
- Low insertion impedance reduces device under test loading
- Split-core construction allows easy circuit connection
- Status indicators provide visual operating status and notification of potential error conditions - degauss, probe open, overload, not terminated into 50  $\Omega$ , noncompatible probe type

- Low DC drift and noise allows improved low-level current measurements
- 3rd party safety certification

<sup>2</sup> Requires a TDS TEKSCOPE oscilloscope or a TekConnect oscilloscope with TCA-BNC adapter

### Applications

- Development and analysis solutions for designers, installers, and service personnel in telecom, data comm, computer, and semiconductor power electronics environments for:
  - Power supplies (switching and linear)
  - Semiconductor devices (SCRs, IGBTs, MOSFETs, CMOS, BJTs)
  - Power inverters/converters
  - Electronic ballasts
  - Industrial/consumer electronics
  - Mobile communications (phone, satellite, relay stations)
  - Motor drives
- Transportation systems (electronic vehicles, electric trains, locomotives, avionics)

### Meets today's AC/DC current measurement applications

The TCPA300 amplifier, when used with TCP312A, TCP305A, or TCP303 probes, provides a wide range of current measurement capability and spans the gap between low-level milliamp measurements to very high current levels. These three probes provide current measurement capabilities of 30 A, 50 A, and 150 A DC continuous. For even higher current levels, the TCPA400 amplifier with the TCP404XL current probe measures 500 A DC continuous and 750 A DC continuous, derated with duty cycle.

Higher-frequency performance is available with the TCP312A w/TCPA300 providing  $\geq 100$  MHz bandwidth and a maximum current of 30 A DC.

## Measurement errors and manual calculations are now a thing of the past

With this new series of current measurement tools, automatic control and on-screen scaling and units is provided for users of Tektronix TDS3000, TDS500, TDS600, TDS700, TDS5000, TDS6000, and TDS7000B series oscilloscope systems (the DPO3000, MDO/MSO/DPO4000, MSO/DPO5000, and DPO7000 series oscilloscopes, the TPA-BNC adapter is required).

The TCP300/TCP400 current measurement systems seamlessly integrate with your TDS series oscilloscope.

Even non-TEKPROBE systems can use the TCPA300/400 series to make proper current measurements by simply multiplying the measured output voltage on the oscilloscope by the TCPA300/400 series range setting.

## Specifications

All specifications apply to all models unless noted otherwise.

### Model overview

	TCP312A w/ TCPA300	TCP305A w/ TCPA300	TCP303 w/ TCPA300	TCP404XL w/ TCPA400
Bandwidth	DC – 100 MHz	DC – 50 MHz	DC – 15 MHz	DC – 2 MHz
Rise time	≤3.5 ns	≤7 ns	≤23 ns	≤175 ns
DC accuracy	±3% of reading	±3% of reading	±3% of reading	±3% of reading
DC accuracy, typical	±1% of reading	±1% of reading	±1% of reading	±1% of reading
Lowest measurable current (at ±3% accuracy at DC) Scope set to 1 mV/div and 20 MHz BW limited	1 mA	5 mA	5 mA	1 A
Maximum Amp-Second product, typical (Based on amplifier range setting)	50 A*μS – 1 A/V 500 A*μS – 10 A/V	500 A*μS – 5 A/V NA – 10 A/V	3,000 A*μS – 5 A/V 15,000 A*μS – 50 A/V	NA – 1 A/mV
Maximum wire voltage, bare insulated	150 V CAT II 300 V CAT II	150 V CAT II 300 V CAT II	600 V CAT I & II 300 V CAT III	600 V CAT I & II 300 V CAT III
AC-coupling low-frequency Bandwidth, typical (Low pass – 3 dB point)	<7 Hz	<7 Hz	<7 Hz	<7 Hz
Displayed RMS noise, typical (at 20 MHz bandwidth limit)	≤250 μA <sub>RMS</sub>	≤1.25 mA <sub>RMS</sub>	≤2.5 mA <sub>RMS</sub>	≤250 mA <sub>RMS</sub>
Signal delay (to output BNC)	17 ns	19 ns	40 ns	80 ns
Insertion impedance	0.11 Ω at 1 MHz 0.12 Ω at 10 MHz 0.35 Ω at 50 MHz 0.7 Ω at 100 MHz	0.02 Ω at 1 MHz 0.1 Ω at 10 MHz 0.35 Ω at 50 MHz	0.01 Ω at 1 MHz 0.025 Ω at 5 MHz 0.1 Ω at 15 MHz	0.1 m Ω at 10 kHz 0.6 m Ω at 100 kHz 8 m Ω at 1 MHz 16 m Ω at 2 MHz

## Characteristics

### Maximum current ratings

#### High-current sensitivity

	TCP312A w/ TCPA300	TCP305A w/ TCPA300	TCP303 w/ TCPA300	TCP404XL w/ TCPA400
Range	10 A/V	10 A/V	50 A/V	1 A/mV
DC (continuous)	30 A	50 A	150 A	500 A (750 A)
RMS (sinusoidal)	21.2 A	35.4 A	150 A	500 A
Peak	50 A	50 A	500 A	750 A

#### Low-current sensitivity

Range	1 A/V	5 A/V	5 A/V	N/A
DC (continuous)	5 A	25 A	25 A	N/A
RMS (sinusoidal)	3.5 A	17.7 A	17.7 A	N/A
Peak	50 A	50 A	500 A	N/A

## Physical characteristics

### Amplifiers

TCPA300/TCPA400	
Length	17.3 cm (6.8 in)
Width	16.7 cm (6.6 in)
Height	9.14 cm (3.6 in)
Weight	1.14 kg (2.5 lb)

### Probes

	TCP305A/TCP312A	TCP303	TCP404XL
Length	20 cm (7.77 in)	26.8 cm (10.55 in)	26.8 cm (10.55 in)
Width	6 cm (0.625 in)	4.1 cm (1.60 in)	4.1 cm (1.60 in)
Height	3.2 cm (1.25 in)	15.6 cm (6.13 in)	15.6 cm (6.13 in)
Weight	0.15 kg (0.33 lb)	0.66 kg (1.45 lb)	0.88 kg (1.90 lb)

### Maximum conductor size

TCP312A	TCP305A	TCP303	TCP404XL
5.0 mm (0.15 in)	5.0 mm (0.15 in)	21 mm x 25 mm (0.83 x 1.0 in)	21 mm x 25 mm (0.83 x 1.0 in)

### Cable length

1.5 m (60 in)	1.5 m (60 in)	2 m (78.7 in)	8 m (315 in)
---------------	---------------	---------------	--------------

## EMC environment and safety

### U.S. NRTL listing

TCP312A/305A probe and amplifier	Amplifiers	TCP303/404XL probe and amplifier
UL61010-2-032, UL61010-1	UL3111-1, first edition	UL3111-2-032, UL3111-2-031; UL3111-1

### Canadian certification

CAN/CSA C22.2 No. 61010-1, CAN/CSA C22.2 No. 61010-2-032	CAN/CSA C22.2 No. 1010.1-92	CAN/CSA C22.2 No. 1010.1-92
--	-----------------------------	-----------------------------

### European Union compliance

EN61010-1, EN61010-2-032	EN61010-1:2001	EN61010-1/A2, EN61010-2-031, EN61010-2-032
--------------------------	----------------	--

### Other

	IEC61010-1/A2	IEC61010-2-032
--	---------------	----------------

### Electromagnetic compatibility

	EC Council Directive 89/336/EEC, FCC Part 15, Subpart B Class A, AS/NZS 2064.1/2.	
--	---	--

## Datasheet

### Temperature

Operating	0 °C to +50 °C (32 °F to 122 °F)
Nonoperating	-40 °C to +75 °C (-40 °F to 167 °F)

### Humidity

Operating	5% to 95% R.H. to +30 °C (86 °F) 5% to 85% R.H. +30 °C to +50 °C (86 °F to 122 °F)
Nonoperating	5% to 95% R.H. to +30 °C (86 °F) 5% to 85% R.H. +30 °C to +75 °C (86 °F to 167 °F)

### Altitude

Operating	2000 m (6800 ft.) maximum
Nonoperating	12,192 m (40,000 ft.) maximum

## Ordering information

### Models

#### Probes

<b>TCP312A Probe</b>	AC/DC current, DC to 100 MHz; 30 A DC (Requires TCPA300 amplifier)
<b>TCP305A Probe</b>	AC/DC current, DC to 50 MHz; 50 A DC (Requires TCPA300 amplifier)
<b>TCP303 Probe</b>	AC/DC current, DC to 15 MHz; 150 A DC (Requires TCPA300 amplifier)
<b>TCP404XL Probe</b>	AC/DC current, DC to 2 MHz; 500 A DC (750 A DC derated with duty cycle) (Requires TCPA400 amplifier)

#### Amplifiers

<b>TCPA300 Amplifier</b>	AC/DC current probe, DC to 100 MHz, (Requires TCP305A or TCP312A or TCP303 probes)
<b>TCPA400 Amplifier</b>	AC/DC current probe, DC to 50 MHz, (Requires TCP404XL probe)

### Recommended accessories

<b>Cover, large probe protective; (for TCP303, TCP404XL)</b>	016-1924-00
<b>Case, transit; current measurement systems</b>	016-1922-00
<b>50 <math>\Omega</math> feedthrough termination</b>	011-0049-02
<b>50 <math>\Omega</math> BNC-to-BNC coaxial cable</b>	012-0117-00
<b>TEKPROBE interface cable, TCPA300 or TCPA400 amplifier to TDS series oscilloscopes</b>	012-1605-00
<b>Current loop, 1 turn, 50 <math>\Omega</math>, BNC connector (for TCP305A, TCP312A, TCP202A)</b>	067-2396-00
<b>Current loop, 1 turn, 50 <math>\Omega</math>, BNC connector (for TCP303, TCP404XL)</b>	015-0601-50

TCPA300/TCPA400 amplifier  
calibration adapter 174-4765-00

Power measurements deskew  
fixture for TCP202A, TCP305A,  
TCP312A, TCP303 probes 067-1478-00

## Warranty

One year parts and labor.

## Power requirements

**Amplifiers** 90 V to 264 V, 47 to 440 Hz, 50 W; Maximum CAT II (auto switch)

**Probes** TCP312A, TCP305A, TCP303 probes require a TCPA300 Amplifier; TCP404XL probe requires a TCPA400 Amplifier

## Options

### Power plug options

**Opt. A0** North America power plug (115 V, 60 Hz)

**Opt. A1** Universal Euro power plug (220 V, 50 Hz)

**Opt. A2** United Kingdom power plug (240 V, 50 Hz)

**Opt. A3** Australia power plug (240 V, 50 Hz)

**Opt. A5** Switzerland power plug (220 V, 50 Hz)

**Opt. A6** Japan power plug (100 V, 110/120 V, 60 Hz)

**Opt. A10** China power plug (50 Hz)

**Opt. A11** India power plug (50 Hz)

**Opt. A12** Brazil power plug (60 Hz)

**Opt. A99** No power cord

### ServiceOptions

**Opt. C3** Calibration Service 3 Years

**Opt. C5** Calibration Service 5 Years

**Opt. D1** Calibration Data Report

**Opt. D3** Calibration Data Report 3 Years (with Opt. C3)

**Opt. D5** Calibration Data Report 5 Years (with Opt. C5)

**Opt. R3** Repair Service 3 Years (including warranty)

**Opt. R3DW** Repair Service Coverage 3 Years (includes product warranty period). 3-year period starts at time of instrument purchase

**Opt. R5** Repair Service 5 Years (including warranty)

**Opt. R5DW** Repair Service Coverage 5 Years (includes product warranty period). 5-year period starts at time of instrument purchase

**Opt. SILV400** Standard warranty extended to 5 years (TCP305A, TCP312A, TCPA300, TCPA400)

**Opt. SILV600** Standard warranty extended to 5 years (TCP303, TCP404XL)

# Datasheet



Tektronix is registered to ISO 9001 and ISO 14001 by SRI Quality System Registrar.

**ASEAN / Australasia** (65) 6356 3900  
**Belgium** 00800 2255 4835\*  
**Central East Europe and the Baltics** +41 52 675 3777  
**Finland** +41 52 675 3777  
**Hong Kong** 400 820 5835  
**Japan** 81 (3) 6714 3010  
**Middle East, Asia, and North Africa** +41 52 675 3777  
**People's Republic of China** 400 820 5835  
**Republic of Korea** 001 800 8255 2835  
**Spain** 00800 2255 4835\*  
**Taiwan** 886 (2) 2722 9622

**Austria** 00800 2255 4835\*  
**Brazil** +55 (11) 3759 7627  
**Central Europe & Greece** +41 52 675 3777  
**France** 00800 2255 4835\*  
**India** 000 800 650 1835  
**Luxembourg** +41 52 675 3777  
**The Netherlands** 00800 2255 4835\*  
**Poland** +41 52 675 3777  
**Russia & CIS** +7 (495) 6647564  
**Sweden** 00800 2255 4835\*  
**United Kingdom & Ireland** 00800 2255 4835\*

**Balkans, Israel, South Africa and other ISE Countries** +41 52 675 3777  
**Canada** 1 800 833 9200  
**Denmark** +45 80 88 1401  
**Germany** 00800 2255 4835\*  
**Italy** 00800 2255 4835\*  
**Mexico, Central/South America & Caribbean** 52 (55) 56 04 50 90  
**Norway** 800 16098  
**Portugal** 80 08 12370  
**South Africa** +41 52 675 3777  
**Switzerland** 00800 2255 4835\*  
**USA** 1 800 833 9200

\* European toll-free number. If not accessible, call: +41 52 675 3777

Updated 10 April 2013

**For Further Information.** Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit [www.tektronix.com](http://www.tektronix.com).

Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.



12 Apr 2013

60W-16458-7

[www.tektronix.com](http://www.tektronix.com)

**Tektronix**<sup>®</sup>





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.