
E-Series Surface Mount Mixer
80 – 2500 MHz

Features


- LO Power +17 dBm
- Up to +14 dBm RF
- Surface Mount




Description

M/A-COM's ESMD-C50H is a Low Cost, Passive Double Double Balanced Mixer. Constructed using very broad band ferrite balun transformers and matched silicon schottky diodes, it's performance is especially suited to high dynamic range receivers. Given it's high 1dB compression point, the ESMD-C50H is also suitable for Transmitter upconversion at any frequency up to 2.5GHz.

Schematic



SM-2 Package



Part Number	Packaging
ESMD-C50H	Tube
ESMD-C50HTR	Tape and Reel

Electrical Specifications @ +25°C

Parameter		Units	Minimum	Typical	Maximum	Mean (x)	Sigma (σ)
Frequency Range	80 - 2500 MHz	—	—	—	—	—	—
IF 1.0 dB Bandwidth = DC - 1000 MHz		—	—	—	—	—	—
Conversion Loss	80 - 1000 MHz	dB	—	—	7.5	6.10	0.15
	1000 - 2500 MHz	dB	—	—	9.0	7.34	0.29
L - R Isolation	80 - 1000 MHz	dB	25.0	33.5	—	—	—
	1000 - 2500 MHz	dB	20.0	28.9	—	—	—
L - I Isolation	80 - 1000 MHz	dB	26.0	31.5	—	—	—
	1000 - 2500 MHz	dB	13.5	17.4	—	—	—
R - I Isolation	80 - 1000 MHz	dB	20.0	26.9	—	—	—
	1000 - 2500 MHz	dB	20.0	25.9	—	—	—
LO VSWR	80 - 1000 MHz	—	—	1.42	2.0	—	—
	1000 - 2500 MHz	—	—	1.63	2.5	—	—
RF VSWR	80 - 1000 MHz	—	—	1.72	2.8	—	—
	1000 - 2500 MHz	—	—	1.71	2.4	—	—
IF VSWR	DC - 600 MHz	—	—	2.55	3.2	—	—
Input IP3	200 - 1000 MHz	dBm	21.0	27.0	—	—	—
	1000 - 2500 MHz	dBm	18.0	25.0	—	—	—
Input 1dB Compression		dBm	—	+14.0	—	—	—

Test Conditions: LO Drive = +17dBm, IF frequency = 70MHz. Mean and Sigma calculated at 900MHz & 1800MHz.

ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.
PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

• **North America** Tel: 800.366.2266 • **Europe** Tel: +353.21.244.6400
• **India** Tel: +91.80.4155721 • **China** Tel: +86.21.2407.1588
Visit www.macomtech.com for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make

Absolute Maximum Ratings


Parameter	Absolute Maximum
RF Input Power	+23dBm
LO Drive Power	+23 dBm
Operating/Storage Temperature	-40°C to +85°C

Pin Configuration


Function	Pin No.
RF	1
LO	2
IF	3
Ground	4,5,6

Typical Performance @ +25°C


Conversion Loss




Isolation




VSWR



IP3 and 1dB Compression



IF Bandwidth



Note: Conversion Loss measured with fixed IF frequency of 70MHz.
All measurements made with input power of +17dBm.

ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.
PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

• **North America** Tel: 800.366.2266 • **Europe** Tel: +353.21.244.6400
• **India** Tel: +91.80.4155721 • **China** Tel: +86.21.2407.1588
Visit www.macomtech.com for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make

Spurious Table: 1800MHz

(In dBc below IF, assuming down conversion)

		$nf_{LO} - mf_{RF}$				
	0	X	-6	12	21	13
	1	29	0	35	18	42
RF	2	64	58	58	51	72
(n)	3	76	80	78	76	73
	4	83	85	85	82	85.34
		0	1	2	3	4
		LO (m)				

RF = 1842.50 MHz, -5dBm
LO = 1772.50 MHz, +17dBm
IF = 70 MHz

Spurious Table: 900MHz

(In dBc below IF, assuming down conversion)

		$nf_{LO} - mf_{RF}$				
	0	X	2	14	12	29
	1	20	0	37	12	39
RF	2	25	26	38	27	32
(n)	3	46	41	44	43	44
	4	57	56	54	55	57
		0	1	2	3	4
		LO (m)				

RF = 970 MHz, -5dBm
LO = 900 MHz, +17dBm
IF = 70 MHz

Spurious Table: 1900MHz

(In dBc below IF, assuming down conversion)

		$nf_{LO} - mf_{RF}$				
	0	X	-8	21	16	19
	1	24	0	39	17	50
RF	2	29	32	29	22	31
(n)	3	51	46	51	41	50
	4	52	55	55	52	55
		0	1	2	3	4
		LO (m)				

RF = 1960 MHz, -5dBm
LO = 1890 MHz, +17dBm
IF = 70 MHz

ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.
PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

• **North America** Tel: 800.366.2266 • **Europe** Tel: +353.21.244.6400
• **India** Tel: +91.80.4155721 • **China** Tel: +86.21.2407.1588
Visit www.macomtech.com for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.