

1		2		3		4		5		6		7																																									
E											SIGN		DATE		DESCRIPTION		APPROVER																																				
											△		10/20'08		Add APPROVAL: : CQC		Kind																																				
											△		12/05'12		Change the screw plating specification		Jacky																																				
											△		12/05'12		Change the dimensional tolerance		Jacky																																				
											△		12/12'13		Add the view		Jacky																																				
											△		12/12'13		Change the withstand voltage and current		Jacky																																				
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!																																																					
D											MATERIALS ELECTRICAL				cULus		CQC																																				
											RATED VOLTAGE & CURRENT:				250 V, 10 A				/ 250 V, 9A△5																																		
											WITHSTAND VOLTAGE:				AC 2000 V/Min																																						
											INSULATION RESISTANCE:				1000 MΩOR MORE AT DC 500 V																																						
											OPERATING TEMPERATURE RANG:				-40 °C ~ +115 °C																																						
											SCREW TORQUE VALUE:				5.3 Lb-In.																																						
											WIRE RANGE:				22 - 18 AWG																																						
											1) MOLDED PARTS:				Thermoplastic, UL 94 V-0 BLACK																																						
											2) TERMINAL:				BRASS, 0.8t, Tin PLATED																																						
											△ 3) TERMINAL SCREWS:				STEEL, M3																																						
C											△ APPROVAL: cULus CQC																																										
											PART NO.:																																										
											Critical dimension:▽																																										
B											YK 223 xx 0 x x 00G																																										
											NO. OF POLES																																										
											02: 2 POLES																																										
											03: 3 POLES																																										
											04: 4 POLES																																										
											...																																										
											30: 30 POLES																																										
											G: RoHS compliant (lead<4%) In copper Alloy																																										
											MARK																																										
											0: "@" MARK																																										
A	N = Number of poles△ Dim A=Nx6.35+1.0 Dim B=(N-1)x6.35 <table><tr><td>Poles</td><td>Tol.</td><td>Dim A&B</td></tr><tr><td>2-5p</td><td>±0.20</td><td></td></tr><tr><td>6-10p</td><td>±0.25</td><td></td></tr><tr><td>11-16p</td><td>±0.35</td><td></td></tr><tr><td>17-24p</td><td>±0.40</td><td></td></tr><tr><td>25-30p</td><td>±0.50</td><td></td></tr></table>										Poles	Tol.	Dim A&B	2-5p	±0.20		6-10p	±0.25		11-16p	±0.35		17-24p	±0.40		25-30p	±0.50		0: "ANY" MARK																								
											Poles	Tol.	Dim A&B																																								
											2-5p	±0.20																																									
											6-10p	±0.25																																									
11-16p	±0.35																																																				
17-24p	±0.40																																																				
25-30p	±0.50																																																				
TERMINAL & SCREW PLATED																																																					
0: TERMINAL & SCREW: G/F																																																					
△ 1: TERMINAL: G/F, SCREW: Zinc																																																					
2: TERMINAL: Sn, SCREW: G/F																																																					
△ 3: TERMINAL: Sn, SCREW: Zinc																																																					
<table><tr><td colspan="4">TITLE</td><td colspan="4">YK-223 Series</td></tr><tr><td colspan="4">PART NO.</td><td colspan="2">YK223xx0xx00G</td><td colspan="2">DWG NO.</td><td colspan="2">8YK0001-223</td></tr><tr><td colspan="2">APPROVED</td><td colspan="2">CHECKED</td><td colspan="2">DESIGNED</td><td colspan="2">DRAWN</td><td colspan="2">CUST NO.</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2">Jacky 2013.12.12</td><td colspan="2">Jacky 2013.12.12</td><td colspan="2"></td></tr></table>										TITLE				YK-223 Series				PART NO.				YK223xx0xx00G		DWG NO.		8YK0001-223		APPROVED		CHECKED		DESIGNED		DRAWN		CUST NO.						Jacky 2013.12.12		Jacky 2013.12.12				CUSTOMER COPY					
										TITLE				YK-223 Series																																							
										PART NO.				YK223xx0xx00G		DWG NO.		8YK0001-223																																			
										APPROVED		CHECKED		DESIGNED		DRAWN		CUST NO.																																			
				Jacky 2013.12.12		Jacky 2013.12.12																																															
										ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD																																											
										UNIT: mm				X. ±0.50																																							
										SCALE: NONE				X.X ±0.30																																							
										SHEET: 01/01				REV.: F																																							



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.