

1		2		3		4		5		6		7																								
E											SIGN		DATE		DESCRIPTION		APPROVER																			
											△		10/20'08		Add APPROVAL: : CQC		Kind																			
											△		12/05'12		Change the screw plating specification		Jacky																			
											△		12/05'12		Change the dimensional tolerance		Jacky																			
											△		12/12'13		Add the view		Jacky																			
											△		12/12'13		Change the withstand voltage and current		Jacky																			
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!																																				
D											MATERIALS ELECTRICAL				cULus				CQC																	
											RATED VOLTAGE & CURRENT:				250 V, 10 A				/ 250 V, 9A△5																	
											WITHSTAND VOLTAGE:				AC 2000 V/Min																					
											INSULATION RESISTANCE:				1000 MΩOR MORE AT DC 500 V																					
											OPERATING TEMPERATURE RANG:				-40 °C ~ +115 °C																					
											SCREW TORQUE VALUE:				5.3 Lb-In.																					
											WIRE RANGE:				22 - 18 AWG																					
											1) MOLDED PARTS:				Thermoplastic, UL 94 V-0 BLACK																					
											2) TERMINAL:				BRASS, 0.8t, Tin PLATED																					
											△ 3) TERMINAL SCREWS:				STEEL, M3																					
C											△ APPROVAL: cULus CQC																									
											PART NO.:																									
											Critical dimension:▽																									
B											YK 223xx0xx00G																									
											NO. OF POLES								G: RoHS compliant (lead<4%) In copper Alloy																	
											02: 2 POLES								MARK																	
											03: 3 POLES								0: "@" MARK																	
											04: 4 POLES								1: "ANY" MARK																	
											...								TERMINAL & SCREW PLATED																	
											30: 30 POLES								0: TERMINAL & SCREW: G/F																	
																			△ 1: TERMINAL: G/F, SCREW: Zinc																	
																			2: TERMINAL: Sn, SCREW: G/F																	
																			△ 3: TERMINAL: Sn, SCREW: Zinc																	
A	N = Number of poles△ Dim A=Nx6.35+1.0 Dim B=(N-1)x6.35 <table><tr><td>Poles</td><td>Tol.</td><td>Dim A&B</td></tr><tr><td>2-5p</td><td>±0.20</td><td></td></tr><tr><td>6-10p</td><td>±0.25</td><td></td></tr><tr><td>11-16p</td><td>±0.35</td><td></td></tr><tr><td>17-24p</td><td>±0.40</td><td></td></tr><tr><td>25-30p</td><td>±0.50</td><td></td></tr></table>										Poles	Tol.	Dim A&B	2-5p	±0.20		6-10p	±0.25		11-16p	±0.35		17-24p	±0.40		25-30p	±0.50		ANYTEK				CUSTOMER COPY			
											Poles	Tol.	Dim A&B																							
											2-5p	±0.20																								
											6-10p	±0.25																								
11-16p	±0.35																																			
17-24p	±0.40																																			
25-30p	±0.50																																			
TITLE				YK-223 Series				ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD																												
PART NO.		YK223xx0xx00G		DWG NO.		8YK0001-223																														
APPROVED		CHECKED		DESIGNED		DRAWN		CUST NO.		Tolerance																										
				Jacky		Jacky				X. ±0.50																										
				2013.12.12		2013.12.12				X.X ±0.30																										
								SHEET: 01/01		X.XX ±0.10																										
								REV.: F		X° ±1°																										
1		2		3		4		5		6		7																								



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.