

4		3		2		1																																																																																													
THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION		LOC		DIST		REVISIONS																																																																																											
© COPYRIGHT - By -		ALL RIGHTS RESERVED.		G		14		P	LTR	DESCRIPTION	DATE	DWN	APVD																																																																																						
									H1	REVISED PER ECO-11-005027	12MAR11	RK	HMR																																																																																						
1 1.606 MAX AMP 16-14* INSULATION BODY AMP WIRE RANGE 16-14 AWG STRANDED 1 STAMP AMP 16-14* APPROX AS SHOWN 2 WIRE INSULATION .190 MAX DIA. <table><tr><td colspan="2">2500</td><td colspan="2">ON TAPE, REEL</td><td colspan="2">2-55825-1</td></tr><tr><td colspan="2">50</td><td colspan="2">LOOSE PIECE</td><td colspan="2">8-55825-2</td></tr><tr><td colspan="2">1000</td><td colspan="2">LOOSE PIECE</td><td colspan="2">55825-1</td></tr><tr><td colspan="2">QTY</td><td colspan="2">PACKAGE TYPE</td><td colspan="2">PART NO</td></tr></table> <table><tr><td colspan="2">AMP INCORPORATED CUSTOMER SERVICE SYSTEMS</td><td colspan="2">MAX RECOMMENDED OPERATING TEMPERATURE: 125° C MAX</td><td colspan="2">THIS DRAWING IS A CONTROLLED DOCUMENT.</td></tr><tr><td colspan="2">FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS</td><td colspan="2">PRODUCT INFORMATION CENTER 1-800-522-6752</td><td colspan="2">DIMENSIONS: INCHES</td></tr><tr><td colspan="2">FOR APPLICATION TOOLING INFORMATION</td><td colspan="2">TOOLING ASSISTANCE CENTER 1-800-722-1111</td><td colspan="2">TOLERANCES UNLESS OTHERWISE SPECIFIED:</td></tr><tr><td colspan="2">FOR ORDER ENTRY</td><td colspan="2">1-800-526-5142</td><td colspan="2">FINISH</td></tr><tr><td colspan="2"></td><td colspan="2">THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.</td><td colspan="2">EDP TIN PLATED</td></tr></table> <table><tr><td colspan="2">DWN S S GOULDEN 6/93</td><td colspan="2" rowspan="4"> STE TE Connectivity SPLICE, SEALABLE HEAT SHRINKABLE </td></tr><tr><td colspan="2">CHK R HERSEY 6/93</td></tr><tr><td colspan="2">APVD B BARE 6/93</td></tr><tr><td colspan="2">PRODUCT SPEC - APPLICATION SPEC 408-4022</td></tr><tr><td colspan="2">WEIGHT -</td><td colspan="2">SIZE A3</td><td colspan="2">CAGE CODE 00779</td><td colspan="2">DRAWING NO C-55825</td><td colspan="2">RESTRICTED TO -</td></tr><tr><td colspan="6">CUSTOMER DRAWING</td><td colspan="2">SCALE NTS</td><td colspan="2">SHEET 1 OF 1</td><td colspan="2">REV H1</td></tr></table>														2500		ON TAPE, REEL		2-55825-1		50		LOOSE PIECE		8-55825-2		1000		LOOSE PIECE		55825-1		QTY		PACKAGE TYPE		PART NO		AMP INCORPORATED CUSTOMER SERVICE SYSTEMS		MAX RECOMMENDED OPERATING TEMPERATURE: 125° C MAX		THIS DRAWING IS A CONTROLLED DOCUMENT.		FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS		PRODUCT INFORMATION CENTER 1-800-522-6752		DIMENSIONS: INCHES		FOR APPLICATION TOOLING INFORMATION		TOOLING ASSISTANCE CENTER 1-800-722-1111		TOLERANCES UNLESS OTHERWISE SPECIFIED:		FOR ORDER ENTRY		1-800-526-5142		FINISH				THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.		EDP TIN PLATED		DWN S S GOULDEN 6/93		STE TE Connectivity SPLICE, SEALABLE HEAT SHRINKABLE		CHK R HERSEY 6/93		APVD B BARE 6/93		PRODUCT SPEC - APPLICATION SPEC 408-4022		WEIGHT -		SIZE A3		CAGE CODE 00779		DRAWING NO C-55825		RESTRICTED TO -		CUSTOMER DRAWING						SCALE NTS		SHEET 1 OF 1		REV H1	
2500		ON TAPE, REEL		2-55825-1																																																																																															
50		LOOSE PIECE		8-55825-2																																																																																															
1000		LOOSE PIECE		55825-1																																																																																															
QTY		PACKAGE TYPE		PART NO																																																																																															
AMP INCORPORATED CUSTOMER SERVICE SYSTEMS		MAX RECOMMENDED OPERATING TEMPERATURE: 125° C MAX		THIS DRAWING IS A CONTROLLED DOCUMENT.																																																																																															
FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS		PRODUCT INFORMATION CENTER 1-800-522-6752		DIMENSIONS: INCHES																																																																																															
FOR APPLICATION TOOLING INFORMATION		TOOLING ASSISTANCE CENTER 1-800-722-1111		TOLERANCES UNLESS OTHERWISE SPECIFIED:																																																																																															
FOR ORDER ENTRY		1-800-526-5142		FINISH																																																																																															
		THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.		EDP TIN PLATED																																																																																															
DWN S S GOULDEN 6/93		STE TE Connectivity SPLICE, SEALABLE HEAT SHRINKABLE																																																																																																	
CHK R HERSEY 6/93																																																																																																			
APVD B BARE 6/93																																																																																																			
PRODUCT SPEC - APPLICATION SPEC 408-4022																																																																																																			
WEIGHT -		SIZE A3		CAGE CODE 00779		DRAWING NO C-55825		RESTRICTED TO -																																																																																											
CUSTOMER DRAWING						SCALE NTS		SHEET 1 OF 1		REV H1																																																																																									



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.