




Shielded Power Inductors – LPS4012



- Very low DCR; excellent current handling
- 4.0 × 4.0 mm footprint; less than 1.2 mm tall

Core material Ferrite

Core and winding loss See www.coilcraft.com/coreloss

Terminations RoHS compliant silver-palladium-platinum-glass frit. Other terminations available at additional cost.

Weight 54 – 64 mg

Ambient temperature –40°C to +85°C with Irms current, +85°C to +125°C with derated current

Storage temperature Component: –40°C to +125°C.

Tape and reel packaging: –40°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Failures in Time (FIT) / Mean Time Between Failures (MTBF)

38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332

Packaging 1000/7" reel; 3500/13" reel Plastic tape: 12 mm wide, 0.25 mm thick, 8 mm pocket spacing, 1.32 mm pocket depth

Recommended pick and place nozzle OD: 4 mm; ID: ≤ 2 mm

PCB washing Only pure water or alcohol recommended

Part number ¹	Inductance ² (µH)	DCR max ³ (Ohms)	SRF typ ⁴ (MHz)	Isat (A) ⁵			Irms (A) ⁶	
				10% drop	20% drop	30% drop	20°C rise	40°C rise
LPS4012-331ML	0.33±20%	0.025	375	5.2	5.4	5.5	2.2	3.0
LPS4012-681ML	0.68±20%	0.055	220	3.5	3.6	3.7	1.8	2.4
LPS4012-102NL	1.0±30%	0.060	180	2.8	2.9	3.0	1.7	2.4
LPS4012-152ML	1.5±20%	0.070	140	2.6	2.7	2.8	1.6	2.2
LPS4012-222ML	2.2±20%	0.100	115	2.3	2.4	2.5	1.2	1.75
LPS4012-332ML	3.3±20%	0.100	100	1.3	1.4	1.4	1.45	2.00
LPS4012-472ML	4.7±20%	0.175	70	1.6	1.7	1.8	1.10	1.45
LPS4012-562ML	5.6±20%	0.260	60	1.5	1.6	1.6	0.85	1.10
LPS4012-682ML	6.8±20%	0.340	55	1.3	1.3	1.4	0.80	0.98
LPS4012-103ML	10±20%	0.350	40	0.98	1.0	1.1	0.55	0.75
LPS4012-153ML	15±20%	0.550	30	0.79	0.82	0.84	0.53	0.73
LPS4012-223ML	22±20%	0.600	25	0.74	0.78	0.79	0.52	0.70
LPS4012-333ML	33±20%	0.825	22	0.45	0.47	0.48	0.46	0.61
LPS4012-473ML	47±20%	1.40	19	0.35	0.37	0.38	0.40	0.52
LPS4012-683ML	68±20%	1.70	15	0.30	0.32	0.33	0.35	0.46
LPS4012-104ML	100±20%	2.40	12	0.24	0.26	0.27	0.30	0.40
LPS4012-124ML	120±20%	3.30	11.5	0.23	0.24	0.25	0.27	0.36
LPS4012-154ML	150±20%	3.50	10.0	0.21	0.22	0.23	0.25	0.32
LPS4012-184ML	180±20%	5.00	8.0	0.18	0.19	0.20	0.23	0.29
LPS4012-224ML	220±20%	5.20	7.0	0.15	0.16	0.17	0.21	0.27
LPS4012-334ML	330±20%	7.20	7.0	0.14	0.14	0.15	0.17	0.225
LPS4012-474ML	470±20%	10.0	4.0	0.10	0.11	0.12	0.13	0.175
LPS4012-564ML	560±20%	12.5	3.5	0.10	0.105	0.115	0.11	0.140
LPS4012-684ML	680±20%	13.5	3.0	0.10	0.105	0.110	0.11	0.135
LPS4012-824ML	820±20%	20.0	3.0	0.090	0.095	0.095	0.105	0.132
LPS4012-105ML	1000±20%	21.5	3.0	0.080	0.090	0.095	0.100	0.130
LPS4012-155ML	1500±20%	30.0	2.5	0.080	0.090	0.090	0.087	0.115
LPS4012-185ML	1800±20%	35.0	2.0	0.079	0.085	0.087	0.075	0.100
LPS4012-225ML	2200±20%	42.0	1.0	0.079	0.083	0.085	0.070	0.090
LPS4012-335ML	3300±20%	65.0	0.95	0.074	0.078	0.080	0.050	0.065

1. Please specify **termination** and **packaging** codes:

LPS4012-682MLC

Termination: L = RoHS compliant silver-palladium-platinum-glass frit.
Special order:
T = RoHS tin-silver-copper (95.5/4/0.5)
or S = non-RoHS tin-lead (63/37).

Packaging: C = 7" machine-ready reel. EIA-481 embossed plastic tape (1000 parts per full reel).

B = Less than full reel. In tape, but not machine ready.
To have a leader and trailer added (\$25 charge), use code letter C instead.

D = 13" machine-ready reel. EIA-481 embossed plastic tape. Factory order only, not stocked (3500 parts per full reel).

- Inductance tested at 100 kHz, 0.1 Vrms using an Agilent/HP 4192A. Inductance at 1 MHz is the same for parts with SRF ≥ 10 MHz.
 - DCR measured on a micro-ohmmeter.
 - SRF measured using Agilent/HP 8753ES or equivalent.
 - DC current that causes the specified inductance drop from its value without current.
 - Current that causes the specified temperature rise from 25°C ambient.
 - Electrical specifications at 25°C.
- Refer to Doc 362 "Soldering Surface Mount Components" before soldering.



www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 433-1 Revised 04/24/12

© Coilcraft Inc. 2012


This product may not be used in medical of high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check out web site for latest information.




Shielded SMT Power Inductors – LPS4012 Series

SPICE models
ON OUR WEB SITE


Typical L vs Frequency




Typical L vs Current



Current Derating



Coilcraft **Designer's Kit C392** contains samples of 0.80 μH to 33 μH parts (3 each) from LPS3008, LPS3010 and LPS3015. **Kit C401** contains samples of 0.56 μH to 33 μH parts (3 each) from LPS4012 and LPS4018. **Kit C402** contains samples of 220 μH to 3300 μH parts (3 each) from all five series. For details of kit contents and to order, contact Coilcraft or visit <http://order.coilcraft.com>.



* Dimensions are of the case not including the termination. For maximum overall dimensions including the termination, add 0.005 in / 0,13 mm.

** For optional tin-lead and tin-silver-copper terminations, dimensions are for the mounted part. Dimensions before mounting can be an additional 0.005 inch (0,13 mm).

Dimensions are in $\frac{\text{inches}}{\text{mm}}$



www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 433-2 Revised 04/24/12

© Coilcraft Inc. 2012

This product may not be used in medical of high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check out web site for latest information.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.