

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0548190572](#)
Status: **Active**
Description: USB On-The-Go (OTG) Mini-B Receptacle, Right Angle, SMT Solder Tails and Shell Tabs, with Cover Tape, Lead-free

Documents:
[3D Model](#) [Product Specification PS-56579-015 \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification
UL E29179


General
Product Family I/O Connectors
Series [54819](#)
Application Wire-to-Board
Component Type Receptacle
Product Name USB, USB OTG (On-The-Go)
Type Mini-B

Physical
Circuits (Loaded) 5
Circuits (maximum) 5
Color - Resin Black
Flammability 94V-0
Lock to Mating Part Yes
Material - Metal High Performance Alloy (HPA)
Material - Plating Mating Gold
Material - Plating Termination Tin
Material - Resin High Temperature Thermoplastic
Orientation Right Angle
PCB Locator No
PCB Retention Yes
Packaging Type Embossed Tape on Reel
Panel Mount No
Pitch - Mating Interface (in) 0.031 In
Pitch - Mating Interface (mm) 0.80 mm
Plating min: Mating (µin) 30.4
Plating min: Mating (µm) 0.76
Plating min: Termination (µin) 40
Plating min: Termination (µm) 1
Polarized to Mating Part Yes
Surface Mount Compatible (SMC) N/A
Temperature Range - Operating 0°C to +50°C
Termination Interface: Style Surface Mount
Wire Size AWG N/A

Electrical
Current - Maximum per Contact 1A
Shielded Yes
Voltage - Maximum 30V

Material Info

Reference - Drawing Numbers
Product Specification PS-56579-015, RPS-54819-019, RPS-54819-020,
RPS-54819-022, RPS-54819-024, RPS-54819-026,



EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Not Reviewed
Halogen-Free
Status
Not Reviewed




Need more information on product environmental compliance?
Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)
Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[54819Series](#)

Mates With
[59204-9401](#) , [59205-3301](#)

This document was generated on 03/31/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION




注記 1. 材質
NOTES MATERIAL

ハウジング: ポリアミド, ガラス充填, 黒色, UL94V-0
HOUSING: PA, GLASS FILLED, BLACK, UL94V-0
ターミナル: 銅合金 (t=0.2)
TERMINAL: COPPER ALLOY (t=0.2)
シールド ケース: 銅合金 (t=0.4)
SHIELD CASE: COPPER ALLOY (t=0.4)
カバー テープ: ポリイミド (t=0.08)
COVER TAPE: POLYIMIDE (t=0.08)

2. メッキ仕様
PLATING

ターミナル
TERMINAL
接点部: 金メッキ 0.75 MICROMETER MIN.
CONTACT AREA: GOLD 0.75 MICROMETER MINIMUM.
半田付け部: 錫メッキ 無光沢 1.0 MICROMETER MIN.
SOLDER TAIL AREA: MATTETIN 1.0 MICROMETER MINIMUM.
下地部: ニッケルメッキ 4.0 MICROMETER MIN.
UNDER PLATING: NICKEL 4.0 MICROMETER MINIMUM.
シールド ケース
SHIELD CASE
: 錫メッキ 半光沢 1.0 MICROMETER MIN.
: SEMI-MATTETIN 1.0 MICROMETER MINIMUM.
下地部: ニッケルメッキ 4.0 MICROMETER MIN.
UNDER PLATING: NICKEL 4.0 MICROMETER MINIMUM.

3. テール、ネール平坦度は 0.1mm MAX.
TAIL, NAIL COPLANARITY 0.1mm MAX.
4. 本製品は 54819-0571 の鉛フリー品である。
THIS PRODUCT IS LEAD FREE OF 54819-0571.




推奨基板寸法 (部品実装側)


RECOMMENDED P.C.B. PATTERN LAYOUT (PART MOUNT SIDE)

54819-0572	54819-0579
EMBOSSD TAPE	MATERIAL No.
ORDER No.	
MODEL No. 54819-**-79	

REVISED EC NO.: J2009-1533 DRAWN BY CHYKDE:HWATSUMOTO APPR:NUKITA	DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 10:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		
		10 UNDER	±0.2	DRAWN BY H. KAWABATA	DATE 2004/05/21	TITLE USB SERIES MINI-B RECEPTACLE ASS'Y FOR SMT -LEAD FREE- MOLEX INCORPORATED				
		10 OVER 30 UNDER	±0.25	CHECKED BY K. TOJO	DATE 2004/05/21					
		30 OVER	±0.3	APPROVED BY M. SASAO	DATE 2004/05/21					
		ANGULAR ±3 °		MATERIAL NO.						
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE TABLE		SD-54819-027		1 OF 2		
REV		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION								




SECTION



MATING


REVISED EC NO: J2009-1533 DRW: SATO CHK: MATSUMOTO APPR: NUKITA		2009/06/25 2009/06/25 2009/06/25		GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 10:1	DESIGN UNITS METRIC	MODEL NO. 54819-**-79 THIRD ANGLE PROJECTION
		10 UNDER		±0.2	DRAWN BY H. KAWABATA	DATE 2004/05/21	TITLE USB SERIES MINI-B RECEPTACLE ASS'Y FOR SMT -LEAD FREE-			
		10 OVER 30 UNDER		±0.25	CHECKED BY K. TOJO	DATE 2004/05/21	MOLEX INCORPORATED			
		30 OVER		±0.3	APPROVED BY M. SASAO	DATE 2004/05/21	DOCUMENT NO. SD-54819-027			
C		REV		DESCRIPTION		MATERIAL NO.		SHEET NO.		2 OF 2
				ANGULAR ±3 °		SEE SHEET 1		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		EN-02JA(021)
				DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS						

10 9 8 7 6 5 4 3 2 1



NOTES

- 54819-0579の詳細はSD-54819-027参照
IN THE PACKAGE PART NO.54819-0579 DETAILED , SEE SD-54819-027
- 梱包数量: 800 個/リール
NUMBER OF CONNECTORS: 800 PCS/REEL
- リードテープ長さ
LEAD TAPE LENGTH




引き出し方向
PULL OUT DIRECTION

- トップテープの剥離強度: 0.1~ 1.3 N {10~130gf}
(剥離方向は下図参照) キャリアテープ幅: 24mm
CARRIER TAPE WIDTH

PEEL-OFF FORCE OF TOP TAPE: 0.1~1.3 N {10~130gf}
(PEELING DIRECTION AS SHOWN IN FOLLOWING FIG.)

尚、本規格値は、出荷時に適用。
THIS REQUIREMENTS SHOULD BE APPLIED AT SHIPMENT
(但し、輸送時に剥離が発生しない事。)
(PEEL OFF SHOULD NOT BE ALLOWED, DURING TRANSPORTATION)



- 材料
MATERIAL
キャリアテープ: ポリプロピレン
CARRIER TAPE: POLYPROPYLENE
トップテープ: ポリエステル, ポリエチレン
TOP TAPE: POLYESTER, POLYETHYLENE
リール: ポリスチレン
REEL: POLYSTYRENE

- 本製品は 54819-0578 の鉛フリー品である。
THIS PRODUCT IS LEAD FREE OF 54819-0578.

54819-0572

MATERIAL NO.

MODEL NO.

54819-**-72

SCALE
2:1

DESIGN UNITS
METRIC

THIRD ANGLE
PROJECTION

DRAWN BY
H. KAWABATA

DATE
2004/05/21

CHECKED BY
K. TOJO

DATE
2004/05/21

APPROVED BY
M. SASAO

DATE
2004/05/21

MATERIAL NO.
SEE CHART

SIZE
A3


TITLE
USB SERIES MINI-B
REC.HS'G EMBOSSED ASS'Y
-LEAD FREE-

MOLEX INCORPORATED

DOCUMENT NO.
SD-54819-028

SHEET NO.
1 OF 1

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION



REVISED
EC NO: J2006-0378
DRWN: YANAGI MOTO 2005/08/03
CHKD: TANAKA 2005/08/03
APPR: NUKITA 2005/08/17

GENERAL TOLERANCES (UNLESS SPECIFIED)	
10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±3 °
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	
1	REV

DIMENSION STYLE MM ONLY	
DRAWN BY	DATE
H. KAWABATA	2004/05/21
CHECKED BY	DATE
K. TOJO	2004/05/21
APPROVED BY	DATE
M. SASAO	2004/05/21
MATERIAL NO.	
SEE CHART	
SIZE	
A3	

SCALE 2:1	
DESIGN UNITS METRIC	
THIRD ANGLE PROJECTION	
TITLE USB SERIES MINI-B REC.HS'G EMBOSSED ASS'Y -LEAD FREE-	
MOLEX INCORPORATED	
DOCUMENT NO. SD-54819-028	SHEET NO. 1 OF 1



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.