

# AC and Pulse Metallized Polypropylene Film Capacitors KP/MKP Radial Lacquered Type



Dimensions in mm

- (1) Hole  $\varnothing$  1.3 for  $d_t = 0.8$  mm
- (2)  $0 \leq \alpha < 50^\circ$
- (3)  $|F - F'| < 0.3$  mm  
 $F = 7.5 + 0.6/-0.1$  mm
- (4)  $A = 2.0 + 1.0/-0.5$  mm for 10 mm pitch  
 $A = 2.5 + 1.5/-0.5$  mm for 15 mm pitch  
 $A = 2.5 + 1.4/-0.5$  mm for pitch  $> 22.5$  mm



Dimensions in mm

## APPLICATIONS

Where high currents and steep pulses occur. For deflection circuits in television sets.

## REFERENCE SPECIFICATIONS

IEC 60384-17

## MARKING

C-value; tolerance; rated voltage; manufacturer's type; manufacturer's location

## DIELECTRIC

Polypropylene film

## ELECTRODES

Metallized and aluminum

## CONSTRUCTION

Internal serial construction

## RATED (DC) VOLTAGE

630 V, 1000 V, 1600 V, 2000 V

## RATED (AC) VOLTAGE

300 V, 400 V, 500 V, 600 V

## RATED PEAK-TO-PEAK VOLTAGE

850 V, 1100 V, 1400 V, 1700 V

## FEATURES

- 10 mm to 27.5 mm pitch
- Supplied loose in box (including lock lead versions) and taped
- Bent back version for automatic insertion available
- Compliant to RoHS directive 2002/95/EC



**RoHS**  
COMPLIANT

## ENCAPSULATION

Flame retardant epoxy material  
(Class UL 94 V-0)

## CLIMATIC TESTING CLASS ACC. TO IEC 60068-1

55/105/56

## CAPACITANCE RANGE (E24 SERIES)

0.1 nF to 270 nF

## CAPACITANCE TOLERANCE

$\pm 5\%$ ;  $\pm 3.5\%$

## LEADS

Tinned wire

## RATED TEMPERATURE

85 °C

## MAXIMUM APPLICATION TEMPERATURE

105 °C

## PERFORMANCE GRADE

for  $C > 5.6$  nF: grade 1 (long life)  
for  $C \leq 5.6$  nF: grade 2

## STABILITY GRADE

Grade 2

## DETAIL SPECIFICATION

For more detailed data and test requirements contact:

[dc-film@vishay.com](mailto:dc-film@vishay.com)

### COMPOSITION OF CATALOG NUMBER

| TYPE AND PITCHES |                | CAPACITANCE<br>(numerically; but not<br>for lock lead) | MULTIPLIER<br>(nF) |   |
|------------------|----------------|--------------------------------------------------------|--------------------|---|
| 375              | 10.0 mm/7.5 mm |                                                        | 0.01               | 1 |
|                  | 15.0 mm/7.5 mm |                                                        | 0.1                | 2 |
|                  | 10.0 mm        |                                                        | 1                  | 3 |
|                  | 15.0 mm        |                                                        | 10                 | 4 |
|                  | 22.5 mm        |                                                        |                    |   |
|                  | 27.5 mm        |                                                        |                    |   |

|                     |     |    |    |   |
|---------------------|-----|----|----|---|
| BFC2                | 375 | XX | YY | Y |
| 2222 <sup>(1)</sup> | 375 | XX | YY | Y |

<sup>(1)</sup> old ordering number

Example:  
104 = 10 x 10 = 100 nF

| TYPE | PACKAGING                                   | LEAD CONFIGURATION                                               | PREFERRED TYPES |            |        |        |        |
|------|---------------------------------------------|------------------------------------------------------------------|-----------------|------------|--------|--------|--------|
|      |                                             |                                                                  | C-TOL.          | 630 V      | 1000 V | 1600 V | 2000 V |
| 375  | Loose in box                                | Lead length 5.0 mm ± 1.0 mm                                      | ± 5 %           | 14         | 24     | 34     | 44     |
|      |                                             | Lock lead 4.0 mm + 1.0/- 0.5 mm                                  | ± 5 %           | 90         | 90     | 90     | 90     |
|      | Taped on reel <sup>(2)</sup><br>(bent back) | H = 16.0 mm; P <sub>0</sub> = 15.0 mm;<br>Reel diameter 500 mm   | ± 5 %           | 16         | 26     | 36     | 46     |
|      |                                             | Dimensions of this code numbers stays between brackets           |                 |            |        |        |        |
|      |                                             |                                                                  |                 | ON REQUEST |        |        |        |
| 375  | Loose in box                                | Lead length 5.0 ± 1.0 mm                                         | ± 3.5 %         | 15         | 25     | 35     | 45     |
|      |                                             | Lead length 3.5 ± 0.5 mm                                         | ± 5 %           | 10         | 20     | 30     | 40     |
|      | ± 3.5 %                                     |                                                                  | 11              | 21         | 31     | 41     |        |
|      | Taped on reel <sup>(2)</sup>                | H = 16.0 mm; P <sub>0</sub> = 12.7 mm;<br>Reel diameter = 500 mm | ± 5 %           | 12         | 22     | 32     | 42     |
|      |                                             | ± 3.5 %                                                          | 13              | 23         | 33     | 43     |        |
|      | Taped on reel <sup>(2)</sup><br>(bent back) | H = 16.0 mm; P <sub>0</sub> = 15.0 mm;<br>Reel diameter = 500 mm | ± 3.5 %         | 17         | 27     | 37     | 47     |
|      |                                             | Dimensions of this code numbers stays between brackets           |                 |            |        |        |        |
|      |                                             | H = 16.0 mm; P <sub>0</sub> = 15.0 mm;<br>Reel diameter = 356 mm | ± 5 %           | 18         | 28     | 38     | 48     |

#### Note

<sup>(1)</sup> For detailed tape specifications refer to "Packaging Information" [www.vishay.com/doc?28139](http://www.vishay.com/doc?28139) or end of catalog

### SPECIFIC REFERENCE DATA (630 V<sub>DC</sub>)

| DESCRIPTION                                                           | VALUE         |         |
|-----------------------------------------------------------------------|---------------|---------|
| Tangent of loss angle at (x 10 <sup>-4</sup> )                        | 10 kHz        | 100 kHz |
| Pitch = 10 mm, 15 mm and 7.5 mm (bent back)                           | ≤ 6           | ≤ 10    |
| Pitch = 22.5 mm                                                       | ≤ 8           | ≤ 15    |
| Pitch = 27.5 mm                                                       | ≤ 8           | ≤ 20    |
| Rated voltage pulse slope (dU/dt) <sub>R</sub> :                      | 15 000 V/μs   |         |
| Pitch = 10 mm                                                         | 8000 V/μs     |         |
| Pitch = 15 mm and 7.5 mm (bent back)                                  | 2800 V/μs     |         |
| Pitch = 22.5 mm                                                       | 1900 V/μs     |         |
| Pitch = 27.5 mm                                                       |               |         |
| R between leads at 500 V, 1 min                                       | > 100 000 MΩ  |         |
| R between interconnected leads and case, 500 V, 1 min                 | > 100 000 MΩ  |         |
| Ionisation (AC) voltage (typical value) at 50 pC peak discharge       | > 400 V       |         |
| at 50 pC peak discharge                                               |               |         |
| at 20 pC peak discharge                                               |               |         |
| Withstanding (DC) voltage (cut off current 10 mA), rise time 1000 V/s | 1008 V, 1 min |         |
| For C ≤ 47 nF                                                         |               |         |
| For C > 47 nF                                                         |               |         |
| Withstanding (DC) voltage between leads and case                      | 2840 V, 1 min |         |
| Maximum application temperature                                       | 105 °C        |         |



## AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents KP/MKP Radial Lacquered Type

$U_{RDC} = 630 \text{ V}$ ;  $U_{RAC} = 300 \text{ V}$ ;  $U_{pp} = 850 \text{ V}$  (kinked);  $C\text{-tol.} = \pm 5 \%$

| C      | DIMENSIONS<br>w x h (h') x l<br>(mm)                         | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 375 XXYYY AND PACKAGING |                            |                |                            |            |            |
|--------|--------------------------------------------------------------|----------------------------|---------------------------------------------|----------------------------|----------------|----------------------------|------------|------------|
|        |                                                              |                            | LOOSE IN BOX                                | REEL                       |                |                            | C<br>VALUE |            |
|        |                                                              |                            |                                             | Leads<br>5 mm ± 1.0 mm     | Original pitch | Pitch = 7.5 mm (bent back) |            | ..YYY      |
|        |                                                              |                            |                                             |                            | Ø 500 mm       | Ø 500 mm                   | Ø 356 mm   |            |
|        |                                                              |                            | XX<br>(SPQ)                                 | XX<br>(SPQ)                | XX<br>(SPQ)    | XX<br>(SPQ)                |            |            |
| C (pF) | Pitch = 10.0 mm ± 0.4 mm; d <sub>t</sub> = 0.60 mm ± 0.06 mm |                            | Pitch = 10.0 mm                             | Pitch = 7.5 mm (bent back) |                |                            |            |            |
| 680    | 5.0 x 13.0 x 14.5                                            | 0.65                       | 14...<br>(2000)                             | 12...<br>(1200)            |                |                            |            |            |
| 750    |                                                              |                            |                                             |                            |                |                            |            | 681<br>751 |
| 820    | 5.5 x 13.5 x 14.5                                            | 0.70                       | 14...<br>(2000)                             | 12...<br>(1100)            |                |                            |            |            |
| 910    |                                                              |                            |                                             |                            |                |                            |            | 821<br>911 |
| 1000   |                                                              |                            |                                             |                            |                |                            |            | 102        |
| 1100   |                                                              | 112                        |                                             |                            |                |                            |            |            |
| 1200   |                                                              | 122                        |                                             |                            |                |                            |            |            |
| 1300   |                                                              | 132                        |                                             |                            |                |                            |            |            |
| 1500   |                                                              | 152                        |                                             |                            |                |                            |            |            |
| 1600   |                                                              | 162                        |                                             |                            |                |                            |            |            |
| 1800   | 6.0 x 14.0 x 14.5                                            | 0.80                       | 14...<br>(1750)                             | 12...<br>(1000)            |                |                            |            |            |
| 2000   |                                                              | 0.85                       |                                             |                            |                |                            |            | 182<br>202 |
| 2200   |                                                              | 0.90                       |                                             |                            |                |                            |            | 222        |
| 2400   |                                                              | 1.0                        |                                             |                            |                |                            |            | 242        |
| 2700   | 6.5 x 14.5 x 14.5                                            | 1.1                        | 14...<br>(1500)                             | 12...<br>(900)             | 272            |                            |            |            |

### Note

<sup>(1)</sup> Net weight for short lead product only

- SPQ = Standard Packing Quantity

## Vishay BCcomponents AC and Pulse Metallized Polypropylene Film Capacitors KP/MKP Radial Lacquered Type

$U_{RDC} = 630 \text{ V}$ ;  $U_{RAC} = 300 \text{ V}$ ;  $U_{pp} = 850 \text{ (kinked)}$ ;  $C\text{-tol.} = \pm 5 \%$

| C      | DIMENSIONS<br>w x h (h') x l<br>(mm)                                      | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 375 XYYYY AND PACKAGING |                 |                            |             |            |
|--------|---------------------------------------------------------------------------|----------------------------|---------------------------------------------|-----------------|----------------------------|-------------|------------|
|        |                                                                           |                            | LOOSE IN BOX                                | REEL            |                            |             | C<br>VALUE |
|        |                                                                           |                            | Leads<br>5 mm $\pm$ 1.0 mm                  | Original pitch  | Pitch = 7.5 mm (bent back) |             | ..YYY      |
|        |                                                                           |                            | XX<br>(SPQ)                                 | XX<br>(SPQ)     | XX<br>(SPQ)                | XX<br>(SPQ) |            |
| C (pF) | Pitch = 15.0 mm $\pm$ 0.4 mm; $d_t = 0.80 \text{ mm} \pm 0.08 \text{ mm}$ |                            |                                             |                 | Pitch = 7.5 mm (bent back) |             |            |
| 3000   | 5.0 x 14.0 (16.0) x 18.5                                                  | 1.0                        | 14...                                       | 12...           | 16 ...                     | 18 ...      | 302        |
| 3300   |                                                                           |                            | (2000)                                      | (1200)          | (1000)                     | (550)       | 332        |
| 3600   |                                                                           |                            |                                             |                 |                            |             | 362        |
| 3900   |                                                                           |                            |                                             |                 |                            |             | 392        |
| 4300   |                                                                           |                            | 14...                                       | 12...           | 16 ...                     | 18 ...      | 432        |
| 4700   | 5.5 x 14.5 (16.0) x 18.5                                                  | 1.1                        | (2000)                                      | (1100)          | (900)                      | (500)       | 472        |
| 5100   |                                                                           |                            |                                             |                 |                            |             | 512        |
| 5600   |                                                                           |                            |                                             |                 |                            |             | 562        |
| 6200   |                                                                           |                            |                                             |                 |                            |             | 622        |
| 6800   |                                                                           |                            |                                             |                 |                            |             | 682        |
| 7500   | 6.0 x 15.0 (16.0) x 18.5                                                  | 1.2                        |                                             |                 |                            |             | 752        |
| 8200   |                                                                           |                            |                                             |                 |                            |             | 822        |
| 9100   |                                                                           |                            | 14...                                       | 12...           | 16 ...                     | 18 ...      | 912        |
| 10 000 |                                                                           |                            | (2000)                                      | (1000)          | (800)                      | (450)       | 103        |
| 11 000 |                                                                           |                            |                                             |                 |                            |             | 113        |
| 12 000 |                                                                           |                            |                                             |                 |                            |             | 123        |
| 13 000 |                                                                           |                            |                                             |                 |                            |             | 133        |
| 15 000 |                                                                           |                            |                                             |                 |                            |             | 153        |
| 16 000 |                                                                           |                            |                                             |                 |                            |             | 163        |
| 18 000 | 6.5 x 15.5 (17.0) x 18.5                                                  | 1.3                        | 14...                                       | 12...           | 16...                      | 18...       | 183        |
| 20 000 |                                                                           |                            | (1500)                                      | (900)           | (750)                      | (400)       | 203        |
| 22 000 | 7.0 x 16.0 (17.5) x 18.5                                                  | 1.5                        | 14...                                       | 12...           | 16...                      | 18...       | 223        |
|        |                                                                           |                            | (1500)                                      | (800)           | (700)                      | (400)       |            |
| 24 000 | 7.5 x 16.5 (18.0) x 18.5                                                  | 1.6                        | 14...                                       | 12...           | 16...                      | 18...       | 243        |
|        |                                                                           |                            | (1250)                                      | (800)           | (650)                      | (350)       |            |
| 27 000 | 8.0 x 17.0 (18.5) x 18.5                                                  | 1.9                        | 14...                                       | 12...           | 16...                      | 18...       | 273        |
| 30 000 |                                                                           |                            | (1250)                                      | (750)           | (600)                      | (350)       | 303        |
| 33 000 | 8.5 x 17.5 (19.0) x 18.5                                                  | 2                          | 14...                                       | 12...           | 16...                      | 18...       | 333        |
|        |                                                                           |                            | (1000)                                      | (700)           | (550)                      | (300)       |            |
| 36 000 | 9.0 x 18.5 (20.0) x 18.5                                                  | 2.3                        | 14...                                       | 12...           | 16...                      | 18...       | ON         |
| 39 000 |                                                                           |                            | (900)                                       | (600)           | (500)                      | (300)       | REQUEST    |
| C (μF) | Pitch = 22.5 mm $\pm$ 0.4 mm; $d_t = 0.80 \text{ mm} \pm 0.08 \text{ mm}$ |                            |                                             | Pitch = 22.5 mm | Pitch = 7.5 mm (bent back) |             |            |
| 0.036  | 7.0 x 20.0 x 26.0                                                         | 2.7                        | 14...                                       | -               | -                          |             | 363        |
| 0.039  |                                                                           |                            |                                             |                 |                            |             | 393        |
| 0.043  |                                                                           |                            |                                             |                 |                            |             | 433        |
| 0.047  |                                                                           |                            |                                             |                 |                            |             | 473        |
| 0.051  |                                                                           |                            |                                             |                 |                            |             | 513        |
| 0.056  |                                                                           |                            |                                             |                 |                            |             | 563        |
| 0.062  |                                                                           |                            |                                             |                 |                            |             | 623        |
| 0.068  | 7.5 x 20.5 x 26.0                                                         | 3                          | 14...                                       | -               | -                          |             | 683        |
|        |                                                                           |                            | (600)                                       |                 |                            |             |            |
| 0.075  | 8.0 x 21.0 x 26.0                                                         | 3.3                        | 14...                                       | -               | -                          |             | 753        |
| 0.082  |                                                                           |                            | (550)                                       |                 |                            |             | 823        |
| 0.091  | 8.5 x 21.5 x 26.0                                                         | 3.8                        | 14...                                       | -               | -                          |             | 913        |
|        |                                                                           |                            | (500)                                       |                 |                            |             |            |
| 0.1    | 9.0 x 22.0 x 26.0                                                         | 4                          | 14...                                       | -               | -                          |             | 104        |
|        |                                                                           |                            | (450)                                       |                 |                            |             |            |

### Note

<sup>(1)</sup> Net weight for short lead product only

• SPQ = Standard Packing Quantity



**AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents**  
**KP/MKP Radial Lacquered Type**

**U<sub>RDC</sub> = 630 V; U<sub>RAC</sub> = 300 V; U<sub>pp</sub> = 850 (kinked); C-tol. = ± 5 %**

| C      | DIMENSIONS<br>w x h (h') x l<br>(mm)                         | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 375 XYYYY AND PACKAGING |                            |                            |             |         |
|--------|--------------------------------------------------------------|----------------------------|---------------------------------------------|----------------------------|----------------------------|-------------|---------|
|        |                                                              |                            | LOOSE IN BOX                                | REEL                       |                            |             | C VALUE |
|        |                                                              |                            | Leads<br>5 mm ± 1.0 mm                      | Original pitch             | Pitch = 7.5 mm (bent back) |             | ..YYY   |
|        |                                                              |                            |                                             | Ø 500 mm                   | Ø 500 mm                   | Ø 356 mm    |         |
|        |                                                              |                            | XX<br>(SPQ)                                 | XX<br>(SPQ)                | XX<br>(SPQ)                | XX<br>(SPQ) |         |
| C (µF) | Pitch = 22.5 mm ± 0.4 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                            | Pitch = 22.5 mm                             | Pitch = 7.5 mm (bent back) |                            |             |         |
| 0.11   | 9.5 x 22.5 x 26.0                                            | 4.3                        | 14...<br>(400)                              | -                          | -                          | 114         |         |
| 0.12   | 10.0 x 23.0 x 26.0                                           | 4.7                        | 14...<br>(400)                              |                            |                            | 124         |         |
| C (µF) | Pitch = 27.5 mm ± 0.5 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                            | Pitch = 27.5mm                              | Pitch = 7.5 mm (bent back) |                            |             |         |
| 0.13   | 9.5 x 22.5 x 30.0                                            | 4.7                        | 14...<br>(500)                              | -                          | -                          | 134         |         |
| 0.15   | 10.0 x 23.0 x 30.0                                           | 5.2                        | 14...<br>(500)                              |                            |                            | 154         |         |
| 0.16   | 10.5 x 23.5 x 30.0                                           | 5.5                        | 14...<br>(450)                              |                            |                            | 164         |         |
| 0.18   | 11.0 x 24.0 x 30.0                                           | 6                          | 14...<br>(400)                              |                            |                            | 184         |         |
| 0.2    | 11.5 x 24.5 x 30.0                                           | 6.6                        | 14...<br>(400)                              |                            |                            | 204         |         |
| 0.22   | 12.5 x 25.5 x 30.0                                           | 7.1                        | 14...<br>(350)                              |                            |                            | 224         |         |
| 0.24   | 13.0 x 26.0 x 30.0                                           | 7.7                        | 14...<br>(300)                              |                            |                            | 244         |         |
| 0.27   | 13.5 x 26.5 x 30.0                                           | 8.5                        | 14...<br>(300)                              |                            |                            | 274         |         |

**Notes**

- <sup>(1)</sup> Net weight for short lead product only
- Loose in box, all lengths have same SPQ
  - SPQ = Standard Packing Quantity

**U<sub>RDC</sub> = 630 V; U<sub>RAC</sub> = 300 V; U<sub>pp</sub> = 850 V (lock lead); C-tol. = ± 5 %**

| C      | DIMENSIONS<br>w x h (h') x l<br>(mm)                         | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 375 XYYYY AND PACKAGING |        |
|--------|--------------------------------------------------------------|----------------------------|---------------------------------------------|--------|
|        |                                                              |                            | LOOSE IN BOX                                |        |
|        |                                                              |                            | l <sub>t</sub> = 4.0 mm + 1.0 mm/- 0.5 mm   |        |
|        |                                                              |                            |                                             | (SPQ)  |
| C (pF) | Pitch = 10.0 mm ± 1.0 mm; d <sub>t</sub> = 0.60 mm ± 0.06 mm |                            |                                             |        |
| 680    | 5.0 x 16.0 x 14.5                                            | 0.65                       | 90308                                       | (2000) |
| 750    |                                                              |                            | 90309                                       |        |
| 820    | 5.5 x 16.5 x 14.5                                            | 0.7                        | 90311                                       | (2000) |
| 910    |                                                              | 0.7                        | 90312                                       |        |
| 1000   |                                                              | 0.7                        | 90313                                       |        |
| 1100   |                                                              | 0.75                       | 90314                                       |        |
| 1300   |                                                              | 0.75                       | 90316                                       |        |
| 1500   |                                                              | 0.80                       | 90317                                       |        |
| 1600   |                                                              | 0.85                       | 90318                                       |        |
| 1800   |                                                              | 6.0 x 17.0 x 14.5          | 0.80                                        |        |
| 2000   | 0.85                                                         |                            | 90321                                       |        |
| 2200   | 0.90                                                         |                            | 90322                                       |        |
| 2400   | 1.0                                                          |                            | 90323                                       |        |
| 2700   | 6.5 x 17.5 x 14.5                                            | 1.1                        | 90324                                       | (1500) |

**Notes**

- <sup>(1)</sup> Net weight for short lead product only
- SPQ = Standard Packing Quantity

# KP/MKP 375



## Vishay BCcomponents AC and Pulse Metallized Polypropylene Film Capacitors KP/MKP Radial Lacquered Type

$U_{RDC} = 630 \text{ V}$ ;  $U_{RAC} = 300 \text{ V}$ ;  $U_{pp} = 850 \text{ V}$  (lock lead); C-tol. =  $\pm 5 \%$

| C                                                                                                | DIMENSIONS<br>w x h (h') x l<br>(mm)                         | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 375 XXYYY AND PACKAGING                                                     |        |
|--------------------------------------------------------------------------------------------------|--------------------------------------------------------------|----------------------------|-------------------------------------------------------------------------------------------------|--------|
|                                                                                                  |                                                              |                            | LOOSE IN BOX                                                                                    |        |
|                                                                                                  |                                                              |                            | l <sub>t</sub> = 4.0 mm + 1.0 mm/- 0.5 mm                                                       |        |
|                                                                                                  |                                                              |                            |                                                                                                 | (SPQ)  |
| C (pF)                                                                                           | Pitch = 15.0 mm ± 1.0 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                            |                                                                                                 |        |
| 3000<br>3300                                                                                     | 5.0 x 17.0 x 18.5                                            | 1                          | 90325<br>90326                                                                                  | (2000) |
| 3600<br>3900<br>4300<br>4700<br>5100<br>5600                                                     | 5.5 x 17.5 x 18.5                                            | 1.1                        | 90327<br>90328<br>90329<br>90331<br>90332<br>90333                                              | (2000) |
| 6200<br>6800<br>7500<br>8200<br>9100<br>10 000<br>11 000<br>12 000<br>13 000<br>15 000<br>16 000 | 6.0 x 18.0 x 18.5                                            | 1.3                        | 90334<br>90335<br>90336<br>90337<br>90338<br>90339<br>90236<br>90341<br>90342<br>90343<br>90344 | (2000) |
| 18 000<br>20 000                                                                                 | 6.5 x 18.5 x 18.5                                            | 1.4                        | 90218<br>90345                                                                                  | (1750) |
| 22 000                                                                                           | 7.0 x 19.0 x 18.5                                            | 1.5                        | 90219                                                                                           | (1500) |
| 24 000                                                                                           | 7.5 x 19.5 x 18.5                                            | 1.6                        | 90221                                                                                           | (1400) |
| 27 000<br>30 000                                                                                 | 8.0 x 20.0 x 18.5                                            | 1.9                        | 90223<br>90346                                                                                  | (1250) |
| 33 000                                                                                           | 8.5 x 20.5 x 18.5                                            | 2                          | 90347                                                                                           | (1200) |
| 36 000<br>39 000                                                                                 | 9.0 x 21.5 x 18.5                                            | 2.3                        | ON REQUEST                                                                                      | (1000) |
| C (μF)                                                                                           | Pitch = 22.5 mm ± 1.0 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                            |                                                                                                 |        |
| 0.036<br>0.039<br>0.043<br>0.047<br>0.051<br>0.056<br>0.062                                      | 7.0 x 23.0 x 26.0                                            | 2.7                        | 90348<br>90349<br>90351<br>90352<br>90353<br>90354<br>90355                                     | (600)  |
| 0.068                                                                                            | 7.5 x 23.5 x 26.0                                            | 3                          | 90356                                                                                           | (550)  |
| 0.075<br>0.082                                                                                   | 8.0 x 24.0 x 26.0                                            | 3.3                        | 90357<br>90358                                                                                  | (500)  |
| 0.091                                                                                            | 8.5 x 24.5 x 26.0                                            | 3.8                        | 90359                                                                                           | (450)  |

### Notes

- <sup>(1)</sup> Net weight for short lead product only  
 • SPQ = Standard Packing Quantity



## AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents KP/MKP Radial Lacquered Type

| C      | DIMENSIONS<br>w x h (h') x l<br>(mm)                         | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 375 XYYYY AND PACKAGING |       |
|--------|--------------------------------------------------------------|----------------------------|---------------------------------------------|-------|
|        |                                                              |                            | LOOSE IN BOX                                |       |
|        |                                                              |                            | l <sub>t</sub> = 4.0 mm + 1.0 mm/- 0.5 mm   |       |
|        |                                                              |                            |                                             | (SPQ) |
| C (μF) | Pitch = 22.5 mm ± 1.0 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                            |                                             |       |
| 0.1    | 9.0 x 25.0 x 26.0                                            | 4.0                        | 90361                                       | (450) |
| 0.11   | 9.5 x 25.5 x 26.0                                            | 4.3                        | 90362                                       | (400) |
| 0.12   | 10.0 x 26.0 x 26.0                                           | 4.7                        | 90363                                       | (350) |
| C (μF) | Pitch = 27.5 mm ± 1.0 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                            |                                             |       |
| 0.13   | 9.5 x 25.5 x 30.0                                            | 4.7                        | 90364                                       | (450) |
| 0.15   | 10.0 x 26.0 x 30.0                                           | 5.2                        | 90365                                       | (400) |
| 0.16   | 10.5 x 26.5 x 30.0                                           | 5.5                        | 90366                                       | (350) |
| 0.18   | 11.0 x 27.0 x 30.0                                           | 6.0                        | 90367                                       | (350) |
| 0.2    | 11.5 x 27.5 x 30.0                                           | 6.6                        | 90368                                       | (350) |
| 0.22   | 12.5 x 28.5 x 30.0                                           | 7.1                        | 90369                                       | (300) |
| 0.24   | 13.0 x 29.0 x 30.0                                           | 7.7                        | 90371                                       | (250) |
| 0.27   | 13.5 x 29.5 x 30.0                                           | 8.5                        | 90372                                       | (250) |

### Notes

<sup>(1)</sup> Net weight for short lead product only

- SPQ = Standard Packing Quantity

### SPECIFIC REFERENCE DATA (1000 V<sub>DC</sub>)

| DESCRIPTION                                                           | VALUE                                       |         |
|-----------------------------------------------------------------------|---------------------------------------------|---------|
| Tangent of loss angle at (x 10 <sup>-4</sup> )                        | 10 kHz                                      | 100 kHz |
| Pitch = 10 mm, 15 mm and 7.5 mm (bent back)                           | ≤ 6                                         | ≤ 10    |
| Pitch = 22.5 mm                                                       | ≤ 8                                         | ≤ 15    |
| Pitch = 27.5 mm                                                       | ≤ 8                                         | ≤ 20    |
| Rated voltage pulse slope (dU/d <sub>t</sub> ):                       |                                             |         |
| Pitch = 10 mm                                                         | 27 000 V/μs                                 |         |
| Pitch = 15 mm and 7.5 mm (bent back)                                  | 15 000 V/μs                                 |         |
| Pitch = 22.5 mm                                                       | 5000 V/μs                                   |         |
| Pitch = 27.5 mm                                                       | 3300 V/μs                                   |         |
| R between leads at 500 V, 1 min                                       | > 100 000 MΩ                                |         |
| R between interconnected leads and case, 500 V, 1 min                 | > 100 000 MΩ                                |         |
| Ionisation (AC) voltage (typical value)                               |                                             |         |
| at 50 pC peak discharge                                               | > 500 V                                     |         |
| at 20 pC peak discharge                                               |                                             |         |
| Withstanding (DC) voltage (cut off current 10 mA), rise time 1000 V/s |                                             |         |
| For C ≤ 47 nF                                                         | 1600 V, 1 min                               |         |
| For C > 47 nF                                                         | [1.6 - (0.0364 x (C - 47))] x 1000 V, 1 min |         |
| Withstanding (DC) voltage between leads and case                      | 2840 V, 1 min                               |         |
| Maximum application temperature                                       | 105 °C                                      |         |

## Vishay BCcomponents AC and Pulse Metallized Polypropylene Film Capacitors KP/MKP Radial Lacquered Type

$U_{RDC} = 1000 \text{ V}$ ;  $U_{RAC} = 400 \text{ V}$ ;  $U_{pp} = 1100 \text{ V}$  (kinked); C-tol. =  $\pm 5 \%$

| C      | DIMENSIONS<br>w x h (h') x l<br>(mm)                         | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 375 XXYYY AND PACKAGING |                            |                |                            | C<br>VALUE |       |
|--------|--------------------------------------------------------------|----------------------------|---------------------------------------------|----------------------------|----------------|----------------------------|------------|-------|
|        |                                                              |                            | LOOSE IN BOX                                | REEL                       |                |                            |            |       |
|        |                                                              |                            |                                             | Leads<br>5 mm ± 1.0 mm     | Original pitch | Pitch = 7.5 mm (bent back) |            | ..YYY |
|        |                                                              |                            |                                             |                            | Ø 500 mm       | Ø 500 mm                   | Ø 356 mm   |       |
|        |                                                              |                            | XX<br>(SPQ)                                 | XX<br>(SPQ)                | XX<br>(SPQ)    | XX<br>(SPQ)                |            |       |
| C (pF) | Pitch = 10.0 mm ± 0.4 mm; d <sub>t</sub> = 0.60 mm ± 0.06 mm |                            | Pitch = 10.0 mm                             | Pitch = 7.5 mm (bent back) |                |                            |            |       |
| 100    | 5.0 x 13.0 x 14.5                                            | 0.5                        | 24...<br>(2000)                             | 22...<br>(1200)            |                | -                          | 101        |       |
| 110    |                                                              |                            |                                             |                            |                |                            | 111        |       |
| 120    |                                                              |                            |                                             |                            |                |                            | 121        |       |
| 130    |                                                              |                            |                                             |                            |                |                            | 131        |       |
| 150    |                                                              |                            |                                             |                            |                |                            | 151        |       |
| 160    | 5.5 x 13.5 x 14.5                                            | 0.55                       | 24...<br>(2000)                             | 22...<br>(1100)            |                | -                          | 161        |       |
| 180    |                                                              | 0.55                       |                                             |                            |                |                            | 181        |       |
| 200    |                                                              | 0.55                       |                                             |                            |                |                            | 201        |       |
| 220    |                                                              | 0.60                       |                                             |                            |                |                            | 221        |       |
| 240    |                                                              | 0.60                       |                                             |                            |                |                            | 241        |       |
| 270    |                                                              | 0.60                       |                                             |                            |                |                            | 271        |       |
| 300    |                                                              | 0.60                       |                                             |                            |                |                            | 301        |       |
| 330    |                                                              | 0.60                       |                                             |                            |                |                            | 331        |       |
| 360    |                                                              | 0.60                       |                                             |                            |                |                            | 361        |       |
| 390    |                                                              | 0.65                       |                                             |                            |                |                            | 391        |       |
| 430    |                                                              | 0.70                       |                                             |                            |                |                            | 431        |       |
| 470    |                                                              | 0.75                       |                                             |                            |                |                            | 471        |       |
| 510    |                                                              | 0.75                       |                                             |                            |                |                            | 511        |       |
| 560    |                                                              | 0.80                       |                                             |                            |                |                            | 561        |       |
| 620    |                                                              | 0.80                       |                                             |                            |                |                            | 621        |       |
| 680    |                                                              | 0.80                       |                                             |                            |                |                            | 681        |       |
| 750    |                                                              | 0.70                       |                                             |                            |                |                            | 751        |       |
| 820    |                                                              | 0.70                       |                                             |                            |                |                            | 821        |       |
| 910    |                                                              | 0.70                       |                                             |                            |                |                            | 911        |       |
| 1000   | 6.0 x 14.0 x 14.5                                            | 0.75                       | 24...<br>(1750)                             | 22...<br>(1000)            |                | -                          | 102        |       |
| 1100   |                                                              | 0.85                       |                                             |                            |                |                            | 112        |       |
| 1200   |                                                              | 0.90                       |                                             |                            |                |                            | 122        |       |
| 1300   |                                                              | 0.85                       |                                             |                            |                |                            | 132        |       |
| 1500   |                                                              | 0.90                       |                                             |                            |                |                            | 152        |       |
| C (pF) | Pitch = 15.0 mm ± 0.4 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                            | Pitch = 15.0 mm                             | Pitch = 7.5 mm (bent back) |                |                            |            |       |
| 1600   | 5.5 x 14.5 (16.0) x 18.5                                     | 1.1                        | 24...<br>2000)                              | 22...<br>(1100)            | 26...<br>(900) | 28...<br>(500)             | 162        |       |
| 1800   |                                                              |                            |                                             |                            |                |                            | 182        |       |
| 2000   |                                                              |                            |                                             |                            |                |                            | 202        |       |
| 2200   |                                                              |                            |                                             |                            |                |                            | 222        |       |
| 2400   |                                                              |                            |                                             |                            |                |                            | 242        |       |
| 2700   | 6.0 x 15.0 (16.5) x 18.5                                     | 1.2                        | 24...<br>(2000)                             | 22...<br>(1000)            | 26...<br>(800) | 28...<br>(450)             | 272        |       |
| 3000   |                                                              |                            |                                             |                            |                |                            | 302        |       |
| 3300   |                                                              |                            |                                             |                            |                |                            | 332        |       |
| 3600   |                                                              |                            |                                             |                            |                |                            | 362        |       |
| 3900   |                                                              |                            |                                             |                            |                |                            | 392        |       |
| 4300   |                                                              |                            |                                             |                            |                |                            | 432        |       |
| 4700   |                                                              |                            |                                             |                            |                |                            | 472        |       |
| 5100   |                                                              |                            |                                             |                            |                |                            | 512        |       |
| 5600   |                                                              |                            |                                             |                            |                |                            | 562        |       |

### Notes

- <sup>(1)</sup> Net weight for short lead product only
- Loose in box, all lengths have same SPQ
- SPQ = Standard Packing Quantity



# AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents

## KP/MKP Radial Lacquered Type

$U_{RDC} = 1000 \text{ V}$ ;  $U_{RAC} = 400 \text{ V}$ ;  $U_{pp} = 1100 \text{ V}$  (kinked); C-tol. =  $\pm 5 \%$

| C                    | DIMENSIONS<br>w x h (h') x l<br>(mm)                         | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 375 XYYYY AND PACKAGING                   |                                |                            |                | C VALUE<br><br>..YYY |
|----------------------|--------------------------------------------------------------|----------------------------|---------------------------------------------------------------|--------------------------------|----------------------------|----------------|----------------------|
|                      |                                                              |                            | LOOSE IN BOX<br><br>Leads<br>5 mm ± 1.0 mm<br><br>XX<br>(SPQ) | REEL                           |                            |                |                      |
|                      |                                                              |                            |                                                               | Original pitch<br><br>Ø 500 mm | Pitch = 7.5 mm (bent back) |                |                      |
|                      |                                                              |                            |                                                               |                                | Ø 500 mm                   | Ø 356 mm       |                      |
| C (pF)               | Pitch = 15.0 mm ± 0.4 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm | Pitch = 15.0 mm            | Pitch = 7.5 mm (bent back)                                    |                                |                            |                |                      |
| 6200<br>6800         | 6.0 x 15.0 (16.5) x 18.5                                     | 1.2                        | 24...<br>(2000)                                               | 22...<br>(1000)                | 26...<br>(800)             | 28...<br>(450) | 622<br>682           |
| 7500<br>8200<br>9100 | 7.0 x 16.0 (17.5) x 18.5                                     | 1.4                        | 24...<br>(1500)                                               | 22...<br>(800)                 | 26...<br>(700)             | 28...<br>(400) | 752<br>822<br>912    |
| 10 000               | 7.5 x 16.5 (18.0) x 18.5                                     | 1.6                        | 24...<br>(1250)                                               | 22...<br>(800)                 | 26...<br>(650)             | 28...<br>(350) | 103                  |
| 11 000<br>12 000     | 8.0 x 17.0 (18.5) x 18.5                                     | 1.8                        | 24...<br>(1250)                                               | 22...<br>(750)                 | 26...<br>(600)             | 28...<br>(350) | 113<br>123           |
| 13 000               | 8.5 x 17.5 (19.0) x 18.5                                     | 1.9                        | 24...<br>(1000)                                               | 22...<br>(700)                 | 26...<br>(550)             | 28...<br>(300) | 133                  |
| 15 000               | 9.0 x 18.5 (19.5) x 18.5                                     | 2.1                        | 24...<br>(1000)                                               | 22...<br>(650)                 | 26...<br>(550)             | 28...<br>(300) | 153                  |
| C (µF)               | Pitch = 22.5 mm ± 0.4 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm | Pitch = 22.5 mm            | Pitch = 7.5 mm (bent back)                                    |                                |                            |                |                      |
| 0.016<br>0.018       | 6.0 x 19.0 x 26.0                                            | 2.2                        | 24...<br>(800)                                                |                                |                            |                | 163<br>183           |
| 0.02<br>0.022        | 6.5 x 19.5 x 26.0                                            | 2.5                        | 24...<br>(750)                                                |                                |                            |                | 203<br>223           |
| 0.024                | 7.0 x 20.0 x 26.0                                            | 2.7                        | 24...                                                         |                                |                            |                | 243                  |
| 0.027<br>0.03        | 7.5 x 20.5 x 26.0                                            | 3.1                        | 24...<br>(600)                                                |                                |                            |                | 273<br>303           |
| 0.033                | 8.0 x 21.0 x 26.0                                            | 3.4                        | 24...<br>(550)                                                |                                |                            |                | 333                  |
| 0.036<br>0.039       | 8.5 x 21.5 x 26.0                                            | 3.7                        | 24...<br>(500)                                                |                                |                            |                | 363<br>393           |
| 0.043                | 9.0 x 22.0 x 26.0                                            | 4.1                        | 24...<br>(450)                                                |                                |                            |                | 433                  |
| C (µF)               | Pitch = 27.5 mm ± 0.5 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm | Pitch = 27.5 mm            | Pitch = 7.5 mm (bent back)                                    |                                |                            |                |                      |
| 0.047                | 7.0 x 20.0 x 30.0                                            | 3.1                        | 24...<br>(1000)                                               |                                |                            |                | 473                  |
| 0.051<br>0.056       | 7.5 x 20.5 x 30.0                                            | 3.4                        | 24...<br>(750)                                                |                                |                            |                | 513<br>563           |
| 0.062                | 8.0 x 21.0 x 30.0                                            | 3.8                        | 24...<br>(650)                                                |                                |                            |                | 623                  |
| 0.068                | 8.5 x 21.5 x 30.0                                            | 4.0                        | 24...<br>(550)                                                |                                |                            |                | 683                  |
| 0.075                | 9.0 x 22.0 x 30.0                                            | 4.4                        | 24...<br>(550)                                                |                                |                            |                | 753                  |
| 0.082                | 9.5 x 22.5 x 30.0                                            | 4.7                        | 24...<br>(500)                                                |                                |                            |                | 823                  |
| 0.091                | 10.0 x 23.0 x 30.0                                           | 5.1                        | 24...<br>(500)                                                |                                |                            |                | 913                  |
| 0.10                 | 10.5 x 23.5 x 30.0                                           | 5.5                        | 24...<br>(450)                                                |                                |                            |                | 104                  |
| 0.11                 | 11.0 x 24.0 x 30.0                                           | 5.9                        | 24...<br>(400)                                                |                                |                            |                | 114                  |
| 0.12                 | 11.5 x 24.5 x 30.0                                           | 6.3                        | 24...<br>(400)                                                |                                |                            |                | 124                  |
| 0.13                 | 12.0 x 25.0 x 30.0                                           | 6.8                        | 24 ...<br>(350)                                               |                                |                            |                | 134                  |
| 0.15                 | 12.5 x 25.5 x 30.0                                           | 7.6                        | 24 ...<br>(350)                                               |                                |                            |                | 154                  |

### Notes

- <sup>(1)</sup> Net weight for short lead product only
- Loose in box, all lengths have same SPQ
  - SPQ = Standard Packing Quantity

# KP/MKP 375



## Vishay BCcomponents AC and Pulse Metallized Polypropylene Film Capacitors KP/MKP Radial Lacquered Type

$U_{RDC} = 1000 \text{ V}$ ;  $U_{RAC} = 400 \text{ V}$ ;  $U_{pp} = 1100 \text{ V}$  (lock lead); C-tol =  $\pm 5 \%$

| C      | DIMENSIONS<br>w x h (h') x l<br>(mm)                         | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 375 XYYYY AND PACKAGING |        |
|--------|--------------------------------------------------------------|----------------------------|---------------------------------------------|--------|
|        |                                                              |                            | LOOSE IN BOX                                |        |
|        |                                                              |                            | l <sub>t</sub> = 4.0 mm + 1.0 mm/- 0.5 mm   |        |
|        |                                                              |                            |                                             | (SPQ)  |
| C (pF) | Pitch = 10.0 mm ± 1.0 mm; d <sub>t</sub> = 0.60 mm ± 0.06 mm |                            |                                             |        |
| 100    | 5.0 x 16.0 x 14.5                                            | 0.5                        | 90373                                       | (2000) |
| 110    |                                                              |                            | 90374                                       |        |
| 120    |                                                              |                            | 90375                                       |        |
| 130    |                                                              |                            | 90376                                       |        |
| 150    | 5.5 x 16.5 x 14.5                                            | 0.55                       | 90377                                       | (2000) |
| 160    |                                                              | 0.55                       | 90378                                       |        |
| 180    |                                                              | 0.55                       | 90379                                       |        |
| 200    |                                                              | 0.55                       | 90281                                       |        |
| 220    |                                                              | 0.60                       | 90382                                       |        |
| 240    |                                                              | 0.60                       | 90383                                       |        |
| 270    |                                                              | 0.60                       | 90384                                       |        |
| 300    |                                                              | 0.60                       | 90385                                       |        |
| 330    |                                                              | 0.60                       | 90386                                       |        |
| 360    |                                                              | 0.60                       | 90387                                       |        |
| 390    |                                                              | 0.65                       | 90388                                       |        |
| 430    |                                                              | 0.70                       | 90389                                       |        |
| 470    |                                                              | 0.75                       | 90391                                       |        |
| 510    |                                                              | 0.75                       | 90392                                       |        |
| 560    |                                                              | 0.80                       | 90393                                       |        |
| 620    |                                                              | 0.80                       | 90394                                       |        |
| 680    |                                                              | 0.80                       | 90395                                       |        |
| 750    |                                                              | 0.70                       | 90396                                       |        |
| 820    |                                                              | 0.70                       | 90397                                       |        |
| 910    | 0.70                                                         | 90398                      |                                             |        |
| 1000   | 6.0 x 17.0 x 14.5                                            | 0.75                       | 90399                                       | (1750) |
| 1100   |                                                              | 0.85                       | 90401                                       |        |
| 1200   |                                                              | 0.90                       | 90402                                       |        |
| 1300   |                                                              | 0.85                       | 90403                                       |        |
| 1500   |                                                              | 0.90                       | 90404                                       |        |
| C (pF) | Pitch = 15.0 mm ± 1.0 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                            |                                             |        |
| 1600   | 5.5 x 17.5 x 18.5                                            | 1.1                        | 90405                                       | (2000) |
| 1800   |                                                              |                            | 90406                                       |        |
| 2000   |                                                              |                            | 90407                                       |        |
| 2200   |                                                              |                            | 90408                                       |        |
| 2400   |                                                              |                            | 90409                                       |        |
| 2700   | 6.0 x 18.0 x 18.5                                            | 1.2                        | 90411                                       | (2000) |
| 3000   |                                                              |                            | 90412                                       |        |
| 3300   |                                                              |                            | 90413                                       |        |
| 3600   |                                                              |                            | 90414                                       |        |
| 3900   |                                                              |                            | 90415                                       |        |
| 4300   |                                                              |                            | 90416                                       |        |
| 4700   |                                                              |                            | 90417                                       |        |
| 5100   |                                                              |                            | 90418                                       |        |
| 5600   |                                                              |                            | 90419                                       |        |
| 6200   |                                                              |                            | 90421                                       |        |
| 6800   |                                                              |                            | 90422                                       |        |

### Notes

<sup>(1)</sup> Net weight for short lead product only

- SPQ = Standard Packing Quantity



AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents  
KP/MKP Radial Lacquered Type

| C                    | DIMENSIONS<br>w x h (h') x l<br>(mm)                         | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 375 XYYYY AND PACKAGING |        |
|----------------------|--------------------------------------------------------------|----------------------------|---------------------------------------------|--------|
|                      |                                                              |                            | LOOSE IN BOX                                |        |
|                      |                                                              |                            | l <sub>t</sub> = 4.0 mm + 1.0 mm/- 0.5 mm   |        |
|                      |                                                              |                            |                                             | (SPQ)  |
| C (pF)               | Pitch = 15.0 mm ± 1.0 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                            |                                             |        |
| 7500<br>8200<br>9100 | 7.0 x 19.0 x 18.5                                            | 1.5                        | 90232<br>90423<br>90424                     | (1500) |
| 10 000               | 7.5 x 19.5 x 18.5                                            | 1.6                        | 90425                                       | (1400) |
| 11 000<br>12 000     | 8.0 x 20.0 x 18.5                                            | 1.8                        | 90426<br>90427                              | (1250) |
| 13000                | 8.5 x 20.5 x 18.5                                            | 1.9                        | 90428                                       | (1200) |
| 15000                | 9.0 x 21.0 x 18.5                                            | 2.1                        | 90429                                       | (1100) |
| C (μF)               | Pitch = 22.5 mm ± 1.0 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                            |                                             |        |
| 0.016<br>0.018       | 6.0 x 22.0 x 26.0                                            | 2.2                        | 90431<br>90432                              | (750)  |
| 0.02<br>0.022        | 6.5 x 22.5 x 26.0                                            | 2.5                        | 90433<br>90434                              | (700)  |
| 0.024                | 7.0 x 23.0 x 26.0                                            | 2.7                        | 90435                                       | (600)  |
| 0.027<br>0.03        | 7.5 x 23.5 x 26.0                                            | 3.1                        | 90436<br>90437                              | (550)  |
| 0.033                | 8.0 x 24.0 x 26.0                                            | 3.4                        | 90438                                       | (500)  |
| 0.036<br>0.039       | 8.5 x 24.5 x 26.0                                            | 3.8                        | 90439<br>90224                              | (450)  |
| 0.043                | 9.0 x 25.0 x 26.0                                            | 4.1                        | 90441                                       | (450)  |
| C (μF)               | Pitch = 27.5 mm ± 1.0 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                            |                                             |        |
| 0.047                | 7.0 x 23.0 x 30.0                                            | 3.1                        | 90442                                       | (800)  |
| 0.051<br>0.056       | 7.5 x 23.5 x 30.0                                            | 3.4                        | 90443<br>90444                              | (600)  |
| 0.062                | 8.0 x 24.0 x 30.0                                            | 3.8                        | 90445                                       | (550)  |
| 0.068                | 8.5 x 24.5 x 30.0                                            | 4.0                        | 90446                                       | (550)  |
| 0.075                | 9.0 x 25.0 x 30.0                                            | 4.4                        | 90447                                       | (450)  |
| 0.082                | 9.5 x 25.5 x 30.0                                            | 4.7                        | 90448                                       | (450)  |
| 0.091                | 10.0 x 26.0 x 30.0                                           | 5.1                        | 90449                                       | (400)  |
| 0.1                  | 10.5 x 26.5 x 30.0                                           | 5.5                        | 90451                                       | (350)  |
| 0.11                 | 11.0 x 27.0 x 30.0                                           | 5.9                        | 90452                                       | (350)  |
| 0.12                 | 11.5 x 27.5 x 30.0                                           | 6.3                        | 90453                                       | (350)  |
| 0.13                 | 12.0 x 28.0x 30.0                                            | 6.8                        | 90454                                       | (350)  |
| 0.15                 | 12.0 x 28.5x 30.0                                            | 7.6                        | 90455                                       | (300)  |

**Notes**

<sup>(1)</sup> Net weight for short lead product only

• SPQ = Standard Packing Quantity

**SPECIFIC REFERENCE DATA (1600 V<sub>DC</sub>)**

| DESCRIPTION                                                           | VALUE                |           |
|-----------------------------------------------------------------------|----------------------|-----------|
| Tangent of loss angle at ( $\times 10^{-4}$ ):                        | 10 kHz               | 100 kHz   |
| Pitch = 10 mm, 15 mm and 7.5 mm (bent back)                           | $\leq 6$             | $\leq 10$ |
| Pitch = 22.5 mm                                                       | $\leq 6$             | $\leq 15$ |
| Pitch = 27.5 mm                                                       | $\leq 6$             | $\leq 20$ |
| Rated voltage pulse slope (dU/dt):                                    |                      |           |
| Pitch = 10 mm                                                         | 21 000 V/ $\mu$ s    |           |
| Pitch = 15 mm and 7.5 mm (bent back)                                  | 7000 V/ $\mu$ s      |           |
| Pitch = 22.5 mm                                                       | 4700 V/ $\mu$ s      |           |
| Pitch = 27.5 mm                                                       |                      |           |
| R between leads at 500 V, 1 min                                       | > 100 000 M $\Omega$ |           |
| R between interconnected leads and case, 500 V, 1 min                 | > 100 000 M $\Omega$ |           |
| Ionisation (AC) voltage (typical value)                               | > 550 V              |           |
| at 50 pC peak discharge                                               |                      |           |
| at 10 pC peak discharge                                               |                      |           |
| Withstanding (DC) voltage (cut off current 10 mA), rise time 1000 V/s | 2560 V, 1 min        |           |
| For C $\leq$ 47 nF                                                    |                      |           |
| For C > 47 nF                                                         |                      |           |
| Withstanding (DC) voltage between leads and case                      | 2840 V, 1 min        |           |
| Maximum application temperature                                       | 105 °C               |           |

**U<sub>RDC</sub> = 1600 V; U<sub>RAC</sub> = 500 V; U<sub>pp</sub> = 1400 V (kinked); C-tol. =  $\pm$  5 %**

| C      | DIMENSIONS<br>w x h (h') x l<br>(mm)                         | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 375 XXYYY AND PACKAGING |                            |                |                            |            |       |
|--------|--------------------------------------------------------------|----------------------------|---------------------------------------------|----------------------------|----------------|----------------------------|------------|-------|
|        |                                                              |                            | LOOSE IN BOX                                | REEL                       |                |                            | C<br>VALUE |       |
|        |                                                              |                            |                                             | Leads<br>5 mm ± 1.0 mm     | Original pitch | Pitch = 7.5 mm (bent back) |            | ..YYY |
|        |                                                              |                            |                                             |                            | Ø 500 mm       | Ø 500 mm                   | Ø 356 mm   |       |
|        |                                                              |                            | XX<br>(SPQ)                                 | XX<br>(SPQ)                | XX<br>(SPQ)    | XX<br>(SPQ)                |            |       |
| C (pF) | Pitch = 15.0 mm ± 0.4 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                            | Pitch = 15.0 mm                             | Pitch = 7.5 mm (bent back) |                |                            |            |       |
| 680    | 5.5 x 14.5 (15.0) x 18.5                                     | 0.75                       | 34... (2000)                                | 32... (1100)               | 36... (900)    | 38... (500)                | 681        |       |
| 750    |                                                              |                            |                                             |                            |                |                            | 751        |       |
| 820    |                                                              |                            |                                             |                            |                |                            | 821        |       |
| 910    | 6.0 x 15.0 (15.5) x 18.5                                     | 0.8                        | 34...(2000)                                 | 32... (1000)               | 36... (800)    | 38... (450)                | 911        |       |
| 1000   |                                                              | 0.85                       |                                             |                            |                |                            | 102        |       |
| 1100   |                                                              | 0.85                       |                                             |                            |                |                            | 112        |       |
| 1200   |                                                              | 0.90                       |                                             |                            |                |                            | 122        |       |
| 1300   |                                                              | 0.95                       |                                             |                            |                |                            | 132        |       |
| 1500   | 5.5 x 14.5 (16.0) x 18.5                                     | 1.1                        | 34... (2000)                                | 32... (1100)               | 36... (900)    | 38... (500)                | 152        |       |
| 1600   |                                                              |                            |                                             |                            |                |                            | 162        |       |
| 1800   | 6.0 x 15.0 (16.5) x 18.5                                     | 1.2                        | 34... (2000)                                | 32... (1000)               | 36... (800)    | 38... (450)                | 182        |       |
| 2000   | 6.5 x 15.5 (17.0) x 18.5                                     | 1.3                        | 34... (1500)                                | 32... (900)                | 36... (750)    | 38... (400)                | 202        |       |
| 2200   |                                                              |                            |                                             |                            |                |                            | 222        |       |
| 2400   | 7.0 x 16.0 (17.5) x 18.5                                     | 1.4                        | 34... (1500)                                | 32... (800)                | 36... (700)    | 38... (400)                | 242        |       |
| 2700   | 7.5 x 16.5 (18.0) x 18.5                                     | 1.6                        | 34... (1250)                                | 32... (800)                | 36... (650)    | 38... (350)                | 272        |       |
| 3000   |                                                              |                            |                                             |                            |                |                            | 302        |       |
| 3300   | 8.0 x 17.0 (18.5) x 18.5                                     | 1.7                        | 34... (1250)                                | 32... (750)                | 36... (600)    | 38... (350)                | 332        |       |
| 3600   | 8.5 x 17.5 (19.0) x 18.5                                     | 1.8                        | 34... (1000)                                | 32... (700)                | 36... (550)    | 38... (300)                | 362        |       |
| 3900   | 9.0 x 18.5 (19.5) x 18.5                                     | 2.0                        | 34... (1000)                                | 32... (650)                | 36... (550)    | 38... (300)                | 392        |       |
| 4300   |                                                              |                            |                                             |                            |                |                            | 432        |       |

**Notes**

- <sup>(1)</sup> Net weight for short lead product only
- Loose in box, all lengths have same SPQ
  - SPQ = Standard Packing Quantity



AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents  
KP/MKP Radial Lacquered Type

| C      | DIMENSIONS<br>w x h (h') x l<br>(mm)                         | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 375 XYYYY AND PACKAGING |                            |                |                            |            |       |  |  |
|--------|--------------------------------------------------------------|----------------------------|---------------------------------------------|----------------------------|----------------|----------------------------|------------|-------|--|--|
|        |                                                              |                            | LOOSE IN BOX                                | REEL                       |                |                            | C<br>VALUE |       |  |  |
|        |                                                              |                            |                                             | Leads<br>5 mm ± 1.0 mm     | Original pitch | Pitch = 7.5 mm (bent back) |            | ..YYY |  |  |
|        |                                                              |                            |                                             |                            | Ø 500 mm       | Ø 500 mm                   | Ø 356 mm   |       |  |  |
|        |                                                              |                            | XX<br>(SPQ)                                 | XX<br>(SPQ)                | XX<br>(SPQ)    | XX<br>(SPQ)                |            |       |  |  |
| C (µF) | Pitch = 22.5 mm ± 0.4 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                            | Pitch = 22.5 mm                             | Pitch = 7.5 mm (bent back) |                |                            |            |       |  |  |
| 0.0047 | 6.0 x 19.0 x 26.0                                            | 2.0                        | 34...<br>(800)                              | -                          | -              | -                          | 472        |       |  |  |
| 0.0051 |                                                              |                            |                                             |                            |                |                            | 512        |       |  |  |
| 0.0056 |                                                              |                            |                                             |                            |                |                            | 562        |       |  |  |
| 0.0062 | 6.5 x 19.5 x 26.0                                            | 2.1                        | 34...<br>(750)                              |                            |                |                            | 622        |       |  |  |
| 0.0068 |                                                              |                            |                                             |                            |                |                            | 682        |       |  |  |
| 0.0075 | 7.0 x 20.0 x 26.0                                            | 2.3                        | 34...<br>(650)                              |                            |                |                            | 752        |       |  |  |
| 0.0082 |                                                              |                            |                                             |                            |                |                            | 822        |       |  |  |
| 0.0091 | 7.5 x 20.5 x 26.0                                            | 2.5                        | 34...<br>(600)                              |                            |                |                            | 912        |       |  |  |
| 0.01   | 8.0 x 21.0 x 26.0                                            | 2.6                        | 34...<br>(550)                              |                            |                |                            | 103        |       |  |  |
| 0.011  | 8.5 x 21.5 x 26.0                                            | 2.9                        | 34...<br>(500)                              |                            |                |                            | 113        |       |  |  |
| 0.012  |                                                              |                            |                                             |                            |                |                            | 123        |       |  |  |
| 0.013  | 9.0 x 22.0 x 26.0                                            | 3.1                        | 34...<br>(450)                              |                            |                |                            | 133        |       |  |  |
| 0.015  | 9.5 x 22.5 x 26.0                                            | 3.5                        | 34...<br>(400)                              |                            |                |                            | 153        |       |  |  |
| 0.016  | 10.0 x 23.0 x 26.0                                           | 3.6                        | 34...<br>(400)                              |                            |                |                            | 163        |       |  |  |
| 0.018  | 10.5 x 23.5 x 26.0                                           | 4.0                        | 34...<br>(350)                              |                            |                |                            | 183        |       |  |  |
| C (µF) | Pitch = 27.5 mm ± 0.5 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                            | Pitch = 27.5 mm                             | Pitch = 7.5 mm (bent back) |                |                            |            |       |  |  |
| 0.02   | 9.0 x 22.0 x 30.0                                            | 4.2                        | 34...<br>(550)                              | -                          | -              | -                          | 203        |       |  |  |
| 0.022  | 9.5 x 22.5 x 30.0                                            | 4.4                        | 34...<br>(500)                              |                            |                |                            | 223        |       |  |  |
| 0.024  | 10.0 x 23.0 x 30.0                                           | 4.7                        | 34...<br>(500)                              |                            |                |                            | 243        |       |  |  |
| 0.027  | 10.5 x 23.5 x 30.0                                           | 5.2                        | 34...<br>(450)                              |                            |                |                            | 273        |       |  |  |
| 0.03   | 11.0 x 24.0 x 30.0                                           | 5.6                        | 34...<br>(400)                              |                            |                |                            | 303        |       |  |  |
| 0.033  | 11.5 x 24.5 x 30.0                                           | 6.0                        | 34...<br>(400)                              |                            |                |                            | 333        |       |  |  |
| 0.036  | 12.0 x 25.0 x 30.0                                           | 6.5                        | 34...<br>(350)                              |                            |                |                            | 363        |       |  |  |
| 0.039  | 12.5 x 25.5 x 30.0                                           | 6.9                        | 34...<br>(350)                              |                            |                |                            | 393        |       |  |  |

**Notes**

- <sup>(1)</sup> Net weight for short lead product only
- Loose in box, all lengths have same SPQ
  - SPQ = Standard Packing Quantity

# KP/MKP 375



## Vishay BCcomponents AC and Pulse Metallized Polypropylene Film Capacitors KP/MKP Radial Lacquered Type

$U_{RDC} = 1600 \text{ V}$ ;  $U_{RAC} = 500 \text{ V}$ ;  $U_{pp} = 1400 \text{ V}$  (lock lead); C-tol. =  $\pm 5 \%$

| C                                   | DIMENSIONS<br>w x h (h') x l<br>(mm)                         | MASS<br>(g) <sup>(1)</sup>           | CATALOG NUMBER BFC2 375 XYYYY AND PACKAGING |        |
|-------------------------------------|--------------------------------------------------------------|--------------------------------------|---------------------------------------------|--------|
|                                     |                                                              |                                      | LOOSE IN BOX                                |        |
|                                     |                                                              |                                      | l <sub>t</sub> = 4.0 mm + 1.0 mm/- 0.5 mm   |        |
|                                     |                                                              |                                      |                                             | (SPQ)  |
| C (pF)                              | Pitch = 15.0 mm ± 1.0 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                                      |                                             |        |
| 680<br>750<br>820                   | 5.5 x 17.5 x 18.5                                            | 0.75                                 | 90456<br>90457<br>90458                     | (2000) |
| 910<br>1000<br>1100<br>1200<br>1300 | 6.0 x 18.0 x 18.5                                            | 0.80<br>0.85<br>0.85<br>0.90<br>0.95 | 90459<br>90461<br>90462<br>90463<br>90464   | (2000) |
| 1500<br>1600                        | 5.5 x 17.5 x 18.5                                            | 1.1                                  | 90465<br>90466                              | (2000) |
| 1800                                | 6.0 x 18.0 x 18.5                                            | 1.2                                  | 90467                                       | (2000) |
| 2000<br>2200                        | 6.5 x 18.5 x 18.5                                            | 1.3                                  | 90468<br>90469                              | (1750) |
| 2400                                | 7.0 x 19.0 x 18.5                                            | 1.4                                  | 90471                                       | (1500) |
| 2700<br>3000                        | 7.5 x 19.5 x 18.5                                            | 1.6                                  | 90472<br>90473                              | (1400) |
| 3300                                | 8.0 x 20.0 x 18.5                                            | 1.9                                  | 90141                                       | (1250) |
| 3600                                | 8.5 x 20.5 x 18.5                                            | 2.3                                  | 90142                                       | (1200) |
| 3900<br>4300                        | 9.0 x 21.5 x 18.5                                            | 2.5                                  | 90143<br>90144                              | (1100) |
| C (μF)                              | Pitch = 22.5 mm ± 1.0 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                                      |                                             |        |
| 0.0047<br>0.0051<br>0.0056          | 6.0 x 22.0 x 26.0                                            | 2.4                                  | 90145<br>90146<br>90147                     | (750)  |
| 0.0062<br>0.0068                    | 6.5 x 22.5 x 26.0                                            | 2.6                                  | 90148<br>90149                              | (700)  |
| 0.0075<br>0.0082<br>0.0083          | 7.0 x 23.0 x 26.0                                            | 2.8                                  | 90151<br>90152<br>90202                     | (600)  |
| 0.0091                              | 7.5 x 23.5 x 26.0                                            | 2.9                                  | 90153                                       | (550)  |
| 0.01                                | 8.0 x 24.0 x 26.0                                            | 3.2                                  | 90154                                       | (500)  |
| 0.011<br>0.012                      | 8.5 x 24.5 x 26.0                                            | 3.4                                  | 90155<br>90156                              | (450)  |
| 0.013                               | 9.0 x 25.0 x 26.0                                            | 3.6                                  | 90157                                       | (450)  |
| 0.015                               | 9.5 x 25.5 x 26.0                                            | 4.0                                  | 90158                                       | (400)  |
| 0.016                               | 10.0 x 26.0 x 26.0                                           | 4.3                                  | 90159                                       | (350)  |
| 0.018                               | 10.5 x 26.5 x 26.0                                           | 4.7                                  | 90161                                       | (350)  |
| C (μF)                              | Pitch = 27.5 mm ± 1.0 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                                      |                                             |        |
| 0.02                                | 9.0 x 25.0 x 30.0                                            | 4.2                                  | 90474                                       | (450)  |
| 0.022                               | 9.5 x 25.5 x 30.0                                            | 4.4                                  | 90475                                       | (450)  |
| 0.024                               | 10.0 x 26.0 x 30.0                                           | 4.7                                  | 90476                                       | (400)  |
| 0.027                               | 10.5 x 26.5 x 30.0                                           | 5.2                                  | 90477                                       | (350)  |
| 0.03                                | 11.0 x 27.0 x 30.0                                           | 5.6                                  | 90478                                       | (350)  |
| 0.033                               | 11.5 x 27.5 x 30.0                                           | 6.0                                  | 90479                                       | (350)  |
| 0.036                               | 12.0 x 28.0 x 30.0                                           | 6.5                                  | 90481                                       | (300)  |
| 0.039                               | 12.5 x 28.5 x 30.0                                           | 6.9                                  | 90482                                       | (300)  |

### Notes

- <sup>(1)</sup> Net weight for short lead product only
- SPQ = Standard Packing Quantity



# AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents

## KP/MKP Radial Lacquered Type

**SPECIFIC REFERENCE DATA (2000 V<sub>DC</sub>)**

| DESCRIPTION                                                                                                                         | VALUE                |           |
|-------------------------------------------------------------------------------------------------------------------------------------|----------------------|-----------|
| Tangent of loss angle at ( $\times 10^{-4}$ ):<br>Pitch = 10 mm, 15 mm and 7.5 mm (bent back)<br>Pitch = 22.5 mm<br>Pitch = 27.5 mm | 10 kHz               | 100 kHz   |
|                                                                                                                                     | $\leq 6$             | $\leq 10$ |
|                                                                                                                                     | $\leq 6$             | $\leq 10$ |
|                                                                                                                                     | $\leq 6$             | $\leq 15$ |
| Rated voltage pulse slope (dU/dt):<br>Pitch = 10 mm<br>Pitch = 15 mm and 7.5 mm (bent back)<br>Pitch = 22.5 mm<br>Pitch = 27.5 mm   | 30 000 V/ $\mu$ s    |           |
|                                                                                                                                     | 10 000 V/ $\mu$ s    |           |
|                                                                                                                                     | 6700 V/ $\mu$ s      |           |
|                                                                                                                                     |                      |           |
| R between leads at 500 V, 1 min                                                                                                     | > 100 000 M $\Omega$ |           |
| R between interconnected leads and case, 500 V, 1 min                                                                               | > 100 000 M $\Omega$ |           |
| Ionisation (AC) voltage (typical value)<br>at 50 pC peak discharge<br>at 20 pC peak discharge                                       | > 600 V              |           |
|                                                                                                                                     |                      |           |
|                                                                                                                                     |                      |           |
| Withstanding (DC) voltage (cut off current 10 mA), rise time 1000 V/s<br>For C $\leq$ 47 nF<br>For C > 47 nF                        | 3200 V, 1 min        |           |
|                                                                                                                                     |                      |           |
|                                                                                                                                     |                      |           |
| Withstanding (DC) voltage between leads and case                                                                                    | 2840 V, 1 min        |           |
| Maximum application temperature                                                                                                     | 105 °C               |           |

**U<sub>RDC</sub> = 2000 V; U<sub>RAC</sub> = 600 V; U<sub>pp</sub> = 1700 (kinked); C-tol. =  $\pm 5\%$**

| C      | DIMENSIONS<br>w x h (h') x l<br>(mm)                                 | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 375 XXYYY AND PACKAGING |                      |                            |                      |         |
|--------|----------------------------------------------------------------------|----------------------------|---------------------------------------------|----------------------|----------------------------|----------------------|---------|
|        |                                                                      |                            | LOOSE IN BOX                                | REEL                 |                            |                      | C VALUE |
|        |                                                                      |                            | Leads<br>5 mm $\pm$ 1.0 mm                  | Original pitch       | Pitch = 7.5 mm (bent back) |                      | ..YYY   |
|        |                                                                      |                            |                                             | $\varnothing$ 500 mm | $\varnothing$ 500 mm       | $\varnothing$ 356 mm |         |
| C (pF) | Pitch = 15.0 mm $\pm$ 0.4 mm; d <sub>t</sub> = 0.80 mm $\pm$ 0.08 mm |                            | XX<br>(SPQ)                                 | XX<br>(SPQ)          | XX<br>(SPQ)                | XX<br>(SPQ)          |         |
| 100    | 5.5 x 14.5 (15.0) x 18.5                                             | 0.75                       | 44...<br>(2000)                             | 42...<br>(1100)      | 46...<br>(900)             | 48...<br>(500)       | 101     |
| 110    |                                                                      | 0.75                       |                                             |                      |                            |                      | 111     |
| 120    |                                                                      | 0.75                       |                                             |                      |                            |                      | 121     |
| 130    |                                                                      | 0.75                       |                                             |                      |                            |                      | 131     |
| 150    |                                                                      | 0.75                       |                                             |                      |                            |                      | 151     |
| 160    |                                                                      | 0.75                       |                                             |                      |                            |                      | 161     |
| 180    |                                                                      | 0.75                       |                                             |                      |                            |                      | 181     |
| 200    |                                                                      | 0.75                       |                                             |                      |                            |                      | 201     |
| 220    |                                                                      | 0.75                       |                                             |                      |                            |                      | 221     |
| 240    |                                                                      | 0.75                       |                                             |                      |                            |                      | 241     |
| 270    |                                                                      | 0.75                       |                                             |                      |                            |                      | 271     |
| 300    |                                                                      | 0.75                       |                                             |                      |                            |                      | 301     |
| 330    |                                                                      | 0.75                       |                                             |                      |                            |                      | 331     |
| 360    |                                                                      | 0.75                       |                                             |                      |                            |                      | 361     |
| 390    |                                                                      | 0.75                       |                                             |                      |                            |                      | 391     |
| 430    |                                                                      | 0.75                       |                                             |                      |                            |                      | 431     |
| 470    |                                                                      | 0.80                       |                                             |                      |                            |                      | 471     |
| 510    |                                                                      | 0.80                       |                                             |                      |                            |                      | 511     |
| 560    |                                                                      | 0.80                       |                                             |                      |                            |                      | 561     |

**Notes**

- <sup>(1)</sup> Net weight for short lead product only  
• SPQ = Standard Packing Quantity

Vishay BCcomponents AC and Pulse Metallized Polypropylene Film Capacitors  
KP/MKP Radial Lacquered Type

| C      | DIMENSIONS<br>w x h (h') x l<br>(mm)                         | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 375 XXYYY AND PACKAGING |                            |                |                            |         |          |     |
|--------|--------------------------------------------------------------|----------------------------|---------------------------------------------|----------------------------|----------------|----------------------------|---------|----------|-----|
|        |                                                              |                            | LOOSE IN BOX                                | REEL                       |                |                            | C VALUE |          |     |
|        |                                                              |                            |                                             | Leads<br>5 mm ± 1.0 mm     | Original pitch | Pitch = 7.5 mm (bent back) |         |          |     |
|        |                                                              |                            |                                             |                            | Ø 500 mm       | Ø 500 mm                   |         | Ø 356 mm |     |
|        |                                                              |                            | XX<br>(SPQ)                                 | XX<br>(SPQ)                | XX<br>(SPQ)    | XX<br>(SPQ)                | ..YYY   |          |     |
| C (pF) | Pitch = 15.0 mm ± 0.4 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                            | Pitch = 15.0 mm                             | Pitch = 7.5 mm (bent back) |                |                            |         |          |     |
| 620    | 6.0 x 15.0 (15.5) x 18.5                                     | 0.85                       | 44...<br>(2000)                             | 42...<br>(1000)            | 46...<br>(800) | 48...<br>(450)             | 621     |          |     |
| 680    |                                                              | 0.85                       |                                             |                            |                |                            | 681     |          |     |
| 750    |                                                              | 0.90                       |                                             |                            |                |                            | 751     |          |     |
| 820    | 6.5 x 15.5 (16.0) x 18.5                                     | 0.95                       | 44...<br>(1500)                             | 42...<br>(900)             | 46...<br>(750) | 48...<br>(400)             | 821     |          |     |
| 910    | 5.5 x 14.5 (16.0) x 18.5                                     | 1.1                        | 44...<br>(2000)                             | 42...<br>(420)             | 46...<br>(900) | 48...<br>(500)             | 911     |          |     |
| 1000   | 6.0 x 15.0 (16.5) x 18.5                                     | 1.2                        | 44...<br>(2000)                             | 42...<br>(1000)            | 46...<br>(800) | 48...<br>(450)             | 102     |          |     |
| 1100   |                                                              |                            |                                             |                            |                |                            | 112     |          |     |
| 1200   |                                                              |                            |                                             |                            |                |                            | 122     |          |     |
| 1300   | 6.5 x 15.5 (17.0) x 18.5                                     | 1.3                        | 44...<br>(1500)                             | 42...<br>(900)             | 46...<br>(750) | 48...<br>(400)             | 132     |          |     |
| 1500   | 7.0 x 16.0 (17.5) x 18.5                                     | 1.4                        | 44...<br>(1500)                             | 42...<br>(800)             | 46...<br>(700) | 48...<br>(400)             | 152     |          |     |
| 1600   | 7.5 x 16.5 (18.0) x 18.5                                     | 1.5                        | 44...<br>(1250)                             | 42...<br>(800)             | 46...<br>(650) | 48...<br>(350)             | 162     |          |     |
| 1800   |                                                              |                            |                                             |                            |                |                            | 182     |          |     |
| 2000   | 8.0 x 17.0 (18.5) x 18.5                                     | 1.6                        | 44...<br>(1250)                             | 42...<br>(750)             | 46...<br>(600) | 48...<br>(350)             | 202     |          |     |
| 2200   | 8.5 x 17.5 (19.0) x 18.5                                     | 1.7                        | 44...<br>(1000)                             | 42...<br>(700)             | 46...<br>(550) | 48...<br>(300)             | 222     |          |     |
| 2400   | 9.0 x 18.0 (19.5) x 18.5                                     | 1.8                        | 44...<br>(1000)                             | 42...<br>(650)             | 46...<br>(550) | 48...<br>(300)             | 242     |          |     |
| 2700   | 9.5 x 18.5 (20.0) x 18.5                                     | 2.0                        | 44...<br>(900)                              | 42...<br>(600)             | 46...<br>(500) | 48...<br>(300)             | 272     |          |     |
| C (µF) | Pitch = 22.5 mm ± 0.4 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                            | Pitch = 22.5 mm                             | Pitch = 7.5 mm (bent back) |                |                            |         |          |     |
| 0.003  | 6.0 x 19.0 x 26.0                                            | 2.1                        | 44...<br>(800)                              | -                          | -              | -                          | 302     |          |     |
| 0.0033 |                                                              |                            |                                             |                            |                |                            |         | 332      |     |
| 0.0036 |                                                              |                            |                                             |                            |                |                            |         | 362      |     |
| 0.0039 |                                                              |                            |                                             |                            |                |                            |         | 392      |     |
| 0.0043 | 6.5 x 19.5 x 26.0                                            | 2.3                        | 44...<br>(750)                              |                            |                |                            |         |          | 432 |
| 0.0047 |                                                              |                            |                                             |                            |                |                            |         | 472      |     |
| 0.0051 | 7.0 x 20.0 x 26.0                                            | 2.6                        | 44...<br>(650)                              |                            |                |                            |         |          | 512 |
| 0.0056 |                                                              |                            |                                             |                            |                |                            |         | 562      |     |
| 0.0062 | 7.5 x 20.5 x 26.0                                            | 2.8                        | 44...<br>(600)                              |                            |                |                            |         |          | 622 |
| 0.0068 | 8.0 x 21.0 x 26.0                                            | 3.0                        | 44...<br>(550)                              |                            |                |                            |         |          | 682 |
| 0.0075 |                                                              |                            |                                             |                            |                |                            |         | 752      |     |
| 0.0082 | 8.5 x 21.5 x 26.0                                            | 3.3                        | 44...<br>(500)                              |                            |                |                            |         |          | 822 |
| 0.0091 | 9.0 x 22.0 x 26.0                                            | 3.6                        | 44...<br>(450)                              |                            |                |                            |         |          | 912 |
| 0.01   | 9.5 x 22.5 x 26.0                                            | 3.8                        | 44...<br>(400)                              |                            |                | 103                        |         |          |     |

**Notes**

- <sup>(1)</sup> Net weight for short lead product only  
• SPQ = Standard Packing Quantity



AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents  
KP/MKP Radial Lacquered Type

| C      | DIMENSIONS<br>w x h (h') x l<br>(mm)                         | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 375 XYYYY AND PACKAGING |                        |                |                            |         |             |
|--------|--------------------------------------------------------------|----------------------------|---------------------------------------------|------------------------|----------------|----------------------------|---------|-------------|
|        |                                                              |                            | LOOSE IN BOX                                | REEL                   |                |                            | C VALUE |             |
|        |                                                              |                            |                                             | Leads<br>5 mm ± 1.0 mm | Original pitch | Pitch = 7.5 mm (bent back) |         |             |
|        |                                                              |                            |                                             |                        | Ø 500 mm       | Ø 500 mm                   |         | Ø 356 mm    |
|        |                                                              |                            |                                             |                        | XX<br>(SPQ)    | XX<br>(SPQ)                |         | XX<br>(SPQ) |
| C (µF) | Pitch = 27.5 mm ± 0.5 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm | Pitch = 27.5 mm            | Pitch = 7.5 mm (bent back)                  |                        |                |                            |         |             |
| 0.011  | 9.0 x 22.0 x 30.0                                            | 3.8                        | 44...<br>(550)                              | -                      | -              | -                          | 113     |             |
| 0.012  | 9.5 x 22.5 x 30.0                                            | 4.1                        | 44...<br>(500)                              |                        |                |                            | 123     |             |
| 0.013  | 10.0 x 23.0 x 30.0                                           | 4.4                        | 44...<br>(500)                              |                        |                |                            | 133     |             |
| 0.015  | 10.5 x 23.5 x 30.0                                           | 4.9                        | 44...<br>(450)                              |                        |                |                            | 153     |             |
| 0.016  | 11.0 x 24.0 x 30.0                                           | 5.1                        | 44...<br>(400)                              |                        |                |                            | 163     |             |
| 0.018  | 11.5 x 24.5 x 30.0                                           | 5.6                        | 44...<br>(400)                              |                        |                |                            | 183     |             |
| 0.02   | 12.5 x 25.5 x 30.0                                           | 6.1                        | 44...<br>(350)                              |                        |                |                            | 203     |             |
| 0.022  | 13.0 x 26.0 x 30.0                                           | 6.5                        | 44...<br>(300)                              |                        |                |                            | 223     |             |

**Notes**

- <sup>(1)</sup> Net weight for short lead product only
- Loose in box, all lengths have same SPQ
- SPQ = Standard Packing Quantity

U<sub>RDC</sub> = 2000 V; U<sub>RAC</sub> = 600 V; U<sub>pp</sub> = 1700 V (lock lead)

| C      | DIMENSIONS<br>w x h (h') x l<br>(mm)                         | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 375 XYYYY AND PACKAGING |        |
|--------|--------------------------------------------------------------|----------------------------|---------------------------------------------|--------|
|        |                                                              |                            | LOOSE IN BOX                                |        |
|        |                                                              |                            | l <sub>t</sub> = 4.0 mm + 1.0 mm/- 0.5 mm   |        |
|        |                                                              |                            | (SPQ)                                       |        |
| C (pF) | Pitch = 15.0 mm ± 1.0 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                            |                                             |        |
| 100    | 5.5 x 17.5 x 18.5                                            | 0.75                       | 90483                                       | (2000) |
| 110    |                                                              | 0.75                       | 90484                                       |        |
| 120    |                                                              | 0.75                       | 90485                                       |        |
| 130    |                                                              | 0.75                       | 90486                                       |        |
| 150    |                                                              | 0.75                       | 90487                                       |        |
| 160    |                                                              | 0.75                       | 90488                                       |        |
| 180    |                                                              | 0.75                       | 90489                                       |        |
| 200    |                                                              | 0.75                       | 90491                                       |        |
| 220    |                                                              | 0.75                       | 90276                                       |        |
| 240    |                                                              | 0.75                       | 90492                                       |        |
| 270    |                                                              | 0.75                       | 90493                                       |        |
| 300    |                                                              | 0.75                       | 90494                                       |        |
| 330    |                                                              | 0.75                       | 90495                                       |        |
| 360    |                                                              | 0.75                       | 90496                                       |        |
| 390    |                                                              | 0.75                       | 90188                                       |        |
| 430    |                                                              | 0.75                       | 90497                                       |        |
| 470    |                                                              | 0.80                       | 90498                                       |        |
| 510    |                                                              | 0.80                       | 90499                                       |        |
| 560    |                                                              | 0.80                       | 90501                                       |        |

**Note**

- SPQ = Standard Packing Quantity

Vishay BCcomponents AC and Pulse Metallized Polypropylene Film Capacitors  
KP/MKP Radial Lacquered Type

| C      | DIMENSIONS<br>w x h (h') x l<br>(mm)                         | MASS<br>(g) <sup>(1)</sup> | CATALOG NUMBER BFC2 375 XYYYY AND PACKAGING |        |
|--------|--------------------------------------------------------------|----------------------------|---------------------------------------------|--------|
|        |                                                              |                            | LOOSE IN BOX                                |        |
|        |                                                              |                            | l <sub>t</sub> = 4.0 mm + 1.0 mm/- 0.5 mm   |        |
|        |                                                              |                            |                                             | (SPQ)  |
| C (pF) | Pitch = 15.0 mm ± 1.0 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                            |                                             |        |
| 620    | 6.0 x 18.0 x 18.5                                            | 0.85                       | 90502                                       | (2000) |
| 680    |                                                              | 0.85                       | 90229                                       |        |
| 750    |                                                              | 0.90                       | 90503                                       |        |
| 820    | 6.5 x 18.5 x 18.5                                            | 0.95                       | 90504                                       | (1750) |
| 910    | 5.5 x 17.5 x 18.5                                            | 1.1                        | 90505                                       | (2000) |
| 1000   | 6.0 x 18.0 x 18.5                                            | 1.3                        | 90225                                       | (2000) |
| 1100   |                                                              |                            | 90506                                       |        |
| 1200   |                                                              |                            | 90226                                       |        |
| 1300   | 6.5 x 18.5 x 18.5                                            | 1.3                        | 90507                                       | (1750) |
| 1500   | 7.0 x 19.0 x 18.5                                            | 1.5                        | 90266                                       | (1500) |
| 1600   | 7.5 x 19.5 x 18.5                                            | 1.7                        | 90508                                       | (1400) |
| 1800   |                                                              |                            | 90237                                       |        |
| 2000   | 8.0 x 20.0 x 18.5                                            | 1.7                        | 90509                                       | (1250) |
| 2200   | 8.5 x 20.5 x 18.5                                            | 2.3                        | 90227                                       | (1200) |
| 2400   | 9.0 x 21.0 x 18.5                                            | 1.8                        | 90511                                       | (1100) |
| 2700   | 9.5 x 21.5 x 18.5                                            | 2.7                        | 90228                                       | (1000) |
| C (μF) | Pitch = 22.5 mm ± 1.0 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                            |                                             |        |
| 0.003  | 6.0 x 22.0 x 26.0                                            | 2.2                        | 90512                                       | (750)  |
| 0.0033 |                                                              |                            | 90162                                       |        |
| 0.0036 |                                                              |                            | 90163                                       |        |
| 0.0039 |                                                              |                            | 90164                                       |        |
| 0.0043 | 6.5 x 22.5 x 26.0                                            | 2.4                        | 90165                                       | (700)  |
| 0.0047 |                                                              |                            | 90166                                       |        |
| 0.0051 | 7.0 x 23.0 x 26.0                                            | 2.6                        | 90167                                       | (600)  |
| 0.0056 |                                                              |                            | 90168                                       |        |
| 0.0062 | 7.5 x 23.5 x 26.0                                            | 2.8                        | 90169                                       | (550)  |
| 0.0068 | 8.0 x 24.0 x 26.0                                            | 3.0                        | 90171                                       | (500)  |
| 0.0075 |                                                              |                            | 90172                                       |        |
| 0.0082 | 8.5 x 24.5 x 26.0                                            | 3.2                        | 90173                                       | (450)  |
| 0.0091 | 9.0 x 25.0 x 26.0                                            | 3.5                        | 90174                                       | (450)  |
| 0.01   | 9.5 x 25.5 x 26.0                                            | 3.8                        | 90175                                       | (400)  |
| C (μF) | Pitch = 27.5 mm ± 1.0 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm |                            |                                             |        |
| 0.011  | 9.0 x 25.0 x 30.0                                            | 4.4                        | 90176                                       | (450)  |
| 0.012  | 9.5 x 25.5 x 30.0                                            | 4.6                        | 90177                                       | (450)  |
| 0.013  | 10.0 x 26.0 x 30.0                                           | 5.0                        | 90178                                       | (400)  |
| 0.015  | 10.5 x 26.5 x 30.0                                           | 5.4                        | 90179                                       | (350)  |
| 0.016  | 11.0 x 27.0 x 30.0                                           | 5.8                        | 90181                                       | (350)  |
| 0.018  | 11.5 x 27.5 x 30.0                                           | 6.2                        | 90182                                       | (350)  |
| 0.02   | 12.5 x 28.5 x 30.0                                           | 6.1                        | 90513                                       | (300)  |
| 0.022  | 13.0 x 29.0 x 30.0                                           | 6.5                        | 90514                                       | (250)  |

**Notes**

- <sup>(1)</sup> Net weight for short lead product only  
• SPQ = Standard Packing Quantity



## **MOUNTING**

### **Normal Use**

The capacitors are designed for mounting on printed-circuit boards. The capacitors packed in bandoliers are designed for mounting in printed-circuit boards by means of automatic insertion machines.

For detailed tape specifications refer to "Packaging information" [www.vishay.com/doc?28139](http://www.vishay.com/doc?28139) or end of catalog

### **Specific Method of Mounting to Withstand Vibration and Shock**

- For pitches  $\leq 15$  mm capacitors shall be mechanically fixed by the leads
- For larger pitches the capacitors shall be mounted in the same way and the body clamped

### **Storage Temperature**

- Storage temperature:  $T_{stg} = -25\text{ }^{\circ}\text{C}$  to  $+40\text{ }^{\circ}\text{C}$  with RH maximum 80 % without condensation

### **Ratings and Characteristics Reference Conditions**

Unless otherwise specified, all electrical values apply to an ambient temperature of  $23\text{ }^{\circ}\text{C} \pm 1\text{ }^{\circ}\text{C}$ , an atmospheric pressure of 86 kPa to 106 kPa and a relative humidity of  $50\text{ \%} \pm 2\text{ \%}$ .

For reference testing, a conditioning period shall be applied over  $96\text{ h} \pm 4\text{ h}$  by heating the products in a circulating air oven at the rated temperature and a relative humidity not exceeding 20 %.

### CHARACTERISTICS

Capacitance as a function of ambient temperature  
(typical curve)




Impedance as a function of frequency  
(typical curve)



Max. DC voltage as a function of temperature



Max. allowed component temperature rise  
as a function of ambient temperature



AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents  
KP/MKP Radial Lacquered Type

Max. RMS voltage (sinewave) as a function of frequency



Max. RMS voltage (sinewave) as a function of frequency



Max. RMS voltage (sinewave) as a function of frequency



Max. RMS voltage (sinewave) as a function of frequency



Max. RMS voltage (sinewave) as a function of frequency



Max. RMS voltage (sinewave) as a function of frequency



Max. RMS voltage (sinewave) as a function of frequency



Max. RMS voltage (sinewave) as a function of frequency



Tangent of loss angle (typical curve)



1. KP/MPK 10.0 mm and 15 mm pitch all versions  
22.5 mm pitch, 1000 V, 1600 V, 2000 V and 2500 V versions
2. KP/MPK 22.5 mm pitch, 630 V versions  
27.5 mm pitch, 1000 V, 1600 V and 2000 V versions
3. KP/MPK 27.5 mm pitch, 630 V versions

Maximum curves



1. KP/MPK 10.0 mm and 15 mm pitch all versions  
22.5 mm pitch, 1000 V, 1600 V, 2000 V and 2500 V versions
2. KP/MPK 22.5 mm pitch, 630 V versions  
27.5 mm pitch, 1000 V, 1600 V and 2000 V versions
3. KP/MPK 27.5 mm pitch, 630 V versions

Insulation resistance as a function of ambient temperature



**HEAT CONDUCTIVITY (G) AS A FUNCTION OF (ORIGINAL) PITCH AND CAPACITOR BODY THICKNESS IN mW/°C**

| W <sub>max.</sub><br>(mm) | HEAT CONDUCTIVITY (mW/°C) |             |               |               |
|---------------------------|---------------------------|-------------|---------------|---------------|
|                           | PITCH 10 mm               | PITCH 15 mm | PITCH 22.5 mm | PITCH 27.5 mm |
| 4.0                       | 4.0                       | 5.0         | -             | -             |
| 4.5                       | 4.5                       | 6.0         | -             | -             |
| 5.0                       | 5.0                       | 6.0         | 12.0          | 13.0          |
| 5.5                       | 6.0                       | 6.5         | 13.0          | 15.0          |
| 6.0                       | 6.0                       | 6.5         | 13.0          | 15.0          |
| 6.5                       | 6.5                       | 8.0         | 15.0          | 17.0          |
| 7.0                       | -                         | 8.0         | 15.0          | 17.0          |
| 7.5                       | -                         | 9.0         | 17.0          | 18.0          |
| 8.0                       | -                         | 9.0         | 17.0          | 20.0          |
| 8.5                       | -                         | 11.0        | 18.0          | 20.0          |
| 9.0                       | -                         | 11.0        | 18.0          | 22.0          |
| 9.5                       | -                         | 12.0        | 20.0          | 22.0          |
| 10.0                      | -                         | 12.0        | 20.0          | 23.0          |
| 10.5                      | -                         | -           | 22.0          | 25.0          |
| 11.0                      | -                         | -           | 22.0          | 25.0          |
| 11.5                      | -                         | -           | 23.0          | 27.0          |
| 12.0                      | -                         | -           | -             | 27.0          |
| 12.5                      | -                         | -           | -             | 30.0          |
| 13.0                      | -                         | -           | -             | 30.0          |
| 13.5                      | -                         | -           | -             | 30.0          |
| 14.0                      | -                         | -           | -             | 30.0          |
| 14.5                      | -                         | -           | -             | 33.0          |
| 15.0                      | -                         | -           | -             | 33.0          |
| 15.5                      | -                         | -           | -             | 37.0          |
| 16.0                      | -                         | -           | -             | 37.0          |

**POWER DISSIPATION AND MAXIMUM COMPONENT TEMPERATURE RISE**

The power dissipation must be limited in order not to exceed the maximum allowed component temperature rise as a function of the free ambient temperature.

The power dissipation can be calculated according Type detail specification "HQN-384-01/101: Technical Information Film Capacitors

The component temperature rise ( $\Delta T$ ) can be measured (see section "Measuring the component temperature" for more details) or calculated by

$$\Delta T = P/G:$$

- $\Delta T$  = Component temperature rise (°C)
- $P$  = Power dissipation of the component (mW)
- $G$  = Heat conductivity of the component (mW/°C)

### MEASURING THE COMPONENT TEMPERATURE

A thermocouple must be attached to the capacitor body as in:



The temperature is measured in unloaded ( $T_{amb}$ ) and maximum loaded condition ( $T_C$ ).

The temperature rise is given by  $\Delta T = T_C - T_{amb}$ .

To avoid radiation or convection, the capacitor should be tested in a wind-free box.

### APPLICATION NOTE AND LIMITING CONDITIONS

To select the capacitor for a certain application, the following conditions must be checked:

1. The peak voltage ( $U_P$ ) shall not be greater than the rated DC voltage ( $U_{RDC}$ )
2. The peak-to-peak voltage ( $U_{PP}$ ) shall not be greater than the maximum ( $U_{P-P}$ ) to avoid the ionisation inception level
3. The voltage pulse slope ( $dU/dt$ ) shall not exceed the rated voltage pulse slope in an RC-circuit at rated voltage and without ringing. If the pulse voltage is lower than the rated DC voltage, the rated voltage pulse slope may be multiplied by  $U_{Rdc}$  and divided by the applied voltage.

For all other pulses following equation must be fulfilled:

$$2 \times \int_0^T \left( \frac{dU}{dt} \right)^2 \times dt < U_{Rdc} \times \left( \frac{dU}{dt} \right)_{rated}$$

T is the pulse duration.

4. The maximum component surface temperature rise must be lower than the limits

### EXAMPLE

$C = 10 \text{ nF}$  1600 V, KP/MPK

This is a signal as in the drawing below

$U_{P-P} = 1200 \text{ V}$ ;  $U_P = 1100 \text{ V}$ ;  $T_1 = 12 \text{ } \mu\text{s}$ ;  $T_2 = 64 \text{ } \mu\text{s}$

The ambient temperature is  $50 \text{ } ^\circ\text{C}$

Checking conditions:

1. The peak voltage  $U_P = 1100 \text{ V}$  is lower than  $1600 \text{ V}_{DC}$
2. The peak-to-peak voltage  $1200 \text{ V}$  is lower than  $2\sqrt{2} \times 550 \text{ Vac} = 1414 \text{ V}$
3. The voltage pulse slope ( $dU/dt$ ) =  $320 \text{ V}$  is much lower than  $7000 \text{ V}/\mu\text{s}$
4. The dissipated power is  $170 \text{ mW}$  as calculated with fourier terms

This gives a temperature rise of  $170 \text{ mW} / (17 \text{ mW}/^\circ\text{C}) = 10 \text{ } ^\circ\text{C}$  which is allowed acc. fig. "max. allowed temperature rise as a function of ambient temperature" for an ambient temperature of  $50 \text{ } ^\circ\text{C}$



**AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents  
KP/MKP Radial Lacquered Type****INSPECTION REQUIREMENTS****General Notes:**

Sub-clause numbers of tests and performance requirements refer to the “Sectional Specification, Publication IEC 60384-17 and Specific Reference Data”.

**Group C Inspection Requirements**

| SUB-CLAUSE NUMBER AND TEST                          | CONDITIONS                                                                                                                                                                                                                                          | PERFORMANCE REQUIREMENTS                                                                                                                                                                                     |
|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>SUB-GROUP C1A PART OF SAMPLE OF SUB-GROUP C1</b> |                                                                                                                                                                                                                                                     |                                                                                                                                                                                                              |
| 4.1 Dimensions (detail)                             |                                                                                                                                                                                                                                                     | As specified in chapters “General Data” of this specification                                                                                                                                                |
| 4.3.1 Initial measurements                          | Capacitance<br>Tangent of loss angle at 100 kHz                                                                                                                                                                                                     |                                                                                                                                                                                                              |
| 4.3 Robustness of terminations                      | Tensile: Load 10 N; 10 s<br>Bending: Load 5 N; 4 x 90°                                                                                                                                                                                              | No visible damage                                                                                                                                                                                            |
| 4.4 Resistance to soldering heat                    | Method: 1A<br>Solder bath: 280 °C ± 5 °C<br>Duration: 10 s                                                                                                                                                                                          |                                                                                                                                                                                                              |
| 4.14 Component solvent resistance                   | Isopropylalcohol at room temperature<br>Method: 2<br>Immersion time: 5 min ± 0.5 min<br>Recovery time: Min. 1 h, max. 2 h                                                                                                                           |                                                                                                                                                                                                              |
| 4.4.2 Final measurements                            | Visual examination<br><br>Capacitance<br><br>Tangent of loss angle                                                                                                                                                                                  | No visible damage<br>Legible marking<br><br>$ \Delta C/C  \leq 1 \% + 5 \text{ pF}$ of the value measured initially<br><br>Increase of $\tan \delta$ : $\leq 0.0005$<br>Compared to values measured in 4.3.1 |
| <b>SUB-GROUP C1B PART OF SAMPLE OF SUB-GROUP C1</b> |                                                                                                                                                                                                                                                     |                                                                                                                                                                                                              |
| 4.6.1 Initial measurements                          | Capacitance<br>Tangent of loss angle at 100 kHz                                                                                                                                                                                                     |                                                                                                                                                                                                              |
| 4.15 Solvent resistance of the marking              | Isopropylalcohol at room temperature<br>Method: 1<br>Rubbing material: cotton wool<br>Immersion time: 5 min ± 0.5 min                                                                                                                               | No visible damage<br>Legible marking                                                                                                                                                                         |
| 4.6 Rapid change of temperature                     | $\theta A = - 55 \text{ °C}$<br>$\theta B = + 105 \text{ °C}$<br>5 cycles<br>Duration $t = 30 \text{ min}$                                                                                                                                          |                                                                                                                                                                                                              |
| 4.7 Vibration                                       | Visual examination<br>Mounting:<br>See section “Mounting” of this specification<br>Procedure B4<br>Frequency range: 10 Hz to 55 Hz<br>Amplitude: 0.75 mm or<br>Acceleration 98 m/s <sup>2</sup><br>(whichever is less severe)<br>Total duration 6 h | No visible damage                                                                                                                                                                                            |

| SUB-CLAUSE NUMBER AND TEST                                                         | CONDITIONS                                                                                                                                                                                    | PERFORMANCE REQUIREMENTS                                                                                                                                                                                                                                                                                                                             |
|------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 4.7.2 Final inspection                                                             | Visual examination                                                                                                                                                                            | No visible damage                                                                                                                                                                                                                                                                                                                                    |
| 4.9 Shock                                                                          | Mounting:<br>See section "Mounting" of this specification<br>Pulse shape: Half sine<br>Acceleration: 490 m/s <sup>2</sup><br>Duration of pulse: 11 ms                                         |                                                                                                                                                                                                                                                                                                                                                      |
| 4.9.3 Final measurements                                                           | Visual examination<br><br>Capacitance<br><br>Tangent of loss angle<br><br>Insulation resistance                                                                                               | No visible damage<br><br>For $C > 0.027\mu\text{F}$ : $ \Delta C/C  \leq 2\%$ or<br>for $C \leq 0.027\mu\text{F}$ : $ \Delta C/C  \leq 3\% + 5\text{ pF}$<br>of the value measured in 4.6.1.<br>Increase of $\tan \delta$ : $\leq 0.0005$<br>Compared to values measured in 4.6.1<br>As specified in chapter "General data" of this<br>specification |
| <b>SUB-GROUP C1 COMBINED SAMPLE<br/>OF SPECIMENS OF SUB-GROUPS<br/>C1A AND C1B</b> |                                                                                                                                                                                               |                                                                                                                                                                                                                                                                                                                                                      |
| 4.10 Climatic sequence                                                             |                                                                                                                                                                                               |                                                                                                                                                                                                                                                                                                                                                      |
| 4.10.2 Dry heat                                                                    | Temperature: + 105 °C<br>Duration: 16 h                                                                                                                                                       |                                                                                                                                                                                                                                                                                                                                                      |
| 4.10.3 Damp heat cyclic<br>Test Db, first cycle                                    |                                                                                                                                                                                               |                                                                                                                                                                                                                                                                                                                                                      |
| 4.10.4 Cold                                                                        | Temperature: - 55 °C<br>Duration: 2 h                                                                                                                                                         |                                                                                                                                                                                                                                                                                                                                                      |
| 4.10.6 Damp heat cyclic<br>Test Db, remaining cycles                               |                                                                                                                                                                                               |                                                                                                                                                                                                                                                                                                                                                      |
| 4.10.6.2 Final measurements                                                        | Voltage proof = $U_{\text{RDC}}$ for 1 min within 15 min<br>after removal from testchamber<br>Visual examination<br><br>Capacitance<br><br>Tangent of loss angle<br><br>Insulation resistance | No breakdown of flash-over<br><br>No visible damage<br>Legible marking<br>$ \Delta C/C  \leq 3\%$ of the value measured in<br>4.4.2 or 4.9.3<br>Increase of $\tan \delta$ : $\leq 0.001$<br>Compared to values measured in<br>4.3.1 or 4.6.1<br>$\geq 50\%$ of values specified in chapters<br>"General data" of this specification                  |
| <b>SUB-GROUP C2</b>                                                                |                                                                                                                                                                                               |                                                                                                                                                                                                                                                                                                                                                      |
| 4.11 Damp heat steady state                                                        | 56 days, 40 °C, 90 % to 95 % RH                                                                                                                                                               |                                                                                                                                                                                                                                                                                                                                                      |
| 4.11.1 Initial measurements                                                        | Capacitance<br>Tangent of loss angle at 1 kHz                                                                                                                                                 |                                                                                                                                                                                                                                                                                                                                                      |
| 4.11.3 Final measurements                                                          | Voltage proof = $U_{\text{RDC}}$ for 1 min within 15 min<br>after removal from testchamber<br>Visual examination<br><br>Capacitance<br><br>Tangent of loss angle<br><br>Insulation resistance | No breakdown of flash-over<br><br>No visible damage<br>Legible marking<br>$ \Delta C/C  \leq 1\% + 5\text{ pF}$ of the value measured in<br>4.11.1.<br>Increase of $\tan \delta \leq 0.0005$<br>Compared to values measured in 4.11.1<br>$\geq 50\%$ of values specified in section<br>"Insulation Resistance" of this specification                 |



AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents  
KP/MKP Radial Lacquered Type

| SUB-CLAUSE NUMBER AND TEST                                       | CONDITIONS                                                                                                                                                                                              | PERFORMANCE REQUIREMENTS                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>SUB GROUP C3</b>                                              |                                                                                                                                                                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| 4.12.1 Endurance                                                 | Duration: 2000 h<br>Temperature: 85 °C<br>Voltage: 1.25 x max. $U_{RDC}$ $V_{rms}$ , 50 Hz<br>Duration: 2000 h<br>Temperature: 105 °C                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| 4.12.1.1 Initial measurements<br><br>4.12.1.3 Final measurements | Voltage: 0.875 x max. $U_{RDC}$ $V_{rms}$ , 50 Hz<br>Capacitance<br>Tangent of loss angle at 100 kHz<br>Visual examination<br><br>Capacitance<br><br>Tangent of loss angle<br><br>Insulation resistance | No visible damage<br>Legible marking<br>Temperature: 85 °C<br>For $C > 0.056 \mu F$ : $ \Delta C/C  \leq 2 \% + 5 \text{ pF}$ or<br>for $C > 0.056 \mu F$ : $ \Delta C/C  \leq 3 \% + 5 \text{ pF}$<br>of the value measured in 4.12.1.1<br>Temperature: 105 °C<br>$ \Delta C/C  \leq 5 \% + 5 \text{ pF}$<br>Increase of $\tan \delta$ : $\leq 0.001$<br>Compared to values measured in 4.12.1<br>$\geq 50 \%$ of values specified in chapters<br>"General data" of this specification |
| <b>SUB-GROUP C4</b>                                              |                                                                                                                                                                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| 4.2.6 Temperature characteristics                                | Capacitance<br><br>Insulation resistance                                                                                                                                                                | As specified in section "Capacitance" of this specification<br>As specified in chapters "General data" of this specification                                                                                                                                                                                                                                                                                                                                                            |



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.