

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0009930500

Status:

Active

Overview:

kk

Description:

3.96mm (.156") Pitch KK® Crimp Terminal Housing, Friction Ramp, 5 Circuits, Glow Wire Compatible

Documents:

3D Model

Drawing (PDF)

Product Specification PS-99020-0087 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

UL

E29179

General

Product Family

Series

Overview

Product Name

Crimp Housings

3069

kk

KK®

Physical

Circuits (maximum)

Circuits Detail

Color - Resin

Flammability

Gender

Glow-Wire Compliant

Lock to Mating Part

Material - Resin

Number of Rows

Packaging Type

Panel Mount

Pitch - Mating Interface (in)

Pitch - Mating Interface (mm)

Temperature Range - Operating

5

5

Natural

94V-2

Female

Yes

Yes

Nylon

1

Bag

No

0.156 In

3.96 mm

0°C to +75°C

Material Info

Old Part Number

3069-G05


Reference - Drawing Numbers

Product Specification

Sales Drawing

PS-99020-0087

SD-3069-GN***



EU RoHS

ELV and RoHS
Compliant

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Halogen-Free

Need more information on product
environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of
Compliance, [click here](#)

Please visit the [Contact Us](#) section for any
non-product compliance questions.

China RoHS



Search Parts in this Series

3069Series


Mates With

[2220](#) , [3190](#) , [3192](#) , [3243](#), [3246](#), [A4042](#),
[41661](#) , [41662](#) , [41671](#) , [41672](#) , [41681](#) ,
[41682](#) , [41701](#) , [41711](#) , [41721](#) , [41741](#) ,
[41761](#) , [41771](#) , [41772](#) , [41791](#) , [41792](#) ,
[42441](#) , [42461](#) , [42471](#) , [42491](#) , [42492](#)



Use With

[2478](#) Crimp Terminals for 18-24 AWG, [2578](#)
Crimp Terminals for 22-26 AWG


PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION




OPTIONAL WINDOW DETAIL



RECOMMENDED P/C BOARD



LOCKING RAMP OPTIONAL
(2.5) .10



DIRECTION OF
TERMINAL INSERTION.

ENG. No. DESIGNATION

3069 - G N 2

"G" GWT (750°C) PA66 BALCK

"2" INDICATES HOUSING WITHOUT RAMP
"BLANK" INDICATES HOUSING WITH RAMP

NO. OF CKT'S

NOTES:

1. FOR USE WITH TERMINAL No. 2478 OR 2578
2. ASSEMBLED CONNECTOR MATES WITH (1.14)/0.045 SQUARE OR ROUND PIN.
3. EXTENDED PIN ENTRY WINDOWS ARE POSSIBLE.

No. OF CCTS.	C	D	No. OF CCTS.	C	D
14	(51.51 ± .03) 2.028 ± .01	(55.37 ± .03) 2.180 ± .01	2	(3.96 ± .03) .156 ± .005	(7.82 ± .03) .308 ± .01
15	(55.47 ± .03) 2.184 ± .01	(59.33 ± .03) 2.336 ± .01	3	(7.92 ± .03) .312 ± .005	(11.79 ± .03) .464 ± .01
16	(59.44 ± .03) 2.340 ± .01	(63.30 ± .03) 2.492 ± .01	4	(11.89 ± .03) .620 ± .005	(15.75 ± .03) .620 ± .01
17	(63.40 ± .03) 2.496 ± .01	(67.26 ± .03) 2.648 ± .01	5	(15.85 ± .03) .624 ± .005	(19.71 ± .03) .776 ± .01
18	(67.36 ± .03) 2.652 ± .01	(71.22 ± .03) 2.804 ± .01	6	(19.81 ± .03) .780 ± .005	(23.67 ± .03) .932 ± .01
19	(71.32 ± .03) 2.808 ± .01	(75.18 ± .03) 2.960 ± .01	7	(23.77 ± .03) .936 ± .005	(27.64 ± .03) 1.088 ± .01
20	(75.29 ± .03) 2.964 ± .01	(79.15 ± .03) 3.116 ± .01	8	(27.74 ± .03) 1.092 ± .005	(31.60 ± .03) 1.244 ± .01
			9	(31.70 ± .03) 1.248 ± .005	(35.56 ± .03) 1.400 ± .01
			10	(35.66 ± .03) 1.404 ± .005	(39.52 ± .03) 1.556 ± .01
			11	(39.62 ± .03) 1.560 ± .005	(43.48 ± .03) 1.712 ± .01
			12	(43.59 ± .03) 1.716 ± .005	(47.45 ± .03) 1.868 ± .01
			13	(47.55 ± .03) 1.872 ± .005	(51.41 ± .03) 2.024 ± .01

WORKMANAGER ERROR EC NO: E2008-0403 DRAWN:BRUTTE CHKD: CHIKO APPR:BMAGUIRE REV	DESCRIPTION	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM/IN		SCALE 4:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION			
				mm	INCH	DRAWN BY	DATE	TITLE				
			4 PLACES	± ---	± ---	BRIAN RUTLE	10/12/2007	HOUSING KK CONNECTOR (3.96)/0.156 CRIMP				
			3 PLACES	± ---	± .010	CHECKED BY	DATE	750 GLOW WIRE VERSION				
			2 PLACES	± 0.25	± .014	B. MAGUIRE	12/12/2007	MOLEX INCORPORATED				
			1 PLACE	± 0.35	± ---	APPROVED BY	DATE					
			ANGULAR ± 2 °		B. MAGUIRE	14/12/2007						
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO.		DOCUMENT NO.		SHEET NO.			
B	REV		SIZE A		SEE CHART		SD-3069-GN***		1 OF 2			
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION												

	10	9	8	7	6	5	4	3	2	1	
F	No. OF CCTS.	ENG. No.	PART No.	LOCKING RAMP							F
	2	3069-G02	09-93-0200	YES							
		↑ -G022	↑ -94-0200	NO							
	3	-G03	-93-0300	YES							
		-G032	-94-0300	NO							
	4	-G04	-93-0400	YES							
		-G042	-94-0400	NO							
	5	-G05	-93-0500	YES							
		-G052	-94-0500	NO							
	6	-G06	-93-0600	YES							
		-G062	-94-0600	NO							
	7	-G07	-93-0700	YES							
		-G072	-94-0700	NO							
	8	-G08	-93-0800	YES							
		-G082	-94-0800	NO							
	9	-G09	-93-0900	YES							
		-G092	-94-0900	NO							
	10	-G10	-93-1000	YES							
		-G102	-94-1000	NO							
	11	-G11	-93-1100	YES							
		-G112	-94-1100	NO							
	12	-G12	-93-1200	YES							
		-G122	-94-1200	NO							
	13	-G13	-93-1300	YES							
		-G132	-94-1300	NO							
	14	-G14	-93-1400	YES							
		-G142	-94-1400	NO							
	15	-G15	-93-1500	YES							
		-G152	-94-1500	NO							
	16	-G16	-93-1600	YES							
		-G162	-94-1600	NO							
	17	-G17	-93-1700	YES							
		-G172	-94-1700	NO							
	18	-G18	-93-1800	YES							
		-G182	-94-1800	NO							
	19	-G19	-93-1900	YES							
		-G192	-94-1900	NO							
	20	↓ -G20	↓ -93-2000	YES							
		3069-G202	09-94-2000	NO							
E											E
D											D
C											C
B											B
A											A

SEE SHEET 1

EC NO: E2008-0403

DRWN:BRUTTLE

CHKD:

APPR:BMAGUIRE

REV

2008/01/30

2008/01/30

DESCRIPTION

QUALITY SYMBOLS

▽=0

◻=0

2008/01/30

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± .010
2 PLACES	± 0.25	± .014
1 PLACE	± 0.35	± ---
ANGULAR ± 2 °		

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE

MM/IN

DRAWN BY	DATE
BRIAN RUTTLE	10/12/2007
CHECKED BY	DATE
B. MAGUIRE	12/12/2007
APPROVED BY	DATE
B. MAGUIRE	14/12/2007
MATERIAL NO.	

SCALE

1:1

DESIGN UNITS

METRIC

THIRD ANGLE PROJECTION

TITLE

HOUSING KK CONNECTOR (3.96)/0.156 CRIMP 750 GLOW WIRE VERSION

MOLEX INCORPORATED

DOCUMENT NO.

SD-3069-GN***

SHEET NO.

2 OF 2

SIZE

A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.