3M™ BOARDMOUNT SOCKET, 1502 SERIES

2.00MM X 2.00MM STRAIGHT AND SURFACE MOUNT, PLATED THROUGH HOLE



STRAIGHT VERSION



SURFACE MOUNT VERSION

[2] PHYSICAL:

INSULATOR:	
MATERIAL:	HIGH TEMP THERMOPLASTIC
CONTACT:	
MATERIAL:	COPPER ALLOY
PLATING:	
UNDER PLATING:	1.27-3.8µm [50-150µ"] NICKEL-OVERALL
WIPING AREA:	.76µm [30µ"] GOLD
SOLDER TAILS:	5.1µm [200µ"] MATTE TIN (RIA E1 & C1 APPLY)
MARKING:	ORIENTATION DELTA AND 3M LOGO (EXCEPT SURFACE MOUNT)

[2] ELECTRICAL:

CURRENT RATING:	1A
VOLTAGE RATING:	$150V_{AC}$ PER EIA-364-20
INSULATION RESISTANCE:	$>1 \times 10^9$ OHm AT $250V_{DC}$
WITHSTANDING VOLTAGE:	$500V_{DC}$ AT SEA LEVEL

[2] ENVIRONMENTAL:

TEMPERATURE RATING:	-55° C TO 105° C
PROCESS RATING:	MAX. 260° C (PER J-STD-020C)
MOISTURE SENSITIVITY LEVEL:	1 (PER J-STD-020C)

NOTES

1. REGULATORY INFORMATION: ROHS COMPLIANT. SEE THE REGULATORY INFORMATION APPENDIX (RIA) IN THE "ROHS COMPLIANCE" SECTION OF WWW.3MCONNECTORS.COM FOR COMPLIANCE INFORMATION.
2. IN THE EVENT OF CONFLICT BETWEEN THIS DATA AND THAT CONTAINED IN THE PRODUCT SPECIFICATION, THE PRODUCT SPECIFICATION TAKES PRECEDENT.
3. TAPE & REEL INCLUDE VACUUM PICK-UP CAP FOR PICK 'n PLACE HANDLING EQUIPMENT.
4. PARTS IN TRAY PACKAGING ARE SUPPLIED WITHOUT VACUUM CAP.
5. POSITIONS PER ROW, SUBTRACT 1, MULTIPLY BY 2MM SPACING.
6. OPTIONAL LOCATOR POSTS: POSITIONS PER ROW, MULTIPLY BY 2MM SPACING, THEN SUBTRACT 4MM. POSTS ARE ONLY AVAILABLE FOR POSITIONS 08 AND GREATER.

REV	ECO	ISSUE DATE AND DESCRIPTION	DRFT	CHKD
K	63282	SEP 03,2015 REDRAWN & REMOVED RIGHT ANGLE	JNC	ARM

DESIGN REFERENCE / NEXT ASSEMBLY / ACCESS CODES

DRFT: CASTIGLIONE — DATE: SEP 03,2015 — MFG — DATE

CHKD — DATE — APPVL: a. MATHEWS — DATE: SEP 03,2015

DIVISION

DIVISION CODE: EMSD

DO NOT SCALE DRAWING — SCALE: 6:1

THIRD ANGLE PROJECTION

INTERPRET PER ASME Y14.5 - 2009

MAX SURFACE ROUGHNESS: ☐ ALL SURFACES ☐ MARKED ONLY

TOLERANCES EXCEPT AS NOTED

INCHES: .0 ±.1; .00 ±.01; .000 ±.005; .0000 ±.0002

MILLIMETERS: 0 ±2; .0 ±.3; .00 ±.13; .000 ±.005

ANGLES ±

3M Center, St. Paul, MN 55144

© 3M COPYRIGHT 2017

This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.

TITLE: BOARDMOUNT SOCKET, 2MM X 2MM, STRAIGHT & SMT, PAC 20

CAGE NUMBER: 63282 — SIZE: D — DRAWING NO.: 78-5100-0519-8 — REV.: K

MODEL: 1502 — DET. LISTS ☐ YES ☒ NO — SHT 1 OF 4

DIMENSIONS: MM [INCH]
[INCH] FOR REF. ONLY

3M ELECTRONICS MATERIALS SOLUTIONS DIVISION
INTERCONNECT SOLUTIONS
http://www.3mconnectors.com

3M IS A TRADEMARK OF 3M COMPANY.
FOR TECHNICAL, SALES OR ORDERING INFORMATION CALL 800-225-5373

UL FILE NO: E68080

Image: K.3 Central Standard Time 12/7/2017 UTC offset

3M™ BOARDMOUNT SOCKET, 1502 SERIES

2.00MM X 2.00MM STRAIGHT AND SURFACE MOUNT, PLATED THROUGH HOLE





TABLE 1	
CONTACT QTY.	DIM. "A"
04	3.96 [.156]
06	5.87 [.231]
08	7.87 [.310]
10	9.88 [.389]
12	11.86 [.467]
14	13.87 [.546]
16	15.88 [.625]
18	17.88 [.704]
20	19.86 [.782]
22	21.87 [.861]
24	23.88 [.940]
26	25.88 [1.019]
28	27.86 [1.097]
30	29.87 [1.176]
32	31.88 [1.255]
34	33.88 [1.334]
36	35.86 [1.412]
38	37.87 [1.491]
40	39.88 [1.570]
42	41.88 [1.649]
44	43.87 [1.727]
46	45.87 [1.806]
48	47.88 [1.885]
50	49.89 [1.964]
52	51.87 [2.042]
54	53.87 [2.121]
56	55.88 [2.200]
58	57.86 [2.278]
60	59.87 [2.357]



RECOMMENDED HOLE PATTERN
(AS VIEWED FROM CONNECTOR SIDE)

ORDERING INFORMATION

STRAIGHT

1502XX-600X-RB

CONTACT QTY.: SEE TABLE 1

SOLDER TAIL LENGTH: DIMENSION "B"
1 = 1.4MM (SPECIAL ORDER)
2 = 2.54MM (STANDARD)

REV	ECO	ISSUE DATE AND DESCRIPTION	DRFT	CHKD
K	63282	SEP 03,2015 REDRAWN & REMOVED RIGHT ANGLE	JNC	ARM

DESIGN REFERENCE | NEXT ASSEMBLY | ACCESS CODES

DRFT: CASTIGLIONE | DATE: SEP 03,2015 | MFG | DATE

CHKD | DATE | APPVL: a. MATHEWS | DATE: SEP 03,2015

DIVISION | DIVISION CODE: EMSD

DO NOT SCALE DRAWING | SCALE: 6/1

THIRD ANGLE PROJECTION

INTERPRET PER ASME Y14.5 - 2009

MAX SURFACE ROUGHNESS: ☐ ALL SURFACES ☐ MARKED ONLY

TOLERANCES EXCEPT AS NOTED

INCHES: .0 ±.1 | .00 ±.01 | .000 ±.005 | .0000 ±.0002

MILLIMETERS: 0 ±2 | .0 ±.3 | .00 ±.13 | .000 ±.005

ANGLES ±

3M Center, St. Paul, MN 55144
© 3M COPYRIGHT 2017
This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.

TITLE: BOARDMOUNT SOCKET, 2MM X 2MM, STRAIGHT & SMT, PAC 20

CAGE NUMBER | SIZE: D | DRAWING NO.: 78-5100-0519-8 | REV.: K

MODEL: 1502 | DET. LISTS ☐ YES ☒ NO | SHT 2 OF 4

78-5100-0519-8 DRAWING NUMBER | K REVISION

Imaged: K.3 Central Standard Time 12/7/2017 UTC offset

3M™ BOARDMOUNT SOCKET, 1502 SERIES

2.00MM X 2.00MM STRAIGHT AND SURFACE MOUNT, PLATED THROUGH HOLE









RECOMMENDED PAD PATTERN
(AS VIEWED FROM CONNECTOR SIDE)

TABLE 1			
CONTACT QTY.	DIM. "A"	TAPE WIDTH	ORDER CODE
04	3.96 [.156]	N/A	N/A
06	5.87 [.231]	N/A	N/A
08	7.87 [.310]	24 MM	WB
10	9.88 [.389]	24 MM	WB
12	11.86 [.467]	24 MM	WB
14	13.87 [.546]	24 MM	WB
16	15.88 [.625]	24 MM	WB
18	17.88 [.704]	44 MM	WD
20	19.86 [.782]	44 MM	WD
22	21.87 [.861]	44 MM	WD
24	23.88 [.940]	44 MM	WD
26	25.88 [1.019]	44 MM	WD
28	27.86 [1.097]	44 MM	WD
30	29.87 [1.176]	44 MM	WD
32	31.88 [1.255]	56 MM	WE
34	33.88 [1.334]	56 MM	WE
36	35.86 [1.412]	56 MM	WE
38	37.87 [1.491]	56 MM	WE
40	39.88 [1.570]	56 MM	WE
42	41.88 [1.649]	56 MM	WE
44	43.87 [1.727]	72 MM	WF
46	45.87 [1.806]	72 MM	WF
48	47.88 [1.885]	72 MM	WF
50	49.89 [1.964]	72 MM	WF
52	51.87 [2.042]	72 MM	WF
54	53.87 [2.121]	72 MM	WF
56	55.88 [2.200]	72 MM	WF
58	57.86 [2.278]	88 MM	WG
60	59.87 [2.357]	88 MM	WG

ORDERING INFORMATION
SURFACE MOUNT
1502XX-20X0-RB-XX

CONTACT QTY.:
SEE TABLE 1

BOARD LOCATION POST:
0 = NONE (STANDARD)
2 = WITH BOARD LOCATION POSTS
(SPECIAL ORDER)

PACKAGING STYLE:
BLANK = TRAY PACKAGING
WX = TAPE & REEL PACKAGING
(SEE TABLE 1 FOR ORDERING CODE)

REV	ECO	ISSUE DATE AND DESCRIPTION	DRFT	CHKD
K	63282	SEP 03,2015 REDRAWN & REMOVED RIGHT ANGLE	JNC	ARM

DESIGN REFERENCE | NEXT ASSEMBLY | ACCESS CODES

DRFT: CASTIGLIONE DATE: SEP 03,2015 | MFG | DATE
CHKD | DATE | APPVL: Q. MATHEWS DATE: SEP 03,2015

DIVISION | DIVISION CODE: EMSD

DO NOT SCALE DRAWING | SCALE: 6/1

THIRD ANGLE PROJECTION

INTERPRET PER ASME Y14.5 - 2009

MAX SURFACE ROUGHNESS: ☐ ALL SURFACES ☐ MARKED ONLY

TOLERANCES EXCEPT AS NOTED

INCHES
.0 ±.1
.00 ±.01
.000 ±.005
.0000 ±.0002

MILLIMETERS
0 ±2
.0 ±.3
.00 ±.13
.000 ±.005

ANGLES ±

3M Center St. Paul, MN 55144

© 3M COPYRIGHT 2017
This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.

TITLE: BOARDMOUNT SOCKET, 2MM X 2MM, STRAIGHT & SMT, PAC 20

CAGE NUMBER | SIZE: D | DRAWING NO.: 78-5100-0519-8 | REV.: K

MODEL: 1502 | DET. LISTS ☐ YES ☒ NO | SHT 3 OF 4

78-5100-0519-8 (DRAWING NUMBER) K (REVISION)

Imaged: K.3 Central Standard Time 12/7/2017 UTC Offset

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

REV	ECO	ISSUE DATE AND DESCRIPTION	DRFT	CHKD
K	63282	SEP 03,2015 REDRAWN & REMOVED RIGHT ANGLE	JNC	ARM

DESIGN REFERENCE | NEXT ASSEMBLY

ACCESS CODES

DRFT: CASTIGLIONE | DATE: SEP 03,2015 | MFG | DATE

CHKD | DATE | APPVL: G. MATHEWS | DATE: SEP 03,2015

DIVISION

DIVISION CODE: EMSD

DO NOT SCALE DRAWING | SCALE 1/1

THIRD ANGLE PROJECTION

INTERPRET PER ASME Y14.5 - 2009

MAX SURFACE ROUGHNESS
☐ ALL SURFACES
☐ MARKED ONLY

TOLERANCES EXCEPT AS NOTED

INCHES
.0 : .1
.00 : .01
.000 : .005
.0000 : .0002

MILLIMETERS
0 : 2
.0 : .3
.00 : .13
.000 : .005

ANGLES ±

3M 3M Center St. Paul, MN 55144

© 3M COPYRIGHT 2017
This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.

TITLE
BOARDMOUNT SOCKET, 2MM X 2MM, STRAIGHT & SMT, PAC 20

CAGE NUMBER | SIZE D | DRAWING NO. 78-5100-0519-8 | REV. K

MODEL 1502 | DET LISTS ☐ YES ☒ NO | SHT 4 OF 4

78-5100-0519-8 K
DRAWING NUMBER REVISION

Imaged: K.3 Central Standard Time12/7/2017UTC Offset

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.