

## DM74ALS574A

### Octal D-Type Edge-Triggered Flip-Flop with 3-STATE Outputs

#### General Description

These 8-bit registers feature totem-pole 3-STATE outputs designed specifically for driving highly-capacitive or relatively low-impedance loads. The high-impedance state and increased high-logic-level drive provide these registers with the capability of being connected directly to and driving the bus lines in a bus-organized system without need for interface or pull-up components. They are particularly attractive for implementing buffer registers, I/O ports, bidirectional bus drivers, and working registers.

The eight flip-flops of the DM74ALS574A are edge-triggered D-type flip-flops. On the positive transition of the clock, the Q outputs will be set to the logic states that were set up at the D inputs.

A buffered output control input can be used to place the eight outputs in either a normal logic state (HIGH or LOW logic levels) or a high-impedance state. In the high-impedance state the outputs neither load nor drive the bus lines significantly.

The output control does not affect the internal operation of the flip-flops. That is, the old data can be retained or new data can be entered even while the outputs are OFF.

#### Features


- Switching specifications at 50 pF
- Switching specifications guaranteed over full temperature and  $V_{CC}$  range
- Advanced oxide-isolated, ion-implanted Schottky TTL process
- Functionally equivalent with DM74LS374
- Improved AC performance over DM74LS374 at approximately half the power
- 3-STATE buffer-type outputs drive bus lines directly

#### Ordering Code:

| Order Number  | Package Number | Package Description                                                       |
|---------------|----------------|---------------------------------------------------------------------------|
| DM74ALS574AWM | M20B           | 20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300 Wide |
| DM74ALS574ASJ | M20D           | 20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide             |
| DM74ALS574AN  | N20A           | 20-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300 Wide     |

Devices also available in Tape and Reel. Specify by appending the suffix letter "X" to the ordering code.

#### Connection Diagram




## Function Table

| Output Control | Clock      | D | Output Q |
|----------------|------------|---|----------|
| L              | $\uparrow$ | H | H        |
| L              | $\uparrow$ | L | L        |
| L              | L          | X | $Q_0$    |
| H              | X          | X | Z        |

L = LOW State  
 H = HIGH State  
 X = Don't Care  
 $\uparrow$  = Positive Edge Transition  
 Z = High Impedance State  
 $Q_0$  = Previous Condition of Q

## Logic Diagram



**Absolute Maximum Ratings**(Note 1)

|                                      |                 |
|--------------------------------------|-----------------|
| Supply Voltage                       | 7V              |
| Input Voltage                        | 7V              |
| Voltage Applied to Disabled Output   | 5.5V            |
| Operating Free Air Temperature Range | 0°C to +70°C    |
| Storage Temperature Range            | –65°C to +150°C |
| Typical $\theta_{JA}$                |                 |
| N Package                            | 56.0°C/W        |
| M Package                            | 75.0°C/W        |

**Note 1:** The "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the Electrical Characteristics tables are not guaranteed at the absolute maximum ratings. The "Recommended Operating Conditions" table will define the conditions for actual device operation.

**Recommended Operating Conditions**

| Symbol      | Parameter                      | Min           | Nom | Max  | Units |
|-------------|--------------------------------|---------------|-----|------|-------|
| $V_{CC}$    | Supply Voltage                 | 4.5           | 5   | 5.5  | V     |
| $V_{IH}$    | HIGH Level Input Voltage       | 2             |     |      | V     |
| $V_{IL}$    | LOW Level Input Voltage        |               |     | 0.8  | V     |
| $I_{OH}$    | HIGH Level Output Current      |               |     | –2.6 | mA    |
| $I_{OL}$    | LOW Level Output Current       |               |     | 24   | mA    |
| $f_{CLOCK}$ | Clock Frequency                | 0             |     | 35   | MHz   |
| $t_W$       | Width of Clock Pulse           | HIGH          | 14  |      | ns    |
|             |                                | LOW           | 14  |      | ns    |
| $t_{SU}$    | Data Setup Time (Note 2)       | 15 $\uparrow$ |     |      | ns    |
| $t_H$       | Data Hold Time (Note 2)        | 0 $\uparrow$  |     |      | ns    |
| $T_A$       | Free Air Operating Temperature | 0             |     | 70   | °C    |

**Note 2:** The ( $\uparrow$ ) arrow indicates the positive edge of the Clock is used for reference.

**Electrical Characteristics**


over recommended operating free air temperature range. All typical values are measured at  $V_{CC} = 5V$ ,  $T_A = 25^\circ C$ .

| Symbol    | Parameter                                               | Conditions                                      | Min                          | Typ          | Max  | Units   |
|-----------|---------------------------------------------------------|-------------------------------------------------|------------------------------|--------------|------|---------|
| $V_{IK}$  | Input Clamp Voltage                                     | $V_{CC} = 4.5V$ , $I_I = -18\text{ mA}$         |                              |              | –1.2 | V       |
| $V_{OH}$  | HIGH Level Output Voltage                               | $V_{CC} = 4.5V$<br>$V_{IL} = V_{IL\text{ Max}}$ | $I_{OH} = \text{Max}$        | 2.4          | 3.2  | V       |
|           |                                                         | $V_{CC} = 4.5V$ to $5.5V$                       | $I_{OH} = -400\text{ }\mu A$ | $V_{CC} - 2$ |      | V       |
| $V_{OL}$  | LOW Level Output Voltage                                | $V_{CC} = 4.5V$<br>$V_{IH} = 2V$                | $I_{OL} = 12\text{ mA}$      | 0.25         | 0.4  | V       |
|           |                                                         |                                                 | $I_{OL} = 24\text{ mA}$      | 0.35         | 0.5  | V       |
| $I_I$     | Input Current at Max Input Voltage                      | $V_{CC} = 5.5V$ , $V_{IH} = 7V$                 |                              |              | 0.1  | mA      |
| $I_{IH}$  | HIGH Level Input Current                                | $V_{CC} = 5.5V$ , $V_{IH} = 2.7V$               |                              |              | 20   | $\mu A$ |
| $I_{IL}$  | LOW Level Input Current                                 | $V_{CC} = 5.5V$ , $V_{IL} = 0.4V$               |                              |              | –0.2 | mA      |
| $I_O$     | Output Drive Current                                    | $V_{CC} = 5.5V$ , $V_O = 2.25V$                 | –30                          |              | –112 | mA      |
| $I_{OZH}$ | OFF-State Output Current<br>HIGH Level Voltage Applied  | $V_{CC} = 5.5V$ , $V_{IH} = 2V$<br>$V_O = 2.7V$ |                              |              | 20   | $\mu A$ |
| $I_{OZL}$ | OFF-State Output Current d<br>LOW Level Voltage Applied | $V_{CC} = 5.5V$ , $V_{IH} = 2V$<br>$V_O = 0.4V$ |                              |              | –20  | $\mu A$ |
| $I_{CC}$  | Supply Current                                          | $V_{CC} = 5.5V$<br>Outputs Open                 | Outputs HIGH                 | 11           | 18   | mA      |
|           |                                                         |                                                 | Outputs LOW                  | 17           | 27   | mA      |
|           |                                                         |                                                 | Outputs Disabled             | 17           | 28   | mA      |

## Switching Characteristics



over recommended operating free air temperature range

| Symbol    | Parameter                                          | Conditions                                                      | From           | To    | Min | Max | Units |
|-----------|----------------------------------------------------|-----------------------------------------------------------------|----------------|-------|-----|-----|-------|
| $f_{MAX}$ | Maximum Clock Frequency                            | $V_{CC} = 4.5V$ to $5.5V$<br>$R_L = 500\Omega$<br>$C_L = 50$ pF |                |       | 35  |     | MHz   |
| $t_{PLH}$ | Propagation Delay Time<br>LOW-to-HIGH Level Output |                                                                 | Clock          | Any Q | 4   | 14  | ns    |
| $t_{PHL}$ | Propagation Delay Time<br>HIGH-to-LOW Level Output |                                                                 | Clock          | Any Q | 4   | 14  | ns    |
| $t_{PZH}$ | Output Enable Time<br>to HIGH Level Output         |                                                                 | Output Control | Any Q | 4   | 18  | ns    |
| $t_{PZL}$ | Output Enable Time<br>to LOW Level Output          |                                                                 | Output Control | Any Q | 4   | 18  | ns    |
| $t_{PHZ}$ | Output Disable Time<br>from HIGH Level Output      |                                                                 | Output Control | Any Q | 2   | 10  | ns    |
| $t_{PLZ}$ | Output Disable Time<br>from LOW Level Output       |                                                                 | Output Control | Any Q | 2   | 12  | ns    |


**Physical Dimensions** inches (millimeters) unless otherwise noted


**20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300 Wide  
Package Number M20B**



# Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



## LAND PATTERN RECOMMENDATION



DIMENSIONS ARE IN MILLIMETERS



## DETAIL A


### NOTES:

- CONFORMS TO EIAJ EDR-7320 REGISTRATION, ESTABLISHED IN DECEMBER, 1998.
- DIMENSIONS ARE IN MILLIMETERS.
- DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.

M20DRevB1

20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide  
Package Number M20D

# Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



N20A (REV G)

20-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300 Wide  
Package Number N20A

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[www.fairchildsemi.com](http://www.fairchildsemi.com)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.