



SERIAL SERVER WITH
GALVANIC ISOLATION



DIGI CONNECT® ES (EXTENDED SAFETY)

Extended safety terminal server designed for serial over Ethernet applications that require isolation on and between ports

Digi Connect ES provides serial over Ethernet connectivity. It is IEC 60601 3rd Edition compliant and consists of four or eight galvanic isolated RS-232 serial ports, with a 10/100 Mbps network interface and optional Ethernet switch. Digi Connect ES is used in applications that provide Ethernet connections from serial devices to the central data management system.

Galvanic isolation provides extended electrical safety. There is no electrical path for current to earth ground, ensuring no electrical shock when making physical contact with the Digi Connect ES. There is no electrical path from port to port,

ensuring a ground fault will not affect the operation of the Digi Connect ES or the operation of any device connected to it.

Digi's patented RealPort technology makes it possible to establish a connection between the host and a networked serial device by creating a local COM or TTY port on the host computer. Incoming/outgoing and Telnet sessions on each port give system administrators a high level of control over networked serial devices.

BENEFITS

- 4/8-port RS-232 serial-to-network connectivity
- IEC 60601 3rd Edition compliant
- Galvanic isolation on all ports
- Wall mountable
- Patented Digi RealPort® technology provides local serial port functionality
- RealPort with encryption available for SSL-based protection for additional security
- Ports may be shared between multiple hosts running different operating systems

APPLICATION EXAMPLE



RELATED PRODUCTS



ConenctPort®
TS




PortServer®
TS



ConnectPort®
LTS



Digi Connect®
SP



Cables and
Accessories

SPECIFICATIONS	Digi Connect® ES
FEATURES	
MANAGEMENT	HTTP/HTTPS, CLI or Telnet, Optional secure enterprise management via Digi Remote Manager™
PROTOCOLS	UDP/TCP, DHCP, Extended Telnet RFC 2217, Telnet, Reverse Telnet, Rlogin & Auto Connect, TFTP
SECURITY	SSL, SSL/TLS, SSHv2, FIPS 197 (serial ports), SNMPv2
SOFTWARE	Device-initiated patented RealPort COM port redirector and RFC 2217, Python scripting, Custom development environment
STATUS LEDS	Power, Locator, Serial and Ethernet link/activity
OPERATING SYSTEMS	AIX, HP-UX, Solaris, Linux®, Windows® 2000, Windows® XP, Windows® 7, Windows® 8, Windows® 8.1, Windows® 10, Windows Server® 2003, Windows Server® 2008, Windows Server® 2012. Note: TCP/UDP socket services are operating system independent.
DIMENSIONS (L X W X D)	9.30 in x 10.60 in x 2.10 in (23.5 cm x 26.9 cm x 4.20 cm)
WEIGHT	3.0 lb (1.34 kg)
INTERFACES	
SERIAL	
PORTS	4/8 separately isolated RS-232 ports (2.5kV)
THROUGHPUT	Up to 230 Kbps
SIGNAL SUPPORT	TXD, RXD, RTS, CTS, DTR, DSR, DCD
ETHERNET	
PORTS	1 uplink, Optional 4-port switch
PHYSICAL LAYER	10/100 Base-T separately isolated (1.5kV)
MODE	Full or half duplex
POWER REQUIREMENTS	
POWER SUPPLY	Internal 100-240VAC, 50-60 Hz 0.2A max
PRODUCT SURGE PROTECTION (ESD)	4 kV burst (EFT) per EN61000-4-4, 2 kV surge transient per EN61000-4-5 4 kV isolation input to output 2 kV surge per EN61000-4-5
ENVIRONMENTAL	
OPERATING TEMPERATURE	0° C to 55° C (32° F to 130° F)
STORAGE TEMPERATURE	-30° C to +85° C (-22° F to +185° F)
RELATIVE HUMIDITY	5 to 95% (non-condensing)
SERIAL PORT PROTECTION (ESD)	15 kV human body model
STANDARDS COMPLIANCE	
EMISSIONS	EN 55011, EN 55022, CISPR 11, CISPR 22
SAFETY	EN 60950-1, IEC 60950-1, EN 60601-1, EN 60601-1-2, IEC 60601-1
IMMUNITY	EN 55024, CISPR 24

PART NUMBERS	DESCRIPTION
DC-ES-4SB-EU	Digi Connect ES 4SB - 4 ports (International)
DC-ES-4SB-SW-EU	Digi Connect ES 4SB w/ Switch - 4 ports (International)
DC-ES-8SB-EU	Digi Connect ES 8SB - 8 ports (International)
DC-ES-8SB-SW-EU	Digi Connect ES 8SB w/ Switch - 8 ports (International)

DIGI SERVICE AND SUPPORT / You can purchase with confidence knowing that Digi is always available to serve you with expert technical support and our industry leading warranty. For detailed information visit www.digi.com/support.

© 1996-2018 Digi International Inc. All rights reserved.
All trademarks are the property of their respective owners.

91001320
G3/618

DIGI INTERNATIONAL WORLDWIDE HQ
877-912-3444 / 952-912-3444 / www.digi.com

DIGI INTERNATIONAL GERMANY
+49-89-540-428-0

DIGI INTERNATIONAL JAPAN
+81-3-5428-0261 / www.digi-intl.co.jp

DIGI INTERNATIONAL SINGAPORE
+65-6213-5380

DIGI INTERNATIONAL CHINA
+86-21-50492199 / www.digi.com.cn





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.