

# DATA SHEET

## **BTA216X series D, E and F** Three quadrant triacs guaranteed commutation

Product specification

September 2018

# Three quadrant triacs guaranteed commutation

# BTA216X series D, E and F

## GENERAL DESCRIPTION

Passivated guaranteed commutation triacs in a full pack, plastic envelope intended for use in motor control circuits or with other highly inductive loads. These devices balance the requirements of commutation performance and gate sensitivity. The "sensitive gate" E series and "logic level" D series are intended for interfacing with low power drivers, including micro controllers.


## QUICK REFERENCE DATA

| SYMBOL       | PARAMETER                            | MAX.                                             | UNIT |
|--------------|--------------------------------------|--------------------------------------------------|------|
| $V_{DRM}$    | Repetitive peak off-state voltages   | <b>600D</b><br><b>600E</b><br><b>600F</b><br>600 | V    |
| $I_{T(RMS)}$ | RMS on-state current                 | 16                                               | A    |
| $I_{TSM}$    | Non-repetitive peak on-state current | 140                                              | A    |


## PINNING - SOT186A

| PIN  | DESCRIPTION     |
|------|-----------------|
| 1    | main terminal 1 |
| 2    | main terminal 2 |
| 3    | gate            |
| case | isolated        |

## PIN CONFIGURATION



## SYMBOL



## LIMITING VALUES

Limiting values in accordance with the Absolute Maximum System (IEC 134).

| SYMBOL       | PARAMETER                                                    | CONDITIONS                                                                                                    | MIN. | MAX.             | UNIT             |
|--------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|------|------------------|------------------|
| $V_{DRM}$    | Repetitive peak off-state voltages                           |                                                                                                               | -    | 600 <sup>1</sup> | V                |
| $I_{T(RMS)}$ | RMS on-state current                                         | full sine wave;<br>$T_{hs} \leq 38 \text{ }^\circ\text{C}$                                                    | -    | 16               | A                |
| $I_{TSM}$    | Non-repetitive peak on-state current                         | full sine wave;<br>$T_j = 25 \text{ }^\circ\text{C}$ prior to surge                                           | -    | 140              | A                |
| $I^2t$       | $I^2t$ for fusing                                            | $t = 20 \text{ ms}$                                                                                           | -    | 150              | A <sup>2</sup> s |
| $dl_T/dt$    | Repetitive rate of rise of on-state current after triggering | $t = 10 \text{ ms}$<br>$I_{TM} = 20 \text{ A}; I_G = 0.2 \text{ A};$<br>$dl_G/dt = 0.2 \text{ A}/\mu\text{s}$ | -    | 98               | A/ $\mu\text{s}$ |
| $I_{GM}$     | Peak gate current                                            |                                                                                                               | -    | 2                | A                |
| $P_{GM}$     | Peak gate power                                              |                                                                                                               | -    | 5                | W                |
| $P_{G(AV)}$  | Average gate power                                           | over any 20 ms period                                                                                         | -    | 0.5              | W                |
| $T_{stg}$    | Storage temperature                                          |                                                                                                               | -40  | 150              | $^\circ\text{C}$ |
| $T_j$        | Operating junction temperature                               |                                                                                                               | -    | 125              | $^\circ\text{C}$ |

<sup>1</sup> Although not recommended, off-state voltages up to 800V may be applied without damage, but the triac may switch to the on-state. The rate of rise of current should not exceed 15 A/ $\mu\text{s}$ .

## Three quadrant triacs guaranteed commutation

## BTA216X series D, E and F

### ISOLATION LIMITING VALUE & CHARACTERISTIC

$T_{hs} = 25\text{ °C}$  unless otherwise specified

| SYMBOL     | PARAMETER                                                              | CONDITIONS                                                                                   | MIN. | TYP. | MAX. | UNIT |
|------------|------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|------|------|------|------|
| $V_{isol}$ | R.M.S. isolation voltage from all three terminals to external heatsink | $f = 50\text{-}60\text{ Hz}$ ; sinusoidal waveform;<br>R.H. $\leq 65\%$ ; clean and dustfree | -    | -    | 2500 | V    |
| $C_{isol}$ | Capacitance from T2 to external heatsink                               | $f = 1\text{ MHz}$                                                                           | -    | 10   | -    | pF   |

### THERMAL RESISTANCES

| SYMBOL                | PARAMETER                               | CONDITIONS                                | MIN. | TYP. | MAX. | UNIT |
|-----------------------|-----------------------------------------|-------------------------------------------|------|------|------|------|
| $R_{th\ j\text{-}hs}$ | Thermal resistance junction to heatsink | full or half cycle with heatsink compound | -    | -    | 4.0  | K/W  |
| $R_{th\ j\text{-}a}$  | Thermal resistance junction to ambient  | without heatsink compound in free air     | -    | 55   | 5.5  | K/W  |

### STATIC CHARACTERISTICS

$T_j = 25\text{ °C}$  unless otherwise stated

| SYMBOL   | PARAMETER                         | CONDITIONS                                                                                                           | MIN. | MAX.              |             |             | UNIT |
|----------|-----------------------------------|----------------------------------------------------------------------------------------------------------------------|------|-------------------|-------------|-------------|------|
|          |                                   | <b>BTA216X-</b>                                                                                                      |      | <b>...D</b>       | <b>...E</b> | <b>...F</b> |      |
| $I_{GT}$ | Gate trigger current <sup>2</sup> | $V_D = 12\text{ V}$ ; $I_T = 0.1\text{ A}$<br>T2+ G+<br>T2+ G-<br>T2- G-<br>T2- G-                                   | -    | 5                 | 10          | 25          | mA   |
| $I_L$    | Latching current                  | $V_D = 12\text{ V}$ ; $I_{GT} = 0.1\text{ A}$<br>T2+ G+<br>T2+ G-<br>T2- G-                                          | -    | 15                | 25          | 30          | mA   |
| $I_H$    | Holding current                   | $V_D = 12\text{ V}$ ; $I_{GT} = 0.1\text{ A}$                                                                        | -    | 15                | 25          | 30          | mA   |
|          |                                   |                                                                                                                      |      | <b>...D, E, F</b> |             |             |      |
| $V_T$    | On-state voltage                  | $I_T = 20\text{ A}$                                                                                                  | -    | 1.5               |             |             | V    |
| $V_{GT}$ | Gate trigger voltage              | $V_D = 12\text{ V}$ ; $I_T = 0.1\text{ A}$<br>$V_D = 400\text{ V}$ ; $I_T = 0.1\text{ A}$ ;<br>$T_j = 125\text{ °C}$ | -    | 1.5               |             |             | V    |
|          |                                   |                                                                                                                      | 0.25 | -                 |             |             | V    |
| $I_D$    | Off-state leakage current         | $V_D = V_{DRM(max)}$ ; $T_j = 125\text{ °C}$                                                                         | -    | 0.5               |             |             | mA   |

<sup>2</sup> Device does not trigger in the T2-, G+ quadrant.

## Three quadrant triacs guaranteed commutation

## BTA216X series D, E and F

### DYNAMIC CHARACTERISTICS

$T_j = 25\text{ °C}$  unless otherwise stated

| SYMBOL        | PARAMETER                                      | CONDITIONS                                                                                                                                        | MIN. |      |      | MAX. | UNIT       |
|---------------|------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|------|------------|
|               |                                                |                                                                                                                                                   | ...D | ...E | ...F |      |            |
| $dV_D/dt$     | Critical rate of rise of off-state voltage     | <b>BTA216X-</b><br>$V_{DM} = 67\% V_{DRM(max)}$ ;<br>$T_j = 110\text{ °C}$ ; exponential waveform; gate open circuit                              | 30   | 60   | 70   | -    | V/ $\mu$ s |
| $di_{com}/dt$ | Critical rate of change of commutating current | $V_{DM} = 400\text{ V}$ ; $T_j = 125\text{ °C}$ ;<br>$I_{T(RMS)} = 16\text{ A}$ ;<br>$dV_{com}/dt = 10\text{ V}/\mu\text{s}$ ; gate open circuit  | 2.5  | 6.2  | 18   | -    | A/ms       |
| $di_{com}/dt$ | Critical rate of change of commutating current | $V_{DM} = 400\text{ V}$ ; $T_j = 125\text{ °C}$ ;<br>$I_{T(RMS)} = 16\text{ A}$ ;<br>$dV_{com}/dt = 0.1\text{ V}/\mu\text{s}$ ; gate open circuit | 12   | 20   | 50   | -    | A/ms       |

Three quadrant triacs  
guaranteed commutation

BTA216X series D, E and F




Fig. 1. Maximum on-state dissipation,  $P_{tot}$ , versus rms on-state current,  $I_{T(RMS)}$ , where  $\alpha =$  conduction angle.




Fig. 4. Maximum permissible rms current  $I_{T(RMS)}$ , versus heatsink temperature  $T_{hs}$ .




Fig. 2. Maximum permissible non-repetitive peak on-state current  $I_{TSM}$ , versus pulse width  $t_p$ , for sinusoidal currents,  $t_p \leq 20$ ms.




Fig. 5. Maximum permissible repetitive rms on-state current  $I_{T(RMS)}$ , versus surge duration, for sinusoidal currents,  $f = 50$  Hz;  $T_{hs} \leq 38$  C.




Fig. 3. Maximum permissible non-repetitive peak on-state current  $I_{TSM}$ , versus number of cycles, for sinusoidal currents,  $f = 50$  Hz.









Fig. 6. Normalised gate trigger voltage  $V_{GT}(T_j) / V_{GT}(25^\circ C)$ , versus junction temperature  $T_j$ .

Three quadrant triacs  
guaranteed commutation

BTA216X series D, E and F




Three quadrant triacs  
guaranteed commutation

BTA216X series D, E and F

**MECHANICAL DATA**

Plastic single-ended package; isolated heatsink mounted; 1 mounting hole; 3-lead TO-220 "full pack"

SOT186A



| UNIT | A   | A <sub>1</sub> | b   | b <sub>1</sub> | b <sub>2</sub> | c   | D    | D <sub>1</sub> | E    | e    | e <sub>1</sub> | j <sup>(2)</sup> | k <sup>(2)</sup> | L    | L <sub>1</sub> | L <sub>2</sub> <sup>(1)</sup><br>max. | P   | Q   | q   | W   | τ <sup>(3)</sup> |
|------|-----|----------------|-----|----------------|----------------|-----|------|----------------|------|------|----------------|------------------|------------------|------|----------------|---------------------------------------|-----|-----|-----|-----|------------------|
| mm   | 4.6 | 2.9            | 0.9 | 1.1            | 1.4            | 0.7 | 15.8 | 6.5            | 10.3 |      |                | 2.7              | 0.6              | 14.4 | 3.30           |                                       | 3.2 | 2.6 | 3.0 |     |                  |
|      | 4.0 | 2.5            | 0.7 | 0.9            | 1.0            | 0.4 | 15.2 | 6.3            | 9.7  | 2.54 | 5.08           | 1.7              | 0.4              | 13.5 | 2.79           | 3                                     | 3.0 | 2.3 | 2.6 | 0.4 | 2.5              |

Notes

1. Terminal dimensions within this zone are uncontrolled
2. Dot lines area designs may vary
3. Eject pin mark is for reference only

| OUTLINE<br>VERSION | REFERENCES |                |       | EUROPEAN<br>PROJECTION | ISSUE DATE |
|--------------------|------------|----------------|-------|------------------------|------------|
|                    | IEC        | JEDEC          | JEITA |                        |            |
| SOT186A            |            | 3 LEADS TO220F |       |                        | 2013-11-14 |

## Legal information

### Data sheet status

| Document status [1][2]         | Product status [3] | Definition                                                                            |
|--------------------------------|--------------------|---------------------------------------------------------------------------------------|
| Objective [short] data sheet   | Development        | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet | Qualification      | This document contains data from the preliminary specification.                       |
| Product [short] data sheet     | Production         | This document contains the product specification.                                     |

- [1] Please consult the most recently issued document before initiating or completing a design.
- [2] The term 'short data sheet' is explained in section "Definitions".
- [3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.ween-semi.com>.

### Definitions

**Draft** — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. WeEn Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Short data sheet** — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local WeEn Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

**Product specification** — The information and data provided in a Product data sheet shall define the specification of the product as agreed between WeEn Semiconductors and its customer, unless WeEn Semiconductors and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the WeEn Semiconductors product is deemed to offer functions and qualities beyond those described in the Product data sheet.

### Disclaimers

**Limited warranty and liability** — Information in this document is believed to be accurate and reliable. However, WeEn Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. WeEn Semiconductors takes no responsibility for the content in this document if provided by an information source outside of WeEn Semiconductors.

In no event shall WeEn Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges whether or not such damages are based on tort (including negligence, warranty, breach of contract or any other legal theory).

Notwithstanding any damages that customer might incur for any reason whatsoever, WeEn Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of WeEn Semiconductors.

**Right to make changes** — WeEn Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use** — WeEn Semiconductors products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an WeEn Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. WeEn Semiconductors and its suppliers accept no liability for inclusion and/or use of WeEn Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Quick reference data** — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. WeEn Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using WeEn Semiconductors products, and WeEn Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the WeEn Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

WeEn Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using WeEn Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). WeEn does not accept any liability in this respect.

**Limiting values** — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

**No offer to sell or license** — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

**Export control** — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

**Non-automotive qualified products** — Unless this data sheet expressly states that this specific WeEn Semiconductors product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. WeEn Semiconductors accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without WeEn Semiconductors' warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond WeEn Semiconductors' specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies WeEn Semiconductors for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond WeEn Semiconductors' standard warranty and WeEn Semiconductors' product specifications.



**Translations** — A non-English (translated version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

**Trademarks**

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.