



**FEATURES**

- **Clipped Sine Wave Output**
- **Optional Voltage Control for Frequency Tuning [VCTCXO]**
- 2.5mmx2.0mm Surface Mount Package
- Frequency Range 10 – 52 MHz [Standard Frequencies List Shown Below]
- Fundamental Crystal Design
- Frequency Stability, several options to choose from  $\pm 0.5\text{ppm} \sim \pm 2.5\text{ppm}$
- Operating Voltage, +1.8Vdc  $\sim$  +2.5Vdc
- Operating Temperature to -40°C to +85°C
- Tape & Reel Packaging Available
- **RoHS/Green Compliant (6/6)**



**APPLICATIONS**

The Model 520 Temperature Compensated Crystal Oscillator (TCXO) is a quartz based, clipped sine wave output, with optional frequency tuning, in a hermetically sealed ceramic package. M520 is suitable for wireless communications, broadband access, WLAN/WiMax/WIFI, portable equipment, test and measurement and mobile applications.

**ORDERING INFORMATION**



\* Frequency vs. Temperature Only

- 1] Only available with temperature range codes "H" and "C".
- 2] Only available with temperature range codes "H", "C" and "D".
- 3] Frequency is recorded with two leading digits before the 'M' and 4 significant digits after the 'M' (including zeros).  
[Ex. XXMXXXX (10M0000), XXMXXXX (16M3840)]
- 4] See Electrical Characteristics for Control Voltage range per Supply Voltage selected.

**Not all performance combinations and frequencies may be available.**  
**Contact your local CTS Representative or CTS Customer Service for availability.**

| M520 Standard Frequencies |           |           |           |           |
|---------------------------|-----------|-----------|-----------|-----------|
| 13.000000                 | 16.368000 | 19.200000 | 26.000000 | 40.000000 |
| 16.367667                 | 16.369000 | 20.000000 | 38.400000 |           |

**ELECTRICAL CHARACTERISTICS**

| PARAMETER   | SYMBOL                           | CONDITIONS   | MIN                                  | TYP                             | MAX                                     | UNIT   |
|---|----------------------------------|--|--------------------------------------|---------------------------------|---|--------|
| Maximum Supply Voltage  | V <sub>CC</sub>                  | -  | -0.5                                 | -                               | 6.0                                     | V      |
| Maximum Control Voltage   | V <sub>C</sub>                   | -  | -0.5                                 | -                               | V <sub>CC</sub>                         | V      |
| Storage Temperature   | T <sub>STG</sub>                 | -  | -40                                  | -                               | 85                                      | °C     |
| Frequency Range   | f <sub>0</sub>                   | Std frequencies listed in Ordering Information                               | 10                                   | -                               | 52                                      | MHz    |
| Frequency Stability   | Δf/f <sub>0</sub>                | Frequency vs. Temperature Only   | 0.5, 1.0, 1.5<br>2.0, 2.5            |                                 |   | ± ppm  |
| Frequency Stability vs. Initial Calibration vs. Supply Voltage vs. Load vs. Reflow Shift vs. Aging              | -                                | @25°C<br>±5% change<br>±10% change<br>After 2 reflows<br>1st year<br>10 year | -                                    | -                               | 2.0<br>0.2<br>0.2<br>2.0<br>1.0<br>10.0 | ± ppm  |
| Operating Temperature<br>Order Code 'W'<br>Order Code 'H'<br>Order Code 'C'<br>Order Code 'D'<br>Order Code 'I' | T <sub>A</sub>                   | -  | 0<br>-10<br>-20<br>-30<br>-40        | 25                              | 55<br>60<br>70<br>85<br>85              | °C     |
| Supply Voltage<br>Order Code 'M'<br>Order Code 'N'<br>Order Code 'T'<br>Order Code 'R'<br>Order Code 'L'        | V <sub>CC</sub>                  | ±5%  | 1.77<br>2.38<br>2.66<br>2.85<br>3.14 | 1.8<br>2.5<br>2.8<br>3.0<br>3.3 | 1.83<br>2.63<br>2.94<br>3.15<br>3.47    | V      |
| Supply Current  | I <sub>CC</sub>                  | 10.00 MHz - 25.99 MHz<br>26.00 MHz - 52.00 MHz                               | -                                    | -                               | 2<br>2.5                                | mA     |
| Control Voltage   | V <sub>C</sub>                   | 2.5V, 2.8V, 3.0V, 3.3V<br>1.8V   | 0.4<br>0.3                           | 1.5<br>0.9                      | 2.4<br>1.5                              | V      |
| Frequency Tuning [VCTCXO Only]  | -                                | Specified V <sub>C</sub> Range   | 5.0                                  | -                               | -                                       | ± ppm  |
| V <sub>C</sub> Input Impedance  | ZV <sub>C</sub>                  | -  | 500                                  | -                               | -                                       | kOhm   |
| Output Waveform   |                                  | AC coupled Clipped Sinewave  |                                      |                                 |   |        |
| Output Voltage Levels   | V <sub>O</sub>                   |  | 0.8                                  | -                               | -                                       | Vp-p   |
| Output Load   | R <sub>L</sub> // C <sub>L</sub> |  | 10 kOhm // 10 pF                     |                                 |   |        |
| Start Up Time   | T <sub>S</sub>                   |  | -                                    | -                               | 2                                       | ms     |
| Phase Noise   | -                                | Varies based on output frequency. See example plot @ 19.2 MHz below.         |                                      |                                 |   | dBc/Hz |

ELECTRICAL PARAMETERS



**ELECTRICAL CHARACTERISTICS**

**D.U.T. PIN ASSIGNMENTS**

| PIN | SYMBOL          | DESCRIPTION                                     |
|-----|-----------------|---|
| 1   | V <sub>C</sub>  | GND – TCXO [Note 1]<br>Control Voltage – VCTCXO |
| 2   | GND             | Circuit & Package Ground                        |
| 3   | Output          | Clipped Sine Wave Output [Note 2]               |
| 4   | V <sub>CC</sub> | Supply Voltage                                  |

**NOTES**

1. Connect to ground for TCXO (no AFC) option.
2. DC-Cut Capacitor Required.  
Add 1000pF capacitor between TCXO output and input of load.

**TEST CIRCUIT – RL//CL LOAD**



\* DC-Cut Capacitor

**MECHANICAL SPECIFICATIONS**

**PACKAGE DRAWING**



Key:  $\frac{\text{mm}}{\text{Inch}}$

**MARKING INFORMATION**


1. M520 - CTS Model Series.
2. ● – Pin 1 identifier.
3. D – Date code. See Table I for codes.
4. XXX – Frequency code. Reference CTS document 016-1454-01.

Complete CTS part number, frequency value and date code information must appear on reel and carton labels.

**NOTES**

1. DO NOT make connections to non-labeled pins and castellations, as they may have internal connections used in the manufacturing process.
2. Termination pads (e4); barrier plating is nickel (Ni) with gold (Au) flash plate.
3. Reflow conditions per JEDEC J-STD-020, 260°C maximum.

**SUGGESTED SOLDER PAD GEOMETRY**




C<sub>BYPASS</sub> should be ≥ 0.01 uF.

**TABLE I – DATE CODE**

| YEAR \ MONTH |      |      |      |      | JAN | FEB | MAR | APR | MAY | JUN | JUL | AUG | SEP | OCT | NOV | DEC |
|--------------|------|------|------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 2001         | 2005 | 2009 | 2013 | 2017 | A   | B   | C   | D   | E   | F   | G   | H   | J   | K   | L   | M   |
| 2002         | 2006 | 2010 | 2014 | 2018 | N   | P   | Q   | R   | S   | T   | U   | V   | W   | X   | Y   | Z   |
| 2003         | 2007 | 2011 | 2015 | 2019 | a   | b   | c   | d   | e   | f   | g   | h   | j   | k   | l   | m   |
| 2004         | 2008 | 2012 | 2016 | 2020 | n   | p   | q   | r   | s   | t   | u   | v   | w   | x   | y   | z   |

**PACKAGING INFORMATION [Reference]**

Device quantity is 1k pieces minimum and 3k maximum per 180mm reel.





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.