

## 8477 Multi-Conductor - High-Conductivity Copper Speaker Cable Twisted Jacket Con



For more Information  
please call

1-800-Belden1

**Description:**

12 AWG stranded (65x30) tinned copper conductors, PVC insulation, twisted pair, PVC jacket.

**Physical Characteristics (Overall)****Conductor****AWG:**

| # Pairs | AWG | Stranding | Conductor Material |
|---------|-----|-----------|--------------------|
| 1       | 12  | 65x30     | TC - Tinned Copper |

Total Number of Conductors: 2

**Insulation****Insulation Material:**

| Insulation Material      | Wall Thickness (in.) |
|--------------------------|----------------------|
| PVC - Polyvinyl Chloride | 0.033                |

**Outer Shield****Outer Shield Material:**

| Outer Shield Material |
|-----------------------|
| Unshielded            |

**Outer Jacket****Outer Jacket Material:**

| Outer Jacket Material    | Nom. Wall Thickness (in.) |
|--------------------------|---------------------------|
| PVC - Polyvinyl Chloride | .035                      |

**Overall Cable**

Overall Nominal Diameter: 0.386 in.

**Pair****Pair Color Code Chart:**

| Number | Color         |
|--------|---------------|
| 1      | Black & White |

**Mechanical Characteristics (Overall)**

|                                   |                          |
|-----------------------------------|--------------------------|
| Operating Temperature Range:      | -20°C To +90°C           |
| Non-UL Temperature Rating:        | 90°C (UL AWM Style 2587) |
| Bulk Cable Weight:                | 80 lbs/1000 ft.          |
| Max. Recommended Pulling Tension: | 150 lbs.                 |
| Min. Bend Radius/Minor Axis:      | 4 in.                    |

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

|                                |                            |
|--------------------------------|----------------------------|
| NEC/(UL) Specification:        | CL3R                       |
| AWM Specification:             | UL Style 2587 (600 V 90°C) |
| EU CE Mark:                    | Yes                        |
| EU Directive 2000/53/EC (ELV): | Yes                        |

## 8477 Multi-Conductor - High-Conductivity Copper Speaker Cable Twisted Jacket Con

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire &amp; Cable): Yes

MII Order #39 (China RoHS): Yes

## Flame Test

UL Flame Test: UL1666 Vertical Shaft

## Plenum/Non-Plenum

Plenum (Y/N): No

## Electrical Characteristics (Overall)

## Nom. Inductance:

Inductance (μH/ft)

0.18

## Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)

35

## Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

1.8

## Max. Operating Voltage - UL:

| Voltage   | Description       |
|-----------|-------------------|
| 300 V RMS | CL3R              |
| 600 V RMS | UL AWM Style 2587 |

## Max. Recommended Current:

Current

13 Amps per conductor @ 25°C

## Notes (Overall)

Notes: See NEC Guidelines for applicable CL3 voltage ratings.

## Put Ups and Colors:

| Item #       | Putup    | Ship Weight | Color  | Notes | Item Desc       |
|--------------|----------|-------------|--------|-------|-----------------|
| 8477 060U500 | 500 FT   | 41.500 LB   | CHROME |       | 2 #12 PVC FRPVC |
| 8477 0601000 | 1,000 FT | 87.000 LB   | CHROME | C     | 2 #12 PVC FRPVC |
| 8477 060500  | 500 FT   | 43.500 LB   | CHROME | C     | 2 #12 PVC FRPVC |
| 8477 0605000 | 5,000 FT | 410.000 LB  | CHROME | C Z   | 2 #12 PVC FRPVC |

## Notes:

C = CRATE REEL PUT-UP.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 2    Revision Date: 09-20-2012

© 2012 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.  
Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the

## 8477 Multi-Conductor - High-Conductivity Copper Speaker Cable Twisted Jacket Con

compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.