

PRODUCT NUMBER
10080598-XXXXXXXXLF

BASE NUMBER DASH NUMBER
10080598 - XXXXXXXLF

LEAD FREE (SEE NOTE 9)
NEXT AVAILABLE NUMBER
SEE NOTE 2

SIGNAL WIRE SIZE

A:	22 AWG
B:	24 AWG
C:	26 AWG
D:	NONE
E:	MULTI NOTE 3, 5

COLOR: GREEN, UNLESS OTHERWISE SPECIFIED

POWER WIRE SIZE

CONFIGURATION	WIRE SIZE	NOTES
A:	ALL POWER	4mm ²
B:	P+S+P	4mm ²
C:	P+S	4mm ²
D:	S+P	4mm ²
E:	ALL POWER	6mm ²
F:	P+S+P	6mm ²
G:	P+S	6mm ²
H:	S+P	6mm ²
J:	ALL POWER	10mm ²
K:	P+S+P	10mm ²
L:	P+S	10mm ²
M:	S+P	10mm ²
N:	ALL SIGNAL	

COLOR: BLACK, UNLESS OTHERWISE SPECIFIED

STYLE

TERMINATION

1:	STR SINGLE ENDED	BLUNT CUT CABLES SEE NOTE 7
2:	STR SINGLE ENDED	YES-SEE NOTE 8
3:	STR DOUBLE ENDED	P2 CONNECTOR IS DEFINED
4:	PANEL MOUNT SINGLE ENDED	BLUNT CUT CABLES SEE NOTE 7
5:	PANEL MOUNT SINGLE ENDED	YES-SEE NOTE 8
6:	PANEL MOUNT DOUBLE ENDED	P2 CONNECTOR IS DEFINED
7:	PI:PANEL MOUNT/P2:STR DOUBLE ENDED	P2 CONNECTOR IS DEFINED
8:	PI:STR/P2:PANEL MOUNT DOUBLE ENDED	P2 CONNECTOR IS DEFINED
A:	LATCH EAR SINGLE ENDED	BLUNT CUT CABLES SEE NOTE 7
B:	LATCH EAR SINGLE ENDED	YES-SEE NOTE 8
C:	LATCH EAR DOUBLE ENDED	P2 CONNECTOR IS DEFINED
D:	PI:PANEL MOUNT/P2:LATCH EAR DOUBLE ENDED	P2 CONNECTOR IS DEFINED
E:	PI:LATCH EAR/P2:PANEL MOUNT DOUBLE ENDED	P2 CONNECTOR IS DEFINED
F:	PI:STR/P2:LATCH EAR DOUBLE ENDED	P2 CONNECTOR IS DEFINED
G:	PI:LATCH EAR/P2:STR DOUBLE ENDED	P2 CONNECTOR IS DEFINED

NOTES:

- PwrBlade CABLE ASSEMBLY OFFERING FOR ASSEMBLIES WITH mm² CABLES:
10080598- XXXXXXXLF = WITH mm² CABLES
CUSTOMER REQUIREMENTS LIST (E-3610) MUST BE FILLED OUT FOR EACH
PART NUMBER REQUEST.
SIGNAL WIRES ARE ALL THE SAME SIZE, IF REQUIRED.
- NEXT AVAILABLE DASH NUMBER WILL BE DEFINED BY FCI.
- CABLE LENGTHS, WIRE COLORS AND POWER PITCH ARE TO BE DEFINED
ON ASSEMBLY DRAWINGS FOR THE ASSIGNED PART NUMBERS.
THE DRAWING WILL ALSO DEFINE SPECIAL MATING CONDITIONS 2.34.
THE DRAWING WILL ALSO DEFINE LOAD PATTERN AND ANY OMITTED CONTACTS.
- FMLB (FIRST MATE, LAST BREAK) FOR POWER CONTACTS
ARE ALWAYS DEFINED ON RECEPTACLES.

FMLB (FIRST MATE, LAST BREAK) OPTIONS FOR SIGNAL CONTACTS
ARE ALWAYS DEFINED ON MATING HEADERS.
- NON- STANDARD OPTIONS ARE DEFINED AS SUCH:
- NOT FULLY LOADED SIGNAL CONTACTS OR NOT FULLY LOADED POWER CONTACTS
- PITCH IS NOT THE STANDARD PITCH OF .250 FOR POWER CONTACTS
- THE COLOR OF THE POWER WIRES ARE NOT BLACK
- THE COLOR OF THE SIGNAL WIRES ARE NOT GREEN
- FMLB (FIRST MATE, LAST BREAK) IS REQUESTED
- PANEL MOUNT WITHOUT GUIDES HAS BEEN REQUESTED
- PITCH IS VARIED ON POWER CONTACTS
- POWER WIRES OF VARIED GAGES ARE REQUIRED.
- POWER WIRES AND OR SIGNAL WIRES OF VARIED COLORS ARE REQUIRED.
- CONNECTOR LENGTH SHALL NOT EXCEED 155.00 mm MAX.
- TYPE OF TERMINATION MUST BE SPECIFIED BY CUSTOMER, EXAMPLE "LUGS".
CUSTOMER DRAWING. STANDARD OFFERING IS BLUNT CUT CABLES.
- TERMINATION OF WIRES ON SINGLE ENDED ASSEMBLIES SHALL BE DEFINED
ON ASSEMBLY DRAWING. TERMINATION TYPES SHALL ALSO BE SPECIFIED ON THE
CRL E-3610. TERMINATION TYPES MAY BE DEFINED AS LUGS, RINGS OR AS
SPECIFIED BY CUSTOMER.
- LEAD FREE PRODUCTS MEET EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-22-008.

www.fciconnect.com		surface <input checked="" type="checkbox"/>	tolerance std	projection	MM
		TOLERANCES UNLESS OTHERWISE SPECIFIED			
Dr	D. INGRAM	2008-07-07	ANGULAR	0.X	±
Eng	C. GROSS	2008-07-07	LINEAR	0.XX	±
Chr	C. GROSS	2008-07-07	0° ±°	0.XXX	±
Appr	C. GROSS	2008-07-07	Product family		ECN V09-0582
				Spec ref	
FCI PART NUMBER SCHEME WITH MM ² CABLES		dwg no		10080598	Rev. C
PwrBlade RECEPTACLE CABEL ASSEMBLIES		CUSTOMER		sheet 1 of 1	
catalog no					

rev	ecn no	dr	date
A	V08-0305	DA1	2008-07-07
B	V08-0327	DA1	2008-07-16
C	V09-0582	DA1	2010-02-12
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.